



# TEST REPORT

## No. I18Z60296-EMC04

for

**HMD Global Oy**

**Smart phone**

**Model Name: TA-1088**

**FCC ID: 2AJOTTA-1088**

with

**Hardware Version: 0301/0305**

**Software Version: 000C\_0\_22A**

**Issued Date: 2018-05-21**



**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I18Z60296-EMC04	Rev.0	1 <sup>st</sup> edition	2018-05-21

## **CONTENTS**

<b>1. TEST LABORATORY .....</b>	<b>4</b>
<b>1.1. TESTING LOCATION .....</b>	<b>4</b>
<b>1.2. TESTING ENVIRONMENT .....</b>	<b>4</b>
<b>1.3. PROJECT DATA .....</b>	<b>4</b>
<b>1.4. SIGNATURE.....</b>	<b>4</b>
<b>2. CLIENT INFORMATION .....</b>	<b>5</b>
<b>2.1. APPLICANT INFORMATION.....</b>	<b>5</b>
<b>2.2. MANUFACTURER INFORMATION.....</b>	<b>5</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....</b>	<b>6</b>
<b>3.1. ABOUT EUT.....</b>	<b>6</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....</b>	<b>6</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....</b>	<b>6</b>
<b>3.4. EUT SET-UPS .....</b>	<b>8</b>
<b>4. REFERENCE DOCUMENTS.....</b>	<b>9</b>
<b>4.1. REFERENCE DOCUMENTS FOR TESTING.....</b>	<b>9</b>
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>10</b>
<b>6. SUMMARY OF TEST RESULTS.....</b>	<b>11</b>
<b>7. TEST EQUIPMENTS UTILIZED.....</b>	<b>12</b>
<b>ANNEX A: MEASUREMENT RESULTS .....</b>	<b>13</b>
<b>ANNEX B: ACCREDITATION CERTIFICATE .....</b>	<b>24</b>

## **1. Test Laboratory**

### **1.1. Testing Location**

CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China100191

### **1.2. Testing Environment**

Normal Temperature: 15-35℃


Relative Humidity: 20-75%

### **1.3. Project data**

Testing Start Date: 2018-04-22

Testing End Date: 2018-05-16

### **1.4. Signature**




---

**Wang Junqing**  
**(Prepared this test report)**



---

**Zhang Ying**  
**(Reviewed this test report)**



---

**Liu Baodian**  
**Deputy Director of the laboratory**  
**(Approved this test report)**



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: HMD Global Oy  
Address /Post: Karaportti 2 02610 Espoo FINLAND  
City: Espoo  
Postal Code: /  
Country: FINLAND  
Contact Email: mikko.kahlos@hmdglobal.com  
Telephone: +358 408036126  
Fax: /

### **2.2. Manufacturer Information**

Company Name: HMD Global Oy  
Address /Post: Karaportti 2 02610 Espoo FINLAND  
City: Espoo  
Postal Code: /  
Country: FINLAND  
Telephone: +358 408036126

### **3. Equipment Under Test (EUT) and Ancillary Equipment (AE)**

#### **3.1. About EUT**

Description	Smart phone
Model Name	TA-1088
FCC ID	2AJOTTA-1088
Extreme vol. Limits	3.6VDC to 4.2VDC (nominal: 3.8VDC)

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL, Telecommunication Technology Labs, CAICT.

#### **3.2. Internal Identification of EUT used during the test**

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	004402972191740/	0301	000C_0_22A
	004402972198943		
EUT7-2	004402972192524/	0305	000C_0_22A
	004402972199727		

\*EUT ID: is used to identify the test sample in the lab internally.

#### **3.3. Internal Identification of AE used during the test**

AE ID*	Description	SN	Remarks
AE1	Battery	/	/
AE2	Charger	/	/
AE3	Charger	/	/
AE4	USB Cable	/	/
AE5	USB Cable	/	/

##### AE1

Model	HE336
Manufacturer	SCUD(Fujian) Electronics Co., Ltd.
Capacitance	2900 mAh
Nominal voltage	3.85 V

##### AE2

Model	AD-10WX
Manufacturer	Salcomp
Length of cable	/

##### AE3

Model	AD-10WX
Manufacturer	/
Length of cable	/

##### AE4

Model	CUBB01M-FA010-DH
Manufacturer	FIT
Length of cable	95cm



AE5

Model	/
Manufacturer	/
Length of cable	95cm

\*AE ID: is used to identify the test sample in the lab internally.

Note: The USB cables are shielded.



### 3.4. EUT set-ups

<b>EUT set-up No.</b>	<b>Combination of EUT and AE</b>	<b>Remarks</b>
Set.1	EUT1+ AE1 + AE2+ AE4/AE5	Charger
Set.2	EUT1+ AE1 + AE4/AE5	USB mode
Set.3	EUT1+ AE1 + AE3+ AE4/AE5	Charger





## **4. Reference Documents**

### **4.1. Reference Documents for testing**

The following documents listed in this section are referred for testing.

<b>Reference</b>	<b>Title</b>	<b>Version</b>
FCC Part 15, Subpart B	Radio frequency devices - Unintentional Radiators	2016
ANSI C63.4	American National Standard for Methods of Measurement of Radio- Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2014

Note: The test methods have no deviation with standards.

## 5. LABORATORY ENVIRONMENT

**Semi-anechoic chamber SAC-1** (23 meters×17meters×10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ±4 dB, 10 m distance
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 6GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

**Semi-anechoic chamber SAC-2** (10 meters×6.7meters×6.1meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 15 %, Max. = 75 %
Shielding effectiveness	0.014MHz - 1MHz, >60dB; 1MHz - 1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω
Normalised site attenuation (NSA)	< ± 4 dB, 3m distance, from 30 to 1000 MHz
Site voltage standing-wave ratio ( $S_{VSWR}$ )	Between 0 and 6 dB, from 1GHz to 18GHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz

**Shielded room** did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 20 %, Max. = 75 %
Shielding effectiveness	0.014MHz-1MHz, >60dB; 1MHz—1000MHz, >90dB.
Electrical insulation	> 2 MΩ
Ground system resistance	< 4 Ω



## 6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:		
Verdict Column	P	Pass
	NA	Not applicable
	F	Fail

Items	Test Name	Clause in FCC rules	Section in this report	Verdict	Test Location
1	Radiated Emission	15.109(a)	B.1	P	CTTL(huayuan North Road)
2	Conducted Emission	15.107(a)	B.2	P	CTTL(huayuan North Road)



## 7. Test Equipments Utilized

NO.	Description	TYPE	SERIES NUMBER	MANUFACTURE	CAL DUE DATE	CALIBRATION INTERVAL
1	Test Receiver	ESU26	100235	R&S	2018-04-01	1 year
2	Test Receiver	ESCI	100948	R&S	2018-07-25	1 Year
3	Universal Radio Communication Tester	CMW500	143008	R&S	2018-11-26	1 year
4	Universal Radio Communication Tester	CMW500	155415	R&S	2019-01-15	1 year
5	LISN	ENV216	101200	R&S	2018-08-03	1 year
6	EMI Antenna	VULB 9163	9163-301	Schwarzbeck	2019-01-03	3 years
7	EMI Antenna	3115	00167250	ETS-Lindgren	2018-11-30	3 years
8	PC	OPTIPLEX 380	2X1YV2X	DELL	N/A	N/A
9	Printer	P1606dn	VNC3L52122	HP	N/A	N/A
10	Keyboard	L100	CN0RH6596589 07ATOI40	DELL	N/A	N/A
11	Mouse	M-UAE119	LZ935220ZRC	Lenovo	N/A	N/A

Test Item	Test Software and Version	Software Vendor
Radiated Continuous Emission	EMC32 V9.01	R&S
Conducted Emission	EMC32 V8.52.0	R&S

## **ANNEX A: MEASUREMENT RESULTS**

### **A.1 Radiated Emission**

#### **Reference**

FCC: CFR Part 15.109(a).

#### **A.1.1 Method of measurement**

The field strength of radiated emissions from the unintentional radiator (USB mode of MS and charging mode of MS) at distances of 10 meters(for 30MHz-1GHz) and 3 meters (for above 1GHz) is tested. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 8.3.

The EUT was placed on a non-conductive table. The measurement antenna was placed at a distance of 3/10 meters from the EUT. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

#### **A.1.2 EUT Operating Mode**

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

#### **A.1.3 Measurement Limit**

Frequency range (MHz)	Field strength limit ( $\mu\text{V/m}$ )		
	Quasi-peak	Average	Peak
30-88	100		
88-216	150		
216-960	200		
960-1000	500		
>1000		500	5000

Note: the above limit is for 3 meters test distance. 10 meters' limit is got by converting.

#### **A.1.4 Test Condition**

Frequency range (MHz)	RBW/VBW	Sweep Time (s)	Detector
30-1000	120kHz (IF Bandwidth)	5	Peak/Quasi-peak
Above 1000	1MHz/1MHz	15	Peak, Average

### A.1.5 Measurement Results

A "reference path loss" is established and the  $A_{Rpl}$  is the attenuation of "reference path loss". It includes the antenna factor of receive antenna and the path loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{Mea}} + A_{\text{Rpl}} = P_{\text{Mea}} + G_A + G_{\text{PL}}$$

Where

$G_A$ : Antenna factor of receive antenna

$G_{\text{PL}}$ : Path Loss

$P_{\text{Mea}}$ : Measurement result on receiver.

Measurement uncertainty (worst case):  $U = 4.3 \text{ dB}$ ,  $k=2$ .

#### Measurement results for Set.1:

##### Charging Mode/Average detector

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Antenna Pol. (H/V)
17803.367	37.6	-18.5	45.6	10.500	H
17847.000	37.6	-18.5	45.6	10.500	V
17441.833	37.6	-19.2	41.5	15.300	V
17860.600	37.6	-18.5	45.6	10.500	V
17901.400	37.6	-18.5	45.6	10.500	H
17405.567	37.5	-19.2	41.5	15.200	H

##### Charging Mode/Peak detector

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Antenna Pol. (H/V)
17874.767	49.5	-18.5	45.6	22.400	H
17299.033	49.3	-19.5	41.5	27.300	H
17888.933	49.2	-18.5	45.6	22.100	V
17320.567	49.2	-19.5	41.5	27.200	V
17879.300	49.0	-18.5	45.6	21.900	H
17423.700	49.0	-19.2	41.5	26.700	H

**Measurement results for Set.2:**

**USB Mode/Average detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17884.400	37.7	-18.5	45.6	10.600	V
17905.367	37.7	-18.5	45.6	10.600	H
17416.333	37.7	-19.2	41.5	15.400	V
17834.533	37.7	-18.5	45.6	10.600	H
17432.767	37.6	-19.2	41.5	15.300	H
17920.667	37.6	-17.7	45.6	9.700	H

**USB Mode/ Peak detector**

Frequency (MHz)	Measurement Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Antenna Pol. (H/V)
17874.767	49.5	-18.5	45.6	22.400	H
17299.033	49.3	-19.5	41.5	27.300	H
17888.933	49.2	-18.5	45.6	22.100	V
17320.567	49.2	-19.5	41.5	27.200	H
17879.300	49.0	-18.5	45.6	21.900	H
17423.700	49.0	-19.2	41.5	26.700	V

**Measurement results for Set.3:**

**Charging Mode/Average detector**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Antenna Pol. (H/V)
17866.267	42.1	-18.5	45.6	15.000	H
17859.467	42.1	-18.5	45.6	15.000	V
17444.100	42.0	-19.2	41.5	19.700	V
17857.767	42.0	-18.5	45.6	14.900	V
17862.300	41.9	-18.5	45.6	14.800	H
17448.633	41.9	-19.2	41.5	19.600	H

**Charging Mode/Peak detector**

Frequency (MHz)	Measurement Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Antenna Pol. (H/V)
17867.400	54.0	-18.5	45.6	26.900	H
17847.000	53.7	-18.5	45.6	26.600	H
17628.267	53.6	-18.9	45.6	26.900	V
17831.133	53.5	-18.5	45.6	26.400	V
17852.667	53.4	-18.5	45.6	26.300	H
17389.700	53.4	-19.2	41.5	31.100	H

Note: The measurement results of Set.1, Set.2, Set.3 showed here are worst cases of the combinations of different batteries and USB cables.



Charging Mode, Set.1




Fig A.1 Radiated Emission from 30MHz to 1GHz




Fig A.2 Radiated Emission from 1GHz to 18GHz

USB Mode, Set.2




Fig A.3 Radiated Emission from 30MHz to 1GHz




Fig A.4 Radiated Emission from 1GHz to 18GHz

Charging Mode, Set.3

Full Spectrum




Fig A.5 Radiated Emission from 30MHz to 1GHz

Full Spectrum




Fig A.6 Radiated Emission from 1GHz to 18GHz

## A.2 Conducted Emission

### Reference

FCC: CFR Part 15.107(a).

### A.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2014, section 7.3.

### A.2.2 EUT Operating Mode

The MS is operating in the USB mode and charging mode. During the test MS is connected to a PC via a USB cable in the case of USB mode and is connected to a charger in the case of charging mode. The model of the PC is DELL OPTIPLEX 380, and the serial number of the PC is 2X1YV2X. The software is used to let the PC keep on copying data to MS, reading and erasing the data after copy action was finished.

Note: I/O information: Printer – USB, Mouse – PS/2, Keyboard – USB.

### A.2.3 Measurement Limit

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency

### A.2.4 Test Condition in charging mode

Voltage (V)	Frequency (Hz)
120	60

RBW/IF bandwidth	Sweep Time(s)
9kHz	1

### A.2.5 Measurement Results

Measurement uncertainty:  $U= 2.9$  dB,  $k=2$ .

#### Charging Mode, Set.1




Fig A.7 Conducted Emission

#### Final Result 1


Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.366000	38.3	2000.0	9.000	L1	19.8	20.3	58.6
0.694500	39.7	2000.0	9.000	L1	19.8	16.3	56.0
0.757500	44.7	2000.0	9.000	L1	19.8	11.3	56.0
1.986000	40.1	2000.0	9.000	N	19.6	15.9	56.0
3.066000	39.5	2000.0	9.000	L1	19.7	16.5	56.0
4.830000	41.5	2000.0	9.000	L1	19.6	14.5	56.0

#### Final Result 2

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.366000	29.4	2000.0	9.000	L1	19.8	19.2	48.6
0.690000	31.5	2000.0	9.000	L1	19.8	14.5	46.0
0.753000	38.5	2000.0	9.000	L1	19.8	7.5	46.0
1.329000	32.0	2000.0	9.000	L1	19.6	14.0	46.0
2.440500	33.8	2000.0	9.000	L1	19.7	12.2	46.0
4.897500	31.8	2000.0	9.000	L1	19.6	14.2	46.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

**USB Mode, Set.2**



**Fig A.8 Conducted Emission**

**Final Result 1**


Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.204000	46.1	2000.0	9.000	L1	19.8	17.4	63.4
0.406500	32.8	2000.0	9.000	L1	19.9	24.9	57.7
0.474000	29.9	2000.0	9.000	N	19.9	26.6	56.4
0.969000	32.8	2000.0	9.000	N	19.7	23.2	56.0
3.399000	30.0	2000.0	9.000	N	19.7	26.0	56.0
4.420500	40.6	2000.0	9.000	N	19.7	15.4	56.0

**Final Result 2**

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.168000	45.1	2000.0	9.000	N	19.8	10.0	55.1
0.406500	28.9	2000.0	9.000	L1	19.9	18.9	47.7
0.748500	28.3	2000.0	9.000	N	19.8	17.7	46.0
1.495500	25.7	2000.0	9.000	N	19.6	20.3	46.0
3.466500	25.7	2000.0	9.000	L1	19.7	20.3	46.0
4.623000	29.0	2000.0	9.000	N	19.7	17.0	46.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

**Charging Mode, Set.3**



**Fig A.9 Conducted Emission**

**Final Result 1**

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.465000	39.4	2000.0	9.000	N	19.9	17.2	56.6
0.969000	33.8	2000.0	9.000	L1	19.6	22.2	56.0
1.383000	33.7	2000.0	9.000	L1	19.6	22.3	56.0
2.674500	35.6	2000.0	9.000	L1	19.7	20.4	56.0
4.105500	32.5	2000.0	9.000	L1	19.6	23.5	56.0
15.792000	34.8	2000.0	9.000	L1	19.9	25.2	60.0

**Final Result 2**

Frequency (MHz)	Average (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.465000	34.5	2000.0	9.000	L1	19.9	12.1	46.6
0.969000	25.9	2000.0	9.000	L1	19.6	20.1	46.0
1.351500	25.6	2000.0	9.000	L1	19.6	20.4	46.0
2.674500	25.5	2000.0	9.000	L1	19.7	20.5	46.0
4.186500	22.5	2000.0	9.000	L1	19.6	23.5	46.0
18.343500	27.2	2000.0	9.000	L1	20.0	22.8	50.0

Note: The measurement results showed here are worst cases of the combinations of different batteries and USB cables.

**ANNEX B: Accreditation Certificate**

United States Department of Commerce  
National Institute of Standards and Technology



---

**Certificate of Accreditation to ISO/IEC 17025:2005**

---

NVLAP LAB CODE: 600118-0

**Telecommunication Technology Labs, CAICT**Beijing  
China

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*

**Electromagnetic Compatibility & Telecommunications**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).*

2016-09-29 through 2017-09-30

Effective Dates

  
For the National Voluntary Laboratory Accreditation Program**\*\*\*END OF REPORT\*\*\***