







BUREAU VERITAS

Test Report No.: RF200629W001-4

Channel Bandwidth: 5MHz 16QAM







**BUREAU
VERITAS**

Test Report No.: RF200629W001-4

Channel Bandwidth: 10MHz QPSK


CHANNEL 23230 1 RB CHANNEL 23230 Full RB



Date: 7.30.2020 05:13:03

Date: 7.30.2020 05:12:33

CHANNEL 23230 1 RB 49




Date: 7.30.2020 05:13:30



**BUREAU
VERITAS**

Test Report No.: RF200629W001-4

Channel Bandwidth: 10MHz 16QAM



3.6 CONDUCTED SPURIOUS EMISSIONS


3.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm

3.6.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.
- b. Measuring frequency range is from 30 MHz to 18GHz for WCDMA Band 4 & LTE Band 4, from 30 MHz to 7.2GHz for LTE Band 12, from 30 MHz to 7.9GHz for LTE Band 13. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

3.6.3 TEST SETUP






BUREAU VERITAS

Test Report No.: RF200629W001-4

3.6.4 TEST RESULTS





BUREAU VERITAS


Test Report No.: RF200629W001-4

LTE BAND 4

1.4MHz / QPSK


CHANNEL 19957

FREQUENCY RANGE : 30MHz~18GHz




CHANNEL 20175

FREQUENCY RANGE : 30MHz~18GHz



CHANNEL 20393

FREQUENCY RANGE : 30MHz~18GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

3MHz / QPSK


CHANNEL 19965

FREQUENCY RANGE : 30MHz~18GHz




CHANNEL 20175

FREQUENCY RANGE : 30MHz~18GHz



CHANNEL 20385

FREQUENCY RANGE : 30MHz~18GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

5MHz / QPSK


CHANNEL 19975

FREQUENCY RANGE : 30MHz~18GHz




CHANNEL 20175

FREQUENCY RANGE : 30MHz~18GHz



CHANNEL 20375

FREQUENCY RANGE : 30MHz~18GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

10MHz / QPSK


CHANNEL 20000

FREQUENCY RANGE : 30MHz~18GHz





CHANNEL 20175

FREQUENCY RANGE : 30MHz~18GHz



CHANNEL 20350

FREQUENCY RANGE : 30MHz~18GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

15MHz / QPSK


CHANNEL 20025

FREQUENCY RANGE : 30MHz~18GHz





CHANNEL 20175

FREQUENCY RANGE : 30MHz~18GHz



CHANNEL 20325

FREQUENCY RANGE : 30MHz~18GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

20MHz / QPSK


CHANNEL 20050

FREQUENCY RANGE : 30MHz~18GHz





CHANNEL 20175

FREQUENCY RANGE : 30MHz~18GHz



CHANNEL 20300

FREQUENCY RANGE : 30MHz~18GHz





BUREAU VERITAS


Test Report No.: RF200629W001-4

LTE BAND 12

1.4MHz / QPSK


CHANNEL 23017

FREQUENCY RANGE : 30MHz~7.2GHz





CHANNEL 23095

FREQUENCY RANGE : 30MHz~7.2GHz



CHANNEL 23173

FREQUENCY RANGE : 30MHz~7.2GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

3MHz / QPSK


CHANNEL 23025

FREQUENCY RANGE : 30MHz~7.2GHz




CHANNEL 23095

FREQUENCY RANGE : 30MHz~7.2GHz



CHANNEL 23165

FREQUENCY RANGE : 30MHz~7.2GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

5MHz / QPSK


CHANNEL 23035

FREQUENCY RANGE : 30MHz~7.2GHz




CHANNEL 23095

FREQUENCY RANGE : 30MHz~7.2GHz



CHANNEL 23155

FREQUENCY RANGE : 30MHz~7.2GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

10MHz / QPSK


CHANNEL 23060

FREQUENCY RANGE : 30MHz~7.2GHz




CHANNEL 23095

FREQUENCY RANGE : 30MHz~7.2GHz



CHANNEL 23130

FREQUENCY RANGE : 30MHz~7.2GHz






BUREAU VERITAS

Test Report No.: RF200629W001-4

LTE BAND 13






BUREAU VERITAS

Test Report No.: RF200629W001-4

10MHz / QPSK

CHANNEL 23230

FREQUENCY RANGE : 30MHz~7.9GHz





3.7 RADIATED EMISSION MEASUREMENT

3.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least $43 + 10 \log_{10}(P)$ dB. The limit of emission equal to -13dBm

3.7.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$.


NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

3.7.3 DEVIATION FROM TEST STANDARD


No deviation

3.7.4 TEST SETUP

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



3.7.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

LTE BAND 13

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 23230	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	32.140	-35.80	-55.63	-13.00	-22.80	19.83	Peak	Horizontal
2 PP	135.260	-32.59	-40.26	-13.00	-19.59	7.67	Peak	Horizontal
3	227.650	-38.71	-50.65	-13.00	-25.71	11.94	Peak	Horizontal
4	285.650	-43.88	-57.45	-13.00	-30.88	13.57	Peak	Horizontal
5	443.650	-47.93	-65.78	-13.00	-34.93	17.85	Peak	Horizontal
6	753.470	-40.00	-63.17	-13.00	-27.00	23.17	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23230	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase	
	MHz	dBm/m	dBm	dBm/m	dB	dB/m			
1	PP	40.250	-28.22	-41.69	-13.00	-15.22	13.47	Peak	Vertical
2		100.020	-35.75	-44.85	-13.00	-22.75	9.10	Peak	Vertical
3		241.360	-43.08	-55.98	-13.00	-30.08	12.90	Peak	Vertical
4		323.680	-47.18	-61.54	-13.00	-34.18	14.36	Peak	Vertical
5		485.170	-44.14	-62.98	-13.00	-31.14	18.84	Peak	Vertical
6		656.880	-38.22	-59.77	-13.00	-25.22	21.55	Peak	Vertical





Test Report No.: RF200629W001-4

ABOVE 1GHz

Note: For higher frequency, the emission is too low to be detected.


WORST-CASE DATA

WCDMA Band IV:

CH 1312

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3418.000	-51.17	-59.76	-13.00	-38.17	8.59	Peak	Horizontal
2	5137.000	-52.13	-61.06	-13.00	-39.13	8.93	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3418.000	-50.07	-59.18	-13.00	-37.07	9.11	Peak	Vertical
2	5137.000	-51.04	-60.89	-13.00	-38.04	9.85	Peak	Vertical






Test Report No.: RF200629W001-4

CH 1413

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-47.96	-56.54	-13.00	-34.96	8.58	Peak	Horizontal
2	5197.000	-50.08	-59.19	-13.00	-37.08	9.11	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-47.86	-57.02	-13.00	-34.86	9.16	Peak	Vertical
2	5197.000	-50.27	-60.09	-13.00	-37.27	9.82	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RF200629W001-4

CH 1513

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3496.000	-51.50	-60.07	-13.00	-38.50	8.57	Peak	Horizontal
2	PP 5257.000	-50.34	-59.63	-13.00	-37.34	9.29	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3496.000	-50.14	-59.33	-13.00	-37.14	9.19	Peak	Vertical
2 PP	5257.000	-49.94	-59.74	-13.00	-36.94	9.80	Peak	Vertical






Test Report No.: RF200629W001-4

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-47.11	-55.69	-13.00	-34.11	8.58	Peak	Horizontal
2	5197.000	-52.02	-61.13	-13.00	-39.02	9.11	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3470.000	-50.29	-59.45	-13.00	-37.29	9.16	Peak	Vertical
2 PP	5197.000	-50.12	-59.94	-13.00	-37.12	9.82	Peak	Vertical






Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3465.000	-48.29	-56.87	-13.00	-35.29	8.58	Peak	Horizontal
2	5186.000	-53.19	-62.27	-13.00	-40.19	9.08	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-49.31	-58.47	-13.00	-36.31	9.16	Peak	Vertical
2	5197.000	-51.30	-61.12	-13.00	-38.30	9.82	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3470.000	-49.20	-57.78	-13.00	-36.20	8.58	Peak	Horizontal
2	5197.000	-50.38	-59.49	-13.00	-37.38	9.11	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-47.70	-56.86	-13.00	-34.70	9.16	Peak	Vertical
2	5197.000	-51.13	-60.95	-13.00	-38.13	9.82	Peak	Vertical






Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 10MHz / QPSK

CH20000

MODE	TX channel 20000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3418.000	-51.74	-60.33	-13.00	-38.74	8.59	Peak	Horizontal
2 PP	5145.000	-51.29	-60.25	-13.00	-38.29	8.96	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3418.000	-50.64	-59.75	-13.00	-37.64	9.11	Peak	Vertical
2 PP	5145.000	-49.81	-59.65	-13.00	-36.81	9.84	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RF200629W001-4

CH20175

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Read	Limit	Over				
Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP 3470.000	-45.72	-54.30	-13.00	-32.72	8.58	Peak	Horizontal
2 5197.000	-51.39	-60.50	-13.00	-38.39	9.11	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-48.18	-57.34	-13.00	-35.18	9.16	Peak	Vertical
2	5197.000	-52.23	-62.05	-13.00	-39.23	9.82	Peak	Vertical






BUREAU VERITAS

Test Report No.: RF200629W001-4

CH20350

MODE	TX channel 20350	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3496.000	-51.01	-59.58	-13.00	-38.01	8.57	Peak	Horizontal
2 PP	5250.000	-51.01	-60.28	-13.00	-38.01	9.27	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20350	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3496.000	-49.87	-59.06	-13.00	-36.87	9.19	Peak	Vertical
2	5250.000	-50.08	-59.88	-13.00	-37.08	9.80	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-48.27	-56.85	-13.00	-35.27	8.58	Peak	Horizontal
2	5197.000	-51.56	-60.67	-13.00	-38.56	9.11	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-46.64	-55.80	-13.00	-33.64	9.16	Peak	Vertical
2	5197.000	-52.36	-62.18	-13.00	-39.36	9.82	Peak	Vertical






Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-48.44	-57.02	-13.00	-35.44	8.58	Peak	Horizontal
2	5197.000	-52.74	-61.85	-13.00	-39.74	9.11	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3470.000	-48.12	-57.28	-13.00	-35.12	9.16	Peak	Vertical
2	5197.000	-49.93	-59.75	-13.00	-36.93	9.82	Peak	Vertical






Test Report No.: RF200629W001-4

LTE BAND 12

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Read	Limit	Over				
1	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1416.000	-43.38	-44.46	-13.00	-30.38	1.08 Peak	Horizontal
2	2122.000	-51.03	-58.70	-13.00	-38.03	7.67 Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-44.23	-45.92	-13.00	-31.23	1.69	Peak	Vertical
2	2122.000	-52.03	-58.72	-13.00	-39.03	6.69	Peak	Vertical






Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-40.87	-41.95	-13.00	-27.87	1.08	Peak	Horizontal
2	2122.000	-50.49	-58.16	-13.00	-37.49	7.67	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-41.84	-43.53	-13.00	-28.84	1.69	Peak	Vertical
2	2122.000	-51.41	-58.10	-13.00	-38.41	6.69	Peak	Vertical






Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-42.71	-43.79	-13.00	-29.71	1.08	Peak	Horizontal
2	2122.000	-50.39	-58.06	-13.00	-37.39	7.67	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-43.66	-45.35	-13.00	-30.66	1.69	Peak	Vertical
2	2122.000	-51.36	-58.05	-13.00	-38.36	6.69	Peak	Vertical






Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 10MHz / QPSK

CH 23060

MODE	TX channel 23060	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1408.000	-43.01	-44.05	-13.00	-30.01	1.04	Peak	Horizontal
2	2112.000	-50.76	-58.42	-13.00	-37.76	7.66	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23060	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1408.000	-43.76	-45.42	-13.00	-30.76	1.66	Peak	Vertical
2	2112.000	-48.84	-55.52	-13.00	-35.84	6.68	Peak	Vertical






BUREAU VERITAS

Test Report No.: RF200629W001-4

CH23095

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1416.000	-40.09	-41.17	-13.00	-27.09	1.08	Peak	Horizontal
2	2122.000	-50.41	-58.08	-13.00	-37.41	7.67	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23095	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Read	Limit	Over				
Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP 1416.000	-38.08	-39.77	-13.00	-25.08	1.69	Peak	Vertical
2 2122.000	-47.80	-54.49	-13.00	-34.80	6.69	Peak	Vertical






BUREAU
VERITAS

Test Report No.: RF200629W001-4

CH 23130

MODE	TX channel 23130	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1422.000	-44.52	-45.63	-13.00	-31.52	1.11	Peak	Horizontal
2	2133.000	-49.53	-57.21	-13.00	-36.53	7.68	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23130	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1422.000	-42.28	-44.00	-13.00	-29.28	1.72	Peak	Vertical
2	2133.000	-51.58	-58.28	-13.00	-38.58	6.70	Peak	Vertical





Test Report No.: RF200629W001-4


LTE BAND 13

CHANNEL BANDWIDTH: 5MHz / QPSK

CH 23205

MODE	TX channel 23205	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1542.000	-31.56	-33.52	-13.00	-18.56	1.96	Peak	Horizontal
2	2340.000	-51.53	-59.42	-13.00	-38.53	7.89	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23205	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1542.000	-33.25	-35.67	-13.00	-20.25	2.42	Peak	Vertical
2	2340.000	-51.75	-58.66	-13.00	-38.75	6.91	Peak	Vertical






Test Report No.: RF200629W001-4

CH 23230

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1546.000	-30.42	-32.43	-13.00	-17.42	2.01	Peak	Horizontal
2	2346.000	-48.99	-56.89	-13.00	-35.99	7.90	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1546.000	-30.69	-33.15	-13.00	-17.69	2.46	Peak	Vertical
2	2346.000	-51.21	-58.12	-13.00	-38.21	6.91	Peak	Vertical






BUREAU VERITAS

Test Report No.: RF200629W001-4

CH 23255

MODE	TX channel 23255	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1550.000	-52.91	-54.97	-13.00	-39.91	2.06	Peak	Horizontal
2	PP 2353.000	-49.46	-57.36	-13.00	-36.46	7.90	Peak	Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23255	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1550.000	-31.15	-33.65	-13.00	-18.15	2.50	Peak	Vertical
2	2353.000	-50.76	-57.68	-13.00	-37.76	6.92	Peak	Vertical






Test Report No.: RF200629W001-4

CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm/m	dBm	dBm/m	dB	dB/m	Pol/Phase
1 PP 1546.000	-30.42	-32.43	-13.00	-17.42	2.01	Peak Horizontal
2 2346.000	-48.99	-56.89	-13.00	-35.99	7.90	Peak Horizontal






Test Report No.: RF200629W001-4

MODE	TX channel 23230	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 1546.000	-30.69	-33.15	-13.00	-17.69	2.46	Peak	Vertical
2	2346.000	-51.21	-58.12	-13.00	-38.21	6.91	Peak	Vertical





Test Report No.: RF200629W001-4

4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.dg@cn.bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: RF200629W001-4

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---