



FCC Test Report

APPLICANT : HMD Global Oy
EQUIPMENT : Mobile Phone
BRAND NAME : NOKIA
MODEL NAME : TA-1285
FCC ID : 2AJOTTA-1285
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jul. 03, 2020 and testing was completed on Aug. 06, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Location 7

 1.7. Test Software 7

 1.8. Applicable Standards 7

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 8

 2.1. Test Mode 8

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system 11

 2.4. EUT Operation Test Setup 12

3. TEST RESULT 13

 3.1. Test of AC Conducted Emission Measurement 13

 3.2. Test of Radiated Emission Measurement 17

4. LIST OF MEASURING EQUIPMENT 22

5. UNCERTAINTY OF EVALUATION 23

APPENDIX A. SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 4.27 dB at 0.150 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 4.83 dB at 44.550 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1. General Description

1.1. Applicant

HMD Global Oy
Bertel Jungin aukio 9, 02600 Espoo, Finland

1.2. Manufacturer

HMD Global Oy
Bertel Jungin aukio 9, 02600 Espoo, Finland

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	NOKIA
Model Name	TA-1285
FCC ID	2AJOTTA-1285
EUT supports Radios application	GSM/WCDMA/LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth BR/EDR/LE FM Receiver and GNSS
IMEI Code	Conduction: 353183110017511 Radiation: 353183110022560
HW Version	MB_V3
SW Version	0-00WW-A01
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, the differences is that please refer to the product equality declaration which is submitted separately. According to the difference, we choose the sample1 perform full test and sample 2 verifies the worst of sample1.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 66 : 2110.7 MHz~ 2179.3 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz FM : 88 MHz ~ 108 MHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna FM : External Earphone Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK HSDPA : QPSK HSUPA : QPSK HSPA+ : 16QAM (16QAM uplink is not supported) LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK



	Bluetooth (2Mbps) : π /4-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK FM: FM
--	---

GNSS=Galileo + GLONASS + GPS + BDS

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS	CN1257	314309

1.7. Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Rx(Middle) + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + Camera(Rear) + USB Cable 1(Charging from Adapter) + Battery 1 for Sample 1
	Mode 2: WCDMA 1900 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + Camera(Front) + USB Cable 2(Charging from Adapter) + Battery 1 for Sample 1
	Mode 3: LTE Band 13 Rx(High) + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + MP4 + USB Cable 1(Charging from Adapter) + Battery 1 for Sample 1
	Mode 4: LTE Band 12 Rx(Middle)+Earphone+Bluetooth Idle + WLAN Idle(2.4G) + FM Rx(98MHz) + USB Cable 1(Charging from Adapter) + Battery 1 for Sample 1
	Mode 5: LTE Band 4 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 6: LTE Band 7 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 for Sample 1
	Mode 7 GSM 850 Rx(Middle) + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + Camera(Rear) + USB Cable 1(Charging from Adapter) + Battery 2 for Sample 2




Radiated Emissions	<p>Mode 1: GSM 850 Rx(Middle) + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + Camera(Rear) + USB Cable 1(Charging from Adapter) + Battery 1 for Sample 1</p> <p>Mode 2: WCDMA 1900 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + Camera(Front) + USB Cable 2(Charging from Adapter) + Battery 1 for Sample 1</p> <p>Mode 3: LTE Band 13 Rx(High) + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + MP4 + USB Cable 2(Charging from Adapter) + Battery 1 for Sample 1</p> <p>Mode 4: LTE Band 12 Rx(Middle) + Earphone + Bluetooth Idle +WLAN Idle(2.4G) + FM Rx(88MHz) + USB Cable 2(Charging from Adapter) + Battery 1 for Sample 1</p> <p>Mode 5: LTE Band 4 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 1 for Sample 1</p> <p>Mode 6: LTE Band 7 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + GNSS Rx + USB Cable 2(Data Link with Notebook) + Battery 1 for Sample 1</p> <p>Mode 7: LTE Band 4 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + GNSS Rx + USB Cable 1(Data Link with Notebook) + Battery 2 for Sample 2</p> <p>Mode 8: LTE Band 4 Rx + Earphone + Bluetooth Idle + WLAN Idle(2.4G) + Camera(Rear) + USB Cable 1(Data Link with Notebook) + Battery 2 for Sample 2</p>
--------------------	--

Remark:

1. The worst case of AC is mode 1; only the test data of this mode is reported.
2. The worst case of RE is mode 5; only the test data of this mode is reported.
3. Data Link with Notebook means data application transferred mode between EUT and Notebook
4. Pre-scanned Low/Middle/High channels for GSM/WCDMA/LTE of bellow 1GHz frequency band, the worst channel was recorded in this report.

2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	LTE Base Station	Anritus	MT8820C	N/A	N/A	Unshielded,1.8m
3.	Base Station	R&S	CMU 200	N/A	N/A	Unshielded,1.8m
4.	Vector Signal Generator	R&S	SMBV100A	258305	N/A	N/A
5.	Signal Generator	R&S	SMBV100A	N/A	N/A	Unshielded,1.8m
6.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
7.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded,1.8m
8.	Bluetooth Earphone	小米	LYEJ02LM	N/A	N/A	N/A
9.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
10.	Notebook	Lenovo	V130-141K B001	N/A	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
11.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
12.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
13.	Hard disk	KINGSHARE	KSP6120G	Fcc DoC	Shielded, 1.2m	N/A
14.	SD Card	Kingston	8GB	N/A	N/A	N/A
15.	SD Card	SanDisk	Uitra	N/A	N/A	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on FM Function.
4. Turn on MPEG4 function.
5. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line




Site : CO01-KS
 Condition : FCC IC-QP LISN-L-191028-CN02 LINE
 Project : (FC) 070302-01
 mode : Mode 1
 : 353183110017511 #31

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
		dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.156	60.14	-5.55	65.69	49.60	0.07	10.47	QP
2	0.156	41.74	-13.95	55.69	31.20	0.07	10.47	Average
3	0.168	57.11	-7.97	65.08	46.60	0.08	10.43	QP
4	0.168	39.41	-15.67	55.08	28.90	0.08	10.43	Average
5	0.181	54.99	-9.47	64.46	44.51	0.08	10.40	QP
6	0.181	38.79	-15.67	54.46	28.31	0.08	10.40	Average
7	0.207	48.05	-15.27	63.32	37.60	0.09	10.36	QP
8	0.207	31.65	-21.67	53.32	21.20	0.09	10.36	Average
9	0.229	50.34	-12.14	62.48	39.90	0.09	10.35	QP
10	0.229	31.74	-20.74	52.48	21.30	0.09	10.35	Average
11	0.267	43.02	-18.18	61.20	32.60	0.10	10.32	QP
12	0.267	25.62	-25.58	51.20	15.20	0.10	10.32	Average
13	0.292	44.62	-15.84	60.46	34.21	0.10	10.31	QP
14	0.292	25.52	-24.94	50.46	15.11	0.10	10.31	Average
15	0.377	42.89	-15.45	58.34	32.49	0.12	10.28	QP
16	0.377	24.59	-23.75	48.34	14.19	0.12	10.28	Average
17	0.449	40.97	-15.92	56.89	30.59	0.13	10.25	QP
18	0.449	22.97	-23.92	46.89	12.59	0.13	10.25	Average
19	2.012	38.12	-17.88	56.00	27.50	0.39	10.23	QP
20	2.012	25.58	-20.42	46.00	14.96	0.39	10.23	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS
 Condition : FCC IC-QP LISN-N-191028-CN02 NEUTRAL
 Project : (FC) 070302-01
 mode : Mode 1
 : 353183110017511 #31

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.150	61.73	-4.27	66.00	51.10	0.15	10.48	QP
2	0.150	45.93	-10.07	56.00	35.30	0.15	10.48	Average
3	0.169	57.19	-7.84	65.03	46.60	0.16	10.43	QP
4	0.169	39.89	-15.14	55.03	29.30	0.16	10.43	Average
5	0.190	52.05	-11.97	64.02	41.51	0.16	10.38	QP
6	0.190	35.45	-18.57	54.02	24.91	0.16	10.38	Average
7	0.234	49.72	-12.58	62.30	39.20	0.18	10.34	QP
8	0.234	33.12	-19.18	52.30	22.60	0.18	10.34	Average
9	0.259	44.11	-17.36	61.47	33.60	0.18	10.33	QP
10	0.259	29.01	-22.46	51.47	18.50	0.18	10.33	Average
11	0.299	44.10	-16.18	60.28	33.60	0.19	10.31	QP
12	0.299	28.10	-22.18	50.28	17.60	0.19	10.31	Average
13	0.371	41.09	-17.38	58.47	30.60	0.21	10.28	QP
14	0.371	27.69	-20.78	48.47	17.20	0.21	10.28	Average
15	0.452	42.07	-14.78	56.85	31.60	0.22	10.25	QP
16	0.452	25.57	-21.28	46.85	15.10	0.22	10.25	Average
17	0.529	42.07	-13.93	56.00	31.60	0.23	10.24	QP
18	0.529	32.77	-13.23	46.00	22.30	0.23	10.24	Average
19	1.980	42.95	-13.05	56.00	32.20	0.52	10.23	QP
20	1.980	29.35	-16.65	46.00	18.60	0.52	10.23	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz






3.2.5. Test Result of Radiated Emission





Test Engineer :	Winter Zhang	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical



Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 44483-3M VERTICAL
 Project : (FC)070302-01

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 !	44.55	35.17	-4.83	40.00	48.36	17.35	1.40	31.94	100	0 Peak	
2	91.11	18.06	-25.44	43.50	33.00	14.93	2.05	31.92	---	---	Peak
3	167.74	22.62	-20.88	43.50	35.81	15.86	2.88	31.93	---	---	Peak
4	328.76	19.90	-26.10	46.00	28.03	19.86	4.06	32.05	---	---	Peak
5	587.75	28.41	-17.59	46.00	29.67	25.70	5.43	32.39	---	---	Peak
6	905.91	31.38	-14.62	46.00	26.75	29.32	6.72	31.41	---	---	Peak
7	3976.00	43.19	-30.81	74.00	55.20	33.70	14.25	59.96	---	---	Peak
8	6032.00	44.67	-29.33	74.00	52.13	34.98	17.66	60.10	---	---	Peak
9	8640.00	46.34	-27.66	74.00	49.83	36.42	21.36	61.27	---	---	Peak
10	11754.00	46.84	-27.16	74.00	44.33	38.22	25.05	60.76	---	---	Peak
11	14382.00	46.63	-27.37	74.00	39.91	39.36	27.99	60.63	---	---	Peak
12	17766.00	47.04	-26.96	74.00	31.84	40.98	31.61	57.39	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 14, 2020	Aug. 06, 2020	Apr. 13, 2021	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 18, 2019	Aug. 06, 2020	Oct. 17, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 28, 2019	Aug. 06, 2020	Oct. 27, 2020	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 18, 2019	Aug. 06, 2020	Oct. 17, 2020	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Oct. 18, 2019	Aug. 05, 2020	Oct. 17,2020	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct.18, 2019	Aug. 05, 2020	Oct. 17, 2020	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 30, 2019	Aug. 05, 2020	Dec. 29, 2020	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 10, 2019	Aug. 05, 2020	Nov. 09, 2020	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	Aug. 05, 2020	Nov. 09, 2020	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 08, 2020	Aug. 05, 2020	Jan. 07, 2021	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 02, 2020	Aug. 05, 2020	Jan. 01, 2021	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5G Hz	Oct. 18, 2019	Aug. 05, 2020	Oct. 17,2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Aug. 05, 2020	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Aug. 05, 2020	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Aug. 05, 2020	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------