



FCC PART 15C TEST REPORT No. I20Z62129-IOT01

for

HMD Global Oy

GSM/WCDMA/LTE phone

TA-1295

With

FCC ID: 2AJOTTA-1295

Hardware Version: 0301

Software Version: 0.2047.11.01

Issued Date: 2021-01-09

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



REPORT HISTORY

Report Number	Revision	Description	Issue Date
I20Z62129-IOT01	Rev.0	1st edition	2021-01-05
I20Z62129-IOT01	Rev.1	Update the duty cycle of 11b	2021-01-09

CONTENTS

1. TEST LABORATORY	5
1.1. INTRODUCTION & ACCREDITATION	5
1.2. TESTING LOCATION	5
1.3. TESTING ENVIRONMENT.....	5
1.4. PROJECT DATE	6
1.5. SIGNATURE	6
2. CLIENT INFORMATION.....	7
2.1. APPLICANT INFORMATION	7
2.2. MANUFACTURER INFORMATION	7
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	8
3.1. ABOUT EUT	8
3.2. INTERNAL IDENTIFICATION OF EUT	8
3.3. INTERNAL IDENTIFICATION OF AE.....	8
3.4. GENERAL DESCRIPTION.....	9
3.5. INTERPRETATION OF THE TEST ENVIRONMENT.....	9
4. REFERENCE DOCUMENTS	9
4.1. DOCUMENTS SUPPLIED BY APPLICANT	9
4.2. REFERENCE DOCUMENTS FOR TESTING.....	9
5. TEST RESULTS	10
5.1. SUMMARY OF TEST RESULTS.....	10
5.2. STATEMENTS.....	10
5.3. TEST CONDITIONS	10
6. TEST FACILITIES UTILIZED	11
7. MEASUREMENT UNCERTAINTY	12
7.1. MAXIMUM OUTPUT POWER.....	12
7.2. PEAK POWER SPECTRAL DENSITY	12
7.3. DTS 6-DB SIGNAL BANDWIDTH.....	12
7.4. BAND EDGES COMPLIANCE	12
7.5. TRANSMITTER SPURIOUS EMISSION	12
7.6. AC POWER-LINE CONDUCTED EMISSION	12
ANNEX A: EUT PARAMETERS.....	12
ANNEX B: DETAILED TEST RESULTS.....	13
B.1. MEASUREMENT METHOD	13
B.2. MAXIMUM OUTPUT POWER.....	14



B.2.1. PEAK OUTPUT POWER-CONDUCTED	14
B.3. PEAK POWER SPECTRAL DENSITY	15
B.4. DTS 6-DB SIGNAL BANDWIDTH.....	21
B.5. BAND EDGES COMPLIANCE	27
B.6. TRANSMITTER SPURIOUS EMISSION	31
B.6.1 TRANSMITTER SPURIOUS EMISSION – CONDUCTED.....	31
B.6.2 TRANSMITTER SPURIOUS EMISSION - RADIATED	71
B.7. AC POWER-LINE CONDUCTED EMISSION.....	82
ANNEX C: ACCREDITATION CERTIFICATE	86



1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

1.2. Testing Location

Location 1:CTTL(Gaolizhang Road)

Address: Cuihu Cloud Center, No.1, Gaolizhang Road, Wenquan,
Haidian District, Beijing, China

Location 2: CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology
Development Area, Beijing, P. R. China 100176

1.3. Testing Environment

Normal Temperature: 15-35°C

Relative Humidity: 20-75%

1.4. Project date

Testing Start Date: 2020-12-01


Testing End Date: 2021-01-04

1.5. Signature



Jiang Xue

(Prepared this test report)



Zheng Wei

(Reviewed this test report)



Hu Xiaoyu

(Approved this test report)



2. Client Information

2.1.Applicant Information

Company Name: HMD Global Oy
Address: Bertel Jungin aukio 9, 02600 Espoo, FINLAND
City: Espoo
Postal Code: /
Country: FINLAND
Telephone: +358 408036126
Fax: +97143697604

2.2.Manufacturer Information

Company Name: HMD Global Oy
Address: Bertel Jungin aukio 9, 02600 Espoo, FINLAND
City: Espoo
Postal Code: /
Country: FINLAND
Telephone: +358 408036126
Fax: +97143697604

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	GSM/WCDMA/LTE phone
Model name	TA-1295
FCC ID	2AJOTTA-1295
With WLAN Function	Yes
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	DSSS/CCK/OFDM
Number of Channels	11
Antenna	Integral Antenna
MAX Conducted Power	21.51dBm
Power Supply	3.8V

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
UT34a	004402972532356	0301	0.2047.11.01
EUT2	355011390000386/1	0301	0.2047.11.01

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE1	Battery
AE2	Charger
AE3	USB Cable
AE4	Headset

AE1

Model	BV-6A
Manufacturer	TIANJIN LISHEN BATTERY JOINT-STOCK CO., LTD.
Capacitance	1500mAh
Nominal voltage	3.85V

AE2

Model	AD-5WU
Manufacturer	DEE VAN ENTERPRISE CO., LTD.
Length of cable	/

AE3

Model	CA-10W
Manufacturer	Shenzhen Rongtaifeng Technology CO.,LTD
Length of cable	/

AE4

Model	WH-108
Manufacturer	Rongtaifeng
Length of cable	/

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment under Test (EUT) is a model of GSM/WCDMA/LTE phone with integrated antenna and inbuilt battery.

It has Bluetooth (EDR) function.

It consists of normal options: travel charger, USB cable.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the client.

3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor $k=2$.

Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

4. Reference Documents

4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902-928MHz, 2400-2483.5 MHz, and 5725-5850 MHz.	2018
ANSI C63.10	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices Federal Communications Commission Office of Engineering and Technology Laboratory Division GUIDANCE FOR COMPLIANCE MEASUREMENTS ON	2013
KDB 558074 D01	DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES	2019

5. Test Results

5.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15C	Sub-clause of IC	Verdict
Maximum Peak Output Power	15.247 (b)	/	P
Peak Power Spectral Density	15.247 (e)	/	P
Occupied 6dB Bandwidth	15.247 (a)	/	P
Band Edges Compliance	15.247 (d)	/	P
Transmitter Spurious Emission - Conducted	15.247 (d)	/	P
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	/	P
AC Powerline Conducted Emission	15.107, 15.207	/	P

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NP	Not Perform, The test was not performed by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

5.2. Statements

The test cases as listed in section 5.1 of this report for the EUT specified in section 3 was performed by CTTL and according to the standards or reference documents listed in section 4.2

The EUT met all requirements of the standards or reference documents, and only the WLAN function was tested in this report.

5.3. Test Conditions

T nom	Normal Temperature
T min	Low Temperature
T max	High Temperature
V nom	Normal Voltage

For this report, if the test cases listed above are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	T nom	26°C
Voltage	V nom	3.8V(By battery)
Humidity	H nom	20-75%

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2021-05-06
2	LISN	ENV216	101459	Rohde & Schwarz	1 year	2021-03-17
3	Test Receiver	ESCI	100766	Rohde & Schwarz	1 year	2021-03-10
4	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100376	Rohde & Schwarz	1 year	2021-09-04
2	BiLog Antenna	VULB9163	9163-514	Schwarzbeck	1 year	2021-02-24
3	Dual-Ridge Waveguide Horn Antenna	3117	00139065	ETS-Lindgren	1 year	2021-10-11
4	Dual-Ridge Waveguide Horn Antenna	3116	2661	ETS-Lindgren	1 year	2021-10-08

7. Measurement Uncertainty

7.1. Maximum Output Power

Measurement Uncertainty: 0.387dB,k=1.96

7.2. Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

7.3. DTS 6-dB Signal Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

7.4. Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

7.5. Transmitter Spurious Emission

Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

Radiated (k=2)

Frequency Range	Uncertainty(dB)
9kHz-30MHz	/
$30\text{MHz} \leq f \leq 1\text{GHz}$	5.40
$1\text{GHz} \leq f \leq 18\text{GHz}$	4.32
$18\text{GHz} \leq f \leq 40\text{GHz}$	5.26

7.6. AC Power-line Conducted Emission

Measurement Uncertainty : 3.08dB,k=2

ANNEX A: EUT parameters

Disclaimer: the power worse case provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

ANNEX B: Detailed Test Results

B.1. Measurement Method

B.1.1. Conducted Measurements

Connect the EUT to the test system as Fig.A.1.1.1 shows.

Set the EUT to the required work mode.

Set the EUT to the required channel.

Set the Vector Signal Analyzer and start measurement.

Record the values. Vector Signal Analyzer




Fig.B.1.1.1: Test Setup Diagram for Conducted Measurements

B.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;




Fig.B.1.2.1: Test Setup Diagram for Radiated Measurements

B.2. Maximum Output Power

Method of Measurement: See ANSI C63.10-2013-clause 11.9.1.2

- a) Set the RBW = 1 MHz.
- b) Set the VBW = 3 MHz.
- c) Set the span $\geq [1.5 \times \text{DTS bandwidth}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select the peak detector).

Measurement Limit:

Standard	Limit (dBm)
FCC CRF Part 15.247(b)	< 30

EUT ID: EUT2

B.2.1. Peak Output Power-conducted

Measurement Results:

Duty Cycle:

Mode	802.11b	802.11g	802.11n-HT20
Duty Cycle	100%	99%	98%

802.11b/g mode

Mode	Data Rate (Mbps)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11b	1	20.24	20.50	19.87
802.11g	6	21.38	21.51	21.15

The data rate 1Mbps and 6Mbps are selected as worse condition, and the following cases are performed with this condition.

802.11n-HT20 mode

Mode	Data Rate (Index)	Test Result (dBm)		
		2412MHz (Ch1)	2437MHz (Ch6)	2462 MHz (Ch11)
802.11n (20MHz)	MCS0	20.45	20.83	19.92

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

Conclusion: Pass

B.3. Peak Power Spectral Density

Method of Measurement: See ANSI C63.10-2013-clause 11.10.2

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to RBW = 3 kHz.
- d) Set the VBW = 10 kHz.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.

Measurement Limit:

Standard	Limit
FCC CRF Part 15.247(e)	< 8 dBm/3 kHz

Measurement Results:

802.11b/g mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11b	1	Fig.B.3.1	-4.88	P
	6	Fig.B.3.2	-5.49	P
	11	Fig.B.3.3	-6.44	P
802.11g	1	Fig.B.3.4	-12.27	P
	6	Fig.B.3.5	-11.46	P
	11	Fig.B.3.6	-13.13	P

802.11n-HT20 mode

Mode	Channel	Power Spectral Density (dBm/3 kHz)		Conclusion
802.11n (HT20)	1	Fig.B.3.7	-13.55	P
	6	Fig.B.3.8	-12.63	P
	11	Fig.B.3.9	-13.16	P

Conclusion: Pass

Test graphs as below:




Fig.B.3.1 Power Spectral Density(802.11b,Ch1)




Fig.B.3.2 Power Spectral Density (802.11b, Ch 6)




Fig.B.3.3 Power Spectral Density (802.11b, Ch 11)




Fig.B.3.4 Power Spectral Density (802.11g, Ch 1)




Fig.B.3.5 Power Spectral Density (802.11g, Ch 6)




Fig.B.3.6 Power Spectral Density (802.11g, Ch 11)




Fig.B.3.7 Power Spectral Density (802.11n-HT20, Ch 1)




Fig.B.3.8 Power Spectral Density (802.11n-HT20, Ch 6)




Fig.B.3.9 Power Spectral Density (802.11n-HT20, Ch 11)

B.4. DTS 6-dB Signal Bandwidth

Method of Measurement: See ANSI C63.10-2013 section 11.8.1.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) = 300 kHz.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measurement Limit:

Standard	Limit (kHz)
FCC 47 CFR Part 15.247 (a)	≥ 500

EUT ID: EUT2

Measurement Result:

802.11b/g mode

Mode	Channel	Occupied 6dB Bandwidth (KHz)		conclusion
802.11b	1	Fig.B.4.1	8550.00	P
	6	Fig.B.4.2	8500.00	P
	11	Fig.B.4.3	8550.00	P
802.11g	1	Fig.B.4.4	16400.00	P
	6	Fig.B.4.5	16400.00	P
	11	Fig.B.4.6	16400.00	P

802.11n-HT20 mode

Mode	Channel	Occupied 6dB Bandwidth (KHz)		conclusion
802.11n (HT20)	1	Fig.B.4.7	17600.00	P
	6	Fig.B.4.8	17350.00	P
	11	Fig.B.4.9	17550.00	P

Conclusion: Pass

Test graphs as below:




Fig.B.4.1 Occupied 6dB Bandwidth(802.11b,Ch 1)




Fig.B.4.2 Occupied 6dB Bandwidth (802.11b, Ch 6)




Fig.B.4.3 Occupied 6dB Bandwidth (802.11b, Ch 11)




Fig.B.4.4 Occupied 6dB Bandwidth (802.11g, Ch 1)




Fig.B.4.5 Occupied 6dB Bandwidth (802.11g, Ch 6)




Fig.B.4.6 Occupied 6dB Bandwidth (802.11g, Ch 11)




Fig.B.4.7 Occupied 6dB Bandwidth (802.11n-20MHz, Ch 1)




Fig.B.4.8 Occupied 6dB Bandwidth (802.11n-HT20, Ch 6)




Fig.B.4.9 Occupied 6dB Bandwidth (802.11n-HT20, Ch 11)

B.5. Band Edges Compliance

Method of Measurement: See ANSI C63.10-2013-clause 6.10.4

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 100MHz
- b) Sweep Time: coupled
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	> 20

EUT ID: EUT2

Measurement Result:

802.11b/g mode

Mode	Channel	Test Results	Conclusion
802.11b	1	Fig.B.5.1	P
	11	Fig.B.5.2	P
802.11g	1	Fig.B.5.3	P
	11	Fig.B.5.4	P

802.11n-HT20 mode

Mode	Channel	Test Results	Conclusion
802.11n (HT20)	1	Fig.B.5.5	P
	11	Fig.B.5.6	P

Conclusion: Pass

Test graphs as below:




Fig.B.5.1 Band Edges (802.11b, Ch 1)




Fig.B.5.2 Band Edges (802.11b, Ch 11)




Fig.B.5.3 Band Edges (802.11g, Ch 1)




Fig.B.5.4 Band Edges (802.11g, Ch 11)




Fig.B.5.5 Band Edges (802.11n-HT20, Ch 1)




Fig.B.5.6 Band Edges (802.11n-HT20, Ch 11)