

Report No.: ZR/2020/9004101-01 Page: 1 of 28

## FCC TEST REPORT

Test Result:	PASS *
Date of Issue:	2021/5/26
Date of Test:	2020/9/21 to 2020/10/15
Date of Receipt:	2020/9/21
Test Method:	FCC KDB 971168 D01 Power Meas License Digital Systems V03r01 C63.26 (2015)
	47 CFR Part 24 subpart E 47 CFR Part 27 subpart C
otanuarus.	47 CFR Part 22 subpart H
Standards:	47 CFR Part 2
FCC ID:	2AJOTTA-1337
Trade Mark:	NOKIA
Model No.:	TA-1337
EUT Description:	Mobile Phone
Address of Manufacturer:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Manufacturer:	HMD Global Oy
Address of Applicant	Bertel Jungin aukio 9, 02600 Espoo, Finland
Applicant:	HMD Global Oy
Application No:	ZR/2020/90041

In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:

Derde yang

Derek Yang Wireless Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation or liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) itested and such asample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN. Doccheck@gs.com.

中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



Report No.: ZR/2020/9004101-01 Page: 2 of 28

## 1 Version

	Revision Record			
Version	Chapter	Date	Modifier	Remark
01		2020/10/15		Original
02		2021/5/26	Sherlock Fang	<ol> <li>Add test site Information</li> <li>Updated equipment list</li> </ol>

\*This report supersedes our previous report ZR/2020/9004101, issued on 2020-10-15, which is hereby deemed null and void.

Authorized for issue by:	
Prepared By	
	Sherlock Fans (Sherlock Fang) / Engineer
Checked By	Dand Chen (David Chen) /Reviewer



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic marks, advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is attent by be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention To check the authenticity of testing (Inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@ags.com



Report No.: ZR/2020/9004101-01 Page: 3 of 28

## Content

1	VER	SION	2
2	TES	T SUMMARY	5
	2.1	GSM850/UMTS BAND 5 & LTE BAND 5	5
	2.2	GSM 1900/UMTS BAND 2	6
	2.3	LTE BAND 7/38/41	7
3	GEN	NERAL INFORMATION	8
	3.1	CLIENT INFORMATION	9
	3.2	TEST LOCATION	9
	3.3	TEST FACILITY	10
	3.4	GENERAL DESCRIPTION OF EUT	11
	3.5	TEST MODE	11
	3.6	TEST ENVIRONMENT	
	3.7	TECHNICAL SPECIFICATION	
	3.8	TEST FREQUENCIES	14
4	DES	CRIPTION OF TESTS	17
	4.1	CONDUCTED OUTPUT POWER	17
	4.2	EFFECTIVE (ISOTROPIC) RADIATED POWER OF TRANSMITTER	17
	4.3	OCCUPIED BANDWIDTH	17
	4.4	BAND EDGE AT ANTENNA TERMINALS	
	4.5	SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	
	4.6	PEAK-AVERAGE RATIO	
	4.7	FIELD STRENGTH OF SPURIOUS RADIATION	
	4.8	FREQUENCY STABILITY / TEMPERATURE VARIATION	20
	4.9	TEST SETUPS	22
	4.9.	1 Test Setup 1	
	4.9.	2 Test Setup 2	
	4.9.	3 Test Setup 3	
	4.9.	4 Test Setup 4	
	4.10	TEST CONDITIONS	24
5	ΜΑΙ	N TEST INSTRUMENTS	26



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T

邮编: 518057 t (86-755) 26012053 f (86-755) 26710594

sgs.china@sgs.com



Report No.: ZR/2020/9004101-01 Page: 4 of 28

6	MEASUREMENT UNCERTAINTY	28
7	APPENDIXES	28



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T



Report No.: ZR/2020/9004101-01 Page: 5 of 28

## 2 Test Summary

## 2.1 GSM850/UMTS Band 5 & LTE Band 5

Test Item	FCC Rule No.	Requirements	Test Result	Verdict	Test Lab*
Effective (Isotropic) Radiated Power Output Data	§2.1046, §22.913	FCC: ERP ≤ 7 W	Section 1 of Appendix B	Pass	А
Peak-Average Ratio		Limit≤13 dB	Section 2 of Appendix B	Pass	А
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass	А
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass	А
Band Edges Compliance	§2.1051, §22.917	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass	А
Spurious Emission at Antenna Terminals	§2.1051, §22.917	FCC: ≤ -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges.	Section 6 of Appendix B	Pass	А
Field Strength of Spurious Radiation	§2.1053, §22.917	FCC: ≤ -13 dBm/100 kHz.	Section 7 of Appendix B	Pass	В
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Section 8 of Appendix B	Pass	А
Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, recomming the provent of the sample (s) tested and such sample(s) are retained for 30 days only.



Report No.: ZR/2020/9004101-01 Page: 6 of 28

#### 2.2 GSM 1900/UMTS Band 2

Test Item	FCC Rule No.	Requirements	Test Result	Verdict	Test Lab*
Effective (Isotropic) Radiated Power Output Data	§2.1046, §24.232	EIRP ≤ 2 W	Section 1 of Appendix B	Pass	A
Peak-Average Ratio	§2.1046, §24.232	Limit≤13 dB	Section 2 of Appendix B	Pass	А
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass	А
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass	А
Band Edges Compliance	§2.1051, §24.238	≤ -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass	A
Spurious Emission at Antenna Terminals	§2.1051, §24.238	<ul> <li>≤ -13 dBm/1 MHz, from 9 kHz to 10<sup>th</sup> harmonics but outside authorized operating frequency ranges.</li> </ul>	Section 6 of Appendix B	Pass	A
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13 dBm/1 MHz.	Section 7 of Appendix B	Pass	В
Frequency Stability	§2.1055, §24.235	≤ ±2.5 ppm.	Section 8 of Appendix B	Pass	А
Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to rerms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T



Report No.: ZR/2020/9004101-01 Page: 7 of 28

### 2.3 LTE Band 7/38/41

Test Item	FCC Rule No.	Requirements	Test Result	Verdict	Test Lab*
Effective (Isotropic) Radiated Power Output Data	§2.1046, §27.50(h)	EIRP ≤ 2W	Section 1 of Appendix B	Pass	A
Peak-Average Ratio	§27.50(a)	≤13 dB	Section 2 of Appendix B	Pass	A
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass	A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Section 4 of Appendix B	Pass	A
Band Edges Compliance	§2.1051, §27.53(m4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section.	Section 5 of Appendix B	Pass	A
Spurious Emission at Antenna Terminals	§2.1051, §27.53(m)	P kHz %5 MHz XMHz 10 <sup>th</sup> harmonics X=Max {6MHz, EBW}	Section 6 of Appendix B	Pass	A
Field Strength of Spurious Radiation	§2.1053, §27.53(m)	Channel Edge -25 dBm/ 1 MHz 9 kHz 9 kHz 9 s MHz X=Max {6MHz, EBW}	Section 7 of Appendix B	Pass	В
Frequency Stability	§2.1055, §27.54	Within authorized bands of operation/frequency block.	Section 8 of Appendix B	Pass	A
Remark: For the verdict, the "N/A" denotes "not applicable", the "N/T" denotes "not tested".					



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions">http://www.sgs.com/en/Terms-and-Conditions</a>. A subject to therms and Conditions for Electronic Tocuments at <a href="http://www.sgs.com/en/Terms-and-Conditions">http://www.sgs.com/en/Terms-and-Conditions</a>. A subject to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this lest report refer only to the sample(s) tested and such sample(s) are relatined for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@gs.com"



Report No.: ZR/2020/9004101-01 Page: 8 of 28

Remark:

All test were performed by Lab A and B.

Parts of test items above were subcontracted to Lab B.

Lab A SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Lab B SGS-CSTC STANDARDS TECHNICAL SERVICES (XI 'AN) CO., LTD.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days on). Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755)8307 1443, or email: ON Docchedmess com



Report No.: ZR/2020/9004101-01 Page: 9 of 28

## **3** General Information

### **3.1 Client Information**

Applicant:	HMD Global Oy
Address of Applicant:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Manufacturer:	HMD Global Oy
Address of Manufacturer:	Bertel Jungin aukio 9, 02600 Espoo, Finland

## 3.2 Test Location

#### Lab A:

Company:	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address:	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code:	518057
Test engineer:	Dee Zheng,Mike Hu

#### Lab B:

Company:	SGS-CSTC STANDARDS TECHNICAL SERVICES (XI 'AN) CO., LTD.
Address:	1/F, Unit D, Building 1, Kanghong Orange Technology Park, No.137, Keyuan 3rd Road, Fengdong New City, Xi'an, Shaanxi China
Post code:	710086
Test engineer:	Ben Huang, Leah Chen



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T



Report No.: ZR/2020/9004101-01 Page: 10 of 28

### 3.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### Lab A:

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC – Designation Number: CN1178

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

#### Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

Lab B:

#### • A2LA (Certificate No. 4854.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (XI 'AN) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4854.01.

• FCC –Designation Number: CN1271



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-enDocument.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) test and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@egs.com



Report No.: ZR/2020/9004101-01 Page: 11 of 28

EUT Description::	Mobile Phone	
Model No.:	TA-1337	
Trade Mark:	NOKIA	
Hardware Version:	MB_V3	
Software Version:	00WW-A01	
Sample Type:	Portable Device, Module	
Antenna Type:	External,      Integrated	
	GSM850: -7dBi;	
	GSM1900:-6dBi	
	WCDMA Band II:-6dBi	
Antenna Gain:	WCDMA Band V:-7dBi	
Antenna Gain.	LTE Band 5:-7dBi;	
	LTE Band 7: -6dBi	
	LTE Band 38:-5dBi;	
	LTE Band 41:-5dBi;	

### 3.4 General Description of EUT

#### 3.5 Test Mode

Test Mode	Test Modes Description
GSM/TM1	GSM system, GSM/GPRS, GMSK modulation
GSM/TM2	GSM system, EGPRS, 8PSK modulation
UMTS/TM1	UMTS system, WCDMA, QPSK modulation
LTE/TM1	LTE system, QPSK modulation
LTE/TM2	LTE system, 16QAM modulation
LTE/TM3	LTE system, 64QAM modulation

Remark: The test mode(s) are selected according to relevant radio technology specifications.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-enD-countert.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refor only to the sample(s) test reation, for grear retained for 30 days only.



Report No.: ZR/2020/9004101-01 Page: 12 of 28

## 3.6 Test Environment

Environment Parameter	Selected Values During Tests		
Relative Humidity	52%		
Atmospheric Pressure:	101.32 KPa		
Temperature	NT 25 °C		
	LV	3.6V	
Voltage:	NV	3.85V	
	HV	4.2V	

Remark: LV= lower extreme test voltage; NV= nominal voltage

HV= upper extreme test voltage; NT= normal temperature

### 3.7 Technical Specification

Characteristics	Description					
	⊠ GSM					
Radio System Type	UMTS					
	🛛 LTE					
	Band	ТХ	RX			
	GSM850	824 to 849 MHz	869 to 894 MHz			
	GSM1900	1850 to 1910 MHz	1930 to 1990 MHz			
	UMTS Band II	1850 to 1910 MHz	1930 to 1990 MHz			
Supported Frequency Range	UMTS Band V	824 to 849 MHz	869 to 894 MHz			
rango	LTE Band 5	824 to 849 MHz	869 to 894 MHz			
	LTE Band 7	2500 to 2570 MHz	2620 to 2690 MHz			
	LTE Band 38	2570 to 2620 MHz	2570 to 2620 MHz			
	LTE Band 41	2535 to 2655MHz	2535 to 2655MHz			
Target TX Output Power	GSM850:34dBm GSM1900: 31dBm UMTS Band II: 23.5dBm UMTS Band V: 25dBm LTE Band 5: 24.5dBm LTE Band 7: 23dBm LTE Band 38: 24.5dBm LTE Band 41: 24.5dBm					
Supported Channel Bandwidth	GSM system:       \alpha 0.2 MHz         UMTS system:       \alpha 5 MHz         LTE Band 5       \alpha 1.4 MHz; \alpha 3 MHz; \alpha 5 MHz; \alpha 10 MHz         LTE Band 7       \alpha 5 MHz; \alpha 10 MHz; \alpha 15 MHz, \alpha 20 MHz         LTE Band38       \alpha 5 MHz; \alpha 10 MHz; \alpha 15 MHz, \alpha 20 MHz         LTE Band41       \alpha 5 MHz; \alpha 10 MHz; \alpha 15 MHz, \alpha 20 MHz					
Characteristics	Description					
Designation of	GSM850	248KGXW; 246KG7W				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document, does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document transfully of the sample(s) tested and such sample(s) are retained for 30 days only. Attention report Sectificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@ags.com} [No.1Workbon\_M10.Middle Section,Science & Technology Park, Shenzhen, China 518057 to (86-755) 28012053 for (86-755) 280710594 www.sgsgroup.com.on



Report No.: ZR/2020/9004101-01 Page: 13 of 28

Emissions	GSM1900	249KGXW; 245KG7W
(Remark: the necessary	UMTS Band II	4M14F9W;
· ·	UMTS Band V	4M15F9W;
bandwidth of which is		1M09G7D;1M09W7D;
the worst value from	LTE Bood E	2M70G7D;2M97W7D;
the measured occupied	LTE Band 5	4M93G7D;4M93W7D;
bandwidths for each		9M72G7D;9M76W7D;
type of channel	LTE Band 7	4M48G7D;4M49W7D;
bandwidth		8M91G7D;8M91W7D;
configuration.)		13M4G7D;13M4W7D;
comgaration.		17M9G7D;17M9W7D;
		4M48G7D;4M50W7D;
	LTE Band 38	8M91G7D;8M91W7D;
		13M5G7D;13M4W7D;
		17M9G7D;17M9W7D;
		4M47G7D;4M50W7D;
	LTE Band 41	8M91G7D;8M91W7D;
		13M5G7D;13M4W7D;
		17M9G7D;17M9W7D;



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T



Report No.: ZR/2020/9004101-01 Page: 14 of 28

### 3.8 Test Frequencies

Test Mode	TX / RX	RF Channel			
Test Mode		Low (L)	Middle (M)	High (H)	
	TX	Channel 128	Channel 190	Channel 251	
GSM850		824.2MHz	836.6 MHz	848.8 MHz	
G2101020		Channel 128	Channel 190	Channel 251	
	RX	869.2 MHz	881.6 MHz	893.8 MHz	

Test Mode	TX / RX	RF Channel			
Test Mode		Low (L)	Middle (M)	High (H)	
GSM1900	ТХ	Channel 512	Channel 661	Channel 810	
		1850.2MHz	1880.0 MHz	1909.8 MHz	
		Channel 512	Channel 661	Channel 810	
	RX	1930.2 MHz	1960.0 MHz	1989.8 MHz	

Test Mode	TX / RX	RF Channel			
Test Mode		Low (L)	Middle (M)	High (H)	
WCDMA Band II	TX RX	Channel 9262	Channel 9400	Channel 9538	
		1852.4 MHz	1880.0 MHz	1907.6 MHz	
		Channel 9662	Channel 9800	Channel 9938	
		1932.4 MHz	1960.0 MHz	1987.6 MHz	

Test Mede	TX / RX	RF Channel			
Test Mode		Low (L)	Middle (M)	High (H)	
	TX RX	Channel 4132	Channel 4182	Channel 4233	
WCDMA		826.4MHz	836.4 MHz	846.6 MHz	
Band V		Channel 4357	Channel 4407	Channel 4458	
	κ۸	871.4 MHz	881.4 MHz	891.6 MHz	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-terms-end-t



Report No.: ZR/2020/9004101-01 Page: 15 of 28

TestMede	Donalusiatta			RF Channel		
Test Mode	Bandwidth	TX/RX	Low (L)	Middle (M)	High (H)	
		тх	Channel 20407	Channel 20525	Channel 20643	
	1.4MHz		824.7 MHz	836.5 MHz	848.3 MHz	
	1.4IVITZ	RX	Channel 2407	Channel 2525	Channel 2643	
		ΓΛ	869.7 MHz	881.5 MHz	893.3 MHz	
		тх	Channel 20415	Channel 20525	Channel 20635	
	3MHz		825.5 MHz	836.5 MHz	847.5 MHz	
		RX	Channel 2415	Channel 2525	Channel 2635	
LTE Band 5			870.5 MHz	881.5 MHz	892.5 MHz	
LIE Dallu S	5MHz	ТХ	Channel 20425	Channel 20525	Channel 20625	
			826.5 MHz	836.5 MHz	846.5 MHz	
	SIVILIZ	RX	Channel 2425	Channel 2525	Channel 2625	
			871.5 MHz	881.5 MHz	891.5 MHz	
		тх	Channel 20450	Channel 20525	Channel 20600	
	10MHz		829 MHz	836.5 MHz	844 MHz	
		PV	Channel 2450	Channel 2525	Channel 2600	
	RX		874 MHz	881.5 MHz	889 MHz	

Test Mede	Dondwidth	TV/DV	RF Channel		
Test Mode	Bandwidth	TX/RX	Low (L)	Middle (M)	High (H)
		ТΧ	Channel 20775	Channel 21100	Channel 21425
	5MHz		2502.5 MHz	2535 MHz	2567.5 MHz
		RX	Channel 2775	Channel 3100	Channel 5825
		БЛ	2622.5 MHz	2655 MHz	2687.5 MHz
		ТХ	Channel 20800	Channel 21100	Channel 21400
	10MHz		2505 MHz	2535 MHz	2565 MHz
		RX	Channel 2800	Channel 3100	Channel 3400
LTE Band 7			2625 MHz	2655 MHz	2685 MHz
LIE Dallu I	15MHz	тх	Channel 20825	Channel 21100	Channel 21375
			2507.5 MHz	2535 MHz	2562.5 MHz
		RX	Channel 2825	Channel 3100	Channel 3375
			2627.5 MHz	2655 MHz	2682.5 MHz
		ТХ	Channel 20850	Channel 21100	Channel 21350
	20MHz		2510 MHz	2535 MHz	2560 MHz
		RX	Channel 2850	Channel 3100	Channel 3350
		ΓΛ	2630 MHz	2655 MHz	2680 MHz

Test Mode	Bandwidth	TX/RX	RF Channel		
Test Mode	Danuwiutn		Low (L)	Middle (M)	High (H)
	5MHz	TX/RX	Channel 37775	Channel38000	Channel 38225
			2572.5 MHz	2595 MHz	2617.5 MHz
	10MHz	TX/RX	Channel 37800	Channel38000	Channel 38200
LTE Band 38			2575 MHz	2595 MHz	2615 MHz
LIE Dallu So	15MHz	TX/RX	Channel 37825	Channel38000	Channel 38175
			2577.5 MHz	2595 MHz	2612.5 MHz
	20MHz	TX/RX	Channel 37850	Channel38000	Channel 38150
	20101112		2580 MHz	2595 MHz	2610 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to rerms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-end-terms-end-t



Report No.: ZR/2020/9004101-01 Page: 16 of 28

Test Mode	Bandwidth	TX / RX		RF Channel	
Test Mode	Danuwiutii		Low (L)	Middle (M)	High (H)
			Channel 40065	Channel40640	Channel 41215
	5MHz	TX/RX	2537.5 MHz	2595 MHz	2652.5 MHz
	10MHz	TX/RX	Channel 40090	Channel40640	Channel 41190
LTE Band 41			2540 MHz	2595 MHz	2650 MHz
LIE Danu 41	15MHz	TX/RX	Channel 40115	Channel40640	Channel 41165
			2542.5 MHz	2595 MHz	2647.5 MHz
	201411-		Channel 40140	Channel40640	Channel 41140
	20MHz	TX/RX	2545 MHz	2595 MHz	2645 MHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T



Report No.: ZR/2020/9004101-01 Page: 17 of 28

## 4 Description of Tests

### 4.1 Conducted Output Power

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and power meter, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The power output at the transmitter antenna port was determined by adding the value of the cable insertion loss to the power reading. The tests were performed at three frequencies (low channel, middle channel and high channel) and on the highest power levels, which can be setup on the transmitters.

**Remark: Reference test setup 1** 

### 4.2 Effective (Isotropic) Radiated Power of Transmitter

Measurement Procedure: FCC KDB 971168 D01 V03r01 ; C63.26 (2015) Calculate power in dBm by the following formula: ERP (dBm) = Conducted Power (dBm) + antenna gain (dBd) EIRP(dBm) = Conducted Power (dBm) + antenna gain (dBi) EIRP=ERP+2.15dB

### 4.3 Occupied Bandwidth

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 4.2

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

#### Remark: Reference test setup 1



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.forms-en-Counditio</u>



Report No.: ZR/2020/9004101-01 Page: 18 of 28

#### Test Settings

- The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 2. RBW = 1 5% of the expected OBW
- 3. VBW ≥ 3 x RBW
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep = auto couple
- 7. The trace was allowed to stabilize
- 8. If necessary, steps 2 7 were repeated after changing the RBW such that it would be within

1 - 5% of the 99% occupied bandwidth observed in Step 7

#### 4.4 Band Edge at Antenna Terminals

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 6.0

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emission are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyzer was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

#### Remark: Reference test setup 1

Test Settings

- 1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
- 2. Span was set large enough so as to capture all out of band emissions near the band edge
- 3. RBW > 1% of the emission bandwidth
- VBW ≥ 3 x RBW
- 5. Detector = RMS
- 6. Number of sweep points ≥ 2 x Span/RBW
- 7. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 8. Sweep time = auto couple
- 9. The trace was allowed to stabilize

### 4.5 Spurious And Harmonic Emissions at Antenna Terminal

Measurement Procedure: FCC KDB 971168 D01 V03r01

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyzer, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to



	Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or
	appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the
	results shown in this test report refer only to the sample's lested and such sample's) are retained for 30 days only.
	Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,
	or email: CN.Doccheck@sgs.com
1.	No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86–755) 26012053 f (86–755) 26710594 www.sgsgroup.com.cn
	中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sqs.china@sqs.com



Report No.: ZR/2020/9004101-01 Page: 19 of 28

force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

#### **Remark: Reference test setup 1**

Test Settings

- Start frequency was set to 30MHz and stop frequency was set to at least 10 \* the fundamental frequency (separated into at least two plots per channel)
- 2. Detector = RMS
- 3. Trace mode = trace average for continuous emissions, max hold for pulse emissions
- 4. Sweep time = auto couple
- 5. The trace was allowed to stabilize
- 6. Please see test notes below for RBW and VBW settings

### 4.6 Peak-Average Ratio

Measurement Procedure: FCC KDB 971168 D01 V03r01 Section 5.7.1

A peak to average ratio measurement is performed at the conducted port of the EUT. For WCDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level. For GSM signals, an average and a peak trace are used on a spectrum analyzer to determine the largest deviation between the average and the peak power of the EUT in a bandwidth greater than the emission bandwidth. The traces are generated with the spectrum analyzer set to zero span mode.

#### Remark: Reference test setup 1

Test Settings

- 1. The signal analyzer's CCDF measurement profile is enabled
- 2. Frequency = carrier center frequency
- 3. Measurement BW > Emission bandwidth of signal
- 4. The signal analyzer was set to collect one million samples to generate the CCDF curve
- 5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power

### 4.7 Field Strength of Spurious Radiation



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Conditio</u>



Report No.: ZR/2020/9004101-01 Page: 20 of 28

Measurement Procedure: FCC KDB 971168 D01 V03r01

#### Below 1GHz test procedure as below:

- 1). The EUT was powered ON and placed on a 80cm high table in the chamber. The antenna of the transmitter was extended to its maximum length.
- 2). The disturbance of the transmitter was maximized on the test receiver display by raising and lowering from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) the receive antenna and by rotating through 360° the turntable. After the fundamental emission was maximized, a field strength measurement was made.
- 3). Steps 1) and 2) were performed with the EUT and the receive antenna in both vertical and horizontal polarization.
- 4). The transmitter was then removed and replaced with another antenna. The center of the antenna was approximately at the same location as the center of the transmitter.
- 5). A signal at the disturbance was fed to the substitution antenna by means of a non-radiating cable. With both the substitution and the receive antennas horizontally polarized, the receive antenna was raised and lowered to obtain a maximum reading at the test receiver. The level of the signal generator was adjusted until the measured field strength level in step 2) is obtained for this set of conditions.
- 6). The output power into the substitution antenna was then measured.
- 7). Steps 5) and 6) were repeated with both antennas polarized.
- 8) Calculate power in dBm by the following formula:

ERP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBd)

Where:

Pd is the dipole equivalent power, Pg is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to Pg [dBm] – cable loss [dB]. The calculated Pd levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of 43 + 10log10(Power [Watts]).

#### Above 1GHz test procedure as below:

- 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber
- 2) Calculate power in dBm by the following formula:

EIRP(dBm) = Pg(dBm) - cable loss (dB) + antenna gain (dBi)

EIRP=ERP+2.15dB

Where:

Pg is the generator output power into the substitution antenna.

- 3. Test the EUT in the lowest channel, the middle channel the Highest channel
- 4. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, Only the test worst case mode is recorded in the report.
- 5. Repeat above procedures until all frequencies measured was complete

Remark: Reference test setup 3

## 4.8 Frequency Stability / Temperature Variation

Measurement Procedure:

Frequency stability testing is performed in accordance with the guidelines of FCC KDB 971168 D01 V03r01; ANSI/C63.26 (2015)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fulles extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 280710594 www.sgsgroup.com.cn http://www.sgs.com/en/Ters/Size012053 f (86-755) 280710594 www.sgsgroup.com.cn http://www.sgs.com/en/Ters/Size012053 f (86-755) 280710594 sps.com/en/Ters/Size012053 f (86-755) 280710594 sps.com



Report No.: ZR/2020/9004101-01 Page: 21 of 28

. The frequency stability of the transmitter is measured by:

a.) **Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.

b.) **Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$  ppm) of the center frequency.

#### Time Period and Procedure:

- 1. The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- 2. The equipment is turned on in a "standby" condition for fifteen minutes before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- 3. Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A period of at least one half-hour is provided to allow stabilization of the equipment at each temperature level.

#### Remark: Reference test setup 4




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755)8307 1443, results in Cli Dupoched/Gense comp



Report No.: ZR/2020/9004101-01 Page: 22 of 28

## 4.9 Test Setups

#### 4.9.1 Test Setup 1



#### 4.9.2 Test Setup 2




Figure 1. 30MHz to 1GHz

Figure 2. above 1GHz



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <u>http://www.sgs.com/en/Terms-and-Conditions.aspx</u>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unawful and obligation report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN\_Doccheck@asg.com

 No.1 Workhon, M-10 Midde Section, Science & TechnologyPark, Shenzhen, China 518057
 t (86-755) 26012053 f (86-755) 26710594
 www.sgsgroup.com.on

 Pia · 深圳 · 科技图中区M-10 · To · State · To · State · To · State · To · State · Stenhal@sections, John · Other · State · Stenhal@sections, John · Other · State · Stenhal@sections, John · Midde · State · Stenhal@sections, John · Markong · State · Stenhal@sections · State · Stenhal@sectio



Report No.: ZR/2020/9004101-01 Page: 23 of 28

### 4.9.3 Test Setup 3




Figure 1. Below 30MHz





Figure 2. 30MHz to 1GHz

#### Figure 3. above 1GHz

#### 4.9.4 Test Setup 4



Ground Reference Plane

中国·深圳·科技园中区M-10栋一号厂房



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: QA.Doccheck@gs.com</a>. Not Workshon, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 to (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn

邮编: 518057

sgs.china@sgs.com

t (86-755) 26012053 f (86-755) 26710594



Report No.: ZR/2020/9004101-01 Page: 24 of 28

### 4.10 Test Conditions

Test Case		Test Conditions			
		Test Environment	Ambient Climate & Rated Voltage		
	Average	Test Setup	Test Setup 1		
	Power, Total	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= hig channel )		
Transmit		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
Output			LTE/TM1;LTE/TM2		
Power Data	Average	Test Environment	Ambient Climate & Rated Voltage		
Dula	Power,	Test Setup	Test Setup 1		
	Spectral Density (if	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel )		
	required)	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
			LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
Dook to Av	orago Datio	Test Setup	Test Setup 1		
Peak-to-Ave (if required)	-	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel )		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; LTE/TM1;LTE/TM2		
		Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 1		
Modulation	tion	RF Channels (TX)	M (M= middle channel )		
Characteris	lics	. ,	GSM/TM1;GSM/TM2;UMTS/TM1;		
		Test Mode	LTE/TM1;LTE/TM2		
	Occupied Bandwidth	Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 1		
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel )		
		Toot Mode	GSM/TM1;GSM/TM2;UMTS/TM1;		
Bandwidth		Test Mode	LTE/TM1;LTE/TM2		
Danuwium	Emission Bandwidth (if required)	Test Environment	Ambient Climate & Rated Voltage		
		Test Setup	Test Setup 1		
		RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel )		
		Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; LTE/TM1;LTE/TM2		
Band Edges	lS	Test Environment	Ambient Climate & Rated Voltage		
Dana Luges	•		, material contractor a real of a re		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions.Terms-en-Document.aspx. Attention is drawn to the limitation of liability. Indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unavful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755)83071443, or email: CN\_Doccheck@sgs.com

 No.1 Workhon, M-10 Midde Section, Science & Technology Park, Shenzhen, China 518057
 t (86-755)26012053 f (86-755)26710594
 www.sgs.com.cn

 main: CN\_Doccheck@sgs.com
 msis: 518057
 t (86-755)26012053 f (86-755)26710594
 sys.china@sgs.com



Report No.: ZR/2020/9004101-01 Page: 25 of 28

Compliance	Test Setup	Test Setup 1			
	RF Channels (TX)	L, H (L= low channel, H= high channel )			
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;			
	Test Mode	LTE/TM1;LTE/TM2			
	Test Environment	Ambient Climate & Rated Voltage			
	Test Setup	Test Setup 1			
Spurious Emission at Antenna Terminals	RF Channels (TX)	L,M, H (L= low channel, M= middle channel, H= high channel			
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1; LTE/TM1;LTE/TM2			
	Test Environment	Ambient Climate & Rated Voltage			
	Test Setup	Test Setup 2			
		GSM/TM1;GSM/TM2;UMTS/TM1;			
Field Strength of		LTE/TM1;LTE/TM2;			
Spurious Radiation	Test Mode	Remark: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.			
	RF Channels (TX)	L, M, H (L= low channel, M= middle channel, H= high channel)			
		(1) -30 °C to +50 °C with step 10 °C at Rated Voltage;			
	Test Environment	(2) VL, VN and VH of Rated Voltage at Ambient Climate.			
Frequency Stability	Test Setup	<ul> <li>(L= low channel, M= middle channel, H= high channel )</li> <li>GSM/TM1;GSM/TM2;UMTS/TM1;</li> <li>LTE/TM1;LTE/TM2</li> <li>Ambient Climate &amp; Rated Voltage</li> <li>Test Setup 2</li> <li>GSM/TM1;GSM/TM2;UMTS/TM1;</li> <li>LTE/TM1;LTE/TM2;</li> <li>Remark: If applicable, the EUT conf. that has maximum power density (based on the equivalent power level) is selected.</li> <li>L, M, H (L= low channel, M= middle channel, H= high channel )</li> <li>(1) -30 °C to +50 °C with step 10 °C at Rated Voltage;</li> <li>(2) VL, VN and VH of Rated Voltage at Ambient Climate.</li> <li>Test Setup 4</li> <li>L, M, H (L= low channel, M= middle channel, H= high channel )</li> </ul>			
	RF Channels (TX)				
	Test Mode	GSM/TM1;GSM/TM2;UMTS/TM1;			
		LTE/TM1;LTE/TM2			



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T



Report No.: ZR/2020/9004101-01 Page: 26 of 28

## 5 Main Test Instruments

RF conducted test					
Test Equipment	Manufacturer	Model No. Inventory No.	Cal. date	Cal.Due date (yyyy-mm-	
Dual Output Mobile Communication DC Source	Agilent Technologies Inc	66311B	W009-09	dd) 2019/10/22	dd) 2020/10/21
Signal Analyzer	Rohde & Schwarz	FSV	W005-02	2020/4/16	2021/4/15
Coaxial Cable	SGS	N/A	SEM031-01	2020/6/12	2021/6/11
Attenuator	Weinschel Associates	WA41	SEM021-09	N/A	N/A
Signal Generator	KEYSIGHT	N5173B	SEM006-05	2019/10/22	2020/10/21
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	HTC-1	W006-17	2019/10/22	2020/10/21
Temperature Chamber	GIANT FORCE	ICT-150- 40-CP-AR	W027-03	2019/10/22	2020/10/21
Wideband Radio CommunicationTeste	Anristu	MT8821C	6201462742	2020/4/16	2021/4/15
Wideband Radio CommunicationTester	Rohde & Schwarz	CMW500	W005-02	2019/10/22	2020/10/21



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/T

Report No.: ZR/2020/9004101 Page: 27 of 28

RSE Test System					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Semi-Anechoic Chamber	Brilliant-emc	N/A	XAW03-35-01	2019-09-11	2022-09-10
MXA signal analyzer	Keysight	N9020A	XAW01-06-01	2020-04-02	2021-04-01
Test receiver	ROHDE&SCHWARZ	ESR	XAW01-08-01	2020-09-11	2021-09-10
Receiving antenna (30MHz-3GHz)	Schwarzbeck	VULB 9163	XAW01-09-01	2019-10-13	2021-10-12
Receiving antenna (1GHz~18GHz)	Schwarzbeck	BBHA 9120D	XAW01-09-02	2019-10-13	2021-10-12
Receiving antenna (15GHz~40GHz)	Schwarzbeck	BBHA 9170	XAW01-09-03	2019-10-13	2021-10-12
Directional antenna rack controller	Max-Full	MF-7802BS	XAW03-03-01	NCR	NCR
High-speed antenna rack controller	Max-Full	MF-7802	XAW03-04-01	NCR	NCR
Filter bank	Tonscend	JS0806-F	XAW03-05-01	NCR	NCR
Filter bank	Tonscend	JS0806s	XAW03-05-02	NCR	NCR
Amplifier	Tonscend	TAP00903040	XAW01-41-01	2019-11-18	2020-11-17
Amplifier	Tonscend	TAP01018048	XAW01-41-02	2019-11-18	2020-11-17
Amplifier	Tonscend	TAP18040048	XAW01-41-03	2019-12-03	2020-12-02
Amplifier	Shanghai Steed	YX28980930	XAW01-41-06	2019-11-18	2020-11-17
Temperature and humidity meter	MingGao	TH101B	XAW01-01-01	2019-12-06	2020-12-05
Measurement Software	Tonscend	TS+ RSE V3.0.0.2	XAW02-05-01	NCR	NCR
Radio communication analyzer	ROHDE&SCHWARZ	CMW 500	XAW01-03-02	2020-04-02	2021-04-01



S

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and urisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: (ND Docched@asc.com).



Report No.: ZR/2020/9004101 Page: 28 of 28

## 6 Measurement Uncertainty

For a 95% confidence level (k = 2), the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 as following:

Lab A:		
Test Item	Extended Uncertainty	Data
Transmit Output Power Data	Power [dBm]	U =±0.37 dB
Bandwidth	Magnitude [%]	U =± 0.2%
Band Edge Compliance	Disturbance Power [dBm]	U = ±2.0 dB
Spurious Emissions, Conducted	Disturbance Power [dBm]	U = ±2.0 dB
Frequency Stability	Frequency Accuracy [ppm]	U = ±0.24 ppm

Lab B:

. . . .

No.	ltem	Measurement Uncertainty
	Radiated Emission	± 4.8dB (Below 1GHz)
		± 4.8dB (1GHz to 6GHz)
1		± 4.5dB (6GHz to 18GHz)
		± 5.02dB (Above 18GHz)

## 7 Appendixes

Appendix A	Photographs of Set-Up for ZR/2020/90041
Appendix B.1	GSM 850 & 1900
Appendix B.2	WCDMA Band II & V
Appendix B.3	LTE Band 5
Appendix B.4	LTE Band 7
Appendix B.5	LTE Band 38
Appendix B.6	LTE Band 41

The End



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cose not exconerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document tory of terms here prove be added and such sample(s) tested and such sample(s) are retained for 30 days only. Terms-int its of segs.com containt if any. Documents at here here, which authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755)8001443, or email: GN\_Doccheck@gs.com</a>. No.1 Workhop, M-10, Midde Section, Science & Technology Park, Shenzhen, China 518057 tt (86-755)26012053 ft (86-755)26710594 www.sgsgroup.com.cn