



ANNEX- Spot Check of Output Power

Company Name: HMD Global Oy

Product Name: Multi-band GSM/WCDMA/LTE phone with Bluetooth, WLAN

Model Name: TA-1347(FCC ID: 2AJOTTA-1347)、TA-1343(FCC ID: 2AJOTTA-1343)

TA-1336(FCC ID: 2AJOTTA-1336)

Differences between models

Model Type	TA-1347 (Original)	TA-1343	TA-1336
SIM num.	single	dual	dual
Whether the same WCDMA and LTE band is supported	/	N	Y

Spot Check of Different Mode

Model	Mode	Frequency (MHz)	Conducted Output Power (dBm)	E.I.R.P (dBm)
TA-1347	LE 2M	2480(CH39)	-2.69	-0.49
	BR(GFSK)	2480(CH78)	6.30	8.50
	802.11b	2462 (CH11)	18.28	20.38
TA-1343	LE 2M	2480(CH39)	-2.85	-0.65
	BR(GFSK)	2480(CH78)	6.27	8.47
	802.11b	2462 (CH11)	18.13	20.23
TA-1336	LE 2M	2480(CH39)	-2.76	-0.56
	BR(GFSK)	2480(CH78)	6.30	8.50
	802.11b	2462 (CH11)	18.27	20.37

Note: E.I.R.P value = Conducted values (with conducted samples) + Antenna Gain.

Spot check test data included for the variants based on worst-case results reported in the original FCC ID filing.

From the above data, it can be concluded that the conducted output power of the variant is better than that of the original. And the variant test data can refer to the original report.

This condition applies to the reports **I20N03311** and **I20N03314**.