



# FCC RF Test Report

APPLICANT : HMD Global Oy  
EQUIPMENT : GSM/WCDMA/LTE Mobile Phone  
BRAND NAME : NOKIA  
MODEL NAME : TA-1395  
FCC ID : 2AJOTTA-1395  
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L)  
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jan. 21, 2021 and completely tested on Mar. 09, 2021. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

*Jason Jia*

Reviewed by: Jason Jia / Supervisor

*Alex Wang*

Approved by: Alex Wang / Manager



**Sporton International (Kunshan) Inc.**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY.....3**

**SUMMARY OF TEST RESULT .....4**

**1 GENERAL DESCRIPTION .....5**

1.1 Applicant.....5

1.2 Manufacturer .....5

1.3 Product Feature of Equipment Under Test .....5

1.4 Product Specification of Equipment Under Test .....5

1.5 Modification of EUT .....6

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....6

1.7 Testing Location .....7

1.8 Test Software .....7

1.9 Applicable Standards .....7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....8**

2.1 Test Mode.....8

2.2 Connection Diagram of Test System .....8

2.3 Support Unit used in test configuration .....9

2.4 Measurement Results Explanation Example .....9

2.5 Frequency List of Low/Middle/High Channels.....9

**3 CONDUCTED TEST RESULT.....10**

3.1 Measuring Instruments.....10

3.2 Test Setup .....10

3.3 Test Result of Conducted Test.....10

3.4 Conducted Output Power and ERP/EIRP .....11

3.5 Peak-to-Average Ratio .....12

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....13

3.7 Conducted Band Edge .....14

3.8 Conducted Spurious Emission .....15

3.9 Frequency Stability.....16

**4 RADIATED TEST ITEMS .....17**

4.1 Measuring Instruments.....17

4.2 Test Setup .....17

4.3 Test Result of Radiated Test.....18

4.4 Field Strength of Spurious Radiation Measurement .....19

**5 LIST OF MEASURING EQUIPMENT .....20**

**6 UNCERTAINTY OF EVALUATION .....21**

**APPENDIX A. TEST RESULTS OF CONDUCTED TEST**

**APPENDIX B. TEST RESULTS OF RADIATED TEST**

**APPENDIX C. TEST SETUP PHOTOGRAPHS**



### REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG112111A	Rev. 01	Initial issue of report	Mar. 30, 2021



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 32.49 dB at 2510.000. MHz

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

HMD Global Oy  
 Bertel Jungin aukio 9, 02600 Espoo, Finland

## 1.2 Manufacturer

HMD Global Oy  
 Bertel Jungin aukio 9, 02600 Espoo, Finland

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM/WCDMA/LTE Mobile Phone
Brand Name	NOKIA
Model Name	TA-1395
FCC ID	2AJOTTA-1395
EUT supports Radios application	GSM/WCDMA/LTE FM Receiver
IMEI Code	Conducted: N/A Radiation: N/A
HW Version	HW0141
SW Version	0.2105.11.10
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	<b>GSM/GPRS:</b> 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz <b>WCDMA:</b> Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
Rx Frequency	<b>GSM/GPRS:</b> 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz <b>WCDMA:</b>



	Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
<b>Maximum Output Power to Antenna</b>	<b>GSM/GPRS:</b> 850: 32.24 dBm 1900: 29.36 dBm <b>WCDMA:</b> Band V: 23.98 dBm Band II: 23.79 dBm Band IV: 23.83 dBm
<b>Antenna Type</b>	PIFA Antenna
<b>Antenna Gain</b>	Cellular Band: -3.85 dBi PCS Band: -2.71 dBi AWS Band: -3.14 dBi
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK WCDMA : BPSK (Uplink) HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (16QAM uplink is not supported)

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 (GSM)	824.2 ~ 848.8	GMSK	0.4207	0.0191 ppm	242KGXW
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.0628	0.0278 ppm	4M15F9W
Part 24	GSM1900 (GSM)	1850.2 ~ 1909.8	GMSK	0.4624	0.0145 ppm	243KGXW
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.1282	0.0159 ppm	4M15F9W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.1172	0.0144 ppm	4M15F9W



### 1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International (Kunshan) Inc.		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	03CH04-KS TH01-KS	CN1257	314309

### 1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

### 1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

### 2.2 Connection Diagram of Test System







### 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	Power Source	Chroma	61601	N/A	N/A	Unshielded, 1.8 m
3.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m
4.	Earphone	NOKIA	WH-108/RTF	N/A	N/A	N/A

### 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

The following shows an offset computation example with RF cable loss 4.9 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.9 + 10 = 14.9 \text{ (dB)} \end{aligned}$$

### 2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

### 3 Conducted Test Result

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



### 3.4 Conducted Output Power and ERP/EIRP

#### 3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



## **3.5 Peak-to-Average Ratio**

### **3.5.1 Description of the PAR Measurement**

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### **3.5.2 Test Procedures**

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



### 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

#### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.




## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup


#### 4.2.1 For radiated test below 30MHz



#### 4.2.2 For radiated test from 30MHz to 1GHz



### 4.2.3 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

According to engineering evaluation, Conducted Spurious Emission test Low/Middle/High channels, Radiated Spurious Emissions test the middle channel (because the middle channel test data margin > 6 dB).

Please refer to Appendix B.



## 4.4 Field Strength of Spurious Radiation Measurement

### 4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 9 kHz up to the 10th harmonic of the fundamental frequency, the worst-case emissions are reported.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12.  $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 01, 2020	Mar. 04, 2021~ Mar. 09, 2021	Oct. 31, 2021	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	Aug. 27, 2020	Mar. 04, 2021~ Mar. 09, 2021	Aug. 26, 2021	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 03, 2020	Mar. 04, 2021~ Mar. 09, 2021	Jul. 02, 2021	Conducted (TH01-KS)
Thermometer & hygrometer	SHENTUO	HTC-1	KS100807JC GS05	HTC-105	Apr. 14, 2020	Mar. 04, 2021~ Mar. 09, 2021	Apr. 13, 2021	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 15, 2020	Feb. 19, 2021	Apr. 14, 2021	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 01, 2020	Feb. 19, 2021	Oct. 31, 2021	Radiation (03CH04-KS)
Vector Signal Generator	R&S	SMBV100A	258305	9KHz~6GHz	Jan. 06, 2021	Feb. 19, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Signal Generator	R&S	SMR40	100455	10MHz~40GHz	Jan. 06, 2021	Feb. 19, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jun. 08, 2020	Feb. 19, 2021	Jun. 07, 2021	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 20, 2020	Feb. 19, 2021	Apr. 19, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Jan. 06, 2021	Feb. 19, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 06, 2021	Feb. 19, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 07, 2021	Feb. 19, 2021	Jan. 06, 2022	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 AP	2025788	1Ghz-18Ghz	Jan. 06, 2021	Feb. 19, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 14, 2020	Feb. 19, 2021	Oct. 13, 2021	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 19, 2021	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 19, 2021	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 19, 2021	NCR	Radiation (03CH04-KS)
Thermometer & hygrometer	SHENTUO	HTC-1	KS150428JC GS02	HTC-108	Apr. 14, 2020	Feb. 19, 2021	Apr. 13, 2021	Radiation (03CH04-KS)

NCR: No Calibration Required



## 6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.3dB
---	-------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8dB
---	-------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power) and ERP/EIRP

GSM850	Burst Average Power (dBm)			ERP		
	TX Channel	128	189			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GSM 1 Tx slot	32.24	32.23	32.21	0.4207	0.4198	0.4178
GPRS 1 Tx slot	32.22	32.22	32.20	0.4188	0.4188	0.4169
GPRS 2 Tx slots	29.93	29.94	29.91	0.2472	0.2477	0.2460
GPRS 3 Tx slots	27.90	27.88	27.85	0.1549	0.1542	0.1531
GPRS 4 Tx slots	26.07	26.09	26.02	0.1016	0.1021	0.1005

GSM1900	Burst Average Power (dBm)			EIRP		
	TX Channel	512	661			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GSM 1 Tx slot	29.33	29.36	29.31	0.4592	0.4624	0.4571
GPRS 1 Tx slot	29.31	29.35	29.29	0.4571	0.4613	0.4550
GPRS 2 Tx slots	26.69	26.83	26.78	0.2500	0.2582	0.2553
GPRS 3 Tx slots	25.12	25.25	25.17	0.1742	0.1795	0.1762
GPRS 4 Tx slots	23.06	23.09	23.00	0.1083	0.1091	0.1069



Band		WCDMA V			ERP		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.80	23.97	23.92	0.0603	0.0627	0.0619
3GPP Rel 99	RMC 12.2Kbps	23.82	23.98	23.94	0.0605	0.0628	0.0622
3GPP Rel 6	HSDPA Subtest-1	23.84	23.79	23.88	0.0608	0.0601	0.0614
3GPP Rel 6	HSDPA Subtest-2	22.35	22.19	22.33	0.0432	0.0416	0.0430
3GPP Rel 6	HSDPA Subtest-3	22.27	21.99	22.23	0.0424	0.0397	0.0420
3GPP Rel 6	HSDPA Subtest-4	21.63	21.48	21.60	0.0366	0.0353	0.0363
3GPP Rel 6	HSUPA Subtest-1	19.79	19.86	19.68	0.0239	0.0243	0.0233
3GPP Rel 6	HSUPA Subtest-2	20.31	20.43	20.37	0.0270	0.0277	0.0274
3GPP Rel 6	HSUPA Subtest-3	19.71	19.87	19.69	0.0235	0.0244	0.0234
3GPP Rel 6	HSUPA Subtest-4	19.30	19.46	19.33	0.0214	0.0222	0.0215
3GPP Rel 6	HSUPA Subtest-5	23.17	23.32	23.12	0.0521	0.0540	0.0515

Band		WCDMA IV			EIRP		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.80	23.81	23.67	0.1164	0.1167	0.1130
3GPP Rel 99	RMC 12.2Kbps	23.81	23.83	23.69	0.1167	0.1172	0.1135
3GPP Rel 6	HSDPA Subtest-1	22.97	23.25	22.96	0.0962	0.1026	0.0959
3GPP Rel 6	HSDPA Subtest-2	22.65	22.83	22.64	0.0893	0.0931	0.0891
3GPP Rel 6	HSDPA Subtest-3	22.75	22.84	22.62	0.0914	0.0933	0.0887
3GPP Rel 6	HSDPA Subtest-4	22.67	22.81	22.60	0.0897	0.0927	0.0883
3GPP Rel 6	HSUPA Subtest-1	21.18	21.26	21.16	0.0637	0.0649	0.0634
3GPP Rel 6	HSUPA Subtest-2	21.62	21.75	21.60	0.0705	0.0726	0.0701
3GPP Rel 6	HSUPA Subtest-3	21.37	21.44	21.30	0.0665	0.0676	0.0655
3GPP Rel 6	HSUPA Subtest-4	21.36	21.46	21.34	0.0664	0.0679	0.0661
3GPP Rel 6	HSUPA Subtest-5	22.83	22.94	22.84	0.0931	0.0955	0.0933



Band		WCDMA II			EIRP		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.64	23.77	23.73	0.1239	0.1276	0.1265
3GPP Rel 99	RMC 12.2Kbps	23.65	23.79	23.75	0.1242	0.1282	0.1271
3GPP Rel 6	HSDPA Subtest-1	23.62	23.76	23.70	0.1233	0.1274	0.1256
3GPP Rel 6	HSDPA Subtest-2	23.37	23.43	23.35	0.1164	0.1180	0.1159
3GPP Rel 6	HSDPA Subtest-3	22.50	22.63	22.54	0.0953	0.0982	0.0962
3GPP Rel 6	HSDPA Subtest-4	22.19	22.32	22.22	0.0887	0.0914	0.0893
3GPP Rel 6	HSUPA Subtest-1	18.45	18.60	18.53	0.0375	0.0388	0.0382
3GPP Rel 6	HSUPA Subtest-2	20.37	20.43	20.35	0.0583	0.0592	0.0581
3GPP Rel 6	HSUPA Subtest-3	19.85	19.91	19.77	0.0518	0.0525	0.0508
3GPP Rel 6	HSUPA Subtest-4	19.94	20.01	19.88	0.0528	0.0537	0.0521
3GPP Rel 6	HSUPA Subtest-5	23.06	23.17	23.08	0.1084	0.1112	0.1089







## A1. GSM

### Peak-to-Average Ratio

Mode	GSM850	Limit: 13dB
Mod.	GSM	Result
Lowest CH	0.20	PASS
Middle CH	0.12	
Highest CH	0.12	

Mode	GSM1900	Limit: 13dB
Mod.	GSM	Result
Lowest CH	0.20	PASS
Middle CH	0.12	
Highest CH	0.12	









**26dB Bandwidth**

Mode	GSM850
Mod.	GSM
Lowest CH	0.3107
Middle CH	0.3087
Highest CH	0.3107

Mode	GSM1900
Mod.	GSM
Lowest CH	0.3117
Middle CH	0.3147
Highest CH	0.3107









### Occupied Bandwidth

Mode	GSM850
Mod.	GSM
Lowest CH	0.2408
Middle CH	0.2418
Highest CH	0.2418

Mode	GSM1900
Mod.	GSM
Lowest CH	0.2428
Middle CH	0.2408
Highest CH	0.2408













# Conducted Band Edge





# Conducted Spurious Emission







**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GSM)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0108	PASS
40	Normal Voltage	0.0032	
30	Normal Voltage	0.0130	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0145	
0	Normal Voltage	0.0078	
-10	Normal Voltage	0.0175	
-20	Normal Voltage	0.0159	
-30	Normal Voltage	0.0143	
20	Maximum Voltage	0.0096	
20	Normal Voltage	0.0120	
20	Battery End Point	0.0191	

Test Conditions	Middle Channel	GSM1900 (GSM)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0058	PASS
40	Normal Voltage	0.0015	
30	Normal Voltage	0.0119	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0145	
0	Normal Voltage	0.0136	
-10	Normal Voltage	0.0089	
-20	Normal Voltage	0.0021	
-30	Normal Voltage	0.0118	
20	Maximum Voltage	0.0052	
20	Normal Voltage	0.0011	
20	Battery End Point	0.0124	

**Note:**


1. Normal Voltage = 3.9V. ; Battery End Point (BEP) =3.6V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.




## A2. WCDMA

### Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.01	2.81	3.07	<b>PASS</b>
Middle CH	2.99	2.96	2.81	
Highest CH	2.93	2.84	2.99	










**26dB Bandwidth**

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.675	4.675	4.665
Middle CH	4.675	4.675	4.675
Highest CH	4.675	4.665	4.675



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 4 MAR 2021 10:28:29


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 4 MAR 2021 10:14:03

Middle Channel




Date: 4 MAR 2021 10:29:35

Middle Channel




Date: 4 MAR 2021 10:14:50

Highest Channel




Date: 4 MAR 2021 10:30:16

Highest Channel



Date: 4 MAR 2021 10:15:26






## Occupied Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.15	4.15	4.14
Middle CH	4.15	4.15	4.15
Highest CH	4.15	4.15	4.15



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 4 MAR 2021 10:30:58


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 4 MAR 2021 10:16:11

Middle Channel




Date: 4 MAR 2021 10:37:40

Middle Channel




Date: 4 MAR 2021 10:16:45

Highest Channel




Date: 4 MAR 2021 10:38:16

Highest Channel




Date: 4 MAR 2021 10:17:20





# Conducted Band Edge







WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge

Highest Band Edge



Date: 4 MAR 2021 10:06:24





Date: 4 MAR 2021 10:07:30





# Conducted Spurious Emission







**Frequency Stability**

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2KbpsRMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0088	PASS
40	Normal Voltage	0.0255	
30	Normal Voltage	0.0021	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0278	
0	Normal Voltage	0.0243	
-10	Normal Voltage	0.0068	
-20	Normal Voltage	0.0273	
-30	Normal Voltage	0.0036	
20	Maximum Voltage	0.0012	
20	Normal Voltage	0.0234	
20	Battery End Point	0.0263	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0018	PASS
40	Normal Voltage	0.0122	
30	Normal Voltage	0.0118	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0174	
0	Normal Voltage	0.0048	
-10	Normal Voltage	0.0143	
-20	Normal Voltage	0.0159	
-30	Normal Voltage	0.0027	
20	Maximum Voltage	0.0022	
20	Normal Voltage	0.0096	
20	Battery End Point	0.0032	



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0035	PASS
40	Normal Voltage	0.0029	
30	Normal Voltage	0.0150	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0023	
0	Normal Voltage	0.0127	
-10	Normal Voltage	0.0035	
-20	Normal Voltage	0.0144	
-30	Normal Voltage	0.0046	
20	Maximum Voltage	0.0017	
20	Normal Voltage	0.0133	
20	Battery End Point	0.0035	

**Note:**

1. Normal Voltage = 3.9 V. ; Battery End Point (BEP) =3.6 V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



## Appendix B. Test Results of Radiated Test

### Radiated Spurious Emission

GSM850 (GSM)								
Channel	Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-53.58	-13	-40.58	-60.55	1.58	10.70	H
	2510	-52.52	-13	-39.52	-60.77	2.102	12.50	H
	3348	-48.24	-13	-35.24	-57.13	2.856	13.90	H
	1672	-53.98	-13	-40.98	-60.95	1.58	10.70	V
	2510	-45.49	-13	-32.49	-53.74	2.10	12.50	V
	3348	-50.96	-13	-37.96	-59.85	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)								
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-55.95	-13	-42.95	-68.21	2.641	14.90	H
	5640	-54.67	-13	-41.67	-66.53	2.94	14.80	H
	7524	-53.00	-13	-40.00	-62.77	3.39	13.16	H
	3759	-53.77	-13	-40.77	-66.03	2.64	14.90	V
	5640	-55.19	-13	-42.19	-67.05	2.94	14.80	V
	7524	-52.17	-13	-39.17	-61.94	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)								
Channel	Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-64.41	-13	-51.41	-71.38	1.58	10.70	H
	2510	-58.72	-13	-45.72	-66.97	2.102	12.50	H
	3348	-59.60	-13	-46.60	-68.49	2.856	13.90	H
	1672	-63.54	-13	-50.54	-70.51	1.58	10.70	V
	2510	-58.73	-13	-45.73	-66.98	2.10	12.50	V
	3348	-59.80	-13	-46.80	-68.69	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band II(RMC 12.2Kbps)								
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-57.09	-13	-44.09	-69.35	2.64	14.90	H
	5640	-55.04	-13	-42.04	-66.90	2.94	14.80	H
	7524	-51.68	-13	-38.68	-61.45	3.39	13.16	H
	3759	-56.86	-13	-43.86	-69.12	2.64	14.90	V
	5640	-55.56	-13	-42.56	-67.42	2.94	14.80	V
	7524	-52.63	-13	-39.63	-62.40	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV(RMC 12.2Kbps)								
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465	-55.25	-13	-42.25	-65.99	2.604	13.34	H
	5199	-54.65	-13	-41.65	-65.16	3.011	13.52	H
	6936	-54.29	-13	-41.29	-64.49	3.271	13.47	H
	3465	-56.52	-13	-43.52	-67.26	2.604	13.34	V
	5199	-54.53	-13	-41.53	-65.04	3.011	13.52	V
	6936	-53.92	-13	-40.92	-64.12	3.271	13.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.