



# FCC PART 15 TEST REPORT No. I22Z60412-IOT02

for

**HMD Global Oy**

**Smart Phone**

**TA-1448**

**With**

**FCC ID: 2AJOTTA-1448**

**Hardware Version: v1.0**

**Software Version: TMO: 04US\_1\_150**

**Issued Date: 202-05-17**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

**CTTL-Telecommunication Technology Labs, CAICT**

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: [ctl\\_terminals@caict.ac.cn](mailto:ctl_terminals@caict.ac.cn), website: [www.caict.ac.cn](http://www.caict.ac.cn)

## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I22Z60412-IOT02	Rev.0	1st edition	2022-05-17
I22Z60412-IOT02	Rev.1	Adding the note “The plot above is the combination results of both vertical and horizontal polarizations” in P37 Modified the Standard and Limit in P50	2022-05-31

## **CONTENTS**

<b>CONTENTS .....</b>	<b>3</b>
<b>1. TEST LATORATORY .....</b>	<b>5</b>
1.1. INTRODUCTION & ACCREDITATION .....	5
1.2. TESTING LOCATION .....	5
1.3. TESTING ENVIRONMENT.....	5
1.4. PROJECT DATE .....	5
1.5. SIGNATURE .....	5
<b>2. CLIENT INFORMATION.....</b>	<b>6</b>
2.1 APPLICANT INFORMATION.....	6
2.2 MANUFACTURER INFORMATION.....	6
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARYEQUIPMENT(AE).....</b>	<b>7</b>
3.1. ABOUT EUT .....	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	7
3.4. GENERAL DESCRIPTION.....	8
3.5. INTERPRETATION OF THE TEST ENVIRONMENT.....	8
<b>4. REFERENCE DOCUMENTS .....</b>	<b>8</b>
4.1. DOCUMENTS SUPPLIED BY APPLICANT .....	8
4.2. REFERENCE DOCUMENTS FOR TESTING.....	8
<b>5. LABORATORY ENVIRONMENT.....</b>	<b>9</b>
<b>6. SUMMARY OF TEST RESULTS .....</b>	<b>9</b>
6.1. SUMMARY OF TEST RESULTS.....	9
6.2. STATEMENTS.....	9
6.3. TEST CONDITIONS .....	9
<b>7. TEST EQUIPMENTS UTILIZED .....</b>	<b>10</b>
<b>8. MEASUREMENT UNCERTAINTY .....</b>	<b>11</b>
8.1 TRANSMITTER OUTPUT POWER.....	11
8.2 PEAK POWER SPECTRAL DENSITY.....	11
8.3 OCCUPIED CHANNEL BANDWIDTH.....	11
8.4 BAND EDGES COMPLIANCE.....	11
8.5 SPURIOUS EMISSIONS .....	11
8.6 AC POWER-LINE CONDUCTED EMISSION.....	11
<b>ANNEX A: MEASUREMENT RESULTS.....</b>	<b>12</b>
A.1. MEASUREMENT METHOD .....	12
A.2. MAXIMUM OUTPUT POWER .....	13



A.3. PEAK POWER SPECTRAL DENSITY (CONDUCTED).....	16
A.4. OCCUPIED 26DB BANDWIDTH(CONDUCTED).....	17
A.5. BAND EDGES COMPLIANCE .....	35
A5.1 BAND EDGES - RADIATED.....	35
A.6. TRANSMITTER SPURIOUS EMISSION .....	50
A.7. AC POWERLINE CONDUCTED EMISSION (150KHZ- 30MHZ).....	78
A.8. 99% OCCUPIED BANDWIDTH .....	83
A.9. POWER CONTROL .....	88
<b>ANNEX B: EUT PARAMETERS.....</b>	<b>88</b>
<b>ANNEX C: ACCREDITATION CERTIFICATE .....</b>	<b>89</b>

## 1. TEST LABORATORY

### 1.1. Introduction & Accreditation

**Telecommunication Technology Labs, CAICT** is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (ISED#: 24849). The detail accreditation scope can be found on NVLAP website.

### 1.2. Testing Location

Conducted testing Location: CTTL(Huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China100191

Radiated testing Location:CTTL(BDA)

Address: No.18A, Kangding Street, Beijing Economic-Technology  
Development Area, Beijing, P. R. China 100176

### 1.3. Testing Environment

Normal Temperature: 15-35°C


Relative Humidity: 20-75%

### 1.4. Project date

Testing Start Date: 2022-03-09


Testing End Date: 2022-05-17

### 1.5. Signature



---

Xie Xiuzhen  
( Prepared this test report )



---

Zheng Wei  
(Reviewed this test report)



---

Hu Xiaoyu  
(Approved this test report)

## **2. CLIENT INFORMATION**

### **2.1 Applicant Information**

Company Name: HMD Global Oy  
Address: Bertel Jungin aukio 9 02600 Espoo Finland  
City: Espoo  
Postal Code: /  
Country: Finland  
Telephone: /  
Fax: /

### **2.2 Manufacturer Information**

Company Name: HMD Global Oy  
Address: Bertel Jungin aukio 9 02600 Espoo Finland  
City: Espoo  
Postal Code: /  
Country: Finland  
Telephone: /  
Fax: /

### 3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)

#### 3.1. About EUT

Description	Smart Phone
Model name	TA-1448
FCC ID	2AJOTTA-1448
WLAN Frequency Band	ISM Bands: -5150MHz~5250MHz -5250MHz~5350MHz -5470MHz~5725MHz
Type of modulation	OFDM
Antenna	Integral Antenna
Voltage	3.8V

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT4	357713910033809	v1.0	TMO: 04US_1_150
EUT1	357713910006227	v1.0	TMO: 04US_1_150

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

AE ID*	Description
AE1	Battery
AE2	Battery
AE3	Charger
AE4	USB Cable
AE5	Headset
AE1	
Model	HQ610
Manufacturer	Ningde Amperex Technology Limited
Capacity	4900mAh
Voltage	3.87V
AE2	
Model	HQ610
Manufacturer	GUANGDONG FENGHUA NEW ENERGY CO., LTD
Capacity	4900mAh
Voltage	3.87V
AE3	
Model	Charger-AD-020US

Manufacturer Aohai  
 AE4  
 Model USB-SHQ-A119A  
 Manufacturer Saibao(Jiangxi)communication Industrial Co.,Ltd  
 AE5  
 Model JWEP239-H17H  
 Manufacturer JUWEI ELECTRONICS CO.,LTD  
 \*AE ID: is used to identify the test sample in the lab internally.

### 3.4. General Description

The Equipment under Test (EUT) is a model of Smart Phone with integrated antenna and inbuilt battery.  
 It has Bluetooth (EDR)function.  
 It consists of normal options: travel charger, USB cable.  
 Manual and specifications of the EUT were provided to fulfil the test.  
 Samples undergoing test were selected by the client.

### 3.5. Interpretation of the Test Environment

For the test methods, the test environment uncertainty figures correspond to an expansion factor k=2.

#### Measurement Uncertainty

Parameter	Uncertainty
temperature	0.48°C
humidity	2 %
DC voltages	0.003V

## 4. REFERENCE DOCUMENTS

### 4.1. Documents supplied by applicant

EUT feature information is supplied by the applicant or manufacturer, which is the basis of testing.

### 4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

FCC Part15	Title 47 of the Code of Federal Regulations; Chapter I Part 15 - Radio frequency devices	2021
ANSI C63.10	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2013
UNII: KDB 789033 D02	General U-NII Test Procedures New Rules v02r01	2017-12



## 5. LABORATORY ENVIRONMENT

Conducted RF performance testing is performed in shielding room.

EMC performance testing is performed in Semi-anechoic chamber.

## 6. SUMMARY OF TEST RESULTS

### 6.1. Summary of Test Results

SUMMARY OF MEASUREMENT RESULTS	Sub-clause of Part15E	Sub-clause of IC	Verdict
Maximum Output Power	15.407	/	P
Peak Power Spectral Density	15.407	/	P
Occupied 26dB Bandwidth	15.403	/	P
Band edge compliance (Radiated)	15.209	/	P
Transmitter spurious emissions (Radiated)	15.407	/	P
AC Powerline Conducted Emission (150kHz- 30MHz)	15.407	/	P
Frequency Stability	15.407	/	P
99% Occupied bandwidth	/	/	P
Transmit Power Control	15.407	/	NA

Please refer to **ANNEX A** for detail.

Terms used in Verdict column

P	Pass, The EUT complies with the essential requirements in the standard.
NM	Not measured, The test was not measured by CTTL
NA	Not Applicable, The test was not applicable
F	Fail, The EUT does not comply with the essential requirements in the standard

### 6.2. Statements

CTTL has evaluated the test cases requested by the client/matrix manufacturer as listed in section 6.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.1.

This report only deals with the WLAN function among the features described in section 3.

### 6.3. Test Conditions

For this report, all the test cases are tested under normal temperature and normal voltage, and also under norm humidity, the specific condition is shown as follows:

Temperature	26°C
Voltage	3.8V
Humidity	44%

## 7. TEST EQUIPMENTS UTILIZED

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ40	200089	Rohde & Schwarz	1 year	2022-05-24
2	LISN	ENV216	101459	R&S	1 year	2023-03-10
3	Test Receiver	ESCI 7	100766	R&S	1 year	2023-03-02
4	Shielding Room	S81	/	ETS-Lindgren	/	/

### Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100376	R&S	1 year	2022-09-15
2	BiLog Antenna	VULB9163	482	Schwarzbeck	1 year	2022-11-16
3	Dual-Ridge Waveguide Horn Antenna	3115	00167252	ETS-Lindgren	1 year	2022-12-26
4	Horn Antenna	LB-7180-N F	J203001300 005	A-INFO	1 year	2023-02-27
5	Spectrum Analyzer	FSV40	101047	Rohde & Schwarz	1 year	2022-06-03

## 8. Measurement Uncertainty

### 8.1 Transmitter Output Power

Measurement Uncertainty: 0.387dB,k=1.96

### 8.2 Peak Power Spectral Density

Measurement Uncertainty: 0.705dB,k=1.96

### 8.3 Occupied Channel Bandwidth

Measurement Uncertainty: 60.80Hz,k=1.96

### 8.4 Band Edges Compliance

Measurement Uncertainty : 0.62dB,k=1.96

### 8.5 Spurious Emissions

#### Conducted (k=1.96)

Frequency Range	Uncertainty(dB)
$30\text{MHz} \leq f \leq 2\text{GHz}$	1.22
$2\text{GHz} \leq f \leq 3.6\text{GHz}$	1.22
$3.6\text{GHz} \leq f \leq 8\text{GHz}$	1.22
$8\text{GHz} \leq f \leq 12.75\text{GHz}$	1.51
$12.75\text{GHz} \leq f \leq 26\text{GHz}$	1.51
$26\text{GHz} \leq f \leq 40\text{GHz}$	1.59

#### Radiated (k=2)

Frequency Range	Uncertainty(dB)
$f \leq 1\text{GHz}$	5.73
$1\text{GHz} \leq f \leq 18\text{GHz}$	5.58
$18\text{GHz} \leq f \leq 40\text{GHz}$	3.37

### 8.6 AC Power-line Conducted Emission


Measurement Uncertainty : 3.10dB,k=2

## ANNEX A: MEASUREMENT RESULTS

### A.1. Measurement Method

#### A.1.1. Conducted Measurements

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode.
- 3). Set the EUT to the required channel.
- 4). Set the spectrum analyzer to start measurement.
- 5). Record the values. Vector Signal Analyzer




#### A.1.2. Radiated Emission Measurements

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 10Hz;



The measurement is made according to KDB 789033

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

## A.2. Maximum output Power

### Measurement Limit and Method:

Standard	Frequency (MHz)	Limit (dBm)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	24dBm
	5250MHz~5350MHz	24dBm or 11+10logB
	5470MHz~5725MHz	24dBm or 11+10logB

Limit use the less value, and B is the 26dB bandwidth.

The measurement method SA-2 is made according to KDB 789033

Note:

For straddle channel 20MHz Bandwidth 5720MHz, Conducted Output Power Limit:

802.11a=11+10\*log(B)=, B=/2+5=MHz,

802.11n-HT20=11+10\*log(B)=, B=/2+5=MHz,

802.11ac-VHT20=11+10\*log(B)=, B=/2+5=MHz,

For straddle channel 40/80MHz Bandwidth, conducted output power limit=24 dBm

802.11n-HT40: B=45.92/2+15=MHz,

802.11ac-VHT40: B=44.96/2+15=MHz,

802.11ac-VHT80: B=86.40/2+15=MHz

### Measurement Results:

#### 802.11a mode

Mode	Frequency	Test Result (dBm)							
		Data Rate (Mbps)							
		6	9	12	18	24	36	48	54
802.11a	5180MHz	14.71	/	/	/	/	/	/	/
	5200MHz	14.61	/	/	/	/	/	/	/
	5240MHz	14.57	/	/	/	/	/	/	/
	5260MHz	14.59	/	/	/	/	/	/	/
	5280MHz	14.85	/	/	/	/	/	/	/
	5320MHz	15.84	/	/	/	/	/	/	/
	5500MHz	15.42	/	/	/	/	/	/	/
	5580MHz	15.11	/	/	/	/	/	/	/
	5700MHz	15.76	/	/	/	/	/	/	/
	5720MHz	15.41	/	/	/	/	/	/	/

The data rate 6Mbps is selected as worse condition, and the following cases are performed with this condition.

**802.11n-HT20 mode**

Mode	Frequency	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT20)	5180MHz	14.80	/	/	/	/	/	/	/
	5200MHz	15.02	/	/	/	/	/	/	/
	5240MHz	15.86	/	/	/	/	/	/	/
	5260MHz	16.05	/	/	/	/	/	/	/
	5280MHz	16.13	/	/	/	/	/	/	/
	5320MHz	15.88	/	/	/	/	/	/	/
	5500MHz	15.49	/	/	/	/	/	/	/
	5580MHz	16.05	/	/	/	/	/	/	/
	5700MHz	15.10	/	/	/	/	/	/	/
	5720MHz	15.17	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

**802.11ac-HT20 mode**

Mode	Frequency	Test Result (dBm)								
		Data Rate								
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8
802.11ac (HT20)	5180MHz	13.39	/	/	/	/	/	/	/	/
	5200MHz	13.58	/	/	/	/	/	/	/	/
	5240MHz	14.49	/	/	/	/	/	/	/	/
	5260MHz	14.66	/	/	/	/	/	/	/	/
	5280MHz	14.73	/	/	/	/	/	/	/	/
	5320MHz	14.41	/	/	/	/	/	/	/	/
	5500MHz	14.16	/	/	/	/	/	/	/	/
	5580MHz	14.54	/	/	/	/	/	/	/	/
	5700MHz	13.69	/	/	/	/	/	/	/	/
	5720MHz	13.88	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

**802.11n-HT40 mode**

Mode	Frequency	Test Result (dBm)							
		Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
802.11n (HT40)	5190MHz	13.09	/	/	/	/	/	/	/
	5230MHz	13.85	/	/	/	/	/	/	/
	5270MHz	14.48	/	/	/	/	/	/	/
	5310MHz	14.62	/	/	/	/	/	/	/
	5510MHz	13.89	/	/	/	/	/	/	/
	5550MHz	14.04	/	/	/	/	/	/	/
	5670MHz	13.73	/	/	/	/	/	/	/
	5710MHz	13.53	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

**802.11ac-HT40 mode**

Mode	Frequency	Test Result (dBm)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
802.11ac (HT40)	5190MHz	11.66	/	/	/	/	/	/	/	/	/
	5230MHz	12.43	/	/	/	/	/	/	/	/	/
	5270MHz	13.11	/	/	/	/	/	/	/	/	/
	5310MHz	13.07	/	/	/	/	/	/	/	/	/
	5510MHz	12.67	/	/	/	/	/	/	/	/	/
	5550MHz	12.96	/	/	/	/	/	/	/	/	/
	5670MHz	12.37	/	/	/	/	/	/	/	/	/
	5710MHz	12.26	/	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

**802.11ac-HT80 mode**

Mode	Frequency	Test Result (dBm)									
		Data Rate									
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9
802.11ac (HT80)	5210MHz	9.65	/	/	/	/	/	/	/	/	/
	5290MHz	10.57	/	/	/	/	/	/	/	/	/
	5530MHz	10.28	/	/	/	/	/	/	/	/	/
	5610MHz	10.68	/	/	/	/	/	/	/	/	/
	5690MHz	9.79	/	/	/	/	/	/	/	/	/

The data rate MCS0 is selected as worse condition, and the following cases are performed with this condition.

### A.3. Peak Power Spectral Density (conducted)

#### Measurement Limit:

Standard	Frequency (MHz)	Limit (dBm/MHz)
FCC CRF Part 15.407(a)	5150MHz~5250MHz	11
	5250MHz~5350MHz	11
	5470MHz~5725MHz	11

The output power measurement method Section F is made according to KDB 789033

#### Measurement Results:

Mode	Frequency	Power Spectral Density (dBm/MHz)	Conclusion
802.11a	5180 MHz	4.51	P
	5200 MHz	4.62	P
	5240 MHz	5.68	P
	5260 MHz	5.71	P
	5280 MHz	5.76	P
	5320 MHz	5.53	P
	5500 MHz	4.38	P
	5580 MHz	4.98	P
	5700 MHz	4.00	P
	5720 MHz	3.89	P
802.11n HT20	5180 MHz	4.03	P
	5200 MHz	4.17	P
	5240 MHz	5.27	P
	5260 MHz	5.30	P
	5280 MHz	5.35	P
	5320 MHz	5.11	P
	5500 MHz	4.04	P
	5580 MHz	4.49	P
	5700 MHz	3.56	P
	5720 MHz	3.46	P
802.11n HT40	5190 MHz	-2.44	P
	5230 MHz	-1.35	P
	5270 MHz	-0.41	P
	5310 MHz	-0.16	P
	5510 MHz	-0.81	P
	5550 MHz	-0.65	P
	5670 MHz	-0.84	P
	5710 MHz	-1.05	P
802.11ac HT80	5210MHz	-9.03	P
	5290MHz	-7.46	P
	5530MHz	-7.78	P



	5610MHz	-7.07	P
	5690MHz	-8.1	P

**Conclusion: PASS**

#### A.4. Occupied 26dB Bandwidth(conducted)

**Measurement Limit:**

Standard	Limit (kHz)
FCC 47 CFR Part 15.403 (i)	/

The measurement is made according to KDB 789033

**Measurement Uncertainty:**

Measurement Uncertainty	60.80Hz
-------------------------	---------


**Measurement Result:**

Mode	Frequency	Occupied 26dB Bandwidth ( MHz)		conclusion
802.11a	5180 MHz	Fig.1	25.80	P
	5200 MHz	Fig.2	26.15	P
	5240 MHz	Fig.3	25.80	P
	5260 MHz	Fig.4	25.70	P
	5280 MHz	Fig.5	26.15	P
	5320 MHz	Fig.6	25.75	P
	5500 MHz	Fig.7	25.40	P
	5580 MHz	Fig.8	24.45	P
	5700 MHz	Fig.9	24.20	P
	5720 MHz	Fig.10	24.30	P
802.11n HT20	5180 MHz	Fig.11	23.45	P
	5200 MHz	Fig.12	26.30	P
	5240 MHz	Fig.13	25.40	P
	5260 MHz	Fig.14	25.00	P
	5280 MHz	Fig.15	26.10	P
	5320 MHz	Fig.16	25.90	P
	5500 MHz	Fig.17	25.55	P
	5580 MHz	Fig.18	24.45	P
	5700 MHz	Fig.19	24.75	P
	5720 MHz	Fig.20	26.05	P
802.11n HT40	5190 MHz	Fig.21	26.05	P
	5230 MHz	Fig.22	41.75	P
	5270 MHz	Fig.23	42.00	P
	5310 MHz	Fig.24	41.92	P

	5510 MHz	Fig.25	41.84	P
	5550 MHz	Fig.26	41.76	P
	5670 MHz	Fig.27	42.40	P
	5710 MHz	Fig.28	42.32	P
802.11ac HT80	5210MHz	Fig.29	84.32	P
	5290MHz	Fig.30	84.32	P
	5530MHz	Fig.31	84.48	P
	5610MHz	Fig.32	84.64	P
	5690MHz	Fig.33	84.48	P

**Conclusion: PASS**

**Test graphs as below:**



**Fig.1 Occupied 26dB Bandwidth (802.11a, 5180MHz)**




Fig.2 Occupied 26dB Bandwidth (802.11a, 5200MHz)






Fig.3 Occupied 26dB Bandwidth (802.11a, 5240MHz)



**Fig.4 Occupied 26dB Bandwidth (802.11a, 5260MHz)**



**Fig.5 Occupied 26dB Bandwidth (802.11a, 5280MHz)**




Fig.6 Occupied 26dB Bandwidth (802.11a, 5320MHz)







Fig.7 Occupied 26dB Bandwidth (802.11a, 5500MHz)




**Fig.8 Occupied 26dB Bandwidth (802.11a, 5580MHz)**



**Fig.9 Occupied 26dB Bandwidth (802.11a, 5700MHz)**



**Fig.10 Occupied 26dB Bandwidth (802.11a, 5720MHz)**



**Fig.11 Occupied 26dB Bandwidth (802.11n-HT20, 5180MHz)**




Fig.12 Occupied 26dB Bandwidth (802.11n-HT20, 5200MHz)






Fig.13 Occupied 26dB Bandwidth (802.11n-HT20, 5240MHz)







**Fig.14 Occupied 26dB Bandwidth (802.11n-HT20, 5260MHz)**



**Fig.15 Occupied 26dB Bandwidth (802.11n-HT20, 5280MHz)**



**Fig.16 Occupied 26dB Bandwidth (802.11n-HT20, 5320MHz)**



**Fig.17 Occupied 26dB Bandwidth (802.11n-HT20, 5500MHz)**




Fig.18 Occupied 26dB Bandwidth (802. 11n-HT20, 5580MHz)






Fig.19 Occupied 26dB Bandwidth (802. 11n-HT20, 5700MHz)



**Fig.20 Occupied 26dB Bandwidth (802. 11n-HT20, 5720MHz)**



**Fig.21 Occupied 26dB Bandwidth (802.11n-HT40, 5190MHz)**