

FCC TEST REPORT

(Part 15, Subpart C)



Applicant:	HMD Global Oy
Address:	Bertel Jungin aukio 9,02600 Espoo,Finland

Manufacturer or Supplier:	HMD Global Oy
Address:	Bertel Jungin aukio 9,02600 Espoo,Finland
Product:	Mobile phone
Brand Name:	NOKIA
Model Name:	TA-1542
FCC ID:	2AJOTTA-1542
Date of tests:	Feb. 02, 2023 ~ Mar. 02, 2023

The tests have been carried out according to the requirements of the following standard:

- FCC Part 15, Subpart C, Section 15.247**
- ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Chao Wu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
 Date: Mar. 02, 2023	 Date: Mar. 02, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1 SUMMARY OF TEST RESULTS	6
1.1 MEASUREMENT UNCERTAINTY	7
2 GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	11
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	12
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	12
2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	14
2.4 DESCRIPTION OF SUPPORT UNITS	14
3 TEST TYPES AND RESULTS	15
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	15
3.1.2 TEST INSTRUMENTS	15
3.1.3 TEST PROCEDURES	15
3.1.4 DEVIATION FROM TEST STANDARD	16
3.1.5 TEST SETUP	16
3.1.6 EUT OPERATING CONDITIONS	16
3.1.7 TEST RESULTS	17
3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT	19
3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	19
3.2.2 TEST INSTRUMENTS	20
3.2.3 TEST PROCEDURES	21
3.2.4 DEVIATION FROM TEST STANDARD	21
3.2.5 TEST SETUP	22
3.2.6 EUT OPERATING CONDITIONS	23
3.2.7 TEST RESULTS	24
3.3 NUMBER OF HOPPING FREQUENCY USED	57
3.3.1 LIMIT OF HOPPING FREQUENCY USED	57
3.3.2 TEST SETUP	57
3.3.3 TEST INSTRUMENTS	57
3.3.4 TEST PROCEDURES	58
3.3.5 DEVIATION FROM TEST STANDARD	58
3.3.6 TEST RESULTS	58



3.4	DWELL TIME ON EACH CHANNEL	59
3.4.1	LIMIT OF DWELL TIME USED	59
3.4.2	TEST SETUP	59
3.4.3	TEST INSTRUMENTS	59
3.4.4	TEST PROCEDURES	59
3.4.5	DEVIATION FROM TEST STANDARD	60
3.4.6	TEST RESULTS	60
3.5	CHANNEL BANDWIDTH	61
3.5.1	LIMITS OF CHANNEL BANDWIDTH	61
3.5.2	TEST SETUP	61
3.5.3	TEST INSTRUMENTS	61
3.5.4	TEST PROCEDURE	61
3.5.5	DEVIATION FROM TEST STANDARD	61
3.5.6	EUT OPERATING CONDITION	62
3.5.7	TEST RESULTS	62
3.6	HOPPING CHANNEL SEPARATION	63
3.6.1	LIMIT OF HOPPING CHANNEL SEPARATION	63
3.6.2	TEST SETUP	63
3.6.3	TEST INSTRUMENTS	63
3.6.4	TEST PROCEDURES	63
3.6.5	DEVIATION FROM TEST STANDARD	63
3.6.6	TEST RESULTS	64
3.7	MAXIMUM OUTPUT POWER	65
3.7.1	LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT	65
3.7.2	TEST SETUP	65
3.7.3	TEST INSTRUMENTS	65
3.7.4	TEST PROCEDURES	65
3.7.5	DEVIATION FROM TEST STANDARD	66
3.7.6	EUT OPERATING CONDITION	66
3.7.7	TEST RESULTS	67
3.7.7.1	MAXIMUM PEAK OUTPUT POWER	67
3.7.7.2	Average Output Power (FOR REFERENCE)	68
3.8	OUT OF BAND MEASUREMENT	69
3.8.1	LIMITS OF OUT OF BAND MEASUREMENT	69
3.8.2	TEST INSTRUMENTS	69
3.8.3	TEST PROCEDURE	69
3.8.4	DEVIATION FROM TEST STANDARD	69



3.8.5	EUT OPERATING CONDITION	69
3.8.6	TEST RESULTS	69
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	70
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	71
6	APPENDIX	72
	20DB EMISSION BANDWIDTH	72
	TEST RESULT	72
	TEST GRAPHS	73
	OCCUPIED CHANNEL BANDWIDTH	78
	TEST RESULT	78
	TEST GRAPHS	79
	MAXIMUM CONDUCTED OUTPUT POWER	84
	TEST RESULT PEAK	84
	TEST RESULT AVERAGE	84
	CARRIER FREQUENCY SEPARATION	85
	TEST RESULT	85
	TEST GRAPHS	86
	TIME OF OCCUPANCY	88
	TEST RESULT	88
	TEST GRAPHS	89
	NUMBER OF HOPPING CHANNELS	98
	TEST RESULT	98
	TEST GRAPHS	99
	BAND EDGE MEASUREMENTS	102
	TEST RESULT	102
	TEST GRAPHS	103
	CONDUCTED SPURIOUS EMISSION	109
	TEST RESULT	109
	TEST GRAPHS	110
	DUTY CYCLE	119
	TEST RESULT	119
	TEST GRAPHS	120



BUREAU
VERITAS

Test Report No.: W7L-P23010016RF05

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P23010016RF05	Original release	Mar. 02, 2023



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD	TEST TYPE AND LIMIT	RESULT	TEST LAB*
15.207	AC Power Conducted Emission	Compliance	A
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Compliance	A
15.247(a)(1) (iii)	Dwell Time on Each Channel	Compliance	A
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Compliance	A
15.247(b)	Maximum Peak Output Power	Compliance	A
15.247(d)& 15.209	Transmitter Radiated Emissions	Compliance	A
15.247(d)	Out of band Measurement	Compliance	A
15.203	Antenna Requirement	Compliance	A

NOTE:

1. If the Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.
2. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.
3. This report refers to the data of W7L-P23010015RF01(model:TA-1558, FCC ID: 2AJOTTA-1558), the difference of TA-1558 and TA-1542 is TA-1542 change model name, TA-1558 is dual card, TA-1542 is single card, and functions are realized through software. The test data of this report is copied from the report W7L-P23010015RF01(model:TA-1558, FCC ID: 2AJOTTA-1558).

***Test Lab Information Reference**

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zhuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.



1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (30MHz~1GMHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GMHz ~6GMHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GMHz ~18GMHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GMHz ~40GMHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile phone
BRAND NAME	NOKIA
MODEL NAME	TA-1542
NOMINAL VOLTAGE	3.85Vdc (Li-ion, battery) 5.0Vdc (adapter)
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, $\pi/4$ DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	10.28mW (Max. Measured)
ANTENNA TYPE	PIFA Antenna with 1.2dBi gain
HW VERSION	SPR_S63Q0
SW VERSION	00WW_0_122
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB cable1: non-shielded cable, with w/o ferrite core, 1 meter USB cable2: non-shielded cable, with w/o ferrite core, 1 meter USB cable3: non-shielded cable, with w/o ferrite core, 1 meter Earphone: non-shielded cable, with w/o ferrite core, 1.2 meter

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. The product of TA-1542(FCC ID: 2AJOTTA-1542), only the following manufacturer of key parts is different between the first and second supply, other parameters are the same. The details are as follows:

NO.	Change Description	specificatons	first supplier	specificatons	second supplier	
1	PCBA	64GB EMMC	FEMDNN064G-A3A56 BWCTARV11X64G	Longsys	FEMDNN064G-A3A56 BWCTARV11X64G	Biwin
		128GB EMMC	FEMDNN128G-A3A56 BWCTAKJ21X128G	Longsys	FEMDNN128G-A3A56 BWCTAKJ21X128G	Biwin
		3GB	FLXC4003G-50	Longsys	FLXC4003G-50	Biwin



		LPDDR	BWMEXX32H2A-24Gb-X		BWMEXX32H2A-24Gb-X	
		4GB LPDDR	FLXC2004G-30 BWMZCX32H2A-32G-X	Longsys	FLXC2004G-30 BWMZCX32H2A-32G-X	Biwin
		PCB	/	KINGSHINE	/	wuzhu
2	LCM	LCD	6.517 HKC, 360min,400typ, 2.5D	TCL	6.517 HKC, 360min,400typ, 2.5D	Lia
3	Front camera	Camera	8M FF COM	Lianhe	8M FF COM	Shijia
4	Macro CAM	Camera	2M FF	Shijia	2M FF	Lianhe
5	Acoustic	Speaker	1712 1W	Dong Sheng	1712 1W	Xin Rongda
		Vibrator	1027 FPC	Chao Yin	1027 FPC	Kai Long
		Receiver	0809	Dong Sheng	0809	Xin Rongda
		Glass rear cover	Glass, monochrome printing or film	Kaimao	Glass, monochrome printing or film	Longqin gxiangrui
		FPC	/	Lante	/	Kaihong xin
6	Battery		5000MAH	Gaoyuan	5000MAH	Fenghua
7	Data cable		2A typeC	Yuwei	2A typeC	Juwei



4. List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
LCD Panel 1	HKC	MianYang HKC Optoelectronics Technology Co., Ltd.	QM065HS03-1	6.517
LCD Panel 2	BOE	BOE	BV065WBQ-L1B	6.517
Battery 1	Nokia	Guangdong Fenghua New Energy Co.,Ltd.	WT510	Capacity : 3.85 Vdc, 4900mAh
Battery 2	Nokia	HUNAN GAOYUAN BATTERY Co., Ltd.	WT510	Capacity : 3.85 Vdc, 4900mAh
AC Adapter	Nokia	SHENZHEN BAIJUNDA ELECTRONICS.,LTD	AD-010U	I/P: 100-240Vac, 0.35A, O/P: 5.0Vdc, 2.0A
Earphone	Juwei Electronics Co., LTD	Juwei Electronics Co., LTD	JWEP1252-H21H	Signal Line, 1.2meter
USB Cable 1	Juwei Electronics Co., LTD	Juwei Electronics Co., LTD	JWUB1536-H21H	Signal Line, 1.0meter
USB Cable 2	Yu Wei	Dongguan Yuwei Electronic Technology Co., Ltd.	CH2212TC	Signal Line, 1.0meter
USB Cable 3	Sai bao	Saibao (Jiangxi) Industrial Co., Ltd	SHM1-A003A	Signal Line, 1.0meter



2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	GFSK	DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5



POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH1/DH3/DH5
0 to 78	0, 39, 78	FHSS	$\pi/4$ DQPSK	2DH1/2DH3/2DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH1/3DH3/3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V By Adapter	Jace Hu
RE≥1G	23deg. C, 70%RH	DC 5V By Adapter	Jace Hu
PLC	25deg. C, 52%RH	DC 5V By Adapter	James Fu
APCM	25deg. C, 60%RH	DC 3.85V By Battery	James Fu



2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247 **ANSI C63.10-2013**

- NOTE:**
1. All test items have been performed and recorded as per the above standards.
 2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	Thnikpad L440	R90FTFKN	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Feb.25,22	Feb.24,24
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Feb.17,22	Feb.16,24
CABLE	Rohde&Schwarz	W61.01	N/A	Oct.31,22	Apr.29,23
CABLE	Rohde&Schwarz	W601	N/A	Oct.31,22	Apr.29,23

- NOTE:**
1. The test was performed in CE shielded room.
 2. The calibration interval of the above test instruments is 6 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels


under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.




3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Chao Wu		

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.159	38.51	65.52	27.01	20.86	55.52	34.66	10.38	L1	9.000
1	0.681	39.51	56.00	16.49	25.16	46.00	20.84	9.89	L1	9.000
1	1.397	20.77	56.00	35.23	9.62	46.00	36.38	9.69	L1	9.000
1	2.693	23.30	56.00	32.70	10.62	46.00	35.38	9.63	L1	9.000
1	4.871	26.50	56.00	29.50	14.05	46.00	31.95	9.61	L1	9.000
1	11.778	41.92	60.00	18.08	25.49	50.00	24.51	9.66	L1	9.000

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Limit value - Emission level
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Chao Wu		

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.393	32.85	58.00	25.15	18.30	48.00	29.70	9.95	N	9.000
1	0.672	44.87	56.00	11.13	34.58	46.00	11.42	9.90	N	9.000
1	1.919	30.00	56.00	26.00	19.56	46.00	26.44	9.65	N	9.000
1	3.611	29.04	56.00	26.96	17.91	46.00	28.09	9.62	N	9.000
1	6.657	32.83	60.00	27.17	23.07	50.00	26.93	9.62	N	9.000
1	11.409	41.95	60.00	18.05	31.07	50.00	18.93	9.68	N	9.000

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Limit value - Emission level
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





3.2 RADIATED EMISSION AND BANDEGE MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION AND BANDEGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,22	Aug.29,24
Pre-Amplifier	R&S	SCU08F1	101028	Sep.16,22	Sep.15,24
Signal Generator	R&S	SMB100A	182185	Feb.16,22	Feb.15,24
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-E MC-01 Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-E MC-02 Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Feb.25,22	Feb.24,24
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.28,22	Feb.27,24
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,22	Aug.21,24
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Feb.23,22	Feb.22,24
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.22,22	Aug.21,24
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.23,22	Feb.22,24
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.27,22	Jun.26,24
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.31,22	Aug.30,24
Hygrothermograph	DELI	20210528	SZ014	Sep.06,22	Sep.05,24
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Oct.31,22	Apr.29,23
CABLE	R&S	W12.14	N/A	Oct.31,22	Apr.29,23

- NOTE:**
1. The calibration interval of the above test instruments is 6 months or 24 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.

3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation.




3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA:


30 MHz – 1GHz data:

BT_GFSK

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	50.176	17.74	40.00	22.26	-18.00	H	161.2	2	120.000
1	96.009	6.48	43.50	37.02	-21.93	H	161.2	2	120.000
1	122.538	-4.58	43.50	48.08	-24.82	H	62.6	2	120.000
1	209.499	8.05	43.50	35.45	-23.66	H	99.3	1	120.000
1	393.120	0.60	46.00	45.40	-20.44	H	5	1	120.000
1	837.768	7.22	46.00	38.78	-13.22	H	359	2	120.000





**BUREAU
VERITAS**

Test Report No.: W7L-P23010016RF05

REMARKS:


1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.



CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	43.677	15.77	40.00	24.23	-17.03	V	296.5	1	120.000
1	65.211	4.20	40.00	35.80	-20.53	V	296.5	1	120.000
1	104.108	-0.91	43.50	44.41	-21.70	V	296.5	1	120.000
1	183.745	-3.72	43.50	47.22	-24.98	V	197.9	1	120.000
1	321.097	-0.66	46.00	46.66	-21.90	V	197.9	1	120.000
1	386.863	0.67	46.00	45.33	-19.96	V	5	1	120.000



REMARKS:

1. Emission Level(dBuV/m) = Read Level(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission level.



ABOVE 1GHz WORST-CASE DATA:

Note: 1. For radiated emissions testing the full testing range of different modes have been scanned only the worst case harmonic data is reported in the sheet.

2. All other emissions that greater than 20dB below the limit were not recorded

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,374.500	29.13	54.00	24.87	9.72	H	242	2
1	2,390.000	29.88	54.00	24.12	9.84	H	70.1	1
1	2,402.000	96.86			9.85	H	217	2





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,385.000	42.37	74.00	31.63	9.80	H	359	2
1	2,390.000	42.55	74.00	31.45	9.84	H	195.6	1
1	2,402.500	100.00			9.85	H	215.8	2






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,378.500	29.29	54.00	24.71	9.75	V	169.3	1
1	2,390.000	29.85	54.00	24.15	9.84	V	357.4	1
1	2,402.500	86.26			9.85	V	141.8	1





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,376.000	43.27	74.00	30.73	9.73	V	0.9	2
1	2,390.000	42.46	74.00	31.54	9.84	V	91.4	2
1	2,402.500	92.01			9.85	V	170.5	1



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,881.485	52.18	74.00	21.82	40.30	54.00	13.70	15.95	H	359	2
3	6,290.779	56.28	74.00	17.72	44.19	54.00	9.81	21.06	H	359	2





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,880.515	52.22	74.00	21.78	40.31	54.00	13.69	15.95	V	135.8	2
3	5,778.794	62.66	74.00	11.34	46.64	54.00	7.36	19.16	V	0.9	2



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2441MHz: Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.000	94.14			9.89	H	180	1
1	2,483.500	30.68	54.00	23.32	9.88	H	234.9	2
1	2,484.000	30.43	54.00	23.57	9.88	H	234.9	2






Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.000	95.24			9.89	H	257.5	2
1	2,483.500	43.75	74.00	30.25	9.88	H	129.7	2
1	2,484.000	42.32	74.00	31.68	9.88	H	358.4	1






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.000	86.75			9.89	V	165.6	1
1	2,483.500	29.41	54.00	24.59	9.88	V	165.6	1
1	2,484.000	29.12	54.00	24.88	9.88	V	357.8	1





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.500	89.95			9.89	V	131	2
1	2,483.500	41.81	74.00	32.19	9.88	V	24.6	1
1	2,484.500	43.45	74.00	30.55	9.88	V	105.8	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2480MHz: Fundamental frequency.




BT_π/4-DQPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,364.500	29.57	54.00	24.43	9.64	H	0.9	2
1	2,390.000	29.78	54.00	24.22	9.84	H	156	1
1	2,402.000	94.40			9.85	H	211	2






Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,375.000	42.49	74.00	31.51	9.72	H	189.5	2
1	2,390.000	42.60	74.00	31.40	9.84	H	263.6	2
1	2,402.000	99.57			9.85	H	214.6	2






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,384.000	29.29	54.00	24.71	9.79	V	209.8	2
1	2,390.000	29.72	54.00	24.28	9.84	V	1	1
1	2,402.000	88.03			9.85	V	153.6	1





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.500	43.76	74.00	30.24	9.83	V	249.4	1
1	2,390.000	42.71	74.00	31.29	9.84	V	25.7	2
1	2,402.500	91.73			9.85	V	134.7	1



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,882.941	51.84	74.00	22.16	40.20	54.00	13.80	15.95	H	1	1
3	6,202.941	56.65	74.00	17.35	43.74	54.00	10.26	20.90	H	133.4	2





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,882.941	52.20	74.00	21.80	40.41	54.00	13.59	15.95	V	359	2
3	6,254.382	57.08	74.00	16.92	43.97	54.00	10.03	21.18	V	359	2



REMARKS:


- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
- 2441MHz: Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.000	90.84			9.89	H	233.7	2
1	2,483.500	33.03	54.00	20.97	9.88	H	183.6	1
1	2,484.000	32.06	54.00	21.94	9.88	H	183.6	1






Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.500	96.58			9.89	H	181.2	1
1	2,483.500	49.49	74.00	24.51	9.88	H	181.2	1
1	2,484.000	45.34	74.00	28.66	9.88	H	181.2	1






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.000	84.07			9.89	V	153.7	1
1	2,483.500	29.84	54.00	24.16	9.88	V	126.1	2
1	2,485.000	29.59	54.00	24.41	9.88	V	284.1	1





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.500	88.96			9.89	V	153.7	1
1	2,483.500	42.59	74.00	31.41	9.88	V	1	2
1	2,487.000	41.67	74.00	32.33	9.87	V	256.5	1



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2480MHz: Fundamental frequency.



BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,364.500	29.52	54.00	24.48	9.64	H	137	2
1	2,390.000	30.06	54.00	23.94	9.84	H	187	2
1	2,402.000	95.00			9.85	H	212.2	2





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,382.000	42.83	74.00	31.17	9.78	H	0.9	2
1	2,390.000	41.87	74.00	32.13	9.84	H	83	2
1	2,402.000	99.67			9.85	H	211	2






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,364.000	29.65	54.00	24.35	9.64	V	151.2	2
1	2,390.000	29.81	54.00	24.19	9.84	V	201.4	2
1	2,402.500	86.43			9.85	V	157.2	1





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,377.000	42.54	74.00	31.46	9.74	V	2.6	2
1	2,390.000	41.95	74.00	32.05	9.84	V	1	1
1	2,402.000	91.56			9.85	V	152.5	1



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2402MHz: Fundamental frequency.




**BUREAU
VERITAS**

Test Report No.: W7L-P23010016RF05

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,882.941	52.42	74.00	21.58	40.03	54.00	13.97	15.95	H	359	1
3	6,283.500	56.57	74.00	17.43	43.73	54.00	10.27	21.09	H	224.2	1





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,882.941	53.11	74.00	20.89	40.22	54.00	13.78	15.95	V	134.6	2
3	6,288.838	56.30	74.00	17.70	44.00	54.00	10.00	21.07	V	1	2



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2441MHz: Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)


ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.500	89.74			9.89	H	203.9	2
1	2,483.500	31.90	54.00	22.10	9.88	H	228.9	2
1	2,484.500	30.57	54.00	23.43	9.88	H	258.8	2






Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.500	96.42			9.89	H	233.7	2
1	2,483.500	47.29	74.00	26.71	9.88	H	233.7	2
1	2,484.500	43.72	74.00	30.28	9.88	H	178.8	1





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.000	84.07			9.89	V	128.5	2
1	2,483.500	30.11	54.00	23.89	9.88	V	138.2	1
1	2,484.500	29.66	54.00	24.34	9.88	V	107.1	1





Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,480.000	88.00			9.89	V	151.4	1
1	2,483.500	42.03	74.00	31.97	9.88	V	336.6	2
1	2,484.500	41.79	74.00	32.21	9.88	V	282.7	2



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
Margin value = Limit value – Emission level.
2. 2480MHz: Fundamental frequency.

3.3 NUMBER OF HOPPING FREQUENCY USED

3.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

3.3.2 TEST SETUP



3.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	R&S	ESW 44	101973	Feb.25,22	Feb.24,24
Open Switch and Control Unit	R&S	OSP-B157W 8	100836	N/A	N/A
Vector Signal Generator	R&S	SMBV100B	102176	Feb.16,22	Feb.15,24
Signal Generator	R&S	SMB100A03	182185	Feb.16,22	Feb.15,24
Wideband Radio Communication	R&S	CMW500	169399	Jun.26,22	Jun.25,24
Hygrothermograph	DELI	20210528	SZ015	Sep.06,22	Sep.05,24
PC	LENOVO	E14	HRSW0024	N/A	N/A
CABLE	R&S	J12J103539- 00-1	SEP-03-20-069	Oct.31,22	Apr.29,23
CABLE	R&S	J12J103539- 00-1	SEP-03-20-070	Oct.31,22	Apr.29,23
Test Software	EMC32	EMC32	N/A	N/A	N/A
Temperature Chamber	votsch	VT4002	58566078100050	May.31,22	May.30,24

NOTE:

1. The calibration interval of the above test instruments is 6 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.



3.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

3.3.5 DEVIATION FROM TEST STANDARD

No deviation.

3.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

Please Refer to Appendix Of this test report.




3.4 DWELL TIME ON EACH CHANNEL

3.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.



**BUREAU
VERITAS**

Test Report No.: W7L-P23010016RF05

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 TEST RESULTS

Please Refer to Appendix Of this test report




3.5 CHANNEL BANDWIDTH

3.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.



3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.5.7 TEST RESULTS

Please Refer to Appendix Of this test report.




3.6 HOPPING CHANNEL SEPARATION

3.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.



**BUREAU
VERITAS**

Test Report No.: W7L-P23010016RF05

3.6.6 TEST RESULTS

Please Refer to Appendix Of this test report.




3.7 MAXIMUM OUTPUT POWER

3.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

3.7.2 TEST SETUP



3.7.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.



3.7.5 DEVIATION FROM TEST STANDARD

No deviation.

3.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



**BUREAU
VERITAS**

Test Report No.: W7L-P23010016RF05

3.7.7 TEST RESULTS

3.7.7.1 MAXIMUM PEAK OUTPUT POWER

Please Refer to Appendix Of this test report.



3.7.7.2 Average Output Power (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

Please Refer to Appendix Of this test report.



3.8 OUT OF BAND MEASUREMENT

3.8.1 LIMITS OF OUT OF BAND MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

3.8.2 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

3.8.4 DEVIATION FROM TEST STANDARD

No deviation.

3.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Please Refer to Appendix Of this test report.



Test Report No.: W7L-P23010016RF05

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.



6 APPENDIX


20DB EMISSION BANDWIDTH


TEST RESULT

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.9407	2401.531	2402.471	---	PASS
		2441	0.9378	2440.531	2441.468	---	PASS
		2480	0.9378	2479.531	2480.468	---	PASS
2DH5	Ant1	2402	1.2822	2401.363	2402.645	---	PASS
		2441	1.2822	2440.360	2441.642	---	PASS
		2480	1.2793	2479.360	2480.639	---	PASS
3DH5	Ant1	2402	1.2880	2401.345	2402.633	---	PASS
		2441	1.2880	2440.348	2441.636	---	PASS
		2480	1.2880	2479.348	2480.636	---	PASS




TEST GRAPHS







DH5_Ant1_2441



DH5_Ant1_2480



2DH5_Ant1_2402




2DH5_Ant1_2441




BUREAU VERITAS

Test Report No.: W7L-P23010016RF05



2DH5_Ant1_2480




3DH5_Ant1_2402




BUREAU
VERITAS

Test Report No.: W7L-P23010016RF05



3DH5_Ant1_2441



3DH5_Ant1_2480




OCCUPIED CHANNEL BANDWIDTH


TEST RESULT

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.8567	2401.562	2402.419	---	PASS
		2441	0.8567	2440.562	2441.419	---	PASS
		2480	0.8567	2479.560	2480.416	---	PASS
2DH5	Ant1	2402	1.1895	2401.397	2402.587	---	PASS
		2441	1.1808	2440.400	2441.581	---	PASS
		2480	1.1808	2479.400	2480.581	---	PASS
3DH5	Ant1	2402	1.1866	2401.400	2402.587	---	PASS
		2441	1.1808	2440.403	2441.584	---	PASS
		2480	1.1780	2479.403	2480.581	---	PASS




TEST GRAPHS






Date: 19.FEB.2023 01:36:09

DH5_Ant1_2441




Date: 19.FEB.2023 01:35:42

DH5_Ant1_2480




Date: 19.FEB.2023 01:34:24

2DH5_Ant1_2402




Date: 19.FEB.2023 01:34:46

2DH5_Ant1_2441




Date: 19.FEB.2023 01:35:11

2DH5_Ant1_2480




Date: 19.FEB.2023 01:33:57

3DH5_Ant1_2402



Date: 19.FEB.2023 01:33:33

3DH5_Ant1_2441



Date: 19.FEB.2023 01:32:51

3DH5_Ant1_2480



MAXIMUM CONDUCTED OUTPUT POWER

TEST RESULT PEAK

TestMode	Antenna	Channel	Peak Power[dBm]	Peak Power[mw]	Conducted Limit[mw]	Verdict	Power setting
DH5	Ant1	2402	8.72	7.44	≤125	PASS	4
		2441	8.54	7.14	≤125	PASS	4
		2480	6.94	4.45	≤125	PASS	4
2DH5	Ant1	2402	10.02	10.04	≤125	PASS	4
		2441	9.01	7.96	≤125	PASS	4
		2480	7.63	5.79	≤125	PASS	4
3DH5	Ant1	2402	10.12	10.28	≤125	PASS	4
		2441	9.18	8.27	≤125	PASS	4
		2480	7.83	6.06	≤125	PASS	4

TEST RESULT AVERAGE

TestMode	Antenna	Channel	Average Power	Conducted Limit[dBm]	Verdict	Power setting
DH5	Ant1	2402	8.64	/	PASS	4
		2441	8.32	/	PASS	4
		2480	6.69	/	PASS	4
2DH5	Ant1	2402	7.83	/	PASS	4
		2441	6.58	/	PASS	4
		2480	5.23	/	PASS	4
3DH5	Ant1	2402	7.79	/	PASS	4
		2441	6.55	/	PASS	4
		2480	5.24	/	PASS	4




CARRIER FREQUENCY SEPARATION


TEST RESULT

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	Hop	1.0029	≥0.6271	PASS
2DH5	Ant1	Hop	0.9986	≥0.8548	PASS
3DH5	Ant1	Hop	1.0072	≥0.8586	PASS




TEST GRAPHS





Date: 19.FEB.2023 01:48:34

2DH5_Ant1_Hop



Date: 19.FEB.2023 01:50:06

3DH5_Ant1_Hop




TIME OF OCCUPANCY TEST RESULT

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.39	277	0.108	≤0.4	PASS
DH3	Ant1	Hop	1.64	155	0.254	≤0.4	PASS
DH5	Ant1	Hop	2.89	116	0.335	≤0.4	PASS
2DH1	Ant1	Hop	0.38	156	0.059	≤0.4	PASS
2DH3	Ant1	Hop	1.63	160	0.260	≤0.4	PASS
2DH5	Ant1	Hop	2.88	131	0.377	≤0.4	PASS
3DH1	Ant1	Hop	0.38	217	0.081	≤0.4	PASS
3DH3	Ant1	Hop	1.63	131	0.213	≤0.4	PASS
3DH5	Ant1	Hop	2.88	122	0.351	≤0.4	PASS




TEST GRAPHS




Date: 19.FEB.2023 02:05:18

DH1_Ant1_Hop




Date: 19.FEB.2023 02:06:20

DH1_Ant1_Hop




Date: 19.FEB.2023 02:04:20

DH3_Ant1_Hop




Date: 19.FEB.2023 02:03:31

DH3_Ant1_Hop




Date: 19.FEB.2023 01:58:44

DH5_Ant1_Hop




Date: 19.FEB.2023 02:02:14

DH5_Ant1_Hop




Date: 19.FEB.2023 02:08:14

2DH1_Ant1_Hop




Date: 19.FEB.2023 02:07:28

2DH1_Ant1_Hop



Date: 19.FEB.2023 02:09:17

2DH3_Ant1_Hop




Date: 19.FEB.2023 02:10:49

2DH3_Ant1_Hop




BUREAU VERITAS

Test Report No.: W7L-P23010016RF05




Date: 19.FEB.2023 02:13:50

2DH5_Ant1_Hop




Date: 19.FEB.2023 02:12:53

2DH5_Ant1_Hop




Date: 19.FEB.2023 02:14:48

3DH1_Ant1_Hop




Date: 19.FEB.2023 02:15:48

3DH1_Ant1_Hop




Date: 19.FEB.2023 02:17:44

3DH3_Ant1_Hop




Date: 19.FEB.2023 02:16:58

3DH3_Ant1_Hop



Date: 19.FEB.2023 02:18:41

3DH5_Ant1_Hop



Date: 19.FEB.2023 02:19:36

3DH5_Ant1_Hop




NUMBER OF HOPPING CHANNELS


TEST RESULT


TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥ 15	PASS
2DH5	Ant1	Hop	79	≥ 15	PASS
3DH5	Ant1	Hop	79	≥ 15	PASS



TEST GRAPHS










BAND EDGE MEASUREMENTS

TEST RESULT

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	9.13	-46.41	≤-10.87	PASS
		High	2480	6.78	-53.02	≤-13.22	PASS
		Low	Hop_2402	9.34	-46.41	≤-10.66	PASS
		High	Hop_2480	6.98	-53.62	≤-13.02	PASS
2DH5	Ant1	Low	2402	8.69	-35.68	≤-11.31	PASS
		High	2480	5.46	-49.91	≤-14.54	PASS
		Low	Hop_2402	8.66	-37.20	≤-11.34	PASS
		High	Hop_2480	5.68	-50.42	≤-14.73	PASS
3DH5	Ant1	Low	2402	8.78	-35.68	≤-11.31	PASS
		High	2480	5.63	-49.91	≤-14.54	PASS
		Low	Hop_2402	8.97	-37.20	≤-11.34	PASS
		High	Hop_2480	5.81	-51.84	≤-14.32	PASS




TEST GRAPHS




Date: 19.FEB.2023 02:48:15

DH5_Ant1_Low_2402




Date: 19.FEB.2023 02:46:29

DH5_Ant1_High_2480




Date: 19.FEB.2023 02:49:32

DH5_Ant1_Low_Hop_2402




Date: 19.FEB.2023 02:51:14

DH5_Ant1_High_Hop_2480



Date: 19.FEB.2023 02:56:15

2DH5_Ant1_Low_2402




Date: 19.FEB.2023 02:57:40

2DH5_Ant1_High_2480




BUREAU
VERITAS

Test Report No.: W7L-P23010016RF05




Date: 19.FEB.2023 02:53:43

2DH5_Ant1_Low_Hop_2402




Date: 19.FEB.2023 02:52:28

2DH5_Ant1_High_Hop_2480




Date: 19.FEB.2023 03:02:22

3DH5_Ant1_Low_2402




Date: 19.FEB.2023 03:00:34

3DH5_Ant1_High_2480



3DH5_Ant1_Low_Hop_2402



3DH5_Ant1_High_Hop_2480




CONDUCTED SPURIOUS EMISSION

TEST RESULT


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	30~3000	8.89	-53.74	≤-11.11	PASS
			2000~26500	8.98	-46.96	≤-11.02	PASS
		2441	30~3000	9.16	-53.55	≤-10.84	PASS
			2000~26500	9.01	-47.16	≤-10.99	PASS
		2480	30~3000	6.75	-52.97	≤-13.25	PASS
			2000~26500	6.72	-42.37	≤-13.28	PASS
2DH5	Ant1	2402	30~3000	7.97	-53.29	≤-12.03	PASS
			2000~26500	7.69	-47.10	≤-12.31	PASS
		2441	30~3000	7.00	-54.03	≤-13.00	PASS
			2000~26500	7.72	-46.27	≤-12.28	PASS
		2480	30~3000	4.90	-52.78	≤-15.10	PASS
			2000~26500	2.73	-46.92	≤-17.27	PASS
3DH5	Ant1	2402	30~3000	8.36	-53.19	≤-11.64	PASS
			2000~26500	6.18	-46.17	≤-13.82	PASS
		2441	30~3000	7.31	-53.09	≤-12.69	PASS
			2000~26500	7.89	-46.43	≤-12.11	PASS
		2480	30~3000	5.42	-53.90	≤-14.58	PASS
			2000~26500	4.52	-46.66	≤-15.48	PASS



TEST GRAPHS



DH5_Ant1_2402_30~3000




DH5_Ant1_2402_2000~26500




BUREAU VERITAS

Test Report No.: W7L-P23010016RF05



Date: 19.FEB.2023 02:39:06

DH5_Ant1_2441_30~3000




Date: 19.FEB.2023 02:39:47

DH5_Ant1_2441_2000~26500




BUREAU VERITAS

Test Report No.: W7L-P23010016RF05



Date: 19.FEB.2023 02:42:01

DH5_Ant1_2480_30~3000




Date: 19.FEB.2023 02:40:53

DH5_Ant1_2480_2000~26500




BUREAU VERITAS

Test Report No.: W7L-P23010016RF05



2DH5_Ant1_2402_30~3000




2DH5_Ant1_2402_2000~26500




BUREAU VERITAS


Test Report No.: W7L-P23010016RF05



2DH5_Ant1_2441_30~3000




2DH5_Ant1_2441_2000~26500




Date: 19.FEB.2023 02:30:10

2DH5_Ant1_2480_30~3000




Date: 19.FEB.2023 02:31:41

2DH5_Ant1_2480_2000~26500



3DH5_Ant1_2402_30~3000




3DH5_Ant1_2402_2000~26500




BUREAU
VERITAS

Test Report No.: W7L-P23010016RF05



Date: 19.FEB.2023 02:26:02

3DH5_Ant1_2441_30~3000




Date: 19.FEB.2023 02:27:06

3DH5_Ant1_2441_2000~26500




BUREAU VERITAS

Test Report No.: W7L-P23010016RF05



Date: 19.FEB.2023 02:29:07

3DH5_Ant1_2480_30~3000



Date: 19.FEB.2023 02:28:24

3DH5_Ant1_2480_2000~26500



DUTY CYCLE

TEST RESULT


TestMode	Antenna	Channel	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
DH5	Ant1	2441	2.90	3.76	0.7712	77.13	1.13	---	PASS
2DH5	Ant1	2441	2.87	3.75	0.7653	76.53	1.16	---	PASS
3DH5	Ant1	2441	2.89	3.75	0.7707	77.07	1.13	---	PASS




BUREAU VERITAS

Test Report No.: W7L-P23010016RF05

TEST GRAPHS



DH5_Ant1_2441



2DH5_Ant1_2441



BUREAU VERITAS

Test Report No.: W7L-P23010016RF05

