

RF Exposure Evaluation Report

Product : Bluetooth Speaker
Trade mark : N/A
Model/Type reference : Q1
Serial Number : N/A
Report Number : EED32L00379302
FCC ID : 2AJP3-Q1
Date of Issue : Jan. 10, 2020
Test Standards : 47 CFR Part 1.1307(2015)
47 CFR Part 1.1310(2015)
KDB447498D01v06
Test result : PASS

Prepared for:

Shenzhen Betnew Technology Co., Ltd
Room 313, Building C, Hongwan Business center,
Gushu, Xixiang, Baoan Dist., Shenzhen, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by: Sunlight Sun
Sunlight Sun

Reviewed by: Ware Xin
Ware Xin

Approved by: Sam Chuang
Sam Chuang

Date: Jan. 10, 2020

Check No.:3096331829

2 Version

Version No.	Date	Description
00	Jan. 10, 2020	Original

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	5
4.4 TEST LOCATION.....	6
4.5 DEVIATION FROM STANDARDS.....	6
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
5 RF EXPOSURE EVALUATION	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	7
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	8
PHOTOGRAPHS OF TEST SETUP.....	9

4 General Information

4.1 Client Information

Applicant:	Shenzhen Betnew Technology Co., Ltd
Address of Applicant:	Room 313, Building C, Hongwan Business center, Gushu, Xixiang, Baoan Dist.,Shenzhen, China
Manufacturer:	Shenzhen Betnew Technology Co., Ltd
Address of Manufacturer:	Room 313, Building C, Hongwan Business center, Gushu, Xixiang, Baoan Dist.,Shenzhen, China
Factory:	Dongguan Qualitronic Industrial Co., Ltd
Address of Factory:	Building 2, Pengtai industrial park, No. 49 Ludong road, Humen town, Dongguan

4.2 General Description of EUT

Product Name:	Bluetooth Speaker
Model No.(EUT):	Q1
Trade Mark:	N/A
EUT Supports Radios application	BT 5.0 Single mode, 2402MHz to 2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	2402MHz to 2480MHz
Modulation Type:	GFSK, $\pi/4$ DQPSK
Number of Channels:	79
Test Power Grade:	DH5:10 ; 2DH5:10
Test Software of EUT:	FCCAssist 2.4
Antenna Type:	PCB Antenna
Antenna Specification	Bluetooth : Antenna Gain : -0.50 dBi (Numeric gain: 0.89)
Maximum tune up power	Bluetooth: 5.00 dBm (3.162 mW)
Power Supply:	DC 5V/500mA, 3W
Sample Received Date:	Dec. 16, 2019
Sample tested Date:	Dec. 16, 2019 to Dec. 30, 2019
The tested sample(s) and the sample information are provided by the client.	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain


S = Power density in mW / cm²

Bluetooth:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)
39	2441	3.162	0.89	20	0.0006	1

PHOTOGRAPHS OF TEST SETUP

Test mode No:Q1



Radiated spurious emission Test Setup-1 (Below 30MHz)



Radiated spurious emission Test Setup-2 (Below 1GHz)



Radiated spurious emission Test Setup-3(Above 1GHz)



Radiated spurious emission Test Setup-4(Above 1GHz)
There are absorbing materials under the ground.



Conducted Emissions Test Setup

PHOTOGRAPHS OF EUT Constructional Details


Test model No.: Q1




View of Product-1




View of Product-2




View of Product-3



View of Product-4




View of Product-5




View of Product-6




View of Product-7



View of Product-8




View of Product-9



View of Product-10



View of Product-11



View of Product-12

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.