

FCC Report (WIFI)

Applicant: Shenzhen GPD Technology Co., Ltd.
Address of Applicant: 1006, Block 4D, Software Industry Base, High-Tech Industrial Park, Shenzhen, 518000, China
Manufacturer: Shenzhen GPD Technology Co., Ltd.
Address of Manufacturer: 1006, Block 4D, Software Industry Base, High-Tech Industrial Park, Shenzhen, 518000, China
Equipment Under Test (EUT)
Product Name: GPD Micro PC
Model No.: GPD Micro PC
Trade Mark: GPD
FCC ID: 2AJQ5-GPDMICROPC
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt: March 15, 2019
Date of Test: March 15- March 22, 2019
Date of report issued: March 22, 2019
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	March 22, 2019	Original

Prepared By:



Date:

March 22, 2019

Project Engineer

Check By:



Date:

March 22, 2019

Reviewer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 TEST FACILITY.....	7
5.5 TEST LOCATION	7
5.6 ADDITIONAL INSTRUCTIONS.....	8
6 TEST INSTRUMENTS LIST	9
7 TEST RESULTS AND MEASUREMENT DATA.....	11
7.1 ANTENNA REQUIREMENT.....	11
7.2 CONDUCTED EMISSIONS	12
7.3 CONDUCTED PEAK OUTPUT POWER.....	15
7.4 CHANNEL BANDWIDTH	17
7.5 POWER SPECTRAL DENSITY	26
7.6 BAND EDGES.....	36
7.6.1 Conducted Emission Method.....	36
7.6.2 Radiated Emission Method.....	39
7.7 SPURIOUS EMISSION.....	60
7.7.1 Conducted Emission Method.....	60
7.7.2 Radiated Emission Method.....	85
8 TEST SETUP PHOTO.....	102
9 EUT CONSTRUCTIONAL DETAILS	104

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013.

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Name:	GPD Micro PC
Model No.:	GPD Micro PC
Test Model No:	GPD Micro PC
Serial No.:	183726
Test sample(s) ID:	GTS201903000133
Sample(s) Status	Engineer sample
Hardware version:	HV1.0
Software version:	HV1.0
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11 802.11n(HT40):7
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20)/802.11n(HT40): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Internal antenna
Antenna gain:	ANT1: 1.36 dBi ANT2: 1.36 dBi
Power supply:	DC12V by external adapter

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)	
	802.11b/802.11g/802.11n(HT20)	802.11n(HT40)
Lowest channel	2412MHz	2422MHz
Middle channel	2437MHz	2437MHz
Highest channel	2462MHz	2452MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
<i>Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i>	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:				
Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.				
Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	13Mbps

5.3 Description of Support Units

None

5.4 Test Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018. ● Industry Canada (IC) —Registration No.: 9079A-2 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.
--


5.5 Test Location

All tests were performed at:
<p>Global United Technology Services Co., Ltd. Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960</p>

5.6 Additional Instructions

EUT Fixed Frequency Settings:

Power level setup			
Support Units	Description	Manufacturer	Model
	Wideband Radio Communication Tester	Rohde & Schwarz	REALTEK
Mode	Channel	Frequency (MHz)	Level Set
802.11b/g/n(HT20)	CH1	2412	TX level : default
	CH6	2437	
	CH11	2462	
802.11n(HT40)	CH3	2422	
	CH6	2437	
	CH9	2452	



6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019


Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 27 2018	June. 26 2019
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 27 2018	June. 26 2019
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 27 2018	June. 26 2019
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 27 2018	June. 26 2019

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 27 2018	June. 26 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 27 2018	June. 26 2019
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 27 2018	June. 26 2019
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 27 2018	June. 26 2019
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 27 2018	June. 26 2019
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 27 2018	June. 26 2019
8	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 27 2018	June. 26 2019

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:</p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
<p>EUT Antenna:</p>	
<p><i>The antenna is PIFA antenna, the best case gain of the antenna1 is 1.36dBi and antenna2 is 1.36dBi.</i></p>  <p><i>MIMO mode:</i></p> <p><i>Directional gain = $G_{ANT} + 10 \log(N) \text{ dBi} = 4.37 \text{ dBi}$</i></p> <p><i>802.11n20/n40 2.4GHz has MIMO mode.</i></p>	

7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Test Frequency Range:	150KHz to 30MHz														
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table> <p>* Decreases with the logarithm of the frequency.</p>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test setup:	<p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>														
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement. 														
Test Instruments:	Refer to section 6.0 for details														
Test mode:	Refer to section 5.2 for details														
Test results:	Pass														


Measurement data

EUT :	GPD Micro PC	Model Name. :	GPD Micro PC
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	Input: AC120V/60Hz Output: DC 12V	Test Mode :	Link Mode



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2100	39.19	9.65	48.84	63.20	-14.36	QP	
2		0.2140	20.28	9.65	29.93	53.04	-23.11	AVG	
3		0.2819	32.45	9.66	42.11	60.76	-18.65	QP	
4		0.2819	17.36	9.66	27.02	50.76	-23.74	AVG	
5		0.4900	30.67	9.68	40.35	56.17	-15.82	QP	
6		0.4940	21.55	9.68	31.23	46.10	-14.87	AVG	
7		1.4060	16.32	9.70	26.02	46.00	-19.98	AVG	
8		1.4700	28.90	9.70	38.60	56.00	-17.40	QP	
9		4.9780	25.02	9.74	34.76	46.00	-11.24	AVG	
10	*	5.1900	40.89	9.74	50.63	60.00	-9.37	QP	
11		18.9020	34.54	9.86	44.40	60.00	-15.60	QP	
12		20.0380	19.73	9.84	29.57	50.00	-20.43	AVG	

EUT :	GPD Micro PC	Model Name. :	GPD Micro PC
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	Input: AC120V/60Hz Output: DC 12V	Test Mode :	Link Mode




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2140	30.90	9.65	40.55	63.04	-22.49	QP	
2		0.2140	18.25	9.65	27.90	53.04	-25.14	AVG	
3		0.4940	27.73	9.68	37.41	56.10	-18.69	QP	
4		0.4940	20.27	9.68	29.95	46.10	-16.15	AVG	
5		1.4780	23.52	9.70	33.22	56.00	-22.78	QP	
6		1.4780	11.89	9.70	21.59	46.00	-24.41	AVG	
7		2.0540	22.11	9.71	31.82	56.00	-24.18	QP	
8		2.0540	9.15	9.71	18.86	46.00	-27.14	AVG	
9	*	4.7420	37.70	9.74	47.44	56.00	-8.56	QP	
10		4.7420	22.74	9.74	32.48	46.00	-13.52	AVG	
11		18.6140	30.57	9.86	40.43	60.00	-19.57	QP	
12		18.6140	17.03	9.86	26.89	50.00	-23.11	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. *If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.*

7.3 Conducted Peak Output Power


Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D01 DTS Meas Guidance v05r01
Limit:	30dBm
Test setup:	 <p>The diagram shows a Power Meter connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

TX 802.11b Mode			
Frequency (MHz)	Antenna port	Maximum Conducted Output Power(PK) (dBm)	LIMIT (dBm)
2412	Ant 1	8.17	30
	Ant 2	3.06	30
2437	Ant 1	8.24	30
	Ant 2	3.48	30
2462	Ant 1	8.38	30
	Ant 2	3.29	30
TX 802.11g Mode			
2412	Ant 1	7.98	30
	Ant 2	1.35	30
2437	Ant 1	7.76	30
	Ant 2	1.28	30
2462	Ant 1	7.43	30
	Ant 2	1.31	30

Frequency	Antenna port	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(PK)	Total Conducted Output Power(PK)	Total Conducted Output Power(PK)	LIMIT
(MHz)		(dBm)	(mW)	(mW)	(dBm)	dBm
TX 802.11n-HT20 Mode						
2412	Ant 1	6.12	4.09	5.43	7.35	30
	Ant 2	1.45	1.40			
2437	Ant 1	6.30	4.27	5.73	7.58	30
	Ant 2	1.26	1.34			
2462	Ant 1	6.37	4.34	5.59	7.47	30
	Ant 2	1.22	1.32			
TX 802.11n-HT40 Mode						
2422	Ant 1	6.16	4.13	5.53	7.43	30
	Ant 2	1.35	1.36			
2437	Ant 1	6.32	4.29	5.51	7.41	30
	Ant 2	1.47	1.40			
2452	Ant 1	6.18	4.15	5.63	7.51	30
	Ant 2	1.29	1.35			

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D01 DTS Meas Guidance v05r01
Limit:	>500KHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Measurement Data

Antenna 1						
Test CH	Channel Bandwidth (MHz)				Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	10.157	16.307	17.155	36.180	>500	Pass
Middle	10.044	16.056	17.097	35.846		
Highest	10.024	16.221	17.290	36.172		


Antenna 2						
Test CH	Channel Bandwidth (MHz)				Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)		
Lowest	10.079	16.588	17.837	36.482	>500	Pass
Middle	10.041	16.605	17.855	36.479		
Highest	10.077	16.616	17.893	36.529		

Test plot as follows:


Test mode:	802.11b-Antenna 1
------------	-------------------



Lowest channel




Middle channel




Highest channel


Test mode: 802.11g-Antenna 1



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)-Antenna 1



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT40)-Antenna 1



Lowest channel




Middle channel




Highest channel


Test mode:	802.11b-Antenna 2
------------	-------------------



Lowest channel




Middle channel




Highest channel


Test mode: 802.11g-Antenna 2



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)-Antenna 2



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT40)-Antenna 2



Lowest channel




Middle channel



Highest channel

7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 DTS Meas Guidance v05r01
Limit:	8dBm/3kHz
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

TX 802.11b Mode			
Frequency (MHz)	Antenna port	Power Density (dBm)	LIMIT dBm
2412	Ant 1	6.91	8
	Ant 2	-9.515	
2437	Ant 1	6.297	8
	Ant 2	-10.09	
2462	Ant 1	6.898	8
	Ant 2	-10.24	
Result	PASS		


TX 802.11g Mode			
Frequency	Antenna port	Power Density	LIMIT
(MHz)		(dBm)	dBm
2412	Ant 1	-0.341	8
	Ant 2	-10.27	
2437	Ant 1	0.322	8
	Ant 2	-10.38	
2462	Ant 1	0.411	8
	Ant 2	-11.63	
Result	PASS		

TX 802.11n20 Mode						
Frequency	Antenna port	Power Density	Power Density	Total Power Density	Total Power Density	LIMIT
(MHz)		(dBm)	(mW)	(mW)	(dBm)	dBm
2412	Ant 1	1.744	1.4942	1.555	1.92	8
	Ant 2	-12.19	0.0604			
2437	Ant 1	1.26	1.3366	1.409	1.49	8
	Ant 2	-11.40	0.0724			
2462	Ant 1	1.792	1.5108	1.585	2.00	8
	Ant 2	-11.28	0.0745			
Result	PASS					


TX 802.11n40 Mode						
Frequency	Antenna port	Power Density	Power Density	Total Power Density	Total Power Density	LIMIT
(MHz)		(dBm)	(mW)	(mW)	(dBm)	dBm
2412	Ant 1	-2.1	0.6166	0.635	-1.97	8
	Ant 2	-17.32	0.0185			
2437	Ant 1	-1.766	0.6659	0.680	-1.67	8
	Ant 2	-18.38	0.0145			
2462	Ant 1	-1.549	0.7000	0.719	-1.43	8
	Ant 2	-17.26	0.0188			
Result	PASS					

Test plot as follows:


Test mode:	802.11b-Antenna 1
------------	-------------------



Lowest channel




Middle channel




Highest channel


Test mode: 802.11g-Antenna 1



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)-Antenna 1



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT40)-Antenna 1



Lowest channel




Middle channel




Highest channel


Test mode:	802.11b-Antenna 2
------------	-------------------



Lowest channel




Middle channel




Highest channel


Test mode: 802.11g-Antenna 2



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT20)-Antenna 2



Lowest channel




Middle channel




Highest channel


Test mode: 802.11n(HT40)-Antenna 2



Lowest channel




Middle channel



Highest channel


7.6 Band edges

7.6.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance v05r01
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

Test mode: 802.11b




Lowest channel




Highest channel

Test mode: 802.11g




Lowest channel




Highest channel

Test mode: 802.11n(HT20)




Lowest channel




Highest channel

Test mode: 802.11n(HT40)




Lowest channel



Highest channel

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average
Limit:	Frequency		Limit (dBuV/m @3m)		Value
	Above 1GHz		54.00		Average
			74.00		Peak
Test setup:					
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report. 				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.2 for details				
Test results:	Pass				

Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	37.51	27.61	5.36	34.01	36.47	74.00	-37.53	Horizontal
2390.00	50.32	27.59	5.38	34.01	49.28	74.00	-24.72	Horizontal
2400.00	58.60	27.58	5.39	34.01	57.56	74.00	-16.44	Horizontal
2310.00	37.49	27.61	5.36	34.01	36.45	74.00	-37.55	Vertical
2390.00	51.63	27.59	5.38	34.01	50.59	74.00	-23.41	Vertical
2400.00	60.04	27.58	5.39	34.01	59.00	74.00	-15.00	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.91	27.61	5.36	34.01	28.87	54.00	-25.13	Horizontal
2390.00	37.00	27.59	5.38	34.01	35.96	54.00	-18.04	Horizontal
2400.00	45.19	27.58	5.39	34.01	44.15	54.00	-9.85	Horizontal
2310.00	30.06	27.61	5.36	34.01	29.02	54.00	-24.98	Vertical
2390.00	38.75	27.59	5.38	34.01	37.71	54.00	-16.29	Vertical
2400.00	46.49	27.58	5.39	34.01	45.45	54.00	-8.55	Vertical

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	49.87	27.53	5.47	33.92	48.95	74.00	-25.05	Horizontal
2500.00	46.06	27.55	5.49	29.93	49.17	74.00	-24.83	Horizontal
2483.50	51.88	27.53	5.47	33.92	50.96	74.00	-23.04	Vertical
2500.00	48.40	27.55	5.49	29.93	51.51	74.00	-22.49	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.28	27.53	5.47	33.92	36.36	54.00	-17.64	Horizontal
2500.00	33.63	27.55	5.49	29.93	36.74	54.00	-17.26	Horizontal
2483.50	39.09	27.53	5.47	33.92	38.17	54.00	-15.83	Vertical
2500.00	35.46	27.55	5.49	29.93	38.57	54.00	-15.43	Vertical

Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	37.95	27.61	5.36	34.01	36.91	74.00	-37.09	Horizontal
2390.00	50.01	27.59	5.38	34.01	48.97	74.00	-25.03	Horizontal
2400.00	58.47	27.58	5.39	34.01	57.43	74.00	-16.57	Horizontal
2310.00	38.13	27.61	5.36	34.01	37.09	74.00	-36.91	Vertical
2390.00	51.56	27.59	5.38	34.01	50.52	74.00	-23.48	Vertical
2400.00	59.72	27.58	5.39	34.01	58.68	74.00	-15.32	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	30.27	27.61	5.36	34.01	29.23	54.00	-24.77	Horizontal
2390.00	36.53	27.59	5.38	34.01	35.49	54.00	-18.51	Horizontal
2400.00	44.98	27.58	5.39	34.01	43.94	54.00	-10.06	Horizontal
2310.00	30.36	27.61	5.36	34.01	29.32	54.00	-24.68	Vertical
2390.00	38.71	27.59	5.38	34.01	37.67	54.00	-16.33	Vertical
2400.00	45.89	27.58	5.39	34.01	44.85	54.00	-9.15	Vertical

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	47.88	27.53	5.47	33.92	46.96	74.00	-27.04	Horizontal
2500.00	44.36	27.55	5.49	29.93	47.47	74.00	-26.53	Horizontal
2483.50	49.81	27.53	5.47	33.92	48.89	74.00	-25.11	Vertical
2500.00	45.93	27.55	5.49	29.93	49.04	74.00	-24.96	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	36.91	27.53	5.47	33.92	35.99	54.00	-18.01	Horizontal
2500.00	33.33	27.55	5.49	29.93	36.44	54.00	-17.56	Horizontal
2483.50	38.07	27.53	5.47	33.92	37.15	54.00	-16.85	Vertical
2500.00	35.16	27.55	5.49	29.93	38.27	54.00	-15.73	Vertical

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	36.95	27.61	5.36	34.01	35.91	74.00	-38.09	Horizontal
2390.00	49.29	27.59	5.38	34.01	48.25	74.00	-25.75	Horizontal
2400.00	58.40	27.58	5.39	34.01	57.36	74.00	-16.64	Horizontal
2310.00	37.07	27.61	5.36	34.01	36.03	74.00	-37.97	Vertical
2390.00	50.83	27.59	5.38	34.01	49.79	74.00	-24.21	Vertical
2400.00	58.98	27.58	5.39	34.01	57.94	74.00	-16.06	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	30.38	27.61	5.36	34.01	29.34	54.00	-24.66	Horizontal
2390.00	36.81	27.59	5.38	34.01	35.77	54.00	-18.23	Horizontal
2400.00	44.92	27.58	5.39	34.01	43.88	54.00	-10.12	Horizontal
2310.00	30.40	27.61	5.36	34.01	29.36	54.00	-24.64	Vertical
2390.00	38.54	27.59	5.38	34.01	37.50	54.00	-16.50	Vertical
2400.00	45.89	27.58	5.39	34.01	44.85	54.00	-9.15	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.92	27.53	5.47	33.92	48.00	74.00	-26.00	Horizontal
2500.00	45.35	27.55	5.49	29.93	48.46	74.00	-25.54	Horizontal
2483.50	50.80	27.53	5.47	33.92	49.88	74.00	-24.12	Vertical
2500.00	47.30	27.55	5.49	29.93	50.41	74.00	-23.59	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.53	27.53	5.47	33.92	36.61	54.00	-17.39	Horizontal
2500.00	34.02	27.55	5.49	29.93	37.13	54.00	-16.87	Horizontal
2483.50	39.35	27.53	5.47	33.92	38.43	54.00	-15.57	Vertical
2500.00	36.02	27.55	5.49	29.93	39.13	54.00	-14.87	Vertical

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	37.10	27.61	5.36	34.01	36.06	74.00	-37.94	Horizontal
2390.00	49.35	27.59	5.38	34.01	48.31	74.00	-25.69	Horizontal
2400.00	57.01	27.58	5.39	34.01	55.97	74.00	-18.03	Horizontal
2310.00	37.05	27.61	5.36	34.01	36.01	74.00	-37.99	Vertical
2390.00	49.88	27.59	5.38	34.01	48.84	74.00	-25.16	Vertical
2400.00	58.23	27.58	5.39	34.01	57.19	74.00	-16.81	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	29.69	27.61	5.36	34.01	28.65	54.00	-25.35	Horizontal
2390.00	35.95	27.59	5.38	34.01	34.91	54.00	-19.09	Horizontal
2400.00	44.43	27.58	5.39	34.01	43.39	54.00	-10.61	Horizontal
2310.00	29.75	27.61	5.36	34.01	28.71	54.00	-25.29	Vertical
2390.00	38.02	27.59	5.38	34.01	36.98	54.00	-17.02	Vertical
2400.00	45.17	27.58	5.39	34.01	44.13	54.00	-9.87	Vertical

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.36	27.53	5.47	33.92	47.44	74.00	-26.56	Horizontal
2500.00	44.81	27.55	5.49	29.93	47.92	74.00	-26.08	Horizontal
2483.50	50.15	27.53	5.47	33.92	49.23	74.00	-24.77	Vertical
2500.00	46.97	27.55	5.49	29.93	50.08	74.00	-23.92	Vertical



Average value:



Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.32	27.53	5.47	33.92	36.40	54.00	-17.60	Horizontal
2500.00	33.80	27.55	5.49	29.93	36.91	54.00	-17.09	Horizontal
2483.50	39.03	27.53	5.47	33.92	38.11	54.00	-15.89	Vertical
2500.00	35.60	27.55	5.49	29.93	38.71	54.00	-15.29	Vertical



Remark:



1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

802.11b

















802.11g















802.11n20



















802.11n40










7.7 Spurious Emission


7.7.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance v05r01
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by two legs. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass


Test plot as follows:

Test mode:	802.11b-Antenna 1
------------	-------------------


CH 1 (B mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)




CH 1 (B mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 1 (B mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




CH 6 (B mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 6 (B mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 6 (B mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




CH 11 (B mode) - Frequency Band 1 ($30 \text{ MHz} \leq f \leq 1000 \text{ MHz}$)



CH 11 (B mode) - Frequency Band 2 ($1000 \text{ MHz} < f \leq 3000 \text{ MHz}$)




CH 11 (B mode) - Frequency Band 3 ($3000 \text{ MHz} < f \leq 25000 \text{ MHz}$)




Test mode:

802.11g-Antenna 1


CH 1 (G mode) - Frequency Band 1 ($30 \text{ MHz} \leq f \leq 1000 \text{ MHz}$)




CH 1 (G mode) - Frequency Band 2 ($1000 \text{ MHz} < f \leq 3000 \text{ MHz}$)




CH 1 (G mode) - Frequency Band 3 ($3000 \text{ MHz} < f \leq 25000 \text{ MHz}$)




CH 6 (G mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 6 (G mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 6 (G mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




CH 11 (G mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)



CH 11 (G mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 11 (G mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




Test mode: 802.11n(HT20)-Antenna 1


CH 1 (n20 mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)




CH 1 (n20 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 1 (n20 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




CH 6 (n20 mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 6 (n20 mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 6 (n20 mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




CH 11 (n20 mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)



CH 11 (n20 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 11 (n20 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




Test mode: 802.11n(HT40)-Antenna 1


CH 3 (n40 mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)




CH 3 (n40 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 3 (n40 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




CH 6 (n40 mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 6 (n40 mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 6 (n40 mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




CH 9 (n40 mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)



CH 9 (n40 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 9 (n40 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




Test mode: 802.11b-Antenna 2


CH 1 (B mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)




CH 1 (B mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 1 (B mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




CH 6 (B mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)




CH 6 (B mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 6 (B mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




CH 11 (B mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)



CH 11 (B mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 11 (B mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




Test mode: 802.11g-Antenna 2


CH 1 (G mode) - Frequency Band 1 ($30 \text{ MHz} \leq f \leq 1000 \text{ MHz}$)




CH 1 (G mode) - Frequency Band 2 ($1000 \text{ MHz} < f \leq 3000 \text{ MHz}$)




CH 1 (G mode) - Frequency Band 3 ($3000 \text{ MHz} < f \leq 25000 \text{ MHz}$)




CH 6 (G mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 6 (G mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 6 (G mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




CH 11 (G mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)



CH 11 (G mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 11 (G mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




Test mode:

802.11n(HT20)-Antenna 2


CH 1 (n20 mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)




CH 1 (n20 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 1 (n20 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




CH 6 (n20 mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 6 (n20 mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 6 (n20 mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




CH 11 (n20 mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)



CH 11 (n20 mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 11 (n20 mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




Test mode: 802.11n(HT40)-Antenna 2


CH 3 (n40 mode) - Frequency Band 1 (30 MHz ≤ f ≤ 1000 MHz)




CH 3 (n40 mode) - Frequency Band 2 (1000 MHz < f ≤ 3000 MHz)




CH 3 (n40 mode) - Frequency Band 3 (3000 MHz < f ≤ 25000 MHz)




CH 6 (n40 mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 6 (n40 mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)




CH 6 (n40 mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)




CH 9 (n40 mode) - Frequency Band 1 (30 MHz \leq f \leq 1000 MHz)




CH 9 (n40 mode) - Frequency Band 2 (1000 MHz < f \leq 3000 MHz)





CH 9 (n40 mode) - Frequency Band 3 (3000 MHz < f \leq 25000 MHz)



7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	300m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
	 <p>The diagram illustrates the test setup for radiated emissions from 9kHz to 30MHz. It shows an Equipment Under Test (EUT) placed on a turn table at a height of less than 80cm. A test antenna is positioned 3m away from the EUT. A receiver and preamplifier are connected to the antenna, with the receiver at a height of less than 1m.</p>				
For radiated emissions from 30MHz to 1GHz					

	 <p>For radiated emissions above 1GHz</p> 
<p>Test Procedure:</p>	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the

	limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.


Measurement data:

■ **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


■ Below 1GHz

Mode:	Transmitting mode	Polarization:	Horizontal
Temp.:	26°C	Hum.(%H):	56%RH



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
		MHz	dBuV	dB	ment	dB/m	dB	Detector
1		35.8746	29.83	-17.14	12.69	40.00	-27.31	QP
2		119.8556	36.97	-18.07	18.90	43.50	-24.60	QP
3		216.0240	32.81	-15.61	17.20	46.00	-28.80	QP
4		312.1794	31.29	-11.84	19.45	46.00	-26.55	QP
5	*	460.7271	40.57	-8.23	32.34	46.00	-13.66	QP
6		513.6331	34.83	-6.85	27.98	46.00	-18.02	QP

Mode:	Transmitting mode	Polarization:	Vertical
Temp.:	26°C	Hum.(%H):	56%RH



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		49.3594	25.66	-14.70	10.96	40.00	-29.04	QP
2		119.8556	36.27	-18.07	18.20	43.50	-25.30	QP
3		136.9391	40.92	-19.83	21.09	43.50	-22.41	QP
4		216.0240	32.26	-15.61	16.65	46.00	-29.35	QP
5		586.8437	29.57	-4.96	24.61	46.00	-21.39	QP
6	*	866.0879	28.66	0.07	28.73	46.00	-17.27	QP

■ Above 1GHz

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	38.46	31.79	8.62	32.10	46.77	74.00	-27.23	Vertical
7236.00	33.00	36.19	11.68	31.97	48.90	74.00	-25.10	Vertical
9648.00	31.09	38.07	14.16	31.56	51.76	74.00	-22.24	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	37.14	31.79	8.62	32.10	45.45	74.00	-28.55	Horizontal
7236.00	32.71	36.19	11.68	31.97	48.61	74.00	-25.39	Horizontal
9648.00	31.19	38.07	14.16	31.56	51.86	74.00	-22.14	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	27.81	31.79	8.62	32.10	36.12	54.00	-17.88	Vertical
7236.00	22.43	36.19	11.68	31.97	38.33	54.00	-15.67	Vertical
9648.00	22.10	38.07	14.16	31.56	42.77	54.00	-11.23	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	27.74	31.79	8.62	32.10	36.05	54.00	-17.95	Horizontal
7236.00	21.29	36.19	11.68	31.97	37.19	54.00	-16.81	Horizontal
9648.00	21.25	38.07	14.16	31.56	41.92	54.00	-12.08	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *“*”, means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	37.75	31.85	8.66	32.12	46.14	74.00	-27.86	Vertical
7311.00	33.42	36.37	11.71	31.91	49.59	74.00	-24.41	Vertical
9748.00	32.78	38.27	14.25	31.56	53.74	74.00	-20.26	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	38.16	31.85	8.66	32.12	46.55	74.00	-27.45	Horizontal
7311.00	31.66	36.37	11.71	31.91	47.83	74.00	-26.17	Horizontal
9748.00	32.48	38.27	14.25	31.56	53.44	74.00	-20.56	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	27.29	31.85	8.66	32.12	35.68	54.00	-18.32	Vertical
7311.00	20.33	36.37	11.71	31.91	36.50	54.00	-17.50	Vertical
9748.00	20.65	38.27	14.25	31.56	41.61	54.00	-12.39	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	28.37	31.85	8.66	32.12	36.76	54.00	-17.24	Horizontal
7311.00	21.14	36.37	11.71	31.91	37.31	54.00	-16.69	Horizontal
9748.00	22.30	38.27	14.25	31.56	43.26	54.00	-10.74	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	42.46	31.90	8.70	32.15	50.91	74.00	-23.09	Vertical
7386.00	33.38	36.49	11.76	31.83	49.80	74.00	-24.20	Vertical
9848.00	35.69	38.62	14.31	31.77	56.85	74.00	-17.15	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	45.65	31.90	8.70	32.15	54.10	74.00	-19.90	Horizontal
7386.00	36.53	36.49	11.76	31.83	52.95	74.00	-21.05	Horizontal
9848.00	35.59	38.62	14.31	31.77	56.75	74.00	-17.25	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	32.13	31.90	8.70	32.15	40.58	54.00	-13.42	Vertical
7386.00	22.11	36.49	11.76	31.83	38.53	54.00	-15.47	Vertical
9848.00	22.80	38.62	14.31	31.77	43.96	54.00	-10.04	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	31.77	31.90	8.70	32.15	40.22	54.00	-13.78	Horizontal
7386.00	21.58	36.49	11.76	31.83	38.00	54.00	-16.00	Horizontal
9848.00	21.50	38.62	14.31	31.77	42.66	54.00	-11.34	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	lowest
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	38.47	31.79	8.62	32.10	46.78	74.00	-27.22	Vertical
7236.00	33.00	36.19	11.68	31.97	48.90	74.00	-25.10	Vertical
9648.00	31.98	38.07	14.16	31.56	52.65	74.00	-21.35	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	37.37	31.79	8.62	32.10	45.68	74.00	-28.32	Horizontal
7236.00	32.80	36.19	11.68	31.97	48.70	74.00	-25.30	Horizontal
9648.00	31.42	38.07	14.16	31.56	52.09	74.00	-21.91	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	26.97	31.79	8.62	32.10	35.28	54.00	-18.72	Vertical
7236.00	21.40	36.19	11.68	31.97	37.30	54.00	-16.70	Vertical
9648.00	21.68	38.07	14.16	31.56	42.35	54.00	-11.65	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	26.98	31.79	8.62	32.10	35.29	54.00	-18.71	Horizontal
7236.00	20.66	36.19	11.68	31.97	36.56	54.00	-17.44	Horizontal
9648.00	21.21	38.07	14.16	31.56	41.88	54.00	-12.12	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	37.47	31.85	8.66	32.12	45.86	74.00	-28.14	Vertical
7311.00	33.35	36.37	11.71	31.91	49.52	74.00	-24.48	Vertical
9748.00	32.58	38.27	14.25	31.56	53.54	74.00	-20.46	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	36.80	31.85	8.66	32.12	45.19	74.00	-28.81	Horizontal
7311.00	30.33	36.37	11.71	31.91	46.50	74.00	-27.50	Horizontal
9748.00	31.17	38.27	14.25	31.56	52.13	74.00	-21.87	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.43	31.85	8.66	32.12	37.82	54.00	-16.18	Vertical
7311.00	22.30	36.37	11.71	31.91	38.47	54.00	-15.53	Vertical
9748.00	22.96	38.27	14.25	31.56	43.92	54.00	-10.08	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	29.21	31.85	8.66	32.12	37.60	54.00	-16.40	Horizontal
7311.00	21.52	36.37	11.71	31.91	37.69	54.00	-16.31	Horizontal
9748.00	23.14	38.27	14.25	31.56	44.10	54.00	-9.90	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor*
2. *“*”*, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	42.20	31.90	8.70	32.15	50.65	74.00	-23.35	Vertical
7386.00	33.47	36.49	11.76	31.83	49.89	74.00	-24.11	Vertical
9848.00	35.46	38.62	14.31	31.77	56.62	74.00	-17.38	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	40.32	31.90	8.70	32.15	48.77	74.00	-25.23	Horizontal
7386.00	30.90	36.49	11.76	31.83	47.32	74.00	-26.68	Horizontal
9848.00	30.14	38.62	14.31	31.77	51.30	74.00	-22.70	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	33.18	31.90	8.70	32.15	41.63	54.00	-12.37	Vertical
7386.00	23.42	36.49	11.76	31.83	39.84	54.00	-14.16	Vertical
9848.00	24.10	38.62	14.31	31.77	45.26	54.00	-8.74	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	31.98	31.90	8.70	32.15	40.43	54.00	-13.57	Horizontal
7386.00	21.51	36.49	11.76	31.83	37.93	54.00	-16.07	Horizontal
9848.00	21.02	38.62	14.31	31.77	42.18	54.00	-11.82	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	39.03	31.79	8.62	32.10	47.34	74.00	-26.66	Vertical
7236.00	33.38	36.19	11.68	31.97	49.28	74.00	-24.72	Vertical
9648.00	32.30	38.07	14.16	31.56	52.97	74.00	-21.03	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	37.96	31.79	8.62	32.10	46.27	74.00	-27.73	Horizontal
7236.00	33.42	36.19	11.68	31.97	49.32	74.00	-24.68	Horizontal
9648.00	32.31	38.07	14.16	31.56	52.98	74.00	-21.02	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	25.93	31.79	8.62	32.10	34.24	54.00	-19.76	Vertical
7236.00	20.26	36.19	11.68	31.97	36.16	54.00	-17.84	Vertical
9648.00	20.17	38.07	14.16	31.56	40.84	54.00	-13.16	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	26.51	31.79	8.62	32.10	34.82	54.00	-19.18	Horizontal
7236.00	21.62	36.19	11.68	31.97	37.52	54.00	-16.48	Horizontal
9648.00	20.93	38.07	14.16	31.56	41.60	54.00	-12.40	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*”*, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	36.32	31.85	8.66	32.12	44.71	74.00	-29.29	Vertical
7311.00	31.51	36.37	11.71	31.91	47.68	74.00	-26.32	Vertical
9748.00	31.37	38.27	14.25	31.56	52.33	74.00	-21.67	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	38.33	31.85	8.66	32.12	46.72	74.00	-27.28	Horizontal
7311.00	31.65	36.37	11.71	31.91	47.82	74.00	-26.18	Horizontal
9748.00	32.59	38.27	14.25	31.56	53.55	74.00	-20.45	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.48	31.85	8.66	32.12	37.87	54.00	-16.13	Vertical
7311.00	22.21	36.37	11.71	31.91	38.38	54.00	-15.62	Vertical
9748.00	22.81	38.27	14.25	31.56	43.77	54.00	-10.23	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	28.81	31.85	8.66	32.12	37.20	54.00	-16.80	Horizontal
7311.00	21.65	36.37	11.71	31.91	37.82	54.00	-16.18	Horizontal
9748.00	23.17	38.27	14.25	31.56	44.13	54.00	-9.87	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. *Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *“*” means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	43.00	31.90	8.70	32.15	51.45	74.00	-22.55	4924.00
7386.00	34.04	36.49	11.76	31.83	50.46	74.00	-23.54	7386.00
9848.00	36.48	38.62	14.31	31.77	57.64	74.00	-16.36	9848.00
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	40.83	31.90	8.70	32.15	49.28	74.00	-24.72	Horizontal
7386.00	31.22	36.49	11.76	31.83	47.64	74.00	-26.36	Horizontal
9848.00	30.85	38.62	14.31	31.77	52.01	74.00	-21.99	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	33.30	31.90	8.70	32.15	41.75	54.00	-12.25	Vertical
7386.00	23.08	36.49	11.76	31.83	39.50	54.00	-14.50	Vertical
9848.00	24.51	38.62	14.31	31.77	45.67	54.00	-8.33	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	32.38	31.90	8.70	32.15	40.83	54.00	-13.17	Horizontal
7386.00	21.72	36.49	11.76	31.83	38.14	54.00	-15.86	Horizontal
9848.00	20.92	38.62	14.31	31.77	42.08	54.00	-11.92	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

- 1 Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	39.09	31.81	8.63	32.11	47.42	74.00	-26.58	Vertical
7266.00	34.07	36.28	11.69	31.94	50.10	74.00	-23.90	Vertical
9688.00	32.53	38.13	14.21	31.52	53.35	74.00	-20.65	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4844.00	37.36	31.81	8.63	32.11	45.69	74.00	-28.31	Horizontal
7266.00	32.94	36.28	11.69	31.94	48.97	74.00	-25.03	Horizontal
9688.00	31.57	38.13	14.21	31.52	52.39	74.00	-21.61	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844.00	25.54	31.81	8.63	32.11	33.87	54.00	-20.13	Vertical
7266.00	20.10	36.28	11.69	31.94	36.13	54.00	-17.87	Vertical
9688.00	20.44	38.13	14.21	31.52	41.26	54.00	-12.74	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4844.00	26.55	31.81	8.63	32.11	34.88	54.00	-19.12	Horizontal
7266.00	21.11	36.28	11.69	31.94	37.14	54.00	-16.86	Horizontal
9688.00	21.47	38.13	14.21	31.52	42.29	54.00	-11.71	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	37.65	31.85	8.66	32.12	46.04	74.00	-27.96	Vertical
7311.00	33.22	36.37	11.71	31.91	49.39	74.00	-24.61	Vertical
9748.00	32.97	38.27	14.25	31.56	53.93	74.00	-20.07	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	38.49	31.85	8.66	32.12	46.88	74.00	-27.12	Horizontal
7311.00	32.10	36.37	11.71	31.91	48.27	74.00	-25.73	Horizontal
9748.00	33.02	38.27	14.25	31.56	53.98	74.00	-20.02	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	26.81	31.85	8.66	32.12	35.20	54.00	-18.80	Vertical
7311.00	19.74	36.37	11.71	31.91	35.91	54.00	-18.09	Vertical
9748.00	20.42	38.27	14.25	31.56	41.38	54.00	-12.62	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	28.16	31.85	8.66	32.12	36.55	54.00	-17.45	Horizontal
7311.00	20.67	36.37	11.71	31.91	36.84	54.00	-17.16	Horizontal
9748.00	22.22	38.27	14.25	31.56	43.18	54.00	-10.82	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.

Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	41.96	31.88	8.68	32.13	50.39	74.00	-23.61	Vertical
7356.00	33.23	36.45	11.75	31.86	49.57	74.00	-24.43	Vertical
9808.00	35.74	38.43	14.29	31.68	56.78	74.00	-17.22	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4904.00	41.05	31.88	8.68	32.13	49.48	74.00	-24.52	Horizontal
7356.00	31.51	36.45	11.75	31.86	47.85	74.00	-26.15	Horizontal
9808.00	31.29	38.43	14.29	31.68	52.33	74.00	-21.67	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4904.00	33.22	31.88	8.68	32.13	41.51	54.00	-12.49	Vertical
7356.00	22.94	36.45	11.75	31.86	38.74	54.00	-15.26	Vertical
9808.00	24.11	38.43	14.29	31.68	44.58	54.00	-9.42	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4904.00	30.92	31.88	8.68	32.13	39.21	54.00	-14.79	Horizontal
7356.00	21.05	36.45	11.75	31.86	36.85	54.00	-17.15	Horizontal
9808.00	20.58	38.43	14.29	31.68	41.05	54.00	-12.95	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remark:

- 1 Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- 2 “*”, means this data is the too weak instrument of signal is unable to test.

8 Test Setup Photo


Radiated Emission




Conducted Emission






9 EUT Constructional Details
























-----End-----