

# FCC ID: 2AJTV-LBI881

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]^* [ \sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm

and for transmission frequencies between 100 MHz and 6 GHz.

We used a distance 5mm to calculated

Maximum measured transmitter power:

Transmit Frequency (GHz)	Mode	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Result calculation	1-g SAR
2.403	GFSK	-5.44	-6 $\pm$ 1	-5	0.0980	3.0
2.441	GFSK	-6.86	-6 $\pm$ 1	-5	0.0988	3.0
2.471	GFSK	-7.73	-7 $\pm$ 1	-6	0.0790	3.0

### **Conclusion:**

For the max result :  $0.0988 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

EMTEK(SHENZHEN) CO., LTD.



Lisa Wang/EMC Manager