

Size:288x240mm

EG WIRELESS THERMOMETER  
USER MANUAL




VEL-140


PACKAGE CONTENTS



WIRELESS THERMOMETER



TRANSMITTER BASE



POWER DISPLAY ON THE WIRELESS THERMOMETER



BATTERY INSTALLATION

**WIRELESS THERMOMETER**  
1 Remove the battery cover on the back of the wireless thermometer.  
2 Insert 2 AAA 1.5V batteries (batteries included are not included in the warranty service).  
3 Replace the battery cover.

TRANSMITTER BASE

**TRANSMITTER BASE**  
1 Remove the battery cover on the back of the transmitter base.  
2 Insert 2 AAA 1.5V batteries (batteries included are not included in the warranty service).  
3 Replace the battery cover.

OPERATING INSTRUCTIONS

**1. CONNECTING THE PROBE**  
Insert the probe into the left side of the transmitter base. Push the probe connector plug into the port (see Fig. 1).

**TRANSMITTER BASE**  
Insert the probe into the back side of the transmitter base. Push the probe connector plug into the port (see Fig. 2).

POWERING ON WIRELESS THERMOMETER

Press the power button on the right side of the transmitter base. Press the power button on the transmitter base. Press the power button on the transmitter base.

1°C/°F TEMPERATURE DISPLAY

Press the mode button on the back of the wireless thermometer. Press the mode button on the transmitter base. Press the mode button on the transmitter base.

Size:288x240mm

OPERATING INSTRUCTIONS

**4. MODE/ INSTRUCTION BUTTON**  
Press MODE to change between the meat thermometer and the manual thermometer. Press MODE to change between the meat thermometer and the manual thermometer. Press MODE to change between the meat thermometer and the manual thermometer.

**5. SELECT MEAT TYPE**  
Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode.

**6. SELECT AND COOK BY TASTE LEVEL**  
Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode.

**7. COOK WITH MANUALLY SET DESIRED TEMPERATURE**  
Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode.

**8. PROBE INSERTION**  
Insert the probe into the back side of the transmitter base. Insert the probe into the back side of the transmitter base. Insert the probe into the back side of the transmitter base.

**9. CHECK-UP/ COOKING TIME**  
Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode. Press MODE to select TEMPERATURE mode.

OPERATING INSTRUCTIONS

**10. REPLACEMENT**  
Press the power button on the right side of the transmitter base. Press the power button on the transmitter base. Press the power button on the transmitter base.

CARE AND MAINTENANCE

PROBLEM	POSSIBLE CAUSE	CORRECTIVE ACTION
Control temperature does not change in LCD panel properly.	Probe is not inserted properly. Probe is not calibrated. The distance from sensor to the center of the meat is too far.	1 Check to make sure the probe connector plug is inserted into the probe plug. 2 Probe is properly calibrated. 3 Check to make sure the distance from sensor to the center of the meat is within the specified range.
Meat overcooks or undercooks.	Probe is not inserted properly. Probe is not calibrated.	1 Check to make sure the probe connector plug is inserted into the probe plug. 2 Probe is properly calibrated.

FCC CAUTION:

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



Any questions please email us at [export@eg163.com](mailto:export@eg163.com)

Printed in China

INSIDE PAGE 2

INSIDE PAGE 3

BACK COVER