

FCC TEST REPORT

For

Ruixing Hengfang Network (Shenzhen) CO., LTD

Industrial LoRaWAN Gateway

Test Model: RHF2S008

Additional Model No.:RHF2S008P4G-915

Prepared for : Ruixing Hengfang Network (Shenzhen) CO., LTD
Address : Room 507, 2nd tower of KangTai biological building, NO.6 KeFa Rd. NanShan District, Shenzhen 518057 China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : August 01, 2017
Number of tested samples : 1
Serial number : Prototype
Date of Test : July 01, 2017~ August 01, 2017
Date of Report : August 10, 2017

FCC TEST REPORT
FCC CFR 47 PART 15 C(15.247)

Report Reference No. : **LCS170707021AE**

Date of Issue : August 10, 2017

Testing Laboratory Name..... : **Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure : Full application of Harmonised standards ■
 Partial application of Harmonised standards □
 Other standard testing method □

Applicant's Name..... : **Ruixing Hengfang Network (Shenzhen) CO., LTD**

Address : Room 507, 2nd tower of KangTai biological building, NO.6 KeFa
Rd. NanShan District, Shenzhen 518057 China

Test Specification

Standard..... : FCC CFR 47 PART 15 C(15.247)

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description. : Industrial LoRaWAN Gateway

Trade Mark..... : RisingHF

Model/ Type reference : RHF2S008

Ratings : Input: AC 100-240 V 50/60HZ 0.8 A Max
Output: DC 48 V 30W

Result : **Positive**

Compiled by:

Peter Xsu

Dick Su/ File administrators

Supervised by:

Calvin Weng

Calvin Weng/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager

FCC -- TEST REPORT

| | |
|--|---|
| Test Report No. : LCS170707021AE | <u>August 10, 2017</u> Date of issue |
|--|---|

| | |
|---------------------------|---|
| Type / Model..... | : RHF2S008 |
| EUT..... | : Industrial LoRaWAN Gateway |
| Applicant | : Ruixing Hengfang Network (Shenzhen) CO., LTD |
| Address..... | : Room 507, 2nd tower of KangTai biological building, NO.6 KeFa Rd. NanShan District, Shenzhen 518057 China |
| Telephone..... | : / |
| Fax..... | : / |
| Manufacturer | : Ruixing Hengfang Network (Shenzhen) CO., LTD |
| Address..... | : Room 507, 2nd tower of KangTai biological building, NO.6 KeFa Rd. NanShan District, Shenzhen 518057 China |
| Telephone..... | : / |
| Fax..... | : / |
| Factory | : Ruixing Hengfang Network (Shenzhen) CO., LTD |
| Address..... | : Room 507, 2nd tower of KangTai biological building, NO.6 KeFa Rd. NanShan District, Shenzhen 518057 China |
| Telephone..... | : / |
| Fax..... | : / |

| | |
|--------------------|-----------------|
| Test Result | Positive |
|--------------------|-----------------|

The test report merely corresponds to the test sample.
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

| Revision | Issue Date | Revisions | Revised By |
|----------|-----------------|---------------|-------------|
| 00 | August 10, 2017 | Initial Issue | Gavin Liang |
| | | | |
| | | | |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. GENERAL INFORMATION | 6 |
| 1.1. DESCRIPTION OF DEVICE (EUT) | 6 |
| 1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS | 6 |
| 1.3. EXTERNAL I/O CABLE | 6 |
| 1.4. DESCRIPTION OF TEST FACILITY | 6 |
| 1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY | 7 |
| 1.6. MEASUREMENT UNCERTAINTY | 7 |
| 1.7. DESCRIPTION OF TEST MODES | 7 |
| 1.8. FREQUENCY OF CHANNELS | 7 |
| 2. TEST METHODOLOGY | 8 |
| 2.1. EUT CONFIGURATION | 8 |
| 2.2. EUT EXERCISE | 8 |
| 2.3. GENERAL TEST PROCEDURES | 8 |
| 3. SYSTEM TEST CONFIGURATION..... | 9 |
| 3.1. JUSTIFICATION | 9 |
| 3.2. EUT EXERCISE SOFTWARE..... | 9 |
| 3.3. SPECIAL ACCESSORIES | 9 |
| 3.4. BLOCK DIAGRAM/SCHEMATICS..... | 9 |
| 3.5. EQUIPMENT MODIFICATIONS | 9 |
| 3.6. TEST SETUP..... | 9 |
| 4. SUMMARY OF TEST RESULTS..... | 10 |
| 5. TEST RESULT..... | 11 |
| 5.1. ON TIME AND DUTY CYCLE | 11 |
| 5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT..... | 13 |
| 5.3. POWER SPECTRAL DENSITY MEASUREMENT | 15 |
| 5.4. 6 dB SPECTRUM BANDWIDTH MEASUREMENT | 17 |
| 5.5. RADIATED EMISSIONS MEASUREMENT..... | 19 |
| 5.6. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST..... | 28 |
| 5.7. AC POWER LINE CONDUCTED EMISSIONS..... | 31 |
| 5.8. BAND-EDGE MEASUREMENTS FOR RADIATED EMISSIONS | 33 |
| 5.9. ANTENNA REQUIREMENTS..... | 38 |
| 6. LIST OF MEASURING EQUIPMENTS..... | 40 |
| 7. TEST SETUP PHOTOGRAPHS | 41 |
| 8. EXTERIOR PHOTOGRAPHS OF THE EUT..... | 41 |
| 9. INTERIOR PHOTOGRAPHS OF THE EUT | 41 |

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Industrial LoRaWAN Gateway
 Model Number : /
 Model Declaration : /
 Test Model : RHF2S008
 Hardware version : RHF2S008_V4.0
 Software version : 0.0.7
 Power Supply : DC 51V (POE), 0.6A

LoraWAN

Channel frequency : 902.5-927.5MHz
 Channel number : 10 Channel

LTE

LTE Operation Frequency Band : LTE FDD band 4
 LTE Release Version : R8
 LTE Power Class : Class 3
 Modulation Technology : LoRa(CSS) for 902.5-927.5MHz
 : QPSK,16QAM for LTE
 Antenna Type and Gain : 5.0dBi (max.) for LTE FDD Band 4; (External Antenna)
 : 2.0 dBi (max.) for 902.5-927.5MHz (External Antenna)
 Extreme temp. Tolerance : -10°C to +50°C
 GPS function : Support and only RX
 NFC Function : Not Supported
 Extreme vol. Limits : 40.8VDC to 55.2VDC (nominal: 48.0VDC)

1.2. Host System Configuration List and Details

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|-------------|-------|---------------|-------------|
| -- | -- | -- | -- | -- |

1.3. External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|--------------|
| Antenna Port | 3 | 0.8m, Shield |
| LAN | 1 | 0.8m, Shield |

1.4. Description of Test Facility

FCC Registration Number. is 254912.

Industry Canada Registration Number. is 9642A-1.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

NVLAP Registration Code is 600167-0.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

| Test Item | Frequency Range | Uncertainty | Note |
|------------------------|-----------------|-------------|------|
| Radiation Uncertainty | 9KHz~30MHz | ±3.10dB | (1) |
| | 30MHz~200MHz | ±2.96dB | (1) |
| | 200MHz~1000MHz | ±3.10dB | (1) |
| | 1GHz~26.5GHz | ±3.80dB | (1) |
| | 26.5GHz~40GHz | ±3.90dB | (1) |
| Conduction Uncertainty | 150kHz~30MHz | ±1.63dB | (1) |
| Power disturbance | 30MHz~300MHz | ±1.60dB | (1) |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Pre-test AC conducted emission at power adapter mode, recorded worst case.

Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worst case.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power, which was determined to be RoLa mode (Low Channel).

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be RoLa mode(Low Channel).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

1.8. Frequency of Channels

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---------|----------------|---------|----------------|
| 00 | 902.5 | 06 | 917.5 |
| 01 | 905.0 | 07 | 920.0 |
| 02 | 907.5 | 08 | 922.5 |
| 03 | 910.0 | 09 | 925.0 |
| 04 | 912.5 | 10 | 927.5 |
| 05 | 915.0 | | |

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 D01 DTS Meas. Guidance are required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition.

3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (rxhf@rhf2s008) provided by application.

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

| Applied Standard: FCC Part 15 Subpart C | | |
|---|---|------------|
| FCC Rules | Description of Test | Result |
| §15.247(b) | Maximum Conducted Output Power | Compliant |
| §15.247(e) | Power Spectral Density | Compliant |
| §15.247(a)(2) | 6dB Bandwidth | Compliant |
| §15.247(a) | Occupied Bandwidth | Compliant |
| §15.209, §15.247(d) | Radiated and Conducted Spurious Emissions | Compliant |
| §15.205 | Emissions at Restricted Band | Compliant |
| §15.207(a) | Conducted Emissions | Compliant |
| §15.203 | Antenna Requirements | Compliant* |
| §15.247(i)§2.1093 | RF Exposure | Compliant |

Remark:

RHF2S008 use external antenna and use SMA antenna connector, RHF2S008 used as professional installation.

5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None; for reporting purpose only.


5.1.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

5.1.3. Test Procedures

1. Set the center frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=50MHz, Sweep time=5ms;
3. Detector = peak;
4. Trace mode = Single hold.

5.1.4. Test Setup Layout




5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test result

| Mode | On Time B (ms) | Period (ms) | Duty Cycle x (Linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | 1/B Minimum VBW (KHz) |
|-----------|----------------|-------------|-----------------------|----------------|-----------------------------------|-----------------------|
| LORA(CSS) | 5.0 | 5.0 | 1 | 100 | 0 | 0.01 |

On Time and Duty Cycle



Channel 05 / 915 MHz

5.2. Maximum Conducted Output Power Measurement

5.2.1. Standard Applicable

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.


5.2.2. Test Procedures

The transmitter output (antenna port) was connected to the spectrum analyzer. According to KDB558074 D01 DTS Measurement Guidance Section 9.1 Maximum peak conducted output power 9.1.1.

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the RBW \geq DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

5.2.3. Test Setup Layout



5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



5.2.5. Test Result of Maximum Conducted Output Power

| Channel | Frequency (MHz) | Measured Maximum Peak Power (dBm) | Limits (dBm) | Verdict |
|---------|-----------------|-----------------------------------|--------------|---------|
| 00 | 902.5 | 24.655 | 30 | PASS |
| 05 | 915.0 | 24.958 | | |
| 10 | 927.5 | 24.219 | | |

Remark:


- 1. Test results including cable loss;
- 2. Please refer to following plots;

Maximum Peak Output Power



Channel 0 / 902.5 MHz

Channel 05 / 915 MHz



Channel 10 / 927.5 MHz

5.3. Power Spectral Density Measurement

5.3.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


5.3.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.3.3. Test Procedures

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW
5. Set the span to 1.5 times the DTS channel bandwidth.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum power level.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
12. The resulting peak PSD level must be 8 dBm.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


5.3.6. Test Result of Power Spectral Density

| Channel | Frequency (MHz) | Measured Peak Power Spectral Density (dBm/3KHz) | Limits (dBm/3KHz) | Verdict |
|---------|-----------------|---|-------------------|---------|
| 00 | 902.5 | 6.152 | 8 | PASS |
| 05 | 915.0 | 6.284 | | |
| 10 | 927.5 | 5.467 | | |


Remark:

1. Test results including cable loss;
2. Please refer to following plots;


Peak Power Spectral Density



Channel 0 / 902.5 MHz



Channel 05 / 915 MHz



Channel 10 / 927.5 MHz

5.4. 6 dB Spectrum Bandwidth Measurement

5.4.1. Standard Applicable

According to §15.247(a) (2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

5.4.2. Measuring Instruments and Setting


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameter | Setting |
|--------------------|----------|
| Attenuation | Auto |
| Span Frequency | > RBW |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | 100ms |

5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

5.4.4. Test Setup Layout



5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



5.4.6. Test Result of 6dB Spectrum Bandwidth

| Channel | Frequency (MHz) | 6dB Bandwidth (KHz) | 99% Bandwidth (KHz) | Limits (KHz) | Verdict |
|---------|-----------------|---------------------|---------------------|--------------|---------|
| 00 | 902.5 | 609.30 | 663.43 | ≥500 | PASS |
| 05 | 915.0 | 609.40 | 663.11 | | |
| 10 | 927.5 | 608.30 | 662.08 | | |

Remark:


1. Test results including cable loss;
2. Please refer to following plots;

6dB Bandwidth



Channel 0 / 902.5 MHz

Channel 05 / 915 MHz



Channel 10 / 927.5 MHz

5.5. Radiated Emissions Measurement

5.5.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| \1\ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (\2\) |
| 13.36-13.41 | | | |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

5.5.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10 th carrier harmonic |
| RB / VB (Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |

| Receiver Parameter | Setting |
|------------------------|--|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP |

5.5.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.


Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


5.5.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log(\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);
 Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.6. Results of Radiated Emissions (9 KHz~30MHz)

| | | | |
|---------------|---------|----------------|-----------|
| Temperature | 23.4°C | Humidity | 53.4% |
| Test Engineer | Tom Liu | Configurations | LORA(CSS) |

| Freq. (MHz) | Level (dBUV) | Over Limit (dB) | Over Limit (dBUV) | Remark |
|-------------|--------------|-----------------|-------------------|----------|
| - | - | - | - | See Note |

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBUV) + distance extrapolation factor.

5.5.7. Results of Radiated Emissions (30MHz~1GHz)

| | | | |
|---------------|---------|----------------|-----------|
| Temperature | 23.4°C | Humidity | 53.4% |
| Test Engineer | Tom Liu | Configurations | LORA(CSS) |

Vertical



pol:

HORIZONTAL


| | Freq | Reading | CabLos | Antfac | Measured | Limit | Over | Remark |
|---|--------|---------|--------|--------|----------|--------|-------|--------|
| | MHz | dBuV | dB | dB/m | dBuV/m | dBuV/m | dB | |
| 1 | 39.71 | 22.65 | 0.38 | 13.51 | 36.54 | 40.00 | -3.46 | QP |
| 2 | 56.00 | 22.59 | 0.47 | 12.95 | 36.01 | 40.00 | -3.99 | QP |
| 3 | 75.18 | 26.25 | 0.54 | 7.83 | 34.62 | 40.00 | -5.38 | QP |
| 4 | 154.82 | 29.72 | 0.76 | 8.46 | 38.94 | 43.50 | -4.56 | QP |
| 5 | 284.98 | 27.50 | 1.00 | 12.77 | 41.27 | 46.00 | -4.73 | QP |
| 6 | 915.00 | 39.48 | 2.04 | 21.19 | 62.71 | 46.00 | 16.71 | QP |

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported

Horizontal



pol:

VERTICAL

| | Freq | Reading | CabLos | Antfac | Measured | Limit | Over | Remark |
|---|--------|---------|--------|--------|----------|--------|-------|--------|
| | MHz | dBuV | dB | dB/m | dBuV/m | dBuV/m | dB | |
| 1 | 38.21 | 21.95 | 0.38 | 13.12 | 35.45 | 40.00 | -4.55 | QP |
| 2 | 50.06 | 21.37 | 0.54 | 13.25 | 35.16 | 40.00 | -4.84 | QP |
| 3 | 72.08 | 27.65 | 0.55 | 8.30 | 36.50 | 40.00 | -3.50 | QP |
| 4 | 142.82 | 27.87 | 0.71 | 8.21 | 36.79 | 43.50 | -6.71 | QP |
| 5 | 403.25 | 23.95 | 1.32 | 15.13 | 40.40 | 46.00 | -5.60 | QP |
| 6 | 915.00 | 40.11 | 2.04 | 21.19 | 63.34 | 46.00 | 17.34 | QP |

- Note: 1. All readings are Quasi-peak values.
 2. Measured= Reading + Antenna Factor + Cable Loss
 3. The emission that are 20db below the official limit are not reported

Note:

- 1). Pre-scan all modes and recorded the worst case results in this report. Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 2). Corrected Reading: Antenna Factor + Cable Loss + Read Level = Level.
- 3). Red color is fundamental frequency.

5.5.8. Results for Radiated Emissions (Above 1GHz)

Channel 0 / 902.5 MHz

| Freq. MHz | Reading dBuV | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|---------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 1805.00 | 47.44 | 33.06 | 35.04 | 3.94 | 49.40 | 74.00 | -24.60 | Peak | Horizontal |
| 1805.00 | 32.37 | 33.06 | 35.04 | 3.94 | 34.33 | 54.00 | -19.67 | Average | Horizontal |
| 1805.00 | 48.77 | 33.06 | 35.04 | 3.94 | 50.73 | 74.00 | -23.27 | Peak | Vertical |
| 1805.00 | 33.38 | 33.06 | 35.04 | 3.94 | 35.34 | 54.00 | -18.66 | Average | Vertical |

Channel 05 / 915 MHz

| Freq. MHz | Reading dBuV | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|---------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 1830.00 | 47.83 | 33.16 | 35.15 | 3.96 | 49.80 | 74.00 | -24.20 | Peak | Horizontal |
| 1830.00 | 33.18 | 33.16 | 35.15 | 3.96 | 35.15 | 54.00 | -18.85 | Average | Horizontal |
| 1830.00 | 49.36 | 33.16 | 35.15 | 3.96 | 51.33 | 74.00 | -22.67 | Peak | Vertical |
| 1830.00 | 34.26 | 33.16 | 35.15 | 3.96 | 36.23 | 54.00 | -17.77 | Average | Vertical |

Channel 10 / 927.5 MHz

| Freq. MHz | Reading dBuV | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|---------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 1855.00 | 49.71 | 33.26 | 35.14 | 3.98 | 51.81 | 74.00 | -22.19 | Peak | Horizontal |
| 1855.00 | 33.42 | 33.26 | 35.14 | 3.98 | 35.52 | 54.00 | -18.48 | Average | Horizontal |
| 1855.00 | 50.58 | 33.26 | 35.14 | 3.98 | 52.68 | 74.00 | -21.32 | Peak | Vertical |
| 1855.00 | 35.64 | 33.26 | 35.14 | 3.98 | 37.74 | 54.00 | -16.26 | Average | Vertical |

Notes:

- 1). Measuring frequencies from 9 KHz~10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
- 3). Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4). Measured radiated emission used 900-930 MHz band filter in order to avoid spectrum overload.

5.6. Conducted Spurious Emissions and Band Edges Test

5.6.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.6.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|---|---------------|
| Detector | Peak |
| Attenuation | Auto |
| RB / VB (Emission in restricted band) | 100KHz/300KHz |
| RB / VB (Emission in non-restricted band) | 100KHz/300KHz |

5.6.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 KHz to 10 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

5.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 5.4.4.

5.6.5. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

5.6.6. Test Results of Conducted Spurious Emissions


| | | | |
|---------------|---------|----------------|-----------|
| Temperature | 23.4°C | Humidity | 53.4% |
| Test Engineer | Tom Liu | Configurations | LORA(CSS) |

RF Conducted Spurious Emissions

Channel 0 / 902.5 MHz




902.5 MHz




9 KHz – 10 GHz

Channel 5 / 915 MHz




915 MHz




9 KHz – 10 GHz

Channel 10 / 927.5 MHz




927.5 MHz




9 KHz – 10 GHz

Band-edge measurements for conducted emissions



Channel 0 / 902.5 MHz



Channel 10 / 927.5 MHz

5.7. AC Power line conducted emissions


5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dBµV) | |
|-----------------------|---------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

5.7.2 Block Diagram of Test Setup




5.7.3 Test Results

PASS

The test data please refer to following page.

AC Conducted Emission of power adapter @ AC 120V/60Hz (worst case)

Line




Pol: NEUTRAL

| | Freq | Reading | LisnFac | CabLos | Measured | Limit | Over | Remark |
|----|-------|---------|---------|--------|----------|-------|--------|---------|
| | MHz | dBpW | dB | dB | dBpW | dBpW | dB | |
| 1 | 0.18 | 31.40 | 9.64 | 0.02 | 51.06 | 64.59 | -13.53 | QP |
| 2 | 0.18 | 14.60 | 9.63 | 0.02 | 34.25 | 54.59 | -20.34 | Average |
| 3 | 0.32 | 21.16 | 9.61 | 0.03 | 40.80 | 59.66 | -18.86 | QP |
| 4 | 0.32 | -0.25 | 9.61 | 0.03 | 19.39 | 49.66 | -30.27 | Average |
| 5 | 1.08 | 26.00 | 9.63 | 0.05 | 45.68 | 56.00 | -10.32 | QP |
| 6 | 1.08 | 10.81 | 9.63 | 0.05 | 30.49 | 46.00 | -15.51 | Average |
| 7 | 1.73 | 24.89 | 9.63 | 0.05 | 44.57 | 56.00 | -11.43 | QP |
| 8 | 1.74 | 8.67 | 9.63 | 0.05 | 28.35 | 46.00 | -17.65 | Average |
| 9 | 4.55 | 16.76 | 9.66 | 0.06 | 36.48 | 56.00 | -19.52 | QP |
| 10 | 4.55 | 2.07 | 9.66 | 0.06 | 21.79 | 46.00 | -24.21 | Average |
| 11 | 18.04 | 25.35 | 9.81 | 0.11 | 45.27 | 60.00 | -14.73 | QP |
| 12 | 18.04 | 10.08 | 9.81 | 0.11 | 30.00 | 50.00 | -20.00 | Average |

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss.
 2. The emission levels that are 20dB below the official limit are not reported.

Neutral



Pol: LINE

| | Freq | Reading | LisnFac | CabLos | Measured | Limit | Over | Remark |
|----|------|---------|---------|--------|----------|-------|--------|---------|
| | MHz | dBpW | dB | dB | dBpW | dBpW | dB | |
| 1 | 0.19 | 36.61 | 9.61 | 0.02 | 56.24 | 64.02 | -7.78 | QP |
| 2 | 0.19 | 17.75 | 9.61 | 0.02 | 37.38 | 54.02 | -16.64 | Average |
| 3 | 0.54 | 23.23 | 9.62 | 0.04 | 42.89 | 56.00 | -13.11 | QP |
| 4 | 0.54 | 5.18 | 9.62 | 0.04 | 24.84 | 46.00 | -21.16 | Average |
| 5 | 1.06 | 23.28 | 9.63 | 0.05 | 42.96 | 56.00 | -13.04 | QP |
| 6 | 1.06 | 10.41 | 9.63 | 0.05 | 30.09 | 46.00 | -15.91 | Average |
| 7 | 1.58 | 25.92 | 9.63 | 0.05 | 45.60 | 56.00 | -10.40 | QP |
| 8 | 1.58 | 8.58 | 9.63 | 0.05 | 28.26 | 46.00 | -17.74 | Average |
| 9 | 2.66 | 19.18 | 9.64 | 0.05 | 38.87 | 56.00 | -17.13 | QP |
| 10 | 2.67 | 3.09 | 9.64 | 0.05 | 22.78 | 46.00 | -23.22 | Average |
| 11 | 4.70 | 19.12 | 9.66 | 0.06 | 38.84 | 56.00 | -17.16 | QP |
| 12 | 4.70 | 5.07 | 9.66 | 0.06 | 24.79 | 46.00 | -21.21 | Average |

Remarks: 1. Measured = Reading + Lisn Factor +Cable Loss.
 2. The emission levels that are 20dB below the official limit are not reported.


***Note: Pre-scan all modes and recorded the worst case results in this report.

5.8. Band-edge measurements for radiated emissions

5.8.1 Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.8.2. Test Setup Layout



5.8.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.8.4. Test Procedures

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.

--- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

--- The final measurement will be performed with minimum the six highest peaks.


--- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.

--- The final measurement will be done with QP detector with an EMI receiver.

--- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

5.8.5 Test Results


Channel 0 / 902.5 MHz



| | Frequency MHz | Reading dBuV | Cable Loss dB | Antenna factor dB/m | Measured dBuV/m | Limit dBuV/m | Over dB | Pol. | Remark |
|---|---------------|--------------|---------------|---------------------|-----------------|--------------|---------|----------|--------|
| 1 | 901.85 | 0.15 | 1.87 | 21.10 | 23.12 | 46.00 | -22.88 | Vertical | QP |
| 2 | 915.13 | 60.28 | 2.04 | 21.19 | 83.51 | 46.00 | 37.51 | Vertical | QP |

Remark:

1. All reading are Quasi-peak values.
2. Measured = Reading + Antenna Factor + Cable Loss.
3. The emission that at least 20dB below the limits are not report.
4. Red color is fundential frequency.




| | Frequency MHz | Reading dBuV | Cable Loss dB | Antenna factor dB/m | Measured dBuV/m | Limit dBuV/m | Over dB | Pol. | Remark |
|---|---------------|--------------|---------------|---------------------|-----------------|--------------|---------|------------|--------|
| 1 | 901.94 | 0.10 | 1.87 | 21.10 | 23.07 | 46.00 | -22.93 | Horizontal | QP |
| 2 | 915.13 | 62.46 | 2.04 | 21.19 | 85.69 | 46.00 | 39.69 | Horizontal | QP |

Remark:

1. All reading are Quasi-peak values.
2. Measured = Reading + Antenna Factor + Cable Loss.
3. The emission that at least 20dB below the limits are not report.
4. Red color is fundental frequency.


Channel 10 / 927.5 MHz



| | Frequency MHz | Reading dBuV | Cable Loss dB | Antenna factor dB/m | Measured dBuV/m | Limit dBuV/m | Over dB | Pol. | Remark |
|---|---------------|--------------|---------------|---------------------|-----------------|--------------|---------|------------|--------|
| 1 | 915.06 | 63.98 | 2.04 | 21.19 | 87.21 | 46.00 | 41.21 | Horizontal | QP |
| 2 | 928.00 | -2.94 | 1.90 | 21.27 | 20.23 | 46.00 | -25.77 | Horizontal | QP |
| 3 | 953.89 | 12.70 | 2.03 | 21.44 | 36.17 | 46.00 | -9.83 | Horizontal | QP |
| 4 | 960.00 | -0.04 | 1.90 | 21.48 | 23.34 | 46.00 | -22.66 | Horizontal | QP |

Remark:

1. All reading are Quasi-peak values.
2. Measured = Reading + Antenna Factor + Cable Loss.
3. The emission that at least 20dB below the limits are not report.
4. Red color is fundential frequency.



| | Frequency MHz | Reading dBuV | Cable Loss dB | Antenna factor dB/m | Measured dBuV/m | Limit dBuV/m | Over dB | Pol. | Remark |
|---|---------------|--------------|---------------|---------------------|-----------------|--------------|---------|----------|--------|
| 1 | 915.00 | 65.21 | 2.04 | 21.19 | 88.44 | 46.00 | 42.44 | Vertical | QP |
| 2 | 928.00 | 0.44 | 1.90 | 21.27 | 23.61 | 46.00 | -22.39 | Vertical | QP |
| 3 | 953.89 | 14.54 | 2.03 | 21.44 | 38.01 | 46.00 | -7.99 | Vertical | QP |
| 4 | 960.00 | 1.74 | 1.90 | 21.48 | 23.22 | 46.00 | -22.78 | Vertical | QP |

Remark:

1. All reading are Quasi-peak values.
2. Measured = Reading + Antenna Factor + Cable Loss.
3. The emission that at least 20dB below the limits are not report.
4. Red color is fundential frequency.

5.9. Antenna Requirements

5.9.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

5.9.2 Antenna Connected Construction

5.9.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.9.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 2.0dBi, use external antenna and SMA antenna connector, RHF2S008 used as professional installation meets FCC Part §15.203 antenna requirement.

5.9.2.3. Results: Compliance.

Measurement

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refers ANSI C63.10:2013 Output power test procedure for DTS devices.

Radiated power refers to ANSI C63.10:2013 Radiated emissions tests.

Measurement parameters

| Measurement parameter | |
|-----------------------|----------|
| Detector: | Peak |
| Sweep Time: | Auto |
| Resolution bandwidth: | 1MHz |
| Video bandwidth: | 3MHz |
| Trace-Mode: | Max hold |

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Limits

| | |
|--------------|------|
| FCC | ISED |
| Antenna Gain | |
| 6 dBi | |

| Tnom | Vnom | lowest channel 902.5MHz | middle channel 915 MHz | highest channel 927.5 MHz |
|--|------|----------------------------|------------------------------------|------------------------------|
| Conducted power [dBm] Measured with LORA(CSS) modulation | | 24.655 | 24.958 | 24.219 |
| Radiated power [dBm] Measured with LORA(CSS) modulation | | 25.856 | 26.890 | 25.807 |
| Gain [dBi] Calculated | | 1.201 | 1.932 | 1.588 |
| Measurement uncertainty | | | ± 1.6 dB (cond.) / ± 3.8 dB (rad.) | |

6. LIST OF MEASURING EQUIPMENTS

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Next Cal. |
|------|--------------------------|--------------------|----------------------------------|-------------|------------|------------|
| 1 | Power Sensor | R&S | NRV-Z81 | 100458 | 2017-06-17 | 2018-06-16 |
| 2 | Power Sensor | R&S | NRV-Z32 | 10057 | 2017-06-17 | 2018-06-16 |
| 3 | Power Meter | R&S | NRVS | 100444 | 2017-06-17 | 2018-06-16 |
| 4 | DC Filter | MPE | 23872C | N/A | 2017-06-17 | 2018-06-16 |
| 5 | RF Cable | Harbour Industries | 1452 | N/A | 2017-06-17 | 2018-06-16 |
| 6 | SMA Connector | Harbour Industries | 9625 | N/A | 2017-06-17 | 2018-06-16 |
| 7 | Spectrum Analyzer | Agilent | N9020A | MY50510140 | 2016-10-27 | 2017-10-26 |
| 8 | Signal analyzer | Agilent | E4448A(External mixers to 40GHz) | US44300469 | 2017-06-15 | 2018-06-14 |
| 9 | RF Cable | Hubersuhne | Sucoflex104 | FP2RX2 | 2017-06-17 | 2018-06-16 |
| 10 | 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M | 03CH03-HY | 2017-06-17 | 2018-06-16 |
| 11 | Amplifier | SCHAFFNER | COA9231A | 18667 | 2017-06-17 | 2018-06-16 |
| 12 | Amplifier | Agilent | 8449B | 3008A02120 | 2017-06-15 | 2018-06-14 |
| 13 | Amplifier | MITEQ | AMF-6F-260400 | 9121372 | 2017-06-15 | 2018-06-14 |
| 14 | Loop Antenna | R&S | HFH2-Z2 | 860004/001 | 2017-06-17 | 2018-06-16 |
| 15 | By-log Antenna | SCHWARZBECK | VULB9163 | 9163-470 | 2017-06-09 | 2018-06-08 |
| 16 | Horn Antenna | EMCO | 3115 | 6741 | 2017-06-09 | 2018-06-08 |
| 17 | Horn Antenna | SCHWARZBECK | BBHA9170 | BBHA9170154 | 2017-06-09 | 2018-06-08 |
| 18 | RF Cable-R03m | Jye Bao | RG142 | CB021 | 2017-06-17 | 2018-06-16 |
| 19 | RF Cable-HIGH | SUHNER | SUCOFLEX 106 | 03CH03-HY | 2017-06-17 | 2018-06-16 |
| 20 | EMI Test Receiver | R&S | ESCI | 101142 | 2017-06-17 | 2018-06-16 |
| 21 | Artificial Mains | R&S | ENV216 | 101288 | 2017-06-17 | 2018-06-16 |
| 22 | EMI Test Software | AUDIX | E3 | N/A | N/A | N/A |
| 23 | Spectrum Analyzer | R&S | FSP | 100503 | 2017-06-17 | 2018-06-16 |

7. TEST SETUP PHOTOGRAPHS

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----