

FCC

RF

TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.





FOR
RHF76-052 Module


ISSUED TO
RuiXingHengFang Network (Shenzhen) CO., Ltd

Suite B3019, 3rd Tower of Elite (YiLiDa) Building, NO.1092 Nanshan
blvd, Nanshan District, Shenzhen 518054 China



Tested by: 
Cao Shaodong
(Engineer)
Date Nov. 29, 2016

Approved by: 
Wei Yanquan
(Chief Engineer)
Date Nov. 29, 2016



Report No.: BL-SZ16A0433-602
EUT Type: RHF76-052 Module
Model Name: RHF76-052
Brand Name: RisingHF
Test Standard: 47 CFR Part 15 Subpart C
FCC ID: 2AJUZ76052

Test conclusion: Pass
Test Date: Nov. 05, 2016 ~ Nov. 18 2016
Date of Issue: Nov. 29, 2016

NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please visit BALUN website.

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Nov. 23, 2016</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Nov. 29, 2016</u>	<u>Add Host Device information on page 6.</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	5
1.1	Identification of the Testing Laboratory	5
1.2	Identification of the Responsible Testing Location	5
1.3	Laboratory Condition	5
1.4	Announce	5
2	PRODUCT INFORMATION	6
2.1	Applicant Information	6
2.2	Manufacturer Information	6
2.3	Factory Information	6
2.4	General Description for Equipment under Test (EUT)	6
2.5	Ancillary Equipment	6
2.6	Technical Information	7
2.7	Additional Instructions	7
3	SUMMARY OF TEST RESULTS	8
3.1	Test Standards	8
3.2	Verdict	8
4	GENERAL TEST CONFIGURATIONS	9
4.1	Test Environments	9
4.2	Test Equipment List	9
4.3	Measurement Uncertainty	10
4.4	Description of Test Setup	10
4.4.1	For Antenna Port Test	10
4.4.2	For AC Power Supply Port Test	11
4.4.3	For Radiated Test (Below 30 MHz)	11
4.4.4	For Radiated Test (30 MHz-1 GHz)	12

4.4.5	For Radiated Test (Above 1 GHz).....	12
4.5	Measurement Results Explanation Example.....	13
4.5.1	For conducted test items:.....	13
4.5.2	For radiated band edges and spurious emission test:.....	13
5	TEST ITEMS.....	14
5.1	Antenna Requirements.....	14
5.1.1	Standard Applicable	14
5.1.2	Antenna Anti-Replacement Construction	14
5.1.3	Antenna Gain	15
5.2	Output Power	16
5.2.1	Test Limit.....	16
5.2.2	Test Setup	16
5.2.3	Test Procedure	16
5.2.4	Test Result	17
5.3	Occupied Bandwidth	18
5.3.1	Limit.....	18
5.3.2	Test Setup	18
5.3.3	Test Procedure	18
5.3.4	Test Result	18
5.4	Conducted Spurious Emission	19
5.4.1	Limit.....	19
5.4.2	Test Setup	19
5.4.3	Test Procedure	19
5.4.4	Test Result	20
5.5	Band Edge (Authorized-band band-edge).....	21
5.5.1	Limit.....	21
5.5.2	Test Setup	21
5.5.3	Test Procedure	21
5.5.4	Test Result	21
5.6	Conducted Emission	22
5.6.1	Limit.....	22

5.6.2	Test Setup	22
5.6.3	Test Procedure	22
5.6.4	Test Result	22
5.7	Radiated Spurious Emission	23
5.7.1	Limit.....	23
5.7.2	Test Setup	23
5.7.3	Test Procedure	23
5.7.4	Test Result	24
5.8	Band Edge (Restricted-band band-edge).....	25
5.8.1	Limit.....	25
5.8.2	Test Setup	25
5.8.3	Test Procedure	25
1.1.1	Test Result	25
5.9	Power Spectral density (PSD).....	26
5.9.1	Limit.....	26
5.9.2	Test Setup	26
5.9.3	Test Procedure	26
ANNEX A	TEST RESULT	27
A.1	Output Power	27
A.2	Occupied Bandwidth	28
A.3	Conducted Spurious Emissions	30
A.4	Band Edge (Authorized-band band-edge).....	33
A.5	Conducted Emissions.....	35
A.6	Radiated Spurious Emission	36
A.7	Band Edge (Restricted-band band-edge).....	43
A.8	Power Spectral Density (PSD)	44
ANNEX B	TEST SETUP PHOTOS	45
ANNEX C	EUT INTERNAL PHOTOS	45

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100
Fax Number	+86 755 6182 4271

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	<p>The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1.</p> <p>The laboratory has been listed by US Federal Communications Commission to perform electromagnetic emission measurements. The recognition numbers of test site are 832625.</p> <p>The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.</p>
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v5.4.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	RuiXingHengFang Network (Shenzhen) CO., Ltd
Address	Suite B3019, 3 rd Tower of Elite (YiLiDa) Building, NO.1092 Nanshan blvd, Nanshan District, Shenzhen 518054 China

2.2 Manufacturer Information

Manufacturer	RuiXingHengFang Network (Shenzhen) CO., Ltd
Address	Suite B3019, 3 rd Tower of Elite (YiLiDa) Building, NO.1092 Nanshan blvd, Nanshan District, Shenzhen 518054 China

2.3 Factory Information

Factory	RuiXingHengFang Network (Shenzhen) CO., Ltd
Address	Suite B3019, 3 rd Tower of Elite (YiLiDa) Building, NO.1092 Nanshan blvd, Nanshan District, Shenzhen 518054 China

2.4 General Description for Equipment under Test (EUT)

EUT Type	RHF76-052 Module
Model Name Under Test	RHF76-052
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V2.0
Software Version	V2.0.3
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	Lora Spread Spectrum, LoraWAN

2.5 Ancillary Equipment

Ancillary Equipment 1	Host Device	
	Brand Name	RisingHF
	Model No.	RHF1S001
	Product name	RHF1S001 IP64 T&H sensor

2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	DTS
Modulation Type	LoRa
Product Type	Mobile and portable
Frequency Range	The frequency range used is 902 MHz to 928 MHz.
Number of channel	8
Tested Channel	0 (903 MHz), 4 (909.4 MHz), 7 (914.2 MHz)
Antenna Type	PIFA Antenna
Antenna Gain	-2 dBi (All involve the antenna gain test item, has been included in the final results)
Antenna System(MIMO Smart Antenna)	N/A
About the Product	The EUT is supply the DTS, Frequency hopping system and Hybrid system, only the DTS was tested in this report.

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	903.00	4	909.40
1	904.60	5	911.00
2	906.20	6	912.60
3	907.80	7	914.20

2.7 Additional Instructions

EUT Software Settings:

Mode	<input checked="" type="checkbox"/> Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.
------	--

During testing. Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software		
Test Software Version		
Mode	Channel	Soft Set
LoRa	ALL	14

Run Software

```
D:\>CD D:\rCFG
D:\rCFG>rCFG.exe -t RXCLORA -P "902500000,7,500000,12,12,14"
```

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-15 Edition)	Miscellaneous Wireless Communications Services
2	KDB Publication 558074 D01v03r05	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict
1	Antenna Requirement	15.203	N/A	--	Pass ^{Note1}
2	Output Power	15.247(b)	Low/Middle/High	ANNEX A.1	Pass
3	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.2	Pass
4	Conducted Spurious Emission	15.247(d)	Low/Middle/High	ANNEX A.3	Pass
5	Band Edge(Authorized-band band-edge)	15.247(d)	Low/ High	ANNEX A.4	Pass
6	Conducted Emission	15.207	Low/Middle/High	ANNEX A.5	N/A ^{Note2}
7	Radiated Spurious Emission	15.209 15.247(d)	Low/Middle/High	ANNEX A.6	Pass
8	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Low/Middle/High	ANNEX A.7	Pass
9	Power spectral density (PSD)	15.247(e)	Low/Middle/High	ANNEX A.8	Pass

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: The EUT is supply by battery, so the Conducted Emission is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	3.0 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2016.07.13	2017.07.12
Vector Signal Generator	ROHDE&SCHWARZ	SMBV100A	177746	2016.07.13	2017.07.12
Signal Generator	ROHDE&SCHWARZ	SMB100A	260592	2016.07.13	2017.07.12
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2016.07.13	2017.07.12
Spectrum Analyzer	AGILENT	E4440A	MY45304434	2016.11.08	2017.11.07
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2016.07.05	2017.07.04
LISN	SCHWARZBECK	NSLK 8127	8127-687	2016.07.05	2017.07.04
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2016.07.13	2017.07.12
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2016.07.13	2017.07.12
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2016.07.13	2017.07.12
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2016.07.13	2017.07.12
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2015.07.22	2017.07.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2015.07.22	2017.07.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2015.07.22	2017.07.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2015.07.22	2017.07.21
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2015.02.28	2017.02.27
Shielded Enclosure	ChangNing	CN-130701	130703	--	--

4.3 Measurement Uncertainty


The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Occupied Channel Bandwidth	$\pm 4\%$
RF output power, conducted	± 1.4 dB
Power Spectral Density, conducted	± 2.5 dB
Unwanted Emissions, conducted	± 2.8 dB
All emissions, radiated	± 5.4 dB
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 4\%$


4.4 Description of Test Setup

4.4.1 For Antenna Port Test




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

EIRP = Measure Conducted output power Value (dBm) + Maximum transmit antenna gain (dBi) + the appropriate maximum ground reflection factor (dB)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Standard Applicable

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)



An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is An embedded-in	The antenna is welded on the mainboard, can't be replaced by the consumer

Reference Documents	Item
<p>Photo</p> <div data-bbox="145 277 416 353" style="border: 1px solid red; padding: 5px; display: inline-block;">PIFA Antenna</div> 	

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Output Power

5.2.1 Test Limit

FCC § 15.247(b)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements.

RSS-247, 5.4 (4)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. Except as provided in Section 5.4(5), the e.i.r.p. shall not exceed 4 W.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

a) Maximum (average) conducted output power

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

Set the RBW \geq DTS bandwidth.

Set VBW $\geq 3 \times$ RBW.

Set span $\geq 3 \times$ RBW

Sweep time = auto couple.

Detector = RMS

Trace mode = max hold.

Allow trace to fully stabilize.

Use peak marker function to determine the peak amplitude level.

b) Measurements of duty cycle

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal.

Set the center frequency of the instrument to the center frequency of the transmission.

Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value.

Set VBW \geq RBW. Set detector = peak or average.

The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of

sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Occupied Bandwidth

5.3.1 Limit

FCC §15.247(a); RSS-247, 5.1 (1); RSS-GEN, 6.6

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

Use the following spectrum analyzer settings:

Set RBW = 100 kHz.

Set the video bandwidth (VBW) ≥ 3 RBW.

Detector = Peak.

Trace mode = max hold.

Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Conducted Spurious Emission

5.4.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions:

- a) If the maximum peak conducted output power procedure was used to demonstrate compliance as described in 9.1, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).
- b) If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).
- c) In either case, attenuation to levels below the 15.209 general radiated emissions limits is not required.

The following procedures shall be used to demonstrate compliance to these limits. Note that these procedures can be used in either an antenna-port conducted or radiated test set-up. Radiated tests must conform to the test site requirements and utilize maximization procedures defined herein.

Reference level measurement:

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Emission level measurement:

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto couple.

Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Band Edge (Authorized-band band-edge)

5.5.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The following procedures may be used to determine the peak or average field strength or power of an unwanted emission that is within 2 MHz of the authorized band edge. If a peak detector is utilized, use the procedure described in 13.2.1. Use the procedure described in 13.2.2 when using an average detector and the EUT can be configured to transmit continuously (i.e., duty cycle $\geq 98\%$). Use the procedure described in 13.2.3 when using an average detector and the EUT cannot be configured to transmit continuously but the duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent). Use the procedure described in 13.2.4 when using an average detector for those cases where the EUT cannot be configured to transmit continuously and the duty cycle is not constant (duty cycle variations equal or exceed 2 percent).

When using a peak detector to measure unwanted emissions at or near the band edge (within 2 MHz of the authorized band), the following integration procedure can be used.

Set instrument center frequency to the frequency of the emission to be measured (must be within 2 MHz of the authorized band edge).

Set span to 2 MHz

RBW = 100 kHz.

VBW $\geq 3 \times$ RBW.

Detector = peak.

Sweep time = auto.

Trace mode = max hold.

Allow sweep to continue until the trace stabilizes (required measurement time may increase for low duty cycle applications)

Compute the power by integrating the spectrum over 1 MHz using the analyzer's band power measurement function with band limits set equal to the emission frequency (femission) ± 0.5 MHz. If the instrument does not have a band power function, then sum the amplitude levels (in power units) at 100 kHz intervals extending across the 1 MHz spectrum defined by femission ± 0.5 MHz.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Conducted Emission

5.6.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.6.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.6.4 Test Result

Please refer to ANNEX A.5.

5.7 Radiated Spurious Emission

5.7.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dB $\mu\text{V}/\text{m}$) = 20*log[Field Strength ($\mu\text{V}/\text{m}$)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.7.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Band Edge (Restricted-band band-edge)

5.8.1 Limit

FCC §15.209&15.247(d); RSS-GEN, 8.9; RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.8.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

For transmitters operating above 1 GHz repeat the measurement with an average detector.

1.1.1 Test Result

Please refer to ANNEX A.7.

5.9 Power Spectral density (PSD)

5.9.1 Limit

FCC §15.247(e); RSS-247, 5.2 (2)

The same method of determining the conducted output power shall be used to determine the power spectral density. If a peak output power is measured, then a peak power spectral density measurement is required. If an average output power is measured, then an average power spectral density measurement should be used.

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of Section 5.4(4), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

5.9.2 Test Setup

See section 4.4.1 (Diagram 1) for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

Set instrument center frequency to DTS channel center frequency.

Set span to at least 1.5 times the OBW.

Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.

Set VBW $\geq 3 \times \text{RBW}$.

Detector = power averaging (RMS).

Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.

Sweep time = auto couple.

Employ trace averaging (RMS) mode over a minimum of 100 traces.

Use the peak marker function to determine the maximum amplitude level.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced). Test Result

Please refer to ANNEX A.7.

ANNEX A TEST RESULT

A.1 Output Power

Note: The duty cycle of EUT is 100%.

Average Power Test Data

Channel	Measured Output Power		Limit		Verdict
	LoRa		dBm	mW	
	dBm	mW			
Low	13.71	23.50	30	1000	Pass
Middle	13.68	23.33			Pass
High	13.72	23.55			Pass

A.2 Occupied Bandwidth

Test Data

Test Mode	LoRa		
Channel	6 dB Bandwidth (kHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limits (kHz)
Low Channel	0.60	0.62	≥500
Middle Channel	0.66	0.61	≥500
High Channel	0.70	0.60	≥500

Test plots (6 dB Bandwidth)

LOW CHANNEL




Date: 14.NOV.2016 17:10:23

MIDDLE CHANNEL



Date: 14.NOV.2016 17:17:54


HIGH CHANNEL



Date: 14.NOV.2016 17:20:43

Test plots (99% Bandwidth)

LOW CHANNEL




Date: 14.NOV.2016 17:10:27

MIDDLE CHANNEL



Date: 14.NOV.2016 17:17:59

HIGH CHANNEL



Date: 14.NOV.2016 17:20:48


A.3 Conducted Spurious Emissions

Test Data

LoRa				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low	-38.93	13.66	-16.34	Pass
Middle	-38.20	13.69	-16.31	Pass
High	-37.42	13.70	-16.30	Pass


Test Plots

LOW CHANNEL , CARRIER LEVEL




Date: 18 NOV 2016 16:01:18

LOW CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 18 NOV 2016 16:01:41

LOW CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




Date: 18 NOV 2016 16:02:13

MIDDLE CHANNEL , CARRIER LEVEL




Date: 18 NOV 2016 16:09:19

MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 18 NOV 2016 16:09:57

MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz



Date: 18 NOV 2016 16:11:10


High CHANNEL , CARRIER LEVEL




Date: 18 NOV 2016 16:15:00

HIGH CHANNEL , SPURIOUS 30 MHz ~ 3 GHz

HIGH CHANNEL , SPURIOUS 3 GHz ~ 25 GHz



Date: 18 NOV 2016 16:15:42



Date: 18 NOV 2016 16:16:04


A.4 Band Edge (Authorized-band band-edge)

Note: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.

Channel	Measured Max. Band Edge Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 30 dBc Limit	
Low Channel	-34.90	13.63	-16.37	Pass
High Channel	-36.03	13.61	-16.39	Pass


Test Plots

LOW CHANNEL, Carrier level




Date: 14.NOV.2016 17:12:01

LOW CHANNEL, Reference level




Date: 14.NOV.2016 17:13:34

LOW CHANNEL, Band Edge




Date: 14.NOV.2016 17:14:15

HIGH CHANNEL, Carrier level




Date: 14 NOV. 2016 17:21:17

HIGH CHANNEL, Reference level



Date: 14 NOV. 2016 17:22:27

HIGH CHANNEL, Band Edge



Date: 14 NOV. 2016 17:23:28

A.5 Conducted Emissions

N/A

A.6 Radiated Spurious Emission

Cabinet Radiated spurious emission test

Note 1: The symbol of "--" in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Note 4: The marked spikes near 900 MHz with circle should be ignored because they are Fundamental signal.


Test Data and Plots

903 MHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	64.669	17.22	-20.90	40.0	22.78	Peak	240.00	100	Vertical	Pass
2	131.582	20.10	-23.72	43.5	23.40	Peak	300.00	100	Vertical	Pass
3	215.466	22.62	-20.24	43.5	20.88	Peak	123.10	200	Vertical	Pass
4	431.480	24.94	-14.98	46.0	21.06	Peak	360.00	100	Vertical	Pass
5	650.160	27.53	-10.33	46.0	18.47	Peak	138.30	200	Vertical	Pass
6	902.539	106.73	-5.78	46.0	-60.73	Peak	276.00	100	Vertical	N/A

903 MHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	47.941	16.40	-19.01	40.0	23.60	Peak	334.00	300	Horizontal	Pass
2	106.853	17.69	-20.62	43.5	25.81	Peak	6.00	300	Horizontal	Pass
3	181.282	19.93	-22.25	43.5	23.57	Peak	13.00	100	Horizontal	Pass
4	299.108	25.72	-17.96	46.0	20.28	Peak	77.00	100	Horizontal	Pass
5	534.031	25.96	-12.59	46.0	20.04	Peak	109.00	200	Horizontal	Pass
6	909.570	105.71	-5.56	46.0	-59.71	Peak	301.00	100	Horizontal	N/A

909.4 MHz, ANT V




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	48.910	17.47	-18.93	40.0	22.53	Peak	132.00	300	Vertical	Pass
2	98.610	15.71	-20.75	43.5	27.79	Peak	69.00	300	Vertical	Pass
3	201.890	16.91	-20.35	43.5	26.59	Peak	342.00	300	Vertical	Pass
4	360.202	21.81	-16.43	46.0	24.19	Peak	336.00	100	Vertical	Pass
5	664.464	26.41	-10.34	46.0	19.59	Peak	66.00	100	Vertical	Pass
6	909.570	110.84	-5.56	46.0	-64.84	Peak	67.00	100	Vertical	N/A

909.4 MHz, ANT H




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	54.001	17.37	-19.01	40.0	22.63	Peak	307.00	200	Horizontal	Pass
2	109.520	17.46	-20.52	43.5	26.04	Peak	242.00	100	Horizontal	Pass
3	183.222	16.18	-22.07	43.5	27.32	Peak	114.00	100	Horizontal	Pass
4	296.441	18.91	-17.98	46.0	27.09	Peak	3.00	300	Horizontal	Pass
5	514.394	23.70	-13.23	46.0	22.30	Peak	3.00	100	Horizontal	Pass
6	914.419	101.27	-5.58	46.0	-55.27	Peak	43.00	100	Horizontal	N/A

914.2MHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	60.062	16.52	-20.36	40.0	23.48	Peak	352.00	100	Vertical	Pass
2	118.005	15.82	-21.81	43.5	27.68	Peak	287.00	300	Vertical	Pass
3	207.466	16.21	-20.23	43.5	27.29	Peak	112.00	100	Vertical	Pass
4	337.898	21.61	-16.72	46.0	24.39	Peak	315.00	100	Vertical	Pass
5	531.122	27.91	-12.75	46.0	18.09	Peak	105.00	300	Vertical	Pass
6	913.934	104.04	-5.54	46.0	-52.04	Peak	69.00	300	Vertical	N/A

914.2 MHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	54.001	17.37	-19.01	40.0	22.63	Peak	307.00	200	Horizontal	Pass
2	109.520	17.46	-20.52	43.5	26.04	Peak	242.00	100	Horizontal	Pass
3	183.222	16.18	-22.07	43.5	27.32	Peak	114.00	100	Horizontal	Pass
4	296.441	18.91	-17.98	46.0	27.09	Peak	3.00	300	Horizontal	Pass
5	514.394	23.70	-13.23	46.0	22.30	Peak	3.00	100	Horizontal	Pass
6	914.419	101.27	-5.58	46.0	-55.27	Peak	43.00	100	Horizontal	N/A

LOW CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1168.46	41.49	-6.25	74	32.51	Peak	49.8	150	Vertical	Pass
2	1531.37	41.19	-4.71	74	32.81	Peak	114.4	150	Vertical	Pass
3	1755.31	46.19	-3.12	74	27.81	Peak	40.1	150	Vertical	Pass
4	6280.78	50.39	18.58	74	23.61	Peak	21.2	150	Vertical	Pass
5	7920.55	40.80	10.29	74	33.20	Peak	103.5	150	Vertical	Pass
6	8976.29	45.70	10.73	74	28.30	Peak	99.6	150	Vertical	Pass

LOW CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1212.95	41.30	-0.30	74	32.70	Peak	331.6	150	Horizontal	Pass
2	1580.86	44.52	8.96	74	29.48	Peak	228.6	150	Horizontal	Pass
3	1664.33	52.07	15.15	74	21.93	Peak	336.5	150	Horizontal	Pass
4	6269.55	45.36	19.00	74	28.64	Peak	91.8	150	Horizontal	Pass
5	8055.32	47.85	8.55	74	26.15	Peak	84.1	150	Horizontal	Pass
6	8425.96	49.66	11.28	74	24.34	Peak	16.4	150	Horizontal	Pass

MIDDLE CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1363.41	41.76	-6.31	74	32.24	Peak	253.5	150	Vertical	Pass
2	1495.38	44.60	-4.53	74	29.40	Peak	142.2	150	Vertical	Pass
3	1685.83	43.68	-4.11	74	30.32	Peak	184	150	Vertical	Pass
4	6280.78	40.22	20.21	74	33.79	Peak	214.5	150	Vertical	Pass
5	8223.79	46.55	9.02	74	27.45	Peak	192.8	150	Vertical	Pass
6	8942.60	43.09	13.03	74	30.91	Peak	237.2	150	Vertical	Pass

MIDDLE CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1051.99	43.38	-4.08	74	30.62	Peak	238.5	150	Horizontal	Pass
2	1492.38	46.61	1.70	74	27.39	Peak	33.6	150	Horizontal	Pass
3	1953.26	48.29	14.56	74	25.71	Peak	56.5	150	Horizontal	Pass
4	6359.40	41.83	17.12	74	32.17	Peak	256.3	150	Horizontal	Pass
5	7639.77	44.71	11.41	74	29.29	Peak	61.5	150	Horizontal	Pass
6	9043.68	45.96	12.37	74	28.04	Peak	205.3	150	Horizontal	Pass

HIGH CHANNEL 1 GHz to 10 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1088.48	42.31	-6.25	74	31.69	Peak	306.7	150	Vertical	Pass
2	1378.91	42.39	-4.01	74	31.61	Peak	250.9	150	Vertical	Pass
3	1686.33	42.08	-4.34	74	31.92	Peak	16.6	150	Vertical	Pass
4	6202.16	44.84	14.40	74	29.16	Peak	32.4	150	Vertical	Pass
5	7819.47	51.93	9.20	74	22.07	Peak	205.5	150	Vertical	Pass
6	8538.27	49.26	14.01	74	24.74	Peak	15.4	150	Vertical	Pass

HIGH CHANNEL 1 GHz to 10 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1175.46	40.39	-3.71	74	33.61	Peak	194	150	Horizontal	Pass
2	1435.89	46.68	1.46	74	27.32	Peak	252.8	150	Horizontal	Pass
3	1770.81	47.30	13.75	74	26.71	Peak	196.4	150	Horizontal	Pass
4	6247.09	45.47	20.21	74	28.54	Peak	60.3	150	Horizontal	Pass
5	7785.77	43.42	9.33	74	30.58	Peak	47	150	Horizontal	Pass
6	8403.49	47.13	12.49	74	26.87	Peak	54.4	150	Horizontal	Pass

A.7 Band Edge (Restricted-band band-edge)

PASS

Note: The adjacent to the restricted frequency band (608-614MHz and 960-1240MHz) is far away the fundamental, it is noise only. Please refer to Section A.6 for test data.


A.8 Power Spectral Density (PSD)

Test Data

Channel	Spectral power density (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Low Channel	-6.93	8	Pass
Middle Channel	-6.88	8	Pass
High Channel	-6.93	8	Pass


Test plots

LOW CHANNEL




Date: 18 NOV 2016 16:01:08

MIDDLE CHANNEL



Date: 18 NOV 2016 16:07:33

HIGH CHANNEL



Date: 18 NOV 2016 16:14:48

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ16A0433-AR.PDF”.

ANNEX C EUT INTERNAL PHOTOS

Please refer the document “BL-SZ16A0433-AI.PDF”.

--END OF REPORT--