

FCC TEST REPORT

FOR

Foto Electric Supply Co., INC.

Laptop

Test Model: LAP116

Additional Model No.: LAP116-BK, CBL611-BK, LAP116-WH, CBL611-WH,  
LAP116-RD, CBL611-RD

Prepared for : Foto Electric Supply Co., INC.  
Address : 1 Rewe St. Brooklyn, New York 11211, United States

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,  
Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330

Fax : (+86)755-82591332

Web : www.LCS-cert.com

Mail : webmaster@LCS-cert.com

Date of receipt of test sample : Sep 21, 2016

Number of tested samples : 1

Sample number : 16060309

Date of Test : Sep 21, 2016~Oct 14, 2016

Date of Report : Oct 14, 2016

**FCC TEST REPORT**

**FCC CFR 47 PART 15 C(15.247): 2015**

**Report Reference No. .... : LCS1609211554E**

Date of Issue ..... : Oct 14, 2016

**Testing Laboratory Name ..... : Shenzhen LCS Compliance Testing Laboratory Ltd.**

Address ..... : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China

Testing Location/ Procedure ..... : Full application of Harmonised standards   
 Partial application of Harmonised standards   
 Other standard testing method

**Applicant's Name..... : Foto Electric Supply Co., INC.**

Address ..... : 1 Rewe St. Brooklyn, New York 11211, United States

**Test Specification**

Standard ..... : FCC CFR 47 PART 15 C(15.247): 2015 / ANSI C63.10: 2013

Test Report Form No. .... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF ..... : Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test Item Description. .... : Laptop**


Trade Mark..... : SLIDE, COBY

Test Model ..... : LAP116

Ratings ..... : DC 3.7V by Li-ion Battery(10000mAh)  
 Recharge Voltage: DC 12V/3A

**Result ..... : Positive**

**Compiled by:**




Calvin Weng/ Administrators

**Supervised by:**



Glin Lu/ Technique principal

**Approved by:**



Gavin Liang/ Manager

## FCC -- TEST REPORT

<b>Test Report No. : LCS1609211554E</b>	<u>Oct 14, 2016</u> Date of issue
---	--------------------------------------

Test Model..... : LAP116  EUT..... : Laptop
<b>Applicant..... : Foto Electric Supply Co., INC.</b> Address..... : 1 Rewe St. Brooklyn, New York 11211, United States Telephone..... : / Fax..... : /
<b>Manufacturer..... : Foto Electric Supply Co., INC.</b> Address..... : 1 Rewe St. Brooklyn, New York 11211, United States Telephone..... : / Fax..... : /
<b>Factory..... : Foto Electric Supply Co., INC.</b> Address..... : 1 Rewe St. Brooklyn, New York 11211, United States Telephone..... : / Fax..... : /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.  
 It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

### Revision History

Revision	Issue Date	Revisions	Revised By
00	2016-10-14	Initial Issue	Gavin Liang

## TABLE OF CONTENTS

<b>1. GENERAL INFORMATION.....</b>	<b>6</b>
1.1 Description of Device (EUT).....	6
1.2 Support Equipment List.....	7
1.3 External I/O .....	7
1.4 Description of Test Facility .....	7
1.5 List Of Measuring Equipments.....	8
1.6 Statement of The Measurement Uncertainty .....	10
1.7 Measurement Uncertainty.....	10
1.8 Description Of Test Modes.....	11
<b>2. TEST METHODOLOGY .....</b>	<b>12</b>
2.1 EUT Configuration .....	12
2.2 EUT Exercise.....	12
2.3 General Test Procedures .....	12
<b>3. SYSTEM TEST CONFIGURATION.....</b>	<b>13</b>
3.1 Justification.....	13
3.2 EUT Exercise Software .....	13
3.3 Special Accessories .....	13
3.4 Block Diagram/Schematics.....	13
3.5 Equipment Modifications .....	13
3.6 Test Setup .....	13
<b>4. SUMMARY OF TEST RESULTS .....</b>	<b>14</b>
<b>5. ANTENNA PORT MEASUREMENT .....</b>	<b>15</b>
5.1 Conducted Peak Output Power .....	15
5.2 Frequency Separation And 20 dB Bandwidth .....	16
5.3 Number Of Hopping Frequency .....	21
5.4 Time Of Occupancy (Dwell Time).....	23
5.5 Conducted Spurious Emissions and Band Edges Test.....	25
<b>6. RADIATED MEASUREMENT .....</b>	<b>29</b>
6.1 Block Diagram of Test Setup.....	29
6.2 Radiated Emission Limit .....	30
6.3 Instruments Setting .....	31
6.4 Test Procedures.....	32
6.5 Results for Radiated Emissions .....	35
6.6 Results for Band edge Testing (Radiated) .....	38
<b>7. LINE CONDUCTED EMISSIONS.....</b>	<b>39</b>
7.1 Standard Applicable.....	39
7.2 Block Diagram of Test Setup.....	39
7.3 Test Results.....	39
<b>8. ANTENNA REQUIREMENT .....</b>	<b>41</b>
8.1 Standard Applicable.....	41
8.2 Antenna Connected Construction .....	41

## 1. GENERAL INFORMATION

### 1.1 Description of Device (EUT)

EUT	: Laptop
Test Model	: LAP116
Hardware Version	: INET-T102-REV01
Software Version	: WIN10
Power Supply	: DC 3.7V by Li-ion Battery(10000mAh) Recharge Voltage: DC 12V/3A
EUT Supports	: 2.4GHz WIFI/Bluetooth
Radios Application	
Bluetooth	:
Operating Frequency	: 2.402-2.480GHz
Channel Number	: 79 channels for Bluetooth V3.0 (DSS) 40 channels for Bluetooth V4.0 (DTS)
Channel Spacing	: 1MHz for Bluetooth V3.0 (DSS) 2MHz for Bluetooth V4.0 (DTS)
Modulation Type	: GFSK, Pi/4-DQPSK, 8-DPSK for Bluetooth V3.0 (DSS) GFSK for Bluetooth V4.0 (DTS)
Bluetooth Version	: V4.0
Antenna Description	: FPC Antenna, 0dBi(Max.)
WIFI(2.4GHz Band)	:
Operating Frequency	: 2412-2462MHz
Channel Spacing	: 5MHz
Channel Number	: 11 Channel for 20MHz bandwidth(2412~2462MHz)
Modulation Type	: 802.11b: DSSS; 802.11g/n: OFDM
Antenna Description	: FPC Antenna, 0dBi(Max.)

## 1.2 Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
---	---	---	---	---

## 1.3 External I/O

I/O Port Description	Quantity	Cable
Earphone Jack	1	N/A
USB Port	2	N/A
DC in port	1	1.5m

## 1.4 Description of Test Facility

CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

VCCI Registration Number. is C-4260 and R-3804.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

There is one 3m semi-anechoic chamber and one line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.10: 2013, CISPR 22/EN 55022 and CISPR16-1-4 SVSWR requirements.

## 1.5 List Of Measuring Equipments

Instrument	Manufacture	Model No.	Serial No.	Characteristics	Cal Date	Due Date
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Jun 18, 2016	Jun 17, 2017
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	Jul 16, 2016	Jul 15, 2017
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	Jun 18, 2016	Jun 17, 2017
LISN	EMCO	3819/2NM	9703-1839	9KHz-30MHz	Jun 18, 2016	Jun 17, 2017
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	Jun 18, 2016	Jun 17, 2017
ISN	SCHAFFNE	ISN ST08	21653	9KHz-30MHz	Jun 18, 2016	Jun 17, 2017
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30M-18GHz	Jun 18, 2016	Jun 17, 2017
Amplifier	SCHAFFNE	COA9231A	18667	9kHz-2GHz	Apr 18, 2016	Apr 17, 2017
Amplifier	Agilent	8449B	3008A021	1GHz-26.5GHz	Apr 18, 2016	Apr 17, 2017
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz-40GHz	Apr 18, 2016	Apr 17, 2017
Loop Antenna	R&S	HFH2-Z2	860004/00	9k-30MHz	Apr 18, 2016	Apr 17, 2017
By-log Antenna	SCHWARZB	VULB9163	9163-470	30MHz-1GHz	Apr 18, 2016	Apr 17, 2017
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	Apr 18, 2016	Apr 17, 2017
Horn Antenna	SCHWARZB	BBHA9170	BBHA9170	15GHz-40GHz	Apr 18, 2016	Apr 17, 2017
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	Jun 18, 2016	Jun 17, 2017
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-H	1GHz-40GHz	Jun 18, 2016	Jun 17, 2017
Power Meter	R&S	NRVS	100444	DC-40GHz	Jun 18, 2016	Jun 17, 2017
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	Jun 18, 2016	Jun 17, 2017
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	Jun 18, 2016	Jun 17, 2017
AC Power Source	HPC	HPA-500E	HPA-9100	AC 0~300V	Jun 18, 2016	Jun 17, 2017
DC power Source	GW	GPC-6030D	C671845	DC 1V-60V	Jun 18, 2016	Jun 17, 2017
Temp. and Humidigy Chamber	Giant Force	GTH-225-20-S	MAB0103-00	N/A	Jun 18, 2016	Jun 17, 2017
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	Jun 18, 2016	Jun 17, 2017
RF CABLE-2m	JYE Bao	RG142	CB035-2m	20MHz-1GHz	Jun 18, 2016	Jun 17, 2017
Signal Generator	R&S	SMR40	10016	10MHz~40GHz	Jul 16, 2016	Jul 15, 2017
Universal Radio Communication Tester	R&S	CMU200	112012	N/A	Oct 27, 2015	Oct 26, 2016
Wideband Radia Communication Tester	R&S	CMW500	1201.0002 K50	N/A	Nov 19, 2016	Nov 18, 2016
MXG Vector Signal Generator	Agilent	N5182A	MY47071151	250KHz~6GHz	Oct 27, 2015	Oct 26, 2016
MXG Vector Signal Generator	Agilent	E4438C	MY42081396	250KHz~6GHz	Oct 27, 2015	Oct 26, 2016
PSG Analog Signal Generator	Agilent	N8257D	MY46520521	250KHz~20GHz	Nov 19, 2016	Nov 18, 2016
MXA Signal Analyzer	Agilent	N9020A	MY50510140	10Hz~26.5GHz	Oct 27, 2015	Oct 26, 2016
DC Power Supply	Agilent	E3642A	/	0-8V,5A/0-20V,2	May 20,	May 19, 2017
RF Control Unit	Tonscend	JS0806-1	/	/	Nov 19, 2016	Nov 18, 2017

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd..



LTE Test Software	Tonscend	JS1120-1	/	Version: 2.5.7.0	N/A	N/A
X-series USB Peak and Average Power Sensor Agilent	Agilent	U2021XA	MY54080022	/	Oct 27, 2015	Oct 26, 2016
4 Ch.Simultaneous Sampling 14 Bits 2 MS/s	Agilent	U2531A	MY54080016	/	Oct 27, 2015	Oct 26, 2016
Test Software	Ascentest	AT890-SW	20141230	Version:	N/A	N/A
Splitter/Combiner(Qty: 2)	Mini-Circuits	ZAPD-50W 4.2-6.0 GHz	NN256400424	/	Oct 27, 2015	Oct 26, 2016
Splitter/Combine(Qty: 2)	MCLI	PS3-7	4463/4464	/	Oct 27, 2015	Oct 26, 2016
ATT (Qty: 1)	Mini-Circuits	VAT-30+	30912	/	Oct 27, 2015	Oct 26, 2016

## 1.6 Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

## 1.7 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	3.10dB	(1)
	30MHz~200MHz	2.96dB	(1)
	200MHz~1000MHz	3.10dB	(1)
	1GHz~26.5GHz	3.80dB	(1)
	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	1.63dB	(1)
Power disturbance	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

## 1.8 Description Of Test Modes

Bluetooth operates in the unlicensed ISM Band at 2.4GHz. With the introduction of the enhanced data rate (EDR) feature, the data rates can be up to 3 Mb/s. An increase in the peak data rate beyond the basic rate of 1 Mb/s is achieved by modulating the RF carrier using GFSK techniques, resulting in an increase of two to three times the number of bits per symbol. The 2 Mb/s EDR packets use a Pi/4-DQPSK modulation and the 3 Mb/s EDR packets use 8DPSK modulation. The following operating modes were applied for the related test items. For radiated measurement, the test was performed with EUT in X, Y, Z position and the worse case was found when EUT in Y position. All test modes were tested, only the result of the worst case was recorded in the report.

Mode of Operations	Frequency Range (MHz)	Data Rate (Mbps)
GFSK	2402	1
	2441	1
	2480	1
Pi/4 DQPSK	2402	2
	2441	2
	2480	2
8-DPSK	2402	3
	2441	3
	2480	3
For Conducted Emission		
Test Mode	TX Mode	
For Radiated Emission		
Test Mode	TX Mode	

For pre-testing, when performed power line conducted emission measurement, the input Voltage/Frequency AC 120V/60Hz and AC 240V/60Hz were used. Only recorded the worst case in this report.

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was determined to be TX Mode(1Mbps-Hopping).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was determined to be TX-High Channel Mode(1Mbps).

\*\*\*Note: Using a temporary antenna connector for the EUT when conducted measurements are performed.

## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013, FCC CFR PART 15C 15.207, 15.209, 15.247 and DA 00-705.

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209, 15.247 under the FCC Rules Part 15 Subpart C.

### 2.3 General Test Procedures

#### 2.3.1 Conducted Emissions

According to the requirements in Section 6.2 of ANSI C63.10: 2013, AC power-line conducted emissions shall be measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table and the turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10: 2013

### **3. SYSTEM TEST CONFIGURATION**

#### **3.1 Justification**

The system was configured for testing in a continuous transmit condition.

#### **3.2 EUT Exercise Software**

N/A.

#### **3.3 Special Accessories**

N/A.

#### **3.4 Block Diagram/Schematics**

Please refer to the related document.

#### **3.5 Equipment Modifications**

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### **3.6 Test Setup**

Please refer to the test setup photo.


## 4. SUMMARY OF TEST RESULTS

<b>Applied Standard: FCC Part 15 Subpart C</b>		
<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247(b)(1)	Maximum Conducted Output Power	Compliant
§15.247(a)(1)	Frequency Separation And 20 dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Number Of Hopping Frequency	Compliant
§15.247(a)(1)(iii)	Time Of Occupancy (Dwell Time)	Compliant
§15.209, §15.247(d)	Radiated and Conducted Spurious Emissions	Compliant
§15.205	Emissions at Restricted Band	Compliant
§15.207(a)	Line Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant
<p><i>Note: This is a DSS test report for Laptop, please refer to other document for the DTS test report(LCS1609211574E).</i></p>		

## 5. ANTENNA PORT MEASUREMENT

### 5.1 Conducted Peak Output Power

#### 5.1.1 Block Diagram of Test Setup



#### 5.1.2 Limit

According to § 15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

#### 5.1.3 Test Procedure

The transmitter output is connected to the Power Meter.

#### 5.1.4 Test Results

Mode	Frequency (MHz)	Output Power (dBm, Peak)	Output Power (mW, Peak)	Output Power (dBm, AV)	Limit (mW)	Result
GFSK	2402	6.485	4.45	5.128	1000	Pass
	2441	6.477	4.44	5.119	1000	Pass
	2480	6.495	4.46	5.147	1000	Pass
Pi/4 DQPSK	2402	5.079	3.22	4.058	125	Pass
	2441	5.343	3.42	4.134	125	Pass
	2480	5.410	3.48	4.163	125	Pass
8-DPSK	2402	5.080	3.22	4.066	125	Pass
	2441	5.339	3.42	4.172	125	Pass
	2480	5.407	3.47	4.205	125	Pass


Note: AV power was measured only for RF exposure evaluation.

## 5.2 Frequency Separation And 20 dB Bandwidth

### 5.2.1 Limit

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

### 5.2.2 Block Diagram of Test Setup



### 5.2.3 Test Procedure

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set to the maximum power setting and enable the EUT transmit continuously.
- D. For carrier frequency separation measurement, use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW / VBW=100KHz / 300KHz; Sweep = auto; Detector function = peak;  
Trace = max hold.
- E. For 20dB bandwidth measurement, use the following spectrum analyzer settings:  
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;  
RBW/VBW=30KHz / 100KHz; Sweep = auto; Detector function = peak;  
Trace = max hold.



### 5.2.4 Test Results


The Measurement Result With 1Mbps For GFSK Modulation			
20dB Bandwidth Measurement			
Channel	20dB Bandwidth (MHz)	Limit	
Low	0.740	Non-specified	
Middle	0.743	Non-specified	
High	0.746	Non-specified	
Channel Separation Measurement			
Channel	Channel Separation (MHz)	Limit (MHz)	Result
Low	1.000	$\geq 25$ KHz or 20dB BW	Pass
Middle	1.000	$\geq 25$ KHz or 20dB BW	Pass
High	1.000	$\geq 25$ KHz or 20dB BW	Pass

The Measurement Result With 2Mbps For Pi/4 DQPSK Modulation			
20dB Bandwidth Measurement			
Channel	20dB Bandwidth (MHz)	Limit	
Low	1.112	Non-specified	
Middle	1.113	Non-specified	
High	1.112	Non-specified	
Channel Separation Measurement			
Channel	Channel Separation (MHz)	Limit (MHz)	Result
Low	1.000	$\geq 25$ KHz or 2/3 20dB BW	Pass
Middle	1.000	$\geq 25$ KHz or 2/3 20dB BW	Pass
High	1.000	$\geq 25$ KHz or 2/3 20dB BW	Pass

The Measurement Result With 3Mbps For 8-DPSK Modulation			
20dB Bandwidth Measurement			
Channel	20dB Bandwidth (MHz)	Limit	
Low	1.160	Non-specified	
Middle	1.161	Non-specified	
High	1.158	Non-specified	
Channel Separation Measurement			
Channel	Channel Separation (MHz)	Limit (MHz)	Result
Low	1.000	$\geq 25$ KHz or 2/3 20dB BW	Pass
Middle	1.000	$\geq 25$ KHz or 2/3 20dB BW	Pass
High	1.000	$\geq 25$ KHz or 2/3 20dB BW	Pass

The test data refer to the following page.

For Frequency Separation Measurement, the Low, Mid and High channels were performed and only recorded the worst test plots for Middle channel in this report.




**Test Plot Of Frequency Separation (1Mbps)**

**Test Plot Of Frequency Separation (2Mbps)**



**Test Plot Of Frequency Separation (3Mbps)**

**Measurement of 20dB Bandwidth**



**Test frequency: 2402MHz(1Mbps)**

**Test frequency: 2402MHz(2Mbps)**



**Test frequency: 2441MHz(1Mbps)**



**Test frequency: 2441MHz(2Mbps)**



**Test frequency: 2480MHz(1Mbps)**


**Test frequency: 2480MHz(2Mbps)**

### Measurement of 20dB Bandwidth



#### Test frequency: 2402MHz(3Mbps)

#### Test frequency: 2441MHz(3Mbps)




#### Test frequency: 2480MHz(3Mbps)

## 5.3 Number Of Hopping Frequency

### 5.3.1 Limit

According to §15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

### 5.3.2 Block Diagram of Test Setup



### 5.3.3 Test Procedure


- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set Spectrum Analyzer Start=2400MHz, Stop = 2483.5MHz, Sweep = auto.
- D. Set the Spectrum Analyzer as RBW, VBW=1MHz.
- E. Max hold, view and count how many channel in the band.

### 5.3.4 Test Results

Test Mode	Measurement Result (No. of Ch)	Limit (No. of Ch)	Result
Hopping(GFSK)	79	$\geq 15$	Pass
Hopping(Pi/4-DQPSK)	79	$\geq 15$	Pass
Hopping(8-DPSK)	79	$\geq 15$	Pass

The worst test data refer to the following page.

### Test Plot For Number of Hopping Channel(GFSK)




## 5.4 Time Of Occupancy (Dwell Time)

### 5.4.1 Limit

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4seconds multiplied by the number of hopping channels employed.

### 5.4.2 Block Diagram of Test Setup



### 5.4.3 Test Procedure

- A. Place the EUT on the table and set it in transmitting mode.
- B. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Spectrum Analyzer.
- C. Set center frequency of Spectrum Analyzer = operating frequency.
- D. Set the Spectrum Analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = auto.
- E. Repeat above procedures until all frequency measured were complete.


5.4.4 Test Results

The Measurement Result With The Worst Case of 3Mbps For 8-DPSK Modulation

Channel	Time of Pulse for 3DH5 (ms)	Period Time (s)	Dwell Time (ms)	Limit (ms)
Low	2.880	31.6	307.20	400
Middle	2.870	31.6	306.13	400
High	2.880	31.6	307.20	400

Calculation formula: Dwell Time(3DH5)=Burst Length(ms)\*(1600/6)/79\*31.6

Measurement of Time Of Occupancy (Dwell Time)






## 5.5 Conducted Spurious Emissions and Band Edges Test

### 5.5.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 5.5.2 Block Diagram of Test Setup



### 5.5.3 Test Procedure

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.


The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 300 KHz.

Measurements are made over the 9kHz to 26.5GHz range with the transmitter set to the lowest, middle, and highest channels


### 5.5.4 Test Results of Conducted Spurious Emissions

No non-compliance noted. Only record the worst test result (TX-GFSK) in this report. The test data refer to the following page.

**Test Results of Conducted Spurious Emissions (Worst Case)**




**Test frequency: 2402MHz(1Mbps)**




**Test frequency: 2402MHz(1Mbps)**




**Test frequency: 2441MHz(1Mbps)**



**Test frequency: 2441MHz(1Mbps)**



**Test frequency: 2480MHz(1Mbps)**




**Test frequency: 2480MHz(1Mbps)**


### 5.5.5 Test Results of Band Edges Test

No non-compliance noted. Only record the worst test result in this report. The test data refer to the following page.



#### Test Results of Band Edges Test (Worst Case) Hopping On (1Mbps)





#### Hopping Off (1Mbps)



### Hopping On (3Mbps)




### Hopping Off (3Mbps)




## 6. RADIATED MEASUREMENT


### 6.1 Block Diagram of Test Setup



**Below 30MHz**



**Below 1GHz**



Above 1GHz

### 6.2 Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293.	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510MHz.

\2\ Above 38.6

Part 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in

Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector.

Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

Part 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100**	3
88–216	150**	3
216–960	200**	3
Above 960	500	3

### 6.3 Instruments Setting

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

## 6.4 Test Procedures

### 1) Sequence of testing 9 kHz to 30 MHz

#### **Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### **Premeasurement:**

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

#### **Final measurement:**

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

#### 4) Sequence of testing above 18 GHz

##### Setup:

--- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.

--- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.

--- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.

--- Auxiliary equipment and cables were positioned to simulate normal operation conditions

--- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.

--- The measurement distance is 1 meter.

--- The EUT was set into operation.

##### Premeasurement:

--- The antenna is moved spherical over the EUT in different polarisations of the antenna.

##### Final measurement:

--- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.

--- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## 6.5 Results for Radiated Emissions

### **PASS.**


*Only record the worst test result in this report.*

*The radiated emissions from 9kHz to 30MHz are at least 20dB below the official limit and no need to report.*

*The test data please refer to following page:*

**Below 1GHz**


Horizontal:



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	31.95	14.88	0.37	12.32	27.57	40.00	-12.43	QP
2	38.75	8.26	0.38	13.26	21.90	40.00	-18.10	QP
3	99.88	8.29	0.60	13.15	22.04	43.50	-21.46	QP
4	636.13	8.41	1.71	18.58	28.70	46.00	-17.30	QP
5	729.36	10.04	1.70	19.18	30.92	46.00	-15.08	QP
6	900.15	14.21	1.88	21.09	37.18	46.00	-8.82	QP

- Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that ate 20db blow the official limit are not reported

Vertical:



	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	39.71	9.17	0.38	13.51	23.06	40.00	-16.94	QP
2	49.36	11.49	0.54	13.29	25.32	40.00	-14.68	QP
3	95.09	8.04	0.58	12.85	21.47	43.50	-22.03	QP
4	235.82	8.88	0.87	11.90	21.65	46.00	-24.35	QP
5	677.58	9.91	1.73	18.73	30.37	46.00	-15.63	QP
6	972.34	8.78	2.04	21.56	32.38	54.00	-21.62	QP

- Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that ate 20db blow the official limit are not reported

\*\*\*Note:

Pre-scan all mode and recorded the worst case results in this report (TX-High Channel(1Mbps)).

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

**Above 1GHz**

Note: Only recorded the worst test result.

The worst test result for GFSK, TX-Low Channel:

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4804.0	43.81	33.06	35.04	3.94	45.77	74	-28.23	Peak	Horizontal
4804.0	35.86	33.06	35.04	3.94	37.82	54	-16.18	Average	Horizontal
4804.0	45.57	33.06	35.04	3.94	47.53	74	-26.47	Peak	Vertical
4804.0	36.41	33.06	35.04	3.94	38.37	54	-15.63	Average	Vertical

The worst test result for GFSK, TX-Middle Channel:

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4882.0	44.00	33.16	35.15	3.96	45.97	74	-28.03	Peak	Horizontal
4882.0	34.41	33.16	35.15	3.96	36.38	54	-17.62	Average	Horizontal
4882.0	45.73	33.16	35.15	3.96	47.70	74	-26.30	Peak	Vertical
4882.0	35.57	33.16	35.15	3.96	37.54	54	-16.46	Average	Vertical

The worst test result for GFSK, TX-High Channel:

Freq. MHz	Reading dBuV	Ant. Fac. dB/m	Pre. Fac. dB	Cab. Loss dB	Measured dBuV/m	Limit dBuV/m	Margin dB	Remark	Pol.
4960.0	45.15	33.26	35.14	3.98	47.25	74	-26.75	Peak	Horizontal
4960.0	35.16	33.26	35.14	3.98	37.26	54	-16.74	Average	Horizontal
4960.0	44.16	33.26	35.14	3.98	46.26	74	-27.74	Peak	Vertical
4960.0	37.79	33.26	35.14	3.98	39.89	54	-14.11	Average	Vertical

**Notes:**

1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
3. 18~25GHz at least have 20dB margin. No recording in the test report.

## 6.6 Results for Band edge Testing (Conducted)

According to KDB558074 D01 v03r05 Clause 12.2, Emissions in restricted frequency bands can be tested by Antenna-port conducted measurements. following relationship is used to convert the resultant EIRP level to an equivalent electric field strength:

$$E = \text{EIRP} - 20\log D + 104.8 = \text{EIRP} + 95.2, \text{ where } D=3\text{m}.$$

Then, Radiated Emission limits in restricted bands can be convert to Antenna-port conducted Emission limits by following formula:

$$54 - \text{Gain(dBi)} - 95.2 - 10\log(1\text{MHz}/100\text{kHz}) = 54 - 0 - 95.2 - 10 = -51.2\text{dBm}$$

Results:

Compliance as Conducted Emission(Peak) in restricted frequency bands measured with 100kHz Resolution Bandwidth are below -51.2dBm.

Refer to chapter 5.5.5 for test plots.


## 7. LINE CONDUCTED EMISSIONS

### 7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolt (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency Range(MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

### 7.2 Block Diagram of Test Setup




### 7.3 Test Results

PASS.

*The test data please refer to following page.*

Test Result For Line Power Input AC 120V/60Hz (Worst Case)


Line:



	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.15	17.33	9.58	0.02	36.93	65.78	-28.85	QP
2	0.15	1.43	9.58	0.02	21.03	55.77	-34.74	Average
3	0.18	16.78	9.61	0.02	36.41	64.59	-28.18	QP
4	0.18	1.05	9.61	0.02	20.68	54.59	-33.91	Average
5	0.35	15.09	9.62	0.03	34.74	58.96	-24.22	QP
6	0.35	0.48	9.62	0.03	20.13	48.96	-28.83	Average
7	0.50	14.79	9.62	0.04	34.45	56.05	-21.60	QP
8	0.50	-1.40	9.62	0.04	18.26	46.05	-27.79	Average
9	0.70	14.89	9.64	0.04	34.57	56.00	-21.43	QP
10	0.70	-0.84	9.64	0.04	18.84	46.00	-27.16	Average
11	0.86	10.30	9.63	0.04	29.97	56.00	-26.03	QP
12	0.86	-2.67	9.63	0.04	17.00	46.00	-29.00	Average

Remarks: 1. Measured = Reading +Cable Loss.  
 2. The emission levels that are 20dB below the official limit are not reported.

Neutral:



	Freq	Reading	LISNFac	CabLos	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.20	14.93	9.59	0.02	34.54	63.54	-29.00	QP
2	0.20	0.63	9.59	0.02	20.24	53.53	-33.29	Average
3	0.33	17.56	9.61	0.03	37.20	59.44	-22.24	QP
4	0.33	0.80	9.61	0.03	20.44	49.44	-29.00	Average
5	0.35	17.67	9.61	0.03	37.31	58.87	-21.56	QP
6	0.35	-0.60	9.61	0.03	19.04	48.87	-29.83	Average
7	0.45	15.12	9.62	0.04	34.78	56.80	-22.02	QP
8	0.45	-1.13	9.62	0.04	18.53	46.80	-28.27	Average
9	0.70	15.32	9.63	0.04	34.99	56.00	-21.01	QP
10	0.70	-0.93	9.63	0.04	18.74	46.00	-27.26	Average
11	1.44	7.78	9.63	0.05	27.46	56.00	-28.54	QP
12	1.44	-3.16	9.63	0.05	16.52	46.00	-29.48	Average

Remarks: 1. Measured = Reading +Cable Loss.  
 2. The emission levels that are 20dB below the official limit are not reported.

Note: Pre-scan all modes and recorded the worst case results in this report.



## 8. ANTENNA REQUIREMENT

### 8.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 8.2 Antenna Connected Construction

#### 8.2.1. Antenna Connector Construction

The antenna used for transmitting is permanently attached and no consideration of replacement. Please see EUT photo for details.

The BT and WLAN share same FPC antenna, the maximum gain is 0dBi for BT; more information as follows.

#### 8.2.2. Results: Compliance.

##### **Measurement**

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refer ANSI C63.10:2013 Output power test procedure for frequency-hopping spread-spectrum (FHSS) devices.

Radiated power refers to ANSI C63.10:2013 Radiated emissions tests.

**Measurement parameters**

Measurement parameter	
Detector:	Peak
Sweep Time:	Auto
Resolution bandwidth:	1MHz
Video bandwidth:	3MHz
Trace-Mode:	Max hold

**Limits**

FCC	IC
Antenna Gain	
6 dBi	

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal Bluetooth devices, the GFSK mode is used.

T <sub>nom</sub>	V <sub>nom</sub>	Lowest Channel 2402 MHz	Middle Channel 2441 MHz	Highest Channel 2480 MHz
Conducted power [dBm] Measured with GFSK modulation		6.485	6.477	6.495
Radiated power [dBm] Measured with GFSK modulation		5.743	5.692	5.859
Gain [dBi] Calculated		-0.742	-0.785	-0.636
Measurement uncertainty			± 1.6 dB (cond.) / ± 3.8 dB (rad.)	

**Result: -/-**

-----THE END OF REPORT-----