

TEST REPORT

Reference No..... : WTS16S0961016-2E V1
FCC ID : 2AJVK-SP5034
Applicant..... : Foto Electric Supply Co., INC.
Address..... : 1 Rewe St. Brooklyn, New York, 11211, USA
Manufacturer : Foto Electric Supply Co., INC.
Address..... : 1 Rewe St. Brooklyn, New York, 11211, USA
Product Name..... : Smart Phone
Model No..... : SP5034, CBP4305
Brand..... : SLIDE, COBY
Standards..... : FCC CFR47 Part 15.247:2015
Date of Receipt sample : Sep. 19, 2016
Date of Test : Sep. 20, 2016 –Nov. 10, 2016
Date of Issue..... : Nov. 11, 2016
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033


Fax:+86-755-83552400

Compiled by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

2 Laboratories Introduction

Waltek Services Test Group Ltd is a professional third-party testing and certification organization with multi-year product testing and certification experience, established strictly in accordance with ISO/IEC 17025 requirements, and accredited by CNAS (China National Accreditation Service for Conformity Assessment) AQSIIQ, CMA and IECEE for CBTL. Meanwhile, Waltek has got recognition as registration and accreditation laboratory from EMSD (Electrical and Mechanical Services Department), and American Energy star, FCC(The Federal Communications Commission), CPSC(Consumer Product Safety Commission), CEC(California energy efficiency), IC(Industry Canada) and ELI(Efficient Lighting Initiative). It's the strategic partner and data recognition laboratory of international authoritative organizations, such as UL, Intertek(ETL-SEMKO), CSA, TÜV Rheinland, TÜV SÜD, etc.



Waltek Services Test Group Ltd. is one of the largest and the most comprehensive third party testing organizations in China, our headquarter located in Shenzhen and have branches in Foshan, Dongguan, Zhongshan, Suzhou, Ningbo and Hong Kong, Our test capability covered four large fields: safety test. ElectroMagnetic Compatibility(EMC), reliability and energy performance, Chemical test. As a professional, comprehensive, justice international test organization, we still keep the scientific and rigorous work attitude to help each client satisfy the international standards and assist their product enter into globe market smoothly.

3 Contents

| | Page |
|---|-------------|
| 1 COVER PAGE..... | 1 |
| 2 LABORATORIES INTRODUCTION..... | 2 |
| 3 CONTENTS..... | 3 |
| 4 REVISION HISTORY..... | 5 |
| 5 GENERAL INFORMATION..... | 6 |
| 5.1 GENERAL DESCRIPTION OF E.U.T. | 6 |
| 5.2 DETAILS OF E.U.T. | 6 |
| 5.3 CHANNEL LIST..... | 8 |
| 5.4 TEST MODE..... | 9 |
| 5.5 TEST FACILITY..... | 10 |
| 6 TEST SUMMARY..... | 11 |
| 7 EQUIPMENT USED DURING TEST..... | 12 |
| 7.1 EQUIPMENTS LIST..... | 12 |
| 7.2 DESCRIPTION OF SUPPORT UNITS..... | 13 |
| 7.3 MEASUREMENT UNCERTAINTY..... | 13 |
| 7.4 TEST EQUIPMENT CALIBRATION..... | 13 |
| 8 CONDUCTED EMISSION..... | 14 |
| 8.1 E.U.T. OPERATION..... | 14 |
| 8.2 EUT SETUP..... | 14 |
| 8.3 MEASUREMENT DESCRIPTION..... | 14 |
| 8.4 CONDUCTED EMISSION TEST RESULT..... | 15 |
| 9 RADIATED EMISSIONS..... | 19 |
| 9.1 EUT OPERATION..... | 19 |
| 9.2 TEST SETUP..... | 20 |
| 9.3 SPECTRUM ANALYZER SETUP..... | 21 |
| 9.4 TEST PROCEDURE..... | 22 |
| 9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION..... | 22 |
| 9.6 SUMMARY OF TEST RESULTS..... | 23 |
| 10 CONDUCTED SPURIOUS EMISSIONS..... | 39 |
| 10.1 TEST PROCEDURE..... | 39 |
| 10.2 TEST RESULT..... | 40 |
| 11 BAND EDGE MEASUREMENT..... | 56 |
| 11.1 TEST PROCEDURE..... | 56 |
| 11.2 TEST RESULT..... | 57 |
| 12 6 DB BANDWIDTH MEASUREMENT..... | 62 |
| 12.1 TEST PROCEDURE..... | 62 |
| 12.2 TEST RESULT..... | 62 |
| 13 MAXIMUM PEAK OUTPUT POWER..... | 71 |
| 13.1 TEST PROCEDURE..... | 71 |
| 13.2 TEST RESULT..... | 72 |
| 14 POWER SPECTRAL DENSITY..... | 81 |
| 14.1 TEST PROCEDURE..... | 81 |
| 14.2 TEST RESULT..... | 81 |

| | | |
|-----------|---|-----------|
| 15 | ANTENNA REQUIREMENT | 90 |
| 16 | RF EXPOSURE..... | 91 |
| 17 | PHOTOGRAPHS OF TEST SETUP AND EUT..... | 92 |

4 Revision History

| Test report No. | Date of Receipt sample | Date of Test | Date of Issue | Purpose | Comment | Approved |
|---------------------|------------------------|----------------------------|---------------|-----------|---------|----------|
| WTS16S0961016-2E | Sep. 19, 2016 | Sep. 20 – Nov. 10, 2016 | Nov. 11, 2016 | original | - | Replaced |
| WTS16S0961016-2E V1 | Sep. 19, 2016 | Sep. 20 – Nov. 10, 2016 | Nov. 30, 2016 | Version 1 | | Valid |

5 General Information

5.1 General Description of E.U.T.

| | |
|---------------------------------------|---|
| Product Name: | Smart Phone |
| Model No.: | SP5034, CBP4305 |
| Model Description: | Only the model names and brand names are different. |
| GSM Band(s): | GSM 850/900/1800/1900MHz |
| GPRS/EGPRS Class: | 12 |
| WCDMA Band(s): | FDD Band II/ V |
| LTE Band(s): | FDD Band 2/4/5/7/17 |
| Wi-Fi Specification: | 2.4G-802.11b/g/n HT20/n HT40 |
| Bluetooth Version: | Bluetooth v4.0 with BLE |
| GPS: | Support |
| NFC: | N/A |
| Hardware Version: | HCT-T823MB-A2 |
| Software Version: | R01 |
| Highest frequency (Exclude Radio): | 26MHz |
| Storage Location: | Internal Storage |

5.2 Details of E.U.T.

| | |
|-----------------------|---|
| Operation Frequency: | GSM/GPRS/EDGE 850: 824~849MHz PCS/GPRS/EDGE 1900: 1850~1910MHz WCDMA Band II: 1850~1910MHz WCDMA Band V: 824~849MHz LTE Band 2: 1850~1910MHz LTE Band 4: 1710~1755MHz LTE Band 5: 823~850MHz LTE Band 7: 2500-2570MHz LTE Band 17: 704-716MHz WiFi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz Bluetooth: 2402~2480MHz |
| Max. RF output power: | GSM 850: 33.14dBm PCS1900: 32.28dBm WCDMA Band II: 22.47dBm WCDMA Band V: 22.84dBm LTE Band 2: 22.57dBm LTE Band 4: 22.83dBm |

| | |
|-----------------------|---|
| | LTE Band 5: 23.31dBm LTE Band 7: 23.09dBm LTE Band 17: 23.70dBm WiFi(2.4G): 9.42dBm Bluetooth: 5.59dBm |
| Type of Modulation: | GSM,GPRS: GMSK EDGE: GMSK, 8PSK WCDMA: BPSK LTE: QPSK, 16QAM WiFi: CCK, OFDM Bluetooth: GFSK, Pi/4 DQPSK, 8DPSK |
| Antenna installation: | GSM/WCDMA/LTE: internal permanent antenna WiFi/Bluetooth: internal permanent antenna |
| Antenna Gain: | GSM 850: 0.5dBi PCS1900: 1.0dBi WCDMA Band II: 1.0dBi WCDMA Band V: 0.5dBi LTE Band 2: 1.0dBi LTE Band 4: 0.8dBi LTE Band 5: 0.5dBi LTE Band 7: 1.0dBi LTE Band 17: 0.6dBi WiFi(2.4G): 1.0dBi Bluetooth: 1.0dBi |
| Technical Data: | Battery DC 3.7V, 2400mAh DC 5V, 1.0A, charging from adapter (Adapter Input: 100-240V~50/60Hz 0.2A) |
| Adapter: | Manufacture: XINYU EAGLETRON ELECTRONIC CO.LTD. Model No.: SWN006S050100U1 |

5.3 Channel List

WIFI

| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
|-------------|-----------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| 1 | 2412 | 2 | 2417 | 3 | 2422 | 4 | 2427 |
| 5 | 2432 | 6 | 2437 | 7 | 2442 | 8 | 2447 |
| 9 | 2452 | 10 | 2457 | 11 | 2462 | 12 | - |

BT BLE

| Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) | Channel No. | Frequency (MHz) |
|-------------|-----------------|-------------|-----------------|-------------|-----------------|-------------|-----------------|
| 0 | 2402 | 1 | 2404 | 2 | 2406 | 3 | 2408 |
| 4 | 2410 | 5 | 2412 | 6 | 2414 | 7 | 2416 |
| 8 | 2418 | 9 | 2420 | 10 | 2422 | 11 | 2424 |
| 12 | 2426 | 13 | 2428 | 14 | 2430 | 15 | 2432 |
| 16 | 2434 | 17 | 2436 | 18 | 2438 | 19 | 2440 |
| 20 | 2442 | 21 | 2444 | 22 | 2446 | 23 | 2448 |
| 24 | 2450 | 25 | 2452 | 26 | 2454 | 27 | 2456 |
| 28 | 2458 | 29 | 2460 | 30 | 2462 | 31 | 2464 |
| 32 | 2466 | 33 | 2468 | 34 | 2470 | 35 | 2472 |
| 36 | 2474 | 37 | 2476 | 38 | 2478 | 39 | 2480 |

5.4 Test Mode

Table 1 Tests Carried Out Under FCC part 15.247

| Test Items | Mode | Data Rate | Channel | TX/RX |
|--------------------------------|--------------|-----------|---------|-------|
| Maximum Peak Output Power | 802.11b | 1 Mbps | 1/6/11 | TX |
| | 802.11g | 6 Mbps | 1/6/11 | TX |
| | 802.11n HT20 | MCS0 | 1/6/11 | TX |
| | 802.11n HT40 | MCS0 | 3/6/9 | TX |
| Power Spectral Density | 802.11b | 1 Mbps | 1/6/11 | TX |
| | 802.11g | 6 Mbps | 1/6/11 | TX |
| | 802.11n HT20 | MCS0 | 1/6/11 | TX |
| | 802.11n HT40 | MCS0 | 3/6/9 | TX |
| 6dB Bandwidth | 802.11b | 1 Mbps | 1/6/11 | TX |
| | 802.11g | 6 Mbps | 1/6/11 | TX |
| | 802.11n HT20 | MCS0 | 1/6/11 | TX |
| | 802.11n HT40 | MCS0 | 3/6/9 | TX |
| Band Edge | 802.11b | 1 Mbps | 1/6/11 | TX |
| | 802.11g | 6 Mbps | 1/6/11 | TX |
| | 802.11n HT20 | MCS0 | 1/6/11 | TX |
| | 802.11n HT40 | MCS0 | 3/6/9 | TX |
| Transmitter Spurious Emissions | 802.11b | 1 Mbps | 1/6/11 | TX |
| | 802.11g | 6 Mbps | 1/6/11 | TX |
| | 802.11n HT20 | MCS0 | 1/6/11 | TX |
| | 802.11n HT40 | MCS0 | 3/6/9 | TX |

Table 2 Tests Carried Out Under FCC part 15.247

| Test Items | Mode | Data Rate | Channel | TX/RX |
|--------------------------------|--------|-----------|---------|-------|
| Maximum Peak Output Power | BT BLE | 1 Mbps | 0/19/39 | TX |
| Power Spectral Density | BT BLE | 1 Mbps | 0/19/39 | TX |
| 6dB Bandwidth | BT BLE | 1 Mbps | 0/19/39 | TX |
| Band Edge | BT BLE | 1 Mbps | 0/19/39 | TX |
| Transmitter Spurious Emissions | BT BLE | 1 Mbps | 0/19/39 | TX |

Note :Parameters set by test software during channel & power tests, the software provided by the customer was used to set the operating channels as well as the output power level. The RF output power set is the power expected by the manufacturer and is going to be fixed on the firmware of the final product .

5.5 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A**

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014.

6 Test Summary

| Test Items | Test Requirement | Result |
|---|-------------------------------------|--------|
| Radiated Spurious Emissions | 15.247(d) 15.205(a) 15.209(a) | PASS |
| Conducted Spurious Emissions | 15.247(d) | PASS |
| Conducted Emissions | 15.207(a) | PASS |
| 6dB Bandwidth | 15.247(a)(2) | PASS |
| Maximum Peak Output Power | 15.247(b)(3),(4) | PASS |
| Power Spectral Density | 15.247(e) | PASS |
| Band Edge | 15.247(d) | PASS |
| Antenna Requirement | 15.203 | PASS |
| Maximum Permissible Exposure (Exposure of Humans to RF Fields) | 1.1307(b)(1) | PASS |

7 Equipment Used during Test

7.1 Equipments List

| Conducted Emissions Test Site 1# | | | | | | |
|---|----------------------------|----------------------------------|--------------|-----------------|-----------------------|----------------------|
| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1. | EMI Test Receiver | R&S | ESCI | 100947 | Sep.12,2016 | Sep.11,2017 |
| 2. | LISN | R&S | ENV216 | 101215 | Sep.12,2016 | Sep.11,2017 |
| 3. | Cable | Top | TYPE16(3.5M) | - | Sep.12,2016 | Sep.11,2017 |
| Conducted Emissions Test Site 2# | | | | | | |
| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1. | EMI Test Receiver | R&S | ESCI | 101155 | Sep.12,2016 | Sep.11,2017 |
| 2. | LISN | SCHWARZBECK | NSLK 8128 | 8128-289 | Sep.12,2016 | Sep.11,2017 |
| 3. | Limiter | York | MTS-IMP-136 | 261115-001-0024 | Sep.12,2016 | Sep.11,2017 |
| 4. | Cable | LARGE | RF300 | - | Sep.12,2016 | Sep.11,2017 |
| 3m Semi-anechoic Chamber for Radiation Emissions Test site 1# | | | | | | |
| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1 | Spectrum Analyzer | R&S | FSP | 100091 | Apr.29, 2016 | Apr.28, 2017 |
| 2 | Active Loop Antenna | Beijing Dazhi | ZN30900A | - | Apr.09,2016 | Apr.08,2017 |
| 3 | Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 336 | Apr.09,2016 | Apr.08,2017 |
| 4 | Coaxial Cable (below 1GHz) | Top | TYPE16(13M) | - | Sep.12,2016 | Sep.11,2017 |
| 5 | Broad-band Horn Antenna | SCHWARZBECK | BBHA 9120 D | 667 | Apr.09,2016 | Apr.08,2017 |
| 6 | Broad-band Horn Antenna | SCHWARZBECK | BBHA 9170 | 335 | Apr.09,2016 | Apr.08,2017 |
| 7 | Broadband Preamplifier | COMPLIANCE DIRECTION | PAP-1G18 | 2004 | Apr.13,2016 | Apr.12,2017 |
| 8 | Coaxial Cable (above 1GHz) | Top | 1GHz-25GHz | EW02014-7 | Apr.13,2016 | Apr.12,2017 |
| 3m Semi-anechoic Chamber for Radiation Emissions Test site 2# | | | | | | |
| Item | Equipment | Manufacturer | Model No. | Serial No | Last Calibration Date | Calibration Due Date |
| 1 | Test Receiver | R&S | ESCI | 101296 | Apr.13,2016 | Apr.12,2017 |
| 2 | Trilog Broadband Antenna | SCHWARZBECK | VULB9160 | 9160-3325 | Apr.09,2016 | Apr.08,2017 |
| 3 | Amplifier | Compliance pirection systems inc | PAP-0203 | 22024 | Apr.13,2016 | Apr.12,2017 |
| 4 | Cable | HUBER+SUHNER | CBL2 | 525178 | Apr.13,2016 | Apr.12,2017 |

| RF Conducted Testing | | | | | | |
|----------------------|---------------------------------|--------------|-----------|------------|-----------------------|----------------------|
| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1. | EMC Analyzer (9k~26.5GHz) | Agilent | E7405A | MY45114943 | Sep.12,2016 | Sep.11,2017 |
| 2. | Spectrum Analyzer (9k-6GHz) | R&S | FSL6 | 100959 | Sep.12,2016 | Sep.11,2017 |
| 3. | Signal Analyzer (9k~26.5GHz) | Agilent | N9010A | MY50520207 | Sep.12,2016 | Sep.11,2017 |

7.2 Description of Support Units

| Equipment | Manufacturer | Model No. | Series No. |
|-----------|--------------|-----------|------------|
| / | / | / | / |

7.3 Measurement Uncertainty

| Parameter | Uncertainty |
|--|---|
| Radio Frequency | $\pm 1 \times 10^{-6}$ |
| RF Power | ± 1.0 dB |
| RF Power Density | ± 2.2 dB |
| Radiated Spurious Emissions test | ± 5.03 dB (Bilog antenna 30M~1000MHz) |
| | ± 5.47 dB (Horn antenna 1000M~25000MHz) |
| Conducted Emissions test | ± 3.64 dB (AC mains 150KHz~30MHz) |
| Confidence interval : 95%. Confidence factor:k=2 | |

7.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

8 Conducted Emission

Test Requirement: FCC CFR 47 Part 15 Section 15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Class/Severity: Class B

Limit:

| Frequency (MHz) | Limit (dB μ V) | |
|-----------------|--------------------|-----------|
| | Quasi-peak | Average |
| 0.15 to 0.5 | 66 to 56* | 56 to 46* |
| 0.5 to 5 | 56 | 60 |
| 5 to 30 | 60 | 50 |

8.1 E.U.T. Operation

Operating Environment :

Temperature: 21.5 °C

Humidity: 51.9 % RH


Atmospheric Pressure: 101.2kPa

EUT Operation :

The test was performed in TX transmitting mode, the worst data(b mode low channel and BLE low channel) were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10.



8.3 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

8.4 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.


Worst Mode: WIFI mode

Live line:



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit dBuV | Margin (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|------------|-------------|----------|--------|
| 1 | 0.4140 | 32.32 | 10.27 | 42.59 | 57.57 | -14.98 | QP | |
| 2 | 0.4140 | 25.51 | 10.27 | 35.78 | 47.57 | -11.79 | AVG | |
| 3 | 0.4740 | 31.21 | 10.26 | 41.47 | 56.44 | -14.97 | QP | |
| 4 | 0.4740 | 23.70 | 10.26 | 33.96 | 46.44 | -12.48 | AVG | |
| 5 | 0.5340 | 31.53 | 10.27 | 41.80 | 56.00 | -14.20 | QP | |
| 6 | 0.5340 | 24.52 | 10.27 | 34.79 | 46.00 | -11.21 | AVG | |
| 7 | 0.5940 | 31.97 | 10.30 | 42.27 | 56.00 | -13.73 | QP | |
| 8 | 0.5940 | 23.04 | 10.30 | 33.34 | 46.00 | -12.66 | AVG | |
| 9 | 0.7780 | 26.45 | 10.36 | 36.81 | 56.00 | -19.19 | QP | |
| 10 | 0.7780 | 17.50 | 10.36 | 27.86 | 46.00 | -18.14 | AVG | |
| 11 | 0.8340 | 33.40 | 10.37 | 43.77 | 56.00 | -12.23 | QP | |
| 12 | 0.8340 | 23.81 | 10.37 | 34.18 | 46.00 | -11.82 | AVG | |


Neutral line:



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit dBuV | Margin (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|------------|-------------|----------|--------|
| 1 | 0.4180 | 36.42 | 10.27 | 46.69 | 57.49 | -10.80 | QP | |
| 2 | 0.4180 | 32.64 | 10.27 | 42.91 | 47.49 | -4.58 | AVG | |
| 3 | 0.4780 | 34.58 | 10.25 | 44.83 | 56.37 | -11.54 | QP | |
| 4 | 0.4780 | 29.58 | 10.25 | 39.83 | 46.37 | -6.54 | AVG | |
| 5 | 0.5340 | 33.86 | 10.27 | 44.13 | 56.00 | -11.87 | QP | |
| 6 | 0.5340 | 29.89 | 10.27 | 40.16 | 46.00 | -5.84 | AVG | |
| 7 | 0.5940 | 36.19 | 10.30 | 46.49 | 56.00 | -9.51 | QP | |
| 8 | 0.5940 | 31.25 | 10.30 | 41.55 | 46.00 | -4.45 | AVG | |
| 9 | 0.8340 | 37.37 | 10.37 | 47.74 | 56.00 | -8.26 | QP | |
| 10 | 0.8340 | 30.95 | 10.37 | 41.32 | 46.00 | -4.68 | AVG | |
| 11 | 1.0140 | 33.86 | 10.39 | 44.25 | 56.00 | -11.75 | QP | |
| 12 | 1.0140 | 27.10 | 10.39 | 37.49 | 46.00 | -8.51 | AVG | |


Worst Mode: BLE mode

Live line:



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit dBuV | Margin (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|------------|-------------|----------|--------|
| 1 | 0.4180 | 32.89 | 10.27 | 43.16 | 57.49 | -14.33 | QP | |
| 2 | 0.4180 | 25.70 | 10.27 | 35.97 | 47.49 | -11.52 | AVG | |
| 3 | 0.5380 | 30.02 | 10.27 | 40.29 | 56.00 | -15.71 | QP | |
| 4 | 0.5380 | 22.55 | 10.27 | 32.82 | 46.00 | -13.18 | AVG | |
| 5 | 0.5980 | 30.25 | 10.30 | 40.55 | 56.00 | -15.45 | QP | |
| 6 | 0.5980 | 21.07 | 10.30 | 31.37 | 46.00 | -14.63 | AVG | |
| 7 | 0.6540 | 29.13 | 10.33 | 39.46 | 56.00 | -16.54 | QP | |
| 8 | 0.6540 | 18.85 | 10.33 | 29.18 | 46.00 | -16.82 | AVG | |
| 9 | 0.8260 | 30.39 | 10.36 | 40.75 | 56.00 | -15.25 | QP | |
| 10 | 0.8260 | 20.01 | 10.36 | 30.37 | 46.00 | -15.63 | AVG | |
| 11 | 1.0700 | 30.03 | 10.40 | 40.43 | 56.00 | -15.57 | QP | |
| 12 | 1.0700 | 20.10 | 10.40 | 30.50 | 46.00 | -15.50 | AVG | |

Neutral line:



| No. | Freq. (MHz) | Reading (dBuV) | Factor (dB) | Result (dBuV) | Limit dBuV | Margin (dB) | Detector | Remark |
|-----|-------------|----------------|-------------|---------------|------------|-------------|----------|--------|
| 1 | 0.4180 | 36.29 | 10.27 | 46.56 | 57.49 | -10.93 | QP | |
| 2 | 0.4180 | 32.25 | 10.27 | 42.52 | 47.49 | -4.97 | AVG | |
| 3 | 0.4740 | 34.15 | 10.26 | 44.41 | 56.44 | -12.03 | QP | |
| 4 | 0.4740 | 29.27 | 10.26 | 39.53 | 46.44 | -6.91 | AVG | |
| 5 | 0.5980 | 34.71 | 10.30 | 45.01 | 56.00 | -10.99 | QP | |
| 6 | 0.5980 | 29.16 | 10.30 | 39.46 | 46.00 | -6.54 | AVG | |
| 7 | 0.7140 | 32.29 | 10.36 | 42.65 | 56.00 | -13.35 | QP | |
| 8 | 0.7140 | 26.07 | 10.36 | 36.43 | 46.00 | -9.57 | AVG | |
| 9 | 0.8300 | 36.79 | 10.37 | 47.16 | 56.00 | -8.84 | QP | |
| 10 | 0.8300 | 29.52 | 10.37 | 39.89 | 46.00 | -6.11 | AVG | |
| 11 | 1.0100 | 33.93 | 10.39 | 44.32 | 56.00 | -11.68 | QP | |
| 12 | 1.0100 | 26.93 | 10.39 | 37.32 | 46.00 | -8.68 | AVG | |

9 Radiated Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

| Frequency (MHz) | Field Strength | | Field Strength Limit at 3m Measurement Dist | |
|--------------------|-----------------------|-----------------|---|---------------------------------------|
| | uV/m | Distance (m) | uV/m | dBuV/m |
| 0.009 ~ 0.490 | $2400/F(\text{kHz})$ | 300 | $10000 * 2400/F(\text{kHz})$ | $20\log^{(2400/F(\text{kHz}))} + 80$ |
| 0.490 ~ 1.705 | $24000/F(\text{kHz})$ | 30 | $100 * 24000/F(\text{kHz})$ | $20\log^{(24000/F(\text{kHz}))} + 40$ |
| 1.705 ~ 30 | 30 | 30 | $100 * 30$ | $20\log^{(30)} + 40$ |
| 30 ~ 88 | 100 | 3 | 100 | $20\log^{(100)}$ |
| 88 ~ 216 | 150 | 3 | 150 | $20\log^{(150)}$ |
| 216 ~ 960 | 200 | 3 | 200 | $20\log^{(200)}$ |
| Above 960 | 500 | 3 | 500 | $20\log^{(500)}$ |

9.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 52.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in WIFI link mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed Auto
 Detector PK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 Detector Ave.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used druing radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Wifi:

Test Frequency: 9KHz~30MHz

| Frequency | Measurement results dB μ V @3m | Detector PK/QP | Correct factor dB/m | Extrapolation factor dB | Measurement results (calculated) dB μ V/m @30m | Limits dB μ V/m @30m | Margin dB |
|---------------|------------------------------------|----------------|---------------------|-------------------------|--|--------------------------|-----------|
| (MHz) | Measurement results | Detector | Correct factor | Extrapolation factor | Measurement results (calculated) | Limits | Margin |
| 802.11b | | | | | | | |
| 6.021 | 25.34 | QP | 21.84 | 40.00 | 7.18 | 29.54 | -22.36 |
| 8.304 | 26.13 | QP | 21.02 | 40.00 | 7.15 | 29.54 | -22.39 |
| 26.127 | 24.02 | QP | 20.55 | 40.00 | 4.57 | 29.54 | -24.97 |
| 802.11g | | | | | | | |
| 6.032 | 24.53 | QP | 21.84 | 40.00 | 6.37 | 29.54 | -23.17 |
| 8.051 | 24.71 | QP | 21.02 | 40.00 | 5.73 | 29.54 | -23.81 |
| 26.215 | 25.06 | QP | 20.55 | 40.00 | 5.61 | 29.54 | -23.93 |
| 802.11n(HT20) | | | | | | | |
| 6.325 | 25.63 | QP | 21.84 | 40.00 | 7.47 | 29.54 | -22.07 |
| 8.654 | 24.60 | QP | 21.02 | 40.00 | 5.62 | 29.54 | -23.92 |
| 25.690 | 25.61 | QP | 20.55 | 40.00 | 6.16 | 29.54 | -23.38 |
| 802.11n(HT40) | | | | | | | |
| 6.032 | 25.11 | QP | 21.84 | 40.00 | 6.95 | 29.54 | -22.59 |
| 8.051 | 25.23 | QP | 21.02 | 40.00 | 6.25 | 29.54 | -23.29 |
| 26.215 | 24.57 | QP | 20.55 | 40.00 | 5.12 | 29.54 | -24.42 |

Test Frequency : 30MHz ~ 18GHz

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|--------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11b: Low Channel 2412MHz | | | | | | | | | |
| 223.45 | 40.36 | QP | 275.93 | 1.62 | H | 11.62 | 28.74 | 46.00 | -17.26 |
| 223.45 | 35.55 | QP | 340.17 | 1.31 | V | 11.62 | 23.93 | 46.00 | -22.07 |
| 4824.00 | 51.12 | PK | 164.45 | 1.00 | V | 1.06 | 50.06 | 74.00 | -23.94 |
| 4824.00 | 44.52 | Ave | 164.45 | 1.00 | V | 1.06 | 43.46 | 54.00 | -10.54 |
| 7236.00 | 39.87 | PK | 244.93 | 1.85 | H | 1.33 | 41.20 | 74.00 | -32.80 |
| 7236.00 | 43.90 | Ave | 244.93 | 1.85 | H | 1.33 | 45.23 | 54.00 | -8.77 |
| 2337.93 | 46.45 | PK | 330.86 | 1.44 | V | 13.19 | 33.26 | 74.00 | -40.74 |
| 2337.93 | 39.31 | Ave | 330.86 | 1.44 | V | 13.19 | 26.12 | 54.00 | -27.88 |
| 2379.72 | 44.56 | PK | 319.94 | 1.02 | H | 13.14 | 31.42 | 74.00 | -42.58 |
| 2379.72 | 36.41 | Ave | 319.94 | 1.02 | H | 13.14 | 23.27 | 54.00 | -30.73 |
| 2493.44 | 42.77 | PK | 309.97 | 1.48 | V | 13.08 | 29.69 | 74.00 | -44.31 |
| 2493.44 | 36.36 | Ave | 309.97 | 1.48 | V | 13.08 | 23.28 | 54.00 | -30.72 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11b: Middle Channel 2437MHz | | | | | | | | | |
| 223.45 | 40.89 | QP | 107.50 | 1.63 | H | 11.62 | 29.27 | 46.00 | -16.73 |
| 223.45 | 34.66 | QP | 153.90 | 1.51 | V | 11.62 | 23.04 | 46.00 | -22.96 |
| 4874.00 | 51.90 | PK | 73.75 | 1.80 | V | 0.62 | 51.28 | 74.00 | -22.72 |
| 4874.00 | 44.89 | Ave | 73.75 | 1.80 | V | 0.62 | 44.27 | 54.00 | -9.73 |
| 7311.00 | 40.10 | PK | 50.43 | 1.63 | H | 2.21 | 42.31 | 74.00 | -31.69 |
| 7311.00 | 44.20 | Ave | 50.43 | 1.63 | H | 2.21 | 46.41 | 54.00 | -7.59 |
| 2337.21 | 46.12 | PK | 255.02 | 1.77 | V | 13.19 | 32.93 | 74.00 | -41.07 |
| 2337.21 | 38.85 | Ave | 255.02 | 1.77 | V | 13.19 | 25.66 | 54.00 | -28.34 |
| 2351.40 | 42.76 | PK | 257.28 | 1.40 | H | 13.14 | 29.62 | 74.00 | -44.38 |
| 2351.40 | 37.10 | Ave | 257.28 | 1.40 | H | 13.14 | 23.96 | 54.00 | -30.04 |
| 2484.14 | 42.45 | PK | 154.51 | 1.75 | V | 13.08 | 29.37 | 74.00 | -44.63 |
| 2484.14 | 36.72 | Ave | 154.51 | 1.75 | V | 13.08 | 23.64 | 54.00 | -30.36 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|---------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11b: High Channel 2462MHz | | | | | | | | | |
| 223.45 | 41.04 | QP | 340.15 | 1.98 | H | 11.62 | 29.42 | 46.00 | -16.58 |
| 223.45 | 33.30 | QP | 320.32 | 1.66 | V | 11.62 | 21.68 | 46.00 | -24.32 |
| 4924.00 | 52.75 | PK | 287.49 | 1.05 | V | 0.24 | 52.51 | 74.00 | -21.49 |
| 4924.00 | 45.28 | Ave | 287.49 | 1.05 | V | 0.24 | 45.04 | 54.00 | -8.96 |
| 7386.00 | 39.05 | PK | 210.73 | 1.13 | H | 2.84 | 41.89 | 74.00 | -32.11 |
| 7386.00 | 43.65 | Ave | 210.73 | 1.13 | H | 2.84 | 46.49 | 54.00 | -7.51 |
| 2316.95 | 46.90 | PK | 248.66 | 1.56 | V | 13.19 | 33.71 | 74.00 | -40.29 |
| 2316.95 | 37.03 | Ave | 248.66 | 1.56 | V | 13.19 | 23.84 | 54.00 | -30.16 |
| 2350.23 | 44.99 | PK | 59.01 | 1.83 | H | 13.14 | 31.85 | 74.00 | -42.15 |
| 2350.23 | 38.49 | Ave | 59.01 | 1.83 | H | 13.14 | 25.35 | 54.00 | -28.65 |
| 2496.99 | 43.55 | PK | 238.15 | 1.08 | V | 13.08 | 30.47 | 74.00 | -43.53 |
| 2496.99 | 37.43 | Ave | 238.15 | 1.08 | V | 13.08 | 24.35 | 54.00 | -29.65 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|--------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11g: Low Channel 2412MHz | | | | | | | | | |
| 223.45 | 41.51 | QP | 8.15 | 1.89 | H | 11.62 | 29.89 | 46.00 | -16.11 |
| 223.45 | 34.31 | QP | 97.12 | 1.05 | V | 11.62 | 22.69 | 46.00 | -23.31 |
| 4824.00 | 51.66 | PK | 285.14 | 1.55 | V | 1.06 | 50.60 | 74.00 | -23.40 |
| 4824.00 | 45.16 | Ave | 285.14 | 1.55 | V | 1.06 | 44.10 | 54.00 | -9.90 |
| 7236.00 | 38.17 | PK | 190.28 | 1.51 | H | 1.33 | 39.50 | 74.00 | -34.50 |
| 7236.00 | 42.24 | Ave | 190.28 | 1.51 | H | 1.33 | 43.57 | 54.00 | -10.43 |
| 2326.47 | 45.15 | PK | 106.17 | 1.17 | V | 13.19 | 31.96 | 74.00 | -42.04 |
| 2326.47 | 37.63 | Ave | 106.17 | 1.17 | V | 13.19 | 24.44 | 54.00 | -29.56 |
| 2371.44 | 42.98 | PK | 21.53 | 1.84 | H | 13.14 | 29.84 | 74.00 | -44.16 |
| 2371.44 | 36.30 | Ave | 21.53 | 1.84 | H | 13.14 | 23.16 | 54.00 | -30.84 |
| 2499.69 | 43.81 | PK | 181.71 | 1.24 | V | 13.08 | 30.73 | 74.00 | -43.27 |
| 2499.69 | 38.28 | Ave | 181.71 | 1.24 | V | 13.08 | 25.20 | 54.00 | -28.80 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11g: Middle Channel 2437MHz | | | | | | | | | |
| 223.45 | 40.31 | QP | 150.90 | 1.45 | H | 11.62 | 28.69 | 46.00 | -17.31 |
| 223.45 | 35.04 | QP | 51.09 | 1.26 | V | 11.62 | 23.42 | 46.00 | -22.58 |
| 4874.00 | 52.71 | PK | 340.45 | 1.73 | V | 0.62 | 52.09 | 74.00 | -21.91 |
| 4874.00 | 45.39 | Ave | 340.45 | 1.73 | V | 0.62 | 44.77 | 54.00 | -9.23 |
| 7311.00 | 39.35 | PK | 178.89 | 1.44 | H | 2.21 | 41.56 | 74.00 | -32.44 |
| 7311.00 | 42.19 | Ave | 178.89 | 1.44 | H | 2.21 | 44.40 | 54.00 | -9.60 |
| 2333.15 | 45.37 | PK | 165.32 | 1.38 | V | 13.19 | 32.18 | 74.00 | -41.82 |
| 2333.15 | 39.46 | Ave | 165.32 | 1.38 | V | 13.19 | 26.27 | 54.00 | -27.73 |
| 2370.50 | 43.63 | PK | 24.05 | 1.07 | H | 13.14 | 30.49 | 74.00 | -43.51 |
| 2370.50 | 38.51 | Ave | 24.05 | 1.07 | H | 13.14 | 25.37 | 54.00 | -28.63 |
| 2488.67 | 44.19 | PK | 186.26 | 1.65 | V | 13.08 | 31.11 | 74.00 | -42.89 |
| 2488.67 | 37.93 | Ave | 186.26 | 1.65 | V | 13.08 | 24.85 | 54.00 | -29.15 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|---------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11g: High Channel 2462MHz | | | | | | | | | |
| 223.45 | 41.66 | QP | 298.98 | 1.31 | H | 11.62 | 30.04 | 46.00 | -15.96 |
| 223.45 | 34.06 | QP | 249.26 | 1.35 | V | 11.62 | 22.44 | 46.00 | -23.56 |
| 4924.00 | 51.98 | PK | 294.61 | 1.07 | V | 0.24 | 51.74 | 74.00 | -22.26 |
| 4924.00 | 45.36 | Ave | 294.61 | 1.07 | V | 0.24 | 45.12 | 54.00 | -8.88 |
| 7386.00 | 39.22 | PK | 282.91 | 1.39 | H | 2.84 | 42.06 | 74.00 | -31.94 |
| 7386.00 | 40.94 | Ave | 282.91 | 1.39 | H | 2.84 | 43.78 | 54.00 | -10.22 |
| 2321.46 | 45.85 | PK | 179.67 | 1.22 | V | 13.19 | 32.66 | 74.00 | -41.34 |
| 2321.46 | 39.78 | Ave | 179.67 | 1.22 | V | 13.19 | 26.59 | 54.00 | -27.41 |
| 2351.07 | 44.02 | PK | 31.22 | 1.70 | H | 13.14 | 30.88 | 74.00 | -43.12 |
| 2351.07 | 38.36 | Ave | 31.22 | 1.70 | H | 13.14 | 25.22 | 54.00 | -28.78 |
| 2488.62 | 42.81 | PK | 248.56 | 1.76 | V | 13.08 | 29.73 | 74.00 | -44.27 |
| 2488.62 | 38.93 | Ave | 248.56 | 1.76 | V | 13.08 | 25.85 | 54.00 | -28.15 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11n20: Low Channel 2412MHz | | | | | | | | | |
| 223.45 | 42.21 | QP | 335.39 | 1.78 | H | 11.62 | 30.59 | 46.00 | -15.41 |
| 223.45 | 34.44 | QP | 40.15 | 1.81 | V | 11.62 | 22.82 | 46.00 | -23.18 |
| 4824.00 | 50.48 | PK | 199.36 | 1.33 | V | 1.06 | 49.42 | 74.00 | -24.58 |
| 4824.00 | 45.28 | Ave | 199.36 | 1.33 | V | 1.06 | 44.22 | 54.00 | -9.78 |
| 7236.00 | 40.09 | PK | 182.24 | 1.23 | H | 1.33 | 41.42 | 74.00 | -32.58 |
| 7236.00 | 41.67 | Ave | 182.24 | 1.23 | H | 1.33 | 43.00 | 54.00 | -11.00 |
| 2321.90 | 45.29 | PK | 141.79 | 1.54 | V | 13.19 | 32.10 | 74.00 | -41.90 |
| 2321.90 | 39.06 | Ave | 141.79 | 1.54 | V | 13.19 | 25.87 | 54.00 | -28.13 |
| 2358.23 | 44.28 | PK | 46.81 | 1.31 | H | 13.14 | 31.14 | 74.00 | -42.86 |
| 2358.23 | 36.48 | Ave | 46.81 | 1.31 | H | 13.14 | 23.34 | 54.00 | -30.66 |
| 2492.93 | 43.63 | PK | 73.18 | 1.81 | V | 13.08 | 30.55 | 74.00 | -43.45 |
| 2492.93 | 37.09 | Ave | 73.18 | 1.81 | V | 13.08 | 24.01 | 54.00 | -29.99 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|-------------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11n20: Middle Channel 2437MHz | | | | | | | | | |
| 223.45 | 43.67 | QP | 88.80 | 1.42 | H | 11.62 | 32.05 | 46.00 | -13.95 |
| 223.45 | 33.91 | QP | 118.89 | 1.93 | V | 11.62 | 22.29 | 46.00 | -23.71 |
| 4874.00 | 50.36 | PK | 159.12 | 1.56 | V | 0.62 | 49.74 | 74.00 | -24.26 |
| 4874.00 | 45.59 | Ave | 159.12 | 1.56 | V | 0.62 | 44.97 | 54.00 | -9.03 |
| 7311.00 | 38.94 | PK | 70.79 | 1.13 | H | 2.21 | 41.15 | 74.00 | -32.85 |
| 7311.00 | 42.05 | Ave | 70.79 | 1.13 | H | 2.21 | 44.26 | 54.00 | -9.74 |
| 2346.19 | 45.85 | PK | 67.22 | 1.98 | V | 13.19 | 32.66 | 74.00 | -41.34 |
| 2346.19 | 38.90 | Ave | 67.22 | 1.98 | V | 13.19 | 25.71 | 54.00 | -28.29 |
| 2358.30 | 43.64 | PK | 273.47 | 1.40 | H | 13.14 | 30.50 | 74.00 | -43.50 |
| 2358.30 | 38.52 | Ave | 273.47 | 1.40 | H | 13.14 | 25.38 | 54.00 | -28.62 |
| 2484.14 | 44.75 | PK | 315.79 | 1.14 | V | 13.08 | 31.67 | 74.00 | -42.33 |
| 2484.14 | 37.85 | Ave | 315.79 | 1.14 | V | 13.08 | 24.77 | 54.00 | -29.23 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11n20: High Channel 2462MHz | | | | | | | | | |
| 223.45 | 42.24 | QP | 304.58 | 1.33 | H | 11.62 | 30.62 | 46.00 | -15.38 |
| 223.45 | 32.55 | QP | 327.29 | 1.16 | V | 11.62 | 20.93 | 46.00 | -25.07 |
| 4924.00 | 49.42 | PK | 58.12 | 1.06 | V | 0.24 | 49.18 | 74.00 | -24.82 |
| 4924.00 | 46.13 | Ave | 58.12 | 1.06 | V | 0.24 | 45.89 | 54.00 | -8.11 |
| 7386.00 | 39.09 | PK | 85.06 | 1.60 | H | 2.84 | 41.93 | 74.00 | -32.07 |
| 7386.00 | 43.53 | Ave | 85.06 | 1.60 | H | 2.84 | 46.37 | 54.00 | -7.63 |
| 2315.95 | 46.08 | PK | 312.21 | 1.26 | V | 13.19 | 32.89 | 74.00 | -41.11 |
| 2315.95 | 37.03 | Ave | 312.21 | 1.26 | V | 13.19 | 23.84 | 54.00 | -30.16 |
| 2376.04 | 43.30 | PK | 3.79 | 1.65 | H | 13.14 | 30.16 | 74.00 | -43.84 |
| 2376.04 | 36.19 | Ave | 3.79 | 1.65 | H | 13.14 | 23.05 | 54.00 | -30.95 |
| 2483.54 | 43.39 | PK | 163.92 | 1.44 | V | 13.08 | 30.31 | 74.00 | -43.69 |
| 2483.54 | 36.81 | Ave | 163.92 | 1.44 | V | 13.08 | 23.73 | 54.00 | -30.27 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11n40: Low Channel 2422MHz | | | | | | | | | |
| 223.45 | 42.47 | QP | 225.77 | 1.77 | H | 11.62 | 30.85 | 46.00 | -15.15 |
| 223.45 | 32.24 | QP | 17.49 | 1.22 | V | 11.62 | 20.62 | 46.00 | -25.38 |
| 4844.00 | 46.95 | PK | 11.37 | 1.84 | V | 1.06 | 45.89 | 74.00 | -28.11 |
| 4844.00 | 43.99 | Ave | 11.37 | 1.84 | V | 1.06 | 42.93 | 54.00 | -11.07 |
| 7266.00 | 36.72 | PK | 191.65 | 1.63 | H | 1.33 | 38.05 | 74.00 | -35.95 |
| 7266.00 | 42.50 | Ave | 191.65 | 1.63 | H | 1.33 | 43.83 | 54.00 | -10.17 |
| 2321.34 | 45.63 | PK | 166.39 | 1.39 | V | 13.19 | 32.44 | 74.00 | -41.56 |
| 2321.34 | 38.61 | Ave | 166.39 | 1.39 | V | 13.19 | 25.42 | 54.00 | -28.58 |
| 2373.84 | 44.63 | PK | 38.31 | 1.35 | H | 13.14 | 31.49 | 74.00 | -42.51 |
| 2373.84 | 38.10 | Ave | 38.31 | 1.35 | H | 13.14 | 24.96 | 54.00 | -29.04 |
| 2492.64 | 44.19 | PK | 315.44 | 1.83 | V | 13.08 | 31.11 | 74.00 | -42.89 |
| 2492.64 | 38.80 | Ave | 315.44 | 1.83 | V | 13.08 | 25.72 | 54.00 | -28.28 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|-------------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11n40: Middle Channel 2437MHz | | | | | | | | | |
| 223.45 | 41.90 | QP | 170.21 | 1.61 | H | 11.62 | 30.28 | 46.00 | -15.72 |
| 223.45 | 31.92 | QP | 321.36 | 1.21 | V | 11.62 | 20.30 | 46.00 | -25.70 |
| 4874.00 | 46.54 | PK | 306.53 | 1.71 | V | 0.62 | 45.92 | 74.00 | -28.08 |
| 4874.00 | 43.76 | Ave | 306.53 | 1.71 | V | 0.62 | 43.14 | 54.00 | -10.86 |
| 7311.00 | 37.48 | PK | 280.48 | 1.64 | H | 2.21 | 39.69 | 74.00 | -34.31 |
| 7311.00 | 42.39 | Ave | 280.48 | 1.64 | H | 2.21 | 44.60 | 54.00 | -9.40 |
| 2345.34 | 46.41 | PK | 105.33 | 1.43 | V | 13.19 | 33.22 | 74.00 | -40.78 |
| 2345.34 | 38.21 | Ave | 105.33 | 1.43 | V | 13.19 | 25.02 | 54.00 | -28.98 |
| 2364.15 | 43.70 | PK | 71.84 | 1.81 | H | 13.14 | 30.56 | 74.00 | -43.44 |
| 2364.15 | 37.13 | Ave | 71.84 | 1.81 | H | 13.14 | 23.99 | 54.00 | -30.01 |
| 2484.22 | 43.86 | PK | 270.90 | 1.80 | V | 13.08 | 30.78 | 74.00 | -43.22 |
| 2484.22 | 37.13 | Ave | 270.90 | 1.80 | V | 13.08 | 24.05 | 54.00 | -29.95 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.247/209/205 | |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|-------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| 11n40: High Channel 2452MHz | | | | | | | | | |
| 223.45 | 41.37 | QP | 299.63 | 1.33 | H | 11.62 | 29.75 | 46.00 | -16.25 |
| 223.45 | 32.44 | QP | 141.51 | 1.59 | V | 11.62 | 20.82 | 46.00 | -25.18 |
| 4904.00 | 46.18 | PK | 119.27 | 1.80 | V | 0.24 | 45.94 | 74.00 | -28.06 |
| 4904.00 | 43.21 | Ave | 119.27 | 1.80 | V | 0.24 | 42.97 | 54.00 | -11.03 |
| 7356.00 | 36.67 | PK | 291.84 | 1.84 | H | 2.84 | 39.51 | 74.00 | -34.49 |
| 7356.00 | 43.11 | Ave | 291.84 | 1.84 | H | 2.84 | 45.95 | 54.00 | -8.05 |
| 2344.40 | 46.15 | PK | 261.66 | 1.29 | V | 13.19 | 32.96 | 74.00 | -41.04 |
| 2344.40 | 38.49 | Ave | 261.66 | 1.29 | V | 13.19 | 25.30 | 54.00 | -28.70 |
| 2371.68 | 44.35 | PK | 165.73 | 1.66 | H | 13.14 | 31.21 | 74.00 | -42.79 |
| 2371.68 | 36.43 | Ave | 165.73 | 1.66 | H | 13.14 | 23.29 | 54.00 | -30.71 |
| 2498.10 | 43.01 | PK | 17.30 | 1.46 | V | 13.08 | 29.93 | 74.00 | -44.07 |
| 2498.10 | 37.22 | Ave | 17.30 | 1.46 | V | 13.08 | 24.14 | 54.00 | -29.86 |

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

BT BLE:**Test Frequency: 9KHz~26MHz**

| Frequency | Measurement results dB μ V @3m | Detector PK/QP | Correct factor dB/m | Extrapolation factor dB | Measurement results (calculated) dB μ V/m @30m | Limits dB μ V/m @30m | Margin dB |
|-----------|------------------------------------|----------------|---------------------|-------------------------|--|--------------------------|-----------|
| (MHz) | Measurement results | Detector | Correct factor | Extrapolation factor | Measurement results (calculated) | Limits | Margin |
| 6.026 | 25.64 | QP | 21.84 | 40.00 | 7.48 | 29.54 | -22.06 |
| 8.352 | 26.32 | QP | 21.02 | 40.00 | 7.34 | 29.54 | -22.20 |
| 24.965 | 25.61 | QP | 20.55 | 40.00 | 6.16 | 29.54 | -23.38 |

Test Frequency : 26MHz ~ 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | Limit | Margin |
|--------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|----------------|--------|
| | | | | Height | Polar | | | | |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| GFSK Low Channel 2402MHz | | | | | | | | | |
| 268.32 | 36.94 | QP | 168 | 1.6 | H | -13.35 | 23.59 | 46.00 | -22.41 |
| 268.32 | 41.43 | QP | 1 | 1.4 | V | -13.35 | 28.08 | 46.00 | -17.92 |
| 4804.00 | 46.47 | PK | 133 | 1.5 | V | -1.06 | 45.41 | 74.00 | -28.59 |
| 4804.00 | 42.85 | Ave | 133 | 1.5 | V | -1.06 | 41.79 | 54.00 | -12.21 |
| 7206.00 | 41.23 | PK | 176 | 1.0 | H | 1.33 | 42.56 | 74.00 | -31.44 |
| 7206.00 | 35.63 | Ave | 176 | 1.0 | H | 1.33 | 36.96 | 54.00 | -17.04 |
| 2346.36 | 45.32 | PK | 117 | 1.4 | V | -13.19 | 32.13 | 74.00 | -41.87 |
| 2346.36 | 37.19 | Ave | 117 | 1.4 | V | -13.19 | 24.00 | 54.00 | -30.00 |
| 2373.60 | 42.18 | PK | 266 | 1.4 | H | -13.14 | 29.04 | 74.00 | -44.96 |
| 2373.60 | 38.97 | Ave | 266 | 1.4 | H | -13.14 | 25.83 | 54.00 | -28.17 |
| 2487.31 | 44.08 | PK | 211 | 1.0 | V | -13.08 | 31.00 | 74.00 | -43.00 |
| 2487.31 | 38.25 | Ave | 211 | 1.0 | V | -13.08 | 25.17 | 54.00 | -28.83 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | Limit | Margin |
|-----------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|----------------|--------|
| | | | | Height | Polar | | | | |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| GFSK Middle Channel 2440MHz | | | | | | | | | |
| 268.32 | 36.09 | QP | 150 | 1.1 | H | -13.35 | 22.74 | 46.00 | -23.26 |
| 268.32 | 41.14 | QP | 239 | 1.3 | V | -13.35 | 27.79 | 46.00 | -18.21 |
| 4880.00 | 47.79 | PK | 284 | 1.6 | V | -0.62 | 47.17 | 74.00 | -26.83 |
| 4880.00 | 43.41 | Ave | 284 | 1.6 | V | -0.62 | 42.79 | 54.00 | -11.21 |
| 7320.00 | 39.77 | PK | 344 | 1.8 | H | 2.21 | 41.98 | 74.00 | -32.02 |
| 7320.00 | 34.32 | Ave | 344 | 1.8 | H | 2.21 | 36.53 | 54.00 | -17.47 |
| 2345.10 | 45.38 | PK | 298 | 1.0 | V | -13.19 | 32.19 | 74.00 | -41.81 |
| 2345.10 | 38.92 | Ave | 298 | 1.0 | V | -13.19 | 25.73 | 54.00 | -28.27 |
| 2379.87 | 42.52 | PK | 141 | 1.6 | H | -13.14 | 29.38 | 74.00 | -44.62 |
| 2379.87 | 36.80 | Ave | 141 | 1.6 | H | -13.14 | 23.66 | 54.00 | -30.34 |
| 2499.15 | 42.39 | PK | 359 | 2.0 | V | -13.08 | 29.31 | 74.00 | -44.69 |
| 2499.15 | 38.26 | Ave | 359 | 2.0 | V | -13.08 | 25.18 | 54.00 | -28.82 |

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | Limit | Margin |
|---------------------------|------------------|-------------|------------------|------------|-------|------------------|---------------------|----------------|--------|
| | | | | Height | Polar | | | | |
| (MHz) | (dB μ V) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dB μ V/m) | (dB μ V/m) | (dB) |
| GFSK High Channel 2480MHz | | | | | | | | | |
| 268.32 | 37.13 | QP | 108 | 1.1 | H | -13.35 | 23.78 | 46.00 | -22.22 |
| 268.32 | 41.11 | QP | 134 | 1.9 | V | -13.35 | 27.76 | 46.00 | -18.24 |
| 4960.00 | 46.87 | PK | 103 | 1.2 | V | -0.24 | 46.63 | 74.00 | -27.37 |
| 4960.00 | 43.79 | Ave | 103 | 1.2 | V | -0.24 | 43.55 | 54.00 | -10.45 |
| 7440.00 | 39.58 | PK | 260 | 1.6 | H | 2.84 | 42.42 | 74.00 | -31.58 |
| 7440.00 | 34.07 | Ave | 260 | 1.6 | H | 2.84 | 36.91 | 54.00 | -17.09 |
| 2321.08 | 45.84 | PK | 180 | 1.7 | V | -13.19 | 32.65 | 74.00 | -41.35 |
| 2321.08 | 38.11 | Ave | 180 | 1.7 | V | -13.19 | 24.92 | 54.00 | -29.08 |
| 2369.87 | 43.48 | PK | 140 | 1.1 | H | -13.14 | 30.34 | 74.00 | -43.66 |
| 2369.87 | 36.95 | Ave | 140 | 1.1 | H | -13.14 | 23.81 | 54.00 | -30.19 |
| 2487.86 | 43.60 | PK | 165 | 1.5 | V | -13.08 | 30.52 | 74.00 | -43.48 |
| 2487.86 | 36.23 | Ave | 165 | 1.5 | V | -13.08 | 23.15 | 54.00 | -30.85 |

Test Frequency: 18GHz~25GHz

The measurements were more than 20 dB below the limit and not reported.

10 Conducted Spurious Emissions

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016
Test Result: PASS
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

10.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

10.2 Test Result


9KHz – 30MHz

802.11b


Low Channel



Middle Channel




High Channel




802.11g


Low Channel



Middle Channel




High Channel




802.11n HT20


Low Channel



Middle Channel






High Channel




802.11n HT40

Low Channel







BLE Low Channel



Middle Channel






Above 30MHz

802.11b

Low Channel

Fundamental




Middle Channel

Fundamental



High Channel

Fundamental



802.11g

Low Channel

Fundamental




Middle Channel

Fundamental



High Channel


Fundamental



802.11n HT20

Low Channel

Fundamental




Middle Channel

Fundamental



High Channel

Fundamental



802.11n HT40


Low Channel

Fundamental



Middle Channel

Fundamental




High Channel

Fundamental



BLE
Low Channel

Fundamental




Middle Channel

Fundamental



High Channel

Fundamental



11 Band Edge Measurement



| | |
|-------------------|---|
| Test Requirement: | FCC CFR47 Part 15 Section 15.247 |
| Test Method: | KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016 |
| Test Limit: | Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |
| Test Mode: | Transmitting |

11.1 Test Produce


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.2 Test Result


Test result plots shown as follows:




TX 11g: Band edge-left side




TX 11g: Band edge-right side




TX 11n HT20: Band edge-left side




TX 11n HT20: Band edge-right side




TX 11n HT40: Band edge-left side




TX 11n HT40: Band edge-right side



BLE: Band edge-left side



BLE: Band edge-right side



12 6 dB Bandwidth Measurement

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016



12.1 Test Procedure:



1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz



12.2 Test Result:

| Operation mode | Test Channel | Bandwidth (MHz) |
|----------------|--------------|-----------------|
| TX 11b | Channel 1 | 10.092 |
| | Channel 6 | 10.092 |
| | Channel 11 | 10.092 |
| TX 11g | Channel 1 | 16.417 |
| | Channel 6 | 16.417 |
| | Channel 11 | 16.417 |
| TX 11n HT20 | Channel 1 | 17.623 |
| | Channel 6 | 17.623 |
| | Channel 11 | 17.623 |
| TX 11n HT40 | Channel 3 | 36.010 |
| | Channel 6 | 36.010 |
| | Channel 9 | 36.010 |
| BLE | Channel 0 | 0.713 |
| | Channel 19 | 0.713 |
| | Channel 39 | 0.707 |


Test result plot:









Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6





Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3







BLE: channel 0



BLE: channel 19



BLE: channel 39



13 Maximum Peak Output Power

Test Requirement:

FCC CFR47 Part 15 Section 15.247

Test Method:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

13.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

section 9.1.1 (For BLE)

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- a) Set the $RBW \geq$ DTS bandwidth.
- b) Set $VBW \geq 3 \times RBW$.
- c) Set $span \geq 3 \times RBW$
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

section 9.1.2 (For WIFI)

This procedure may be used when the maximum available RBW of the measurement instrument is less than the DTS bandwidth.


- a) Set the $RBW = 1$ MHz.
- b) Set the $VBW \geq 3 \times RBW$
- c) Set the $span \geq 1.5 \times$ DTS bandwidth.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the instrument's band/channel power measurement function with the band limits set equal to the DTS bandwidth edges (for some instruments, this may require a manual override to select peak detector). If the instrument does not have a band power function, sum the spectrum levels (in linear power units) at intervals equal to the RBW extending across the DTS bandwidth.

13.2 Test Result:


| Operation mode | Channel Frequency (MHz) | Maximum Peak Output Power (dBm) | Limit |
|----------------|-------------------------|---------------------------------|----------|
| TX 11b | Low-2412 | 9.23 | 1W/30dBm |
| | Middle-2437 | 9.21 | 1W/30dBm |
| | High-2462 | 9.39 | 1W/30dBm |
| TX 11g | Low-2412 | 9.35 | 1W/30dBm |
| | Middle-2437 | 9.30 | 1W/30dBm |
| | High-2462 | 9.26 | 1W/30dBm |
| TX 11n HT20 | Low-2412 | 9.42 | 1W/30dBm |
| | Middle-2437 | 9.36 | 1W/30dBm |
| | High-2462 | 9.25 | 1W/30dBm |
| TX 11n HT40 | Low-2422 | 9.25 | 1W/30dBm |
| | Middle-2437 | 9.34 | 1W/30dBm |
| | High-2452 | 9.31 | 1W/30dBm |
| BLE | Low-2402 | -2.30 | 1W/30dBm |
| | Middle-2440 | -1.82 | 1W/30dBm |
| | High-2480 | -2.91 | 1W/30dBm |

Test Plot


Mode: TX 11b channel 1




Mode: TX 11b channel 6




Mode: TX 11b channel 11




Mode :TX 11g channel 1




Mode :TX 11g channel 6




Mode :TX 11g channel 11




Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 1






Mode: TX 11n HT40 channel 6



Mode: TX 11n HT40 channel 11







14 Power Spectral density

Test Requirement: FCC CFR47 Part 15 Section 15.247

Test Method: KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016

14.1 Test Procedure:

KDB 558074 D01 DTS Meas Guidance v03r05 April 8, 2016 section 10.2


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

14.2 Test Result:


| Operation mode | Channel Frequency (MHz) | Power Spectral (dBm per 3kHz) | Limit |
|----------------|-------------------------|-------------------------------|---------------|
| TX 11b | Low-2412 | -16.49 | 8dBm per 3kHz |
| | Middle-2437 | -16.83 | 8dBm per 3kHz |
| | High-2462 | -16.24 | 8dBm per 3kHz |
| TX 11g | Low-2412 | -22.96 | 8dBm per 3kHz |
| | Middle-2437 | -23.41 | 8dBm per 3kHz |
| | High-2462 | -22.78 | 8dBm per 3kHz |
| TX 11n HT20 | Low-2412 | -22.19 | 8dBm per 3kHz |
| | Middle-2437 | -22.92 | 8dBm per 3kHz |
| | High-2462 | -23.75 | 8dBm per 3kHz |
| TX 11n HT40 | Low-2422 | -23.08 | 8dBm per 3kHz |
| | Middle-2437 | -24.40 | 8dBm per 3kHz |
| | High-2452 | -26.72 | 8dBm per 3kHz |
| BLE | Low-2402 | -17.93 | 8dBm per 3kHz |
| | Middle-2440 | -17.35 | 8dBm per 3kHz |
| | High-2480 | -18.45 | 8dBm per 3kHz |



Test Plot



Mode: TX 11b channel 1




Mode: TX 11b channel 6









Mode: TX 11n HT20 channel 1




Mode: TX 11n HT20 channel 6




Mode: TX 11n HT20 channel 11




Mode: TX 11n HT40 channel 3




Mode: TX 11n HT40 channel 6




Mode: TX 11n HT40 channel 9




BLE: channel 0



BLE: channel 19





15 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

16 RF Exposure

Remark: refer to SAR test report: WTS16S0961015E.

17 Photographs of test setup and EUT.

Note: Please refer to appendix: WTS16S0961016E_Photo.

=====**End of Report**=====