Request for Modular/Limited Modular Approval

Date: January 19, 2020						
Subject: Manufacturer's Declaration for □ - Modular Approval □ - Split Modular Approval □ - Limited Modular Approval □ - Limited Split		approval				
Confidentiality Request for: 2AJVQ-7668AUFT						
8 Basic Requirements – FCC Part 15.212(a)(1)						
For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the Fo						
Modular Approval Requirement	Require	ment Met				
1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	□ - NO(*)				
Details: < The module contains a metal shield which covers all RF components and circuitry. The sh the board next to antenna connector>	ield is located	on the top of				
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)	⊠ - YES	□ - NO(*)				
$egin{array}{cccccccccccccccccccccccccccccccccccc$						
3. The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	⊠ - YES	□ - NO(*)				
Details: <the application="" block="" chip="" contains="" diagram="" in="" its="" module="" own="" please="" power="" refer="" regulation="" supply="" the="" this="" to="" transmitter="" u1.="" with=""></the>						
4. The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	⊠ - YES	□ - NO(*)				
Details: < The antenna is permanently attached.>						
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)				
Details: <the applic<="" as="" filed="" in="" module="" photographs="" setup="" shown="" stand-alone="" td="" test="" tested="" this="" was="" with=""><td>ation></td><td></td></the>	ation>					

	Modular Approval Requirement	Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748). If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization. If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)	⊠ - YES	□ - NO(*)
	Details: <there a="" application.="" are="" as="" exhibit="" filed="" in="" installation="" instructions="" is="" it="" label="" labeling="" manual="" module="" on="" shown="" the="" this="" with=""></there>	Host specific l	abeling
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: <the 15c="" application.="" complies="" fcc="" filed="" installation="" installer="" instructions="" manual="" module="" oem="" of="" part="" requirements.="" the="" this="" to="" with=""></the>	ire provided ii	n the
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: <the application.="" as="" exclusion="" exposure="" filed="" in="" information="" levels="" meets="" module="" portable="" rf="" shown="" the="" this="" with=""></the>		

* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <N/A>

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement	Requirement Met		
 For non-Software Defined Radio transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280. 	⊠ - Provided in Separate Cover Letter □ - N/A		
Details: <the a="" adjusted="" application.="" as="" be="" by="" can="" cover="" described="" device="" end="" filed="" firmware="" in="" letter="" modified="" not="" of="" or="" separate="" the="" this="" user="" with=""></the>			
 For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812. 	☐ - Provided in Separate Cover Letter ☐ - N/A		
Details: <n a=""></n>			

Split Modular Requirements				
Requirement	Provided in Manual			
 For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained. 	☐ - Provided in Separate Cover Letter	⊠ - N/A		
Details: <n a=""></n>				

	OEM Integration Manua	al Guidance – KDB 996369 D03 Section 2		
		cribing the Conditions, Limitations, and Proced	ures	
for	tnird-parties to use and	/or integrate the module into a host device.		
Requirement				
		□ - No,		
		If No, and LMA applies, the applicant ca	n optionally choose to not	
		make the following detailed info public.		
Is this module intended for	⊠ - YES	to be basic integration instructions for		
sale to third parties?	△ - 1E3		information below must still be included in the operational description. If the applicant wishes to keep this info confidential,	
		this will require a separate statement co		
		module is not for sale to third partie	s and that integration	
<u>-</u> .		instructions are internal confide	ntial documents.	
		manual – See KDB 996369 D03, Section 2 ng information to be in the installation manual.	Modular transmittar	
		ng mormation to be in the instantation manual. ns for all these items indicating clearly when the		
		cate "Not Applicable". Also if a module is limite		
products and not intended for s	sale to third parties, the u	ser instructions may not need to be detailed and	d the following items can	
		n, but this should include a cover letter as cited	above.	
 List of applicable FCC rules. a. Only list rules 	related to the transmitter.	on 2.2		
2. Summarize the specific opera		B 996369 D03 Section 2.3		
		able loss, reduction of power for point to point		
systems, profe	essional installation info			
3. Limited Module Procedures.				
a. Describe alteri limiting condi	~	tee uses to verify the host meets the necessary		
		ry, state how control will be maintained such	□ - All Items shown to	
	ce is ensured, such as Class		the left are provided in	
4. Trace antenna designs. KDB			the Modular Integration Guide (or UM) for Full	
		a, connectors, isolation requirements, tests for	Modular Approval (MA)	
		procedures for ensuring compliance. If nfidential must be identified and information	or LMA.	
	e operational description.	intential must be identified and information		
5. RF exposure considerations.	KDB 996369 D03, Section		☐ - An LMA applies	
		at allow host manufacturers to use the module.	and is approved ONLY for use by the grantee in	
		first to the host manufacturer to define m body) and second additional text needed to be	their own products, and	
	e end user in the host produ	· · · · · · · · · · · · · · · · · · ·	not intended for sale to	
6. Antennas. KDB 996369 D03.			3 rd parties as provided in	
		on and all applicable professional installer	a separate cover letter. Therefore the	
		na list shall also identify the antenna types	information shown to the	
7. Label and compliance inform		"omni-directional" is not considered a type) Section 2.8	left is found in the	
		to provide a physical or e-label stating	theory of operation.	
"Contains FCO	C ID: " with their finished	product		
		ements. KDB 996369 D03, Section 2.9		
		nsideration by host integrators including and simultaneous configurations.		
	nation on how to configure			
9. Additional testing, Part 15 Su				
-				
Sincerely,	itenu /:			
	ifeny li	Caifeng Li		
Ву:				
(Sig	nature/Title ¹)	(Print name)		

¹ - Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.