



Produkte  
 Products

802.11n-HT40, SISO, Ant0





Produkte  
Products

802.11n-HT20, MIMO, Ant0





Produkte  
Products

802.11n-HT20, MIMO, Ant1




Produkte  
Products

802.11n-HT40, MIMO, Ant0



Produkte  
Products

802.11n-HT40, MIMO, Ant1



## 5. Transmitter Spurious Emissions


Note: 1, Testing is carried out with frequency rang 9kHz to the tenth harmonics.  
 2, The margin is greater than 20 dB are not shown in this Appendix.

### 5.1 Transmitter Spurious Emissions, Below 1GHz

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



#### Radiated Emission Measurement



Site: 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11b Low(Ant0)  
 Note:


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		183.2600	52.64	-19.84	32.80	43.50	-10.70	QP			
2	*	215.2700	48.47	-14.92	33.55	43.50	-9.95	QP			
3		364.6500	33.33	-10.29	23.04	46.00	-22.96	QP			
4		466.5000	31.12	-8.30	22.82	46.00	-23.18	QP			
5		631.4000	30.60	-4.71	25.89	46.00	-20.11	QP			
6		799.2100	30.03	-2.03	28.00	46.00	-18.00	QP			

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11b Low(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	76.5600	46.87	-20.32	26.55	40.00	-13.45	QP		
2		90.1400	40.61	-16.41	24.20	43.50	-19.30	QP		
3		166.7700	37.50	-18.31	19.19	43.50	-24.31	QP		
4		214.3000	35.92	-15.01	20.91	43.50	-22.59	QP		
5		239.5200	37.34	-14.09	23.25	46.00	-22.75	QP		
6		972.8400	34.62	-0.15	34.47	54.00	-19.53	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.  
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3 Polarization: **Horizontal** Temperature: 24 C  
Limit: (RE)FCC PART 15 C Power: Humidity: 53 %  
EUT: WIFI Module  
M/N:  
Mode:11b Middle(Ant0)  
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	179.3800	52.33	-19.92	32.41	43.50	-11.09	QP		
2		199.7500	48.48	-16.21	32.27	43.50	-11.23	QP		
3		239.5200	45.50	-14.09	31.41	46.00	-14.59	QP		
4		364.6500	31.60	-10.29	21.31	46.00	-24.69	QP		
5		464.5600	30.82	-8.38	22.44	46.00	-23.56	QP		
6		633.3400	30.13	-4.69	25.44	46.00	-20.56	QP		

\*:Maximum data x:Over limit !:over margin




Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode:11b Middle(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	76.5600	47.09	-20.32	26.77	40.00	-13.23	QP		
2		90.1400	41.07	-16.41	24.66	43.50	-18.84	QP		
3		165.8000	37.24	-18.31	18.93	43.50	-24.57	QP		
4		215.2700	36.57	-14.92	21.65	43.50	-21.85	QP		
5		239.5200	39.06	-14.09	24.97	46.00	-21.03	QP		
6		967.9900	36.39	-0.20	36.19	54.00	-17.81	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Shenzhen EMTEK Co., Ltd.  
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



**Radiated Emission Measurement**

File :TUV HAIXIN Data :#253 Date :17/03/05/ Time:



Site 3m Chamber #3 Polarization: **Horizontal** Temperature: 24 C  
Limit: (RE)FCC PART 15 C Power: Humidity: 53 %  
EUT: WIFI Module  
M/N:  
Mode:11b High(Ant0)  
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		181.3200	51.86	-19.83	32.03	43.50	-11.47	QP			
2	*	201.6900	50.35	-16.05	34.30	43.50	-9.20	QP			
3		215.2700	49.20	-14.92	34.28	43.50	-9.22	QP			
4		239.5200	45.57	-14.09	31.48	46.00	-14.52	QP			
5		299.6600	33.48	-12.02	21.46	46.00	-24.54	QP			
6		645.9500	30.96	-4.56	26.40	46.00	-19.60	QP			


\*:Maximum data x:Over limit !:over margin

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11b High(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	76.5600	47.61	-20.32	27.29	40.00	-12.71	QP		
2		90.1400	41.19	-16.41	24.78	43.50	-18.72	QP		
3		180.3500	37.93	-16.82	21.11	43.50	-22.39	QP		
4		232.7300	35.95	-14.24	21.71	46.00	-24.29	QP		
5		239.5200	37.88	-14.09	23.79	46.00	-22.21	QP		
6		972.8400	36.35	-0.15	36.20	54.00	-17.80	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11g High(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		183.2600	51.92	-19.84	32.08	43.50	-11.42	QP			
2	*	198.7800	49.11	-16.27	32.84	43.50	-10.66	QP			
3		239.5200	45.32	-14.09	31.23	46.00	-14.77	QP			
4		364.6500	31.79	-10.29	21.50	46.00	-24.50	QP			
5		631.4000	31.03	-4.71	26.32	46.00	-19.68	QP			
6		967.9900	33.28	-0.20	33.08	54.00	-20.92	QP			

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11g High(Ant0)  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Detector	Comment
1	*	76.5600	46.72	-20.32	26.40	40.00	-13.60	QP			
2		90.1400	40.80	-16.41	24.39	43.50	-19.11	QP			
3		175.5000	39.27	-17.48	21.79	43.50	-21.71	QP			
4		239.5200	37.18	-14.09	23.09	46.00	-22.91	QP			
5		833.1600	29.50	-1.67	27.83	46.00	-18.17	QP			
6		968.9600	35.02	-0.20	34.82	54.00	-19.18	QP			

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11g Middle(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		166.7700	48.55	-18.31	30.24	43.50	-13.26	QP		
2	*	179.3800	53.19	-19.92	33.27	43.50	-10.23	QP		
3		198.7800	49.40	-16.27	33.13	43.50	-10.37	QP		
4		239.5200	45.79	-14.09	31.70	46.00	-14.30	QP		
5		364.6500	31.96	-10.29	21.67	46.00	-24.33	QP		
6		833.1600	30.12	-1.67	28.45	46.00	-17.55	QP		


\*:Maximum data    x:Over limit    !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11g Middle(Ant0)  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Detector	Comment
1	*	76.5600	47.21	-20.32	26.89	40.00	-13.11	QP			
2		90.1400	41.00	-16.41	24.59	43.50	-18.91	QP			
3		143.4900	34.46	-19.09	15.37	43.50	-28.13	QP			
4		177.4400	35.84	-17.20	18.64	43.50	-24.86	QP			
5		239.5200	37.52	-14.09	23.43	46.00	-22.57	QP			
6		968.9600	35.85	-0.20	35.65	54.00	-18.35	QP			

\*:Maximum data    x:Over limit    !:over margin




Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11g Low(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		166.7700	48.46	-18.31	30.15	43.50	-13.35	QP		
2		178.4100	53.03	-20.05	32.98	43.50	-10.52	QP		
3	*	202.6600	48.99	-15.97	33.02	43.50	-10.48	QP		
4		239.5200	45.69	-14.09	31.60	46.00	-14.40	QP		
5		364.6500	33.11	-10.29	22.82	46.00	-23.18	QP		
6		644.9800	31.72	-4.58	27.14	46.00	-18.86	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: KK




Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11g Low(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	75.5900	46.78	-20.54	26.24	40.00	-13.76	QP		
2		90.1400	40.80	-16.41	24.39	43.50	-19.11	QP		
3		175.5000	36.95	-17.48	19.47	43.50	-24.03	QP		
4		215.2700	35.73	-14.92	20.81	43.50	-22.69	QP		
5		239.5200	37.85	-14.09	23.76	46.00	-22.24	QP		
6		967.9900	37.16	-0.20	36.96	54.00	-17.04	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT20 Low(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		182.2900	53.22	-19.83	33.39	43.50	-10.11	QP			
2	*	200.7200	50.10	-16.14	33.96	43.50	-9.54	QP			
3		215.2700	47.88	-14.92	32.96	43.50	-10.54	QP			
4		366.5900	33.25	-10.26	22.99	46.00	-23.01	QP			
5		464.5600	30.46	-8.38	22.08	46.00	-23.92	QP			
6		644.9800	32.04	-4.58	27.46	46.00	-18.54	QP			

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT20 Low(Ant0)  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Detector	Comment
1	*	76.5600	47.07	-20.32	26.75	40.00	-13.25	QP			
2		90.1400	40.64	-16.41	24.23	43.50	-19.27	QP			
3		178.4100	36.30	-17.05	19.25	43.50	-24.25	QP			
4		215.2700	36.72	-14.92	21.80	43.50	-21.70	QP			
5		239.5200	38.18	-14.09	24.09	46.00	-21.91	QP			
6		971.8700	36.03	-0.16	35.87	54.00	-18.13	QP			

\*:Maximum data    x:Over limit    !:over margin

Operator: KK


Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



**Radiated Emission Measurement**

File :TUV HAIXIN      Data :#263      Date: 17/03/05/      Time:



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode:11nHT20 Middle(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		166.7700	48.84	-18.31	30.53	43.50	-12.97	QP		
2		181.3200	52.10	-19.83	32.27	43.50	-11.23	QP		
3	*	215.2700	48.95	-14.92	34.03	43.50	-9.47	QP		
4		239.5200	45.31	-14.09	31.22	46.00	-14.78	QP		
5		437.4000	32.39	-8.65	23.74	46.00	-22.26	QP		
6		645.9500	30.59	-4.56	26.03	46.00	-19.97	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT20 Middle(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	76.5600	47.85	-20.32	27.53	40.00	-12.47	QP		
2		90.1400	41.20	-16.41	24.79	43.50	-18.71	QP		
3		177.4400	36.96	-17.20	19.76	43.50	-23.74	QP		
4		239.5200	38.03	-14.09	23.94	46.00	-22.06	QP		
5		298.6900	31.01	-12.07	18.94	46.00	-27.06	QP		
6		967.9900	35.32	-0.20	35.12	54.00	-18.88	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT20 High(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		166.7700	48.84	-18.31	30.53	43.50	-12.97	QP			
2		177.4400	52.29	-20.20	32.09	43.50	-11.41	QP			
3	*	214.3000	47.89	-15.01	32.88	43.50	-10.62	QP			
4		239.5200	45.60	-14.09	31.51	46.00	-14.49	QP			
5		366.5900	32.92	-10.26	22.66	46.00	-23.34	QP			
6		631.4000	30.95	-4.71	26.24	46.00	-19.76	QP			

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode:11nHT20 High(Ant0)  
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	75.5900	47.08	-20.54	26.54	40.00	-13.46	QP		
2		90.1400	40.88	-16.41	24.47	43.50	-19.03	QP		
3		166.7700	37.61	-18.31	19.30	43.50	-24.20	QP		
4		239.5200	37.86	-14.09	23.77	46.00	-22.23	QP		
5		565.4400	27.87	-5.90	21.97	46.00	-24.03	QP		
6		968.9600	36.56	-0.20	36.36	54.00	-17.64	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: KK




Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**

File : TUV HAIXIN      Data : #267      Date : 17/03/05/      Time :



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 High(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		187.1400	52.25	-19.85	32.40	43.50	-11.10	QP		
2		198.7800	49.28	-16.27	33.01	43.50	-10.49	QP		
3	*	215.2700	48.34	-14.92	33.42	43.50	-10.08	QP		
4		239.5200	46.18	-14.09	32.09	46.00	-13.91	QP		
5		366.5900	32.47	-10.26	22.21	46.00	-23.79	QP		
6		633.3400	30.62	-4.69	25.93	46.00	-20.07	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: KK




Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 High(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	76.5600	46.91	-20.32	26.59	40.00	-13.41	QP		
2		90.1400	40.87	-16.41	24.46	43.50	-19.04	QP		
3		179.3800	35.96	-16.92	19.04	43.50	-24.46	QP		
4		239.5200	37.19	-14.09	23.10	46.00	-22.90	QP		
5		437.4000	30.12	-8.65	21.47	46.00	-24.53	QP		
6		967.9900	33.40	-0.20	33.20	54.00	-20.80	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 Middle(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree		
1		159.0100	44.77	-18.43	26.34	43.50	-17.16	QP			
2		178.4100	53.53	-20.05	33.48	43.50	-10.02	QP			
3	*	215.2700	48.54	-14.92	33.62	43.50	-9.88	QP			
4		239.5200	45.19	-14.09	31.10	46.00	-14.90	QP			
5		298.6900	34.19	-12.07	22.12	46.00	-23.88	QP			
6		366.5900	32.29	-10.26	22.03	46.00	-23.97	QP			

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Shenzhen EMTEK Co., Ltd.  
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
www.emtek.com.cn Tel:+86-755-2695 4280 Fax:+86-755-2695 4282



**Radiated Emission Measurement**

File :TUV HAIXIN Data :#270 Date: 17/03/05/ Time:



Site 3m Chamber #3 Polarization: **Vertical** Temperature: 24 C  
Limit: (RE)FCC PART 15 C Power: Humidity: 53 %  
EUT: WIFI Module  
M/N:  
Mode:11nHT40 Middle(Ant0)  
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	74.6200	46.65	-20.61	26.04	40.00	-13.96	QP		
2		90.1400	40.06	-16.41	23.65	43.50	-19.85	QP		
3		177.4400	38.03	-17.20	20.83	43.50	-22.67	QP		
4		239.5200	36.70	-14.09	22.61	46.00	-23.39	QP		
5		466.5000	30.67	-8.30	22.37	46.00	-23.63	QP		
6		971.8700	36.20	-0.16	36.04	54.00	-17.96	QP		

\*:Maximum data x:Over limit !:over margin


Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**

File : TUV HAIXIN      Data : #271      Date : 17/03/05/      Time :



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 Low(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		179.3800	52.36	-19.92	32.44	43.50	-11.06	QP		
2	*	200.7200	49.73	-16.14	33.59	43.50	-9.91	QP		
3		215.2700	47.36	-14.92	32.44	43.50	-11.06	QP		
4		239.5200	45.28	-14.09	31.19	46.00	-14.81	QP		
5		364.6500	32.87	-10.29	22.58	46.00	-23.42	QP		
6		464.5600	31.52	-8.38	23.14	46.00	-22.86	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 Low(Ant0)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	75.5900	47.28	-20.54	26.74	40.00	-13.26	QP		
2		90.1400	40.44	-16.41	24.03	43.50	-19.47	QP		
3		178.4100	37.34	-17.05	20.29	43.50	-23.21	QP		
4		239.5200	37.82	-14.09	23.73	46.00	-22.27	QP		
5		464.5600	29.70	-8.38	21.32	46.00	-24.68	QP		
6		967.9900	34.36	-0.20	34.16	54.00	-19.84	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: KK


Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**

File : TUV HAIXIN      Data : #273      Date : 17/03/05/      Time :



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 High(Ant0+Ant1)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		177.4400	52.43	-20.20	32.23	43.50	-11.27	QP		
2	*	214.3000	47.99	-15.01	32.98	43.50	-10.52	QP		
3		239.5200	47.14	-14.09	33.05	46.00	-12.95	QP		
4		633.3400	30.39	-4.69	25.70	46.00	-20.30	QP		
5		833.1600	29.28	-1.67	27.61	46.00	-18.39	QP		
6		969.9300	30.82	-0.19	30.63	54.00	-23.37	QP		


\*:Maximum data    x:Over limit    !:over margin

Operator: KK

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 High(Ant0+Ant1)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	74.6200	46.84	-20.61	26.23	40.00	-13.77	QP		
2		90.1400	42.30	-16.41	25.89	43.50	-17.61	QP		
3		175.5000	36.64	-17.48	19.16	43.50	-24.34	QP		
4		239.5200	37.65	-14.09	23.56	46.00	-22.44	QP		
5		299.6600	30.94	-12.02	18.92	46.00	-27.08	QP		
6		968.9600	34.94	-0.20	34.74	54.00	-19.26	QP		

\*:Maximum data    x:Over limit    !:over margin




Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 Middle(Ant0+Ant1)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		180.3500	51.94	-19.82	32.12	43.50	-11.38	QP		
2	*	215.2700	47.92	-14.92	33.00	43.50	-10.50	QP		
3		239.5200	45.57	-14.09	31.48	46.00	-14.52	QP		
4		464.5600	30.27	-8.38	21.89	46.00	-24.11	QP		
5		644.9800	30.44	-4.58	25.86	46.00	-20.14	QP		
6		798.2400	29.25	-2.05	27.20	46.00	-18.80	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: KK




Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Vertical**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 Middle(Ant0+Ant1)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	75.5900	47.22	-20.54	26.68	40.00	-13.32	QP		
2		90.1400	40.16	-16.41	23.75	43.50	-19.75	QP		
3		177.4400	37.41	-17.20	20.21	43.50	-23.29	QP		
4		366.5900	29.62	-10.26	19.36	46.00	-26.64	QP		
5		565.4400	29.93	-5.90	24.03	46.00	-21.97	QP		
6		972.8400	32.97	-0.15	32.82	54.00	-21.18	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK

Produkte  
 Products

Shenzhen EMTEK Co., Ltd.  
 Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China  
 www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



**Radiated Emission Measurement**



Site 3m Chamber #3      Polarization: **Horizontal**      Temperature: 24 C  
 Limit: (RE)FCC PART 15 C      Power:      Humidity: 53 %  
 EUT: WIFI Module  
 M/N:  
 Mode: 11nHT40 Low (Ant0+Ant1)  
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	177.4400	53.26	-20.20	33.06	43.50	-10.44	QP		
2		200.7200	49.16	-16.14	33.02	43.50	-10.48	QP		
3		215.2700	47.56	-14.92	32.64	43.50	-10.86	QP		
4		239.5200	45.20	-14.09	31.11	46.00	-14.89	QP		
5		366.5900	31.60	-10.26	21.34	46.00	-24.66	QP		
6		796.3000	28.80	-2.09	26.71	46.00	-19.29	QP		

\*:Maximum data    x:Over limit    !:over margin

Operator: KK