

RF Exposure Assessment

Report Reference: MDE_CONTI_2152_MPE_01

on

Telematic Control Unit ZONAR SCM1

FCC ID 2AJW5-SCM1

IC: 21979-SCM1

Test Laboratory:
7layers GmbH
Borsigstrasse 11
40880 Ratingen
Germany

Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7layers GmbH
Borsigstraße 11
40880 Ratingen, Germany
T +49 (0) 2102 749 0
F +49 (0) 2102 749 350

Geschäftsführer/
Managing Directors:
Sebastian Doose
Stefan Kischka
Bernhard Retka
www.7layers.com

Registergericht/registered:
Düsseldorf HRB 75554
USt-Id.-Nr./VAT-No. DE203159652
Steuer-Nr./TAX-No. 147/5869/0385

*a Bureau Veritas
Group Company*

Summary

Type of Report

RF Exposure calculation for the Telematic Control Unit SCM1

Applicable FCC Rules

For RF Exposure:

OET Bulletin 65 Edition 97-01 August 1997

FCC 47 CFR §1.1307

FCC 47 CFR §1.1310

Report version control			
Rev Version	Release date	Changes	Version validity
-	10.11.2021	Initial version	Valid
Rev01	23.11.2022	Simultaneous Transmission added	Valid



(Responsible for the report)
Mr. Imad Hjije

Administrative Data:

Testing Laboratory

Company Name: 7layers GmbH
Address: Borsigstr. 11
40880 Ratingen
Germany

Report Template Version: 2022-05-25

Project Data

Responsible for report: Mr. Imad Hjije
Date of Report: 2022-11-10
Testing Period: - (please see FCC 15.247 test reports)

Applicant Data

Company Name: Continental Automotive GmbH
Address: Heinrich-Hertz-Str. 45
78052, Villingen-Schwenningen
Germany
Contact Person: Dr. Marion Grüner

Manufacturer Data

Company Name: please see Applicant data
Address: -
-
-
Contact Person: -

Test object Data

General Description of Radio Device

Kind of Device product description	Telematics Control Unit
Product name	SCM1
Type / Model	ZONAR V4C
Declared EUT data by the supplier	
Power Supply Type	DC
Nominal Voltage / Frequency	12 – 24 V
Test Voltage / Frequency	12 V
Highest internal frequency	2690 MHz (highest channel from LTE Band 7)
General Description	SCM1 is a vehicle mounted telematics device incorporating - Dual mode Bluetooth for peripheral connectivity

Assessed Radio Devices

Sample Name	Sample Code	Description
EUT 16	DE1480002ag02	Radiated Sample
Sample Parameter	Value	
Serial No.	IMEI: 352763680008833	
HW Version	C	
SW Version	Leap 24.5	
Comment		

General description of ancillary equipment

Device	Details (Manufacturer, Type Model, HW, SW, S/N)	Description
-	-	-

General description of auxiliary equipment

Device	Details (Manufacturer, Type Model, HW, SW, S/N)	Description
AUX A	Panorama Antennas, Model: AGPS26-SRGR, -, -, -	External GNSS antenna

General description of setups

Setup	Combination of EUTs	Description and Rationale
S01_AG02	EUT 16+ AUX A	Radiated Setup

Documents used for assessment supplied to applicant

Radio technology	Details	Description
Bluetooth	Qualcomm module based on a QCA65x4 design	FCC 15.247 Test Report: max. 7.8 dBm conducted
Cellular	Continental Communications Rcvr for use w/ licensed Tx and CBs	Certified under: LHJ-BL28NARD1

Measured RF Output Power (Bluetooth Classic)

BT GFSK (1-DH1)

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]	E.I.R.P [dBm]
2.4 GHz ISM	0	2402	6.9	21.0	14.1	9.9
	39	2441	7.8	21.0	13.2	10.8
	78	2480	6.3	21.0	14.7	9.3

BT π/4 DQPSK (2-DH1)

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]	E.I.R.P [dBm]
2.4 GHz ISM	0	2402	6.0	21.0	15.0	9.0
	39	2441	7.1	21.0	13.9	10.1
	78	2480	5.7	21.0	15.3	8.7

BT 8-DPSK (3-DH1)

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]	E.I.R.P [dBm]
2.4 GHz ISM	0	2402	6.6	21.0	14.4	9.6
	39	2441	7.6	21.0	13.4	10.6
	78	2480	6.2	21.0	14.8	9.2

Measured RF Output Power (Bluetooth Low Energy)

BT LE 1 Mbit/s

Band	Channel No.	Frequency [MHz]	Peak Power [dBm]	Limit [dBm]	Margin to Limit [dB]	E.I.R.P [dBm]
2.4 GHz ISM	0	2402	-1.2	30.0	31.2	1.8
	19	2440	1.0	30.0	29.0	4.0
	39	2480	-0.2	30.0	30.2	2.8

RF Exposure Evaluation

Standards
OET Bulletin 65 Edition 97-01 August 1997
RSS-102 Issue 5 – March 2015

Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm ²)
300 – 1,500	f/1500
1,500 – 100,000	1.0

Limits specified per RSS-102, Issue 5.

Frequency range (MHz)	Power density (W/m ²)	Power density (mW/cm ²)
300 – 6000	0.02619 f ^{0.6834}	mW/cm ² = W/m ² * 0.1

Equation OET bulletin 65, page 18, edition 97-01:
$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Test Protocol

Operational Bands	Frequency (MHz)	Antenna Gain (dBi)	G			P			S		Margin to FCC Limit (mW/cm ²)	Verdict
			Antenna Gain -numeric- (mW/cm ²)	Output Power -conducted- (dBm)	Duty Cycle correction factor	Max. mean output power (dBm)	Output Power -conducted- (mW)	Output Power (EIRP) (mW)	FCC Limit (mW/cm ²)	Power Density value (mW/cm ²)		
Bluetooth Classic	2441	3	1.9953	7.80	0	7.80	6.03	12.02	1.0000	0.0024	0.9976	PASS

Simultaneous Transmission

	1 st Technology Bluetooth Classic (BT)	2 nd Technology Cellular (
(S_{eq} / S_{lim})	0.0060	0.4214
Sum of (S_{eq} / S_{lim})	0.4274	
Limit	1	
Conclusion	passed	

Note: Only worst case was evaluated

<End of Assessment>