



RF TEST REPORT



Report No.: FCC_RF_SL17062101-SEV-039-DTS
Supersede Report No.:





| | | |
|--|---|--|
| Applicant | : | Continental Automotive Systems, Inc |
| Product Name | : | FLEX CM |
| Model No. | : | 1819-X |
| Test Standard | : | 47 CFR 15.247 |
| Test Method | : | ANSI C63.10: 2013 558074 D01 DTS Meas Guidance v04 |
| FCC ID | : | 2AJW5FLEXCM |
| Dates of test | : | 06/22/2017 – 06/23/2017 |
| Issue Date | : | 07/05/2017 |
| Test Result | : | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail |
| Equipment complied with the specification [X] Equipment did not comply with the specification [] | | |

| This Test Report is Issued Under the Authority of: | |
|---|--|
|  |  |
| Rachana Khanduri | Chen Ge |
| Test Engineer | Engineer Reviewer |

Issued By:
SIEMIC Laboratories
775 Montague Expressway, Milpitas, 95035 CA



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile (+1) 408 526 1088

Visit us at: www.siemic.com; Follow us at:    

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

| Country/Region | Accreditation Body | Scope |
|----------------|------------------------|-----------------------------------|
| USA | FCC, A2LA | EMC, RF/Wireless, Telecom |
| Canada | IC, A2LA, NIST | EMC, RF/Wireless, Telecom |
| Taiwan | BSMI, NCC, NIST | EMC, RF, Telecom, Safety |
| Hong Kong | OFTA, NIST | RF/Wireless, Telecom |
| Australia | NATA, NIST | EMC, RF, Telecom, Safety |
| Korea | KCC/RRA, NIST | EMI, EMS, RF, Telecom, Safety |
| Japan | VCCI, JATE, TELEC, RFT | EMI, RF/Wireless, Telecom |
| Mexico | NOM, COFETEL, Caniety | Safety, EMC, RF/Wireless, Telecom |
| Europe | A2LA, NIST | EMC, RF, Telecom, Safety |
| Israel | MOC, NIST | EMC, RF, Telecom, Safety |

Accreditations for Product Certifications

| Country | Accreditation Body | Scope |
|-----------|--------------------|-----------------------|
| USA | FCC TCB, NIST | EMC, RF, Telecom |
| Canada | IC FCB, NIST | EMC, RF, Telecom |
| Singapore | iDA, NIST | EMC, RF, Telecom |
| EU | NB | EMC & R&TTE Directive |
| Japan | MIC (RCB 208) | RF, Telecom |
| Hong Kong | OFTA (US002) | RF, Telecom |

CONTENTS

| | | |
|-----------|---|-----------|
| 1 | REPORT REVISION HISTORY | 4 |
| 2 | EXECUTIVE SUMMARY | 5 |
| 3 | CUSTOMER INFORMATION | 5 |
| 4 | TEST SITE INFORMATION | 5 |
| 5 | MODIFICATION | 5 |
| 6 | EUT INFORMATION | 6 |
| 6.1 | EUT Description | 6 |
| 6.2 | Radio Description | 6 |
| 6.3 | EUT Photos – External | 7 |
| 6.4 | EUT Photos - Internal | 8 |
| 6.5 | EUT Test Setup Photos | 9 |
| 7 | SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION..... | 10 |
| 7.1 | Supporting Equipment | 10 |
| 7.2 | Cabling Description | 10 |
| 7.3 | Test Software Description | 10 |
| 8 | TEST SUMMARY..... | 11 |
| 9 | MEASUREMENT UNCERTAINTY | 12 |
| 9.1 | Conducted Emissions | 12 |
| 9.2 | Radiated Emissions (30MHz to 1GHz)..... | 12 |
| 9.3 | Radiated Emissions (1GHz to 40GHz)..... | 13 |
| 9.4 | RF conducted measurement..... | 13 |
| 10 | MEASUREMENTS, EXAMINATION AND DERIVED RESULTS..... | 14 |
| 10.1 | Radiated Spurious Emissions below 1GHz | 14 |
| 10.2 | Radiated Spurious Emissions between 1GHz – 25GHz | 16 |
| | ANNEX A. TEST INSTRUMENT | 23 |
| | ANNEX B. SIEMIC ACCREDITATION | 24 |

1 Report Revision History

| Report No. | Report Version | Description | Issue Date |
|-------------------------------|----------------|-------------|------------|
| FCC_RF_SL17062101-SEV-039-DTS | None | Original | 07/05/2017 |
| | | | |
| | | | |
| | | | |
| | | | |

2 Executive Summary

The purpose of this test program was to demonstrate compliance of following product

Company: Continental Automotive Systems, Inc
Product: FLEX CM
Model: 1819-X

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1st page.

3 Customer information

| | | |
|----------------------|---|---|
| Applicant Name | : | Continental Automotive Systems, Inc |
| Applicant Address | : | 6755 Snowdrift Road, US |
| Manufacturer Name | : | Continental Automotive Guadalajara México, S.A. de C.V |
| Manufacturer Address | : | Camino a la Tijera 3 Municipio de Tlajomulco de Zuniga, Jalisco Mexico |

4 Test site information

| | |
|----------------------|---|
| Lab performing tests | SIEMIC Laboratories |
| Lab Address | 775 Montague Expressway, Milpitas, CA 95035 |
| FCC Test Site No. | 881796 |
| IC Test Site No. | 4842D-2 |
| VCCI Test Site No. | A0133 |

5 Modification

| Index | Item | Description | Note |
|-------|------|-------------|------|
| - | - | - | - |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

6 EUT Information

6.1 EUT Description

| | | |
|---------------------------|---|--|
| Product Name | : | FLEX CM |
| Model No. | : | 1819-X |
| Trade Name | : | Continental |
| Serial No. | : | 0027 |
| Input Power | : | 12VDC |
| Power Adapter Manu/Model | : | N/A |
| Power Adapter SN | : | N/A |
| Product Hardware version | : | 1819-X |
| Product Software version | : | 4.X.X.X |
| Radio Hardware version | : | PDS6 / RBHA-C213B |
| Radio Software version | : | 3.001 |
| Date of EUT received | : | 06/21/2017 |
| Equipment Class/ Category | : | Class B |
| Port/Connectors | : | USB,RS-232,CAN/LIN, Dig I/O, Ana In, Power, Ground, Ignition |

6.2 Radio Description

| Radio Type | 802.11b | 802.11g | 802.11n-20M |
|------------------------|--------------------------------------|--|------------------------------------|
| Operating Frequency | 2412-2462MHz | 2412-2462MHz | 2412-2462MHz |
| Modulation | DSSS (CCK, DQPSK, DBPSK) | OFDM-CCK (BPSK, QPSK, 16QAM, 64QAM) | OFDM (BPSK, QPSK, 16QAM, 64QAM) |
| Channel Spacing | 5MHz | 5MHz | 5MHz |
| Number of Channels | 11 | 11 | 11 |
| Antenna Type | PCB | | |
| Antenna Gain (Peak) | 4.5dBi | | |
| Antenna Connector Type | intern. microstrip line / ext. FAKRA | | |


6.3 EUT Photos – External




EUT – Front View



EUT – Rear View




EUT – Top View



EUT – Bottom View




EUT – Left Side View




EUT – Right Side View


6.4 EUT Photos - Internal




FLEXCM- External Board- Top View




FLEXCM-External Board- Bottom View




FLEXCM- Main Board- Top View



FLEXCM-Main Board- Bottom View




FLEXCM-WLAN and BT Module




FLEXCM-Cellular Module


6.5 EUT Test Setup Photos




Radiated Emissions (<1GHz) – Front View



Radiated Emissions (<1GHz) – Rear View



Radiated Emissions (>1GHz) – Front View



Radiated Emissions (>1GHz) – Rear View

7 Supporting Equipment/Software and cabling Description

7.1 Supporting Equipment

| Item | Supporting Equipment Description | Model | Serial Number | Manufacturer | Note |
|------|----------------------------------|---------------|---------------|--------------|------|
| 1 | Laptop | Latitude 3550 | N/A | Dell | - |
| 2 | DC Power Supply | DP712 | DP7B190700020 | RIGOL | - |
| | | | | | |

7.2 Cabling Description

| Name | Connection Start | | Connection Stop | | Length / shielding Info | | Note |
|------|------------------|----------|-----------------|----------|-------------------------|-----------|------------|
| | From | I/O Port | To | I/O Port | Length (m) | Shielding | |
| USB | USB | EUT | USB | Laptop | USB | 2 | Unshielded |
| | | | | | | | |

7.3 Test Software Description

| Test Item | Software | Description |
|------------|----------|--|
| RF Testing | Putty | Set the EUT to transmit continuously in diferent test mode |
| | | |
| | | |

8 Test Summary

| Test Item | Test standard | | Test Method/Procedure | | Pass / Fail |
|------------------------------|---------------|-----------|-----------------------|--|--|
| Restricted Band of Operation | FCC | 15.205 | FCC | ANSI C63.10:2013 558074 D01 DTS Meas Guidance v04 | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A |
| AC Conducted Emissions | FCC | 15.207(a) | FCC | ANSI C63.10:2013 | <input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A |

DTS Band Requirement

| Test Item | Test standard | | Test Method/Procedure | | Pass / Fail |
|---|--|--------------|-----------------------|--|--|
| 6dB Bandwidth | FCC | 15.247(a)(2) | FCC | 558074 D01 DTS Meas Guidance v04 | <input checked="" type="checkbox"/> Pass* <input type="checkbox"/> N/A |
| Band Edge and Radiated Spurious Emissions | FCC | 15.247(d) | FCC | ANSI C63.10:2013 558074 D01 DTS Meas Guidance v04 | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> N/A |
| Output Power | FCC | 15.247(b) | FCC | 558074 D01 DTS Meas Guidance v04 | <input checked="" type="checkbox"/> Pass* <input type="checkbox"/> N/A |
| Antenna Gain > 6 dBi | FCC | 15.247(e) | FCC | - | <input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A |
| Power Spectral Density | FCC | 15.247(e) | FCC | 558074 D01 DTS Meas Guidance v04 | <input checked="" type="checkbox"/> Pass * <input type="checkbox"/> N/A |
| RF Exposure requirement | FCC | 15.247(i) | FCC | - | <input type="checkbox"/> Pass <input checked="" type="checkbox"/> N/A |
| Remark | <ol style="list-style-type: none"> All measurement uncertainties do not take into consideration for all presented test results. The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual. Pass * : Please refer to test report no. FCC(WLAN 2G)_A163A-367_LG Innotek_RBHA-C213B. | | | | |

9 Measurement Uncertainty

9.1 Conducted Emissions

The test is to measure the conducted emissions to the mains port of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the LISN
- Uncertainty of cables
- Uncertainty due to the mismatches
- Etc, see the below table for details

| Source of Uncertainty | Value (dB) | Probability Distribution | Division | Sensitivity Coefficient | Expanded Uncertainty |
|-----------------------------------|------------|--------------------------|----------|-------------------------|----------------------|
| Receiver Reading | 0.12 | Rectangular | 1.732 | 1 | 0.069284 |
| Cable Insertion Loss | 0.21 | Normal | 2 | 1 | 0.105 |
| Filter Insertion Loss | 0.25 | Normal | 2 | 1 | 0.125 |
| LISN Insertion Loss | 0.40 | Normal | 2 | 1 | 0.20 |
| Receiver CW accuracy | 0.5 | Rectangular | 1.732 | 1 | 0.2886836 |
| Pulse Amplitude Response | 1.5 | Rectangular | 1.732 | 1 | 0.86605081 |
| PRF Response | 1.5 | Rectangular | 1.732 | 1 | 0.86605081 |
| Mismatch LISN - Receiver | 0.25 | U-Shape | 1.414 | 1 | 0.1768033 |
| LISN Impedance | 2.5 | Triangular | 2.449 | 1 | 1.0208248 |
| Combined Standard Uncertainty | | | | | 1.928133 |
| Expanded Uncertainty (K=2) | | | | | 3.856266 |

The total derived measurement uncertainty is +/- 3.86 dB.

9.2 Radiated Emissions (30MHz to 1GHz)

The test is to measure the radiated emissions of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the antenna
- Uncertainty of cables
- Uncertainty due to the mismatches
- NSA Calibration
- Etc., details see the below table

| Source of Uncertainty | Value (dB) | Probability Distribution | Division | Sensitivity Coefficient | Expanded Uncertainty |
|-----------------------------------|------------|--------------------------|----------|-------------------------|----------------------|
| Receiver Reading | 0.12 | Rectangular | 1.732 | 1 | 0.069284 |
| Cable Insertion Loss | 0.21 | Normal | 2 | 1 | 0.105 |
| Filter Insertion Loss | 0.25 | Normal | 2 | 1 | 0.125 |
| Antenna Factor | 0.65 | Normal | 2 | 1 | 0.325 |
| Receiver CW accuracy | 0.5 | Rectangular | 1.732 | 1 | 0.2886836 |
| Pulse Amplitude Response | 1.5 | Rectangular | 1.732 | 1 | 0.86605081 |
| PRF Response | 1.5 | Rectangular | 1.732 | 1 | 0.86605081 |
| Mismatch Filter - Receiver | 0.25 | U-Shape | 1.414 | 1 | 0.1768033 |
| NSA Calibration | 4.0 | U-Shape | 1.414 | 1 | 2.8288543 |
| Combined Standard Uncertainty | | | | | 3.0059131 |
| Expanded Uncertainty (K=2) | | | | | 6.0118262 |

The total derived measurement uncertainty is +/- 6.00 dB.

9.3 Radiated Emissions (1GHz to 40GHz)

The test is to measure the radiated emissions of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the antenna
- Uncertainty of cables
- Uncertainty due to the mismatches
- VSWR Calibration
- Etc., details see the below table

| Source of Uncertainty | Value (dB) | Probability Distribution | Division | Sensitivity Coefficient | Expanded Uncertainty |
|-----------------------------------|------------|--------------------------|----------|-------------------------|----------------------|
| Receiver Reading | 0.12 | Rectangular | 1.732 | 1 | 0.0692840 |
| Cable Insertion Loss | 0.21 | Normal | 2 | 1 | 0.1050000 |
| Filter Insertion Loss | 0.25 | Normal | 2 | 1 | 0.1250000 |
| Antenna Factor | 0.65 | Normal | 2 | 1 | 0.3250000 |
| Receiver CW accuracy | 0.5 | Rectangular | 1.732 | 1 | 0.2886836 |
| Pulse Amplitude Response | 1.5 | Rectangular | 1.732 | 1 | 0.8660508 |
| PRF Response | 1.5 | Rectangular | 1.732 | 1 | 0.8660508 |
| Mismatch Filter - Receiver | 0.25 | U-Shape | 1.414 | 1 | 0.1768033 |
| VSWR Calibration | 2.0 | U-Shape | 1.414 | 1 | 1.4144272 |
| Combined Standard Uncertainty | | | | | 4.2363 |
| Expanded Uncertainty (K=2) | | | | | 8.4726 |

The total derived measurement uncertainty is +/- 8.47 dB.

9.4 RF conducted measurement

The test is to measure the RF output power from the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the Reference Level Uncertainty
- Uncertainty of variable attenuators
- Uncertainty of cables
- Uncertainty due to the mismatches


| Source of Uncertainty | Value (dB) | Probability Distribution | Division | Sensitivity Coefficient | Expanded Uncertainty |
|-----------------------------------|------------|--------------------------|----------|-------------------------|----------------------|
| Reference Level | 0.12 | Rectangular | 1.732 | 1 | 0.069284 |
| Cable Insertion Loss | 0.21 | Normal | 2 | 1 | 0.105 |
| Attenuator | 0.25 | Normal | 2 | 1 | 0.125 |
| Mismatch | 0.25 | U-Shape | 1.414 | 1 | 0.1768033 |
| Combined Standard Uncertainty | | | | | 0.476087 |
| Expanded Uncertainty (K=2) | | | | | 0.952174 |

The total derived measurement uncertainty is +/- 0.95 dB.

10 Measurements, Examination and Derived Results

10.1 Radiated Spurious Emissions below 1GHz

Requirement(s):

| Spec | Item | Requirement | Applicable | | | | | | | | | | |
|-----------------------|--|--|-----------------------|-----------------------|---------|-----|----------|-----|---------|-----|-----------|-----|---|
| 47CFR§15.247(d) | a) | <p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (uV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table> | Frequency range (MHz) | Field Strength (uV/m) | 30 – 88 | 100 | 88 – 216 | 150 | 216 960 | 200 | Above 960 | 500 | ☒ |
| Frequency range (MHz) | Field Strength (uV/m) | | | | | | | | | | | | |
| 30 – 88 | 100 | | | | | | | | | | | | |
| 88 – 216 | 150 | | | | | | | | | | | | |
| 216 960 | 200 | | | | | | | | | | | | |
| Above 960 | 500 | | | | | | | | | | | | |
| Test Setup |  | | | | | | | | | | | | |
| Procedure | <ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. A Quasi-peak measurement was then made for that frequency point. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. | | | | | | | | | | | | |
| Remark | The EUT was scanned up to 1GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case. | | | | | | | | | | | | |
| Result | ☒ Pass ☐ Fail | | | | | | | | | | | | |


Test Data ☒ Yes (See below) ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test was done by Rachana Khanduri at 10m chamber.

Radiated Emission Test Results (Below 1GHz)

| | | | | | |
|---------------------------|---------------------|------|--|--------|------|
| Test specification | below 1GHz | | | Result | Pass |
| Environmental Conditions: | Temp (°C): | 26.1 | | | |
| | Humidity (%) | 47.5 | | | |
| | Atmospheric (mbar): | 1020 | | | |
| Mains Power: | 120VAC, 60Hz | | | | |
| Tested by: | Rachana Khanduri | | | | |
| Test Date: | 06/22/2017 | | | | |
| Remarks: | 802.11n HT20-2437 | | | | |




| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|--------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 89.99 | 47.04 | 11.59 | -27.99 | 30.64 | Quasi Max | V | 126 | 157 | 43.50 | -12.87 | Pass |
| 30.00 | 25.14 | 10.99 | -13.82 | 22.31 | Quasi Max | V | 292 | 267 | 40.00 | -17.69 | Pass |
| 395.07 | 34.25 | 13.22 | -20.76 | 26.72 | Quasi Max | H | 103 | 266 | 46.00 | -19.28 | Pass |
| 99.97 | 43.79 | 11.65 | -26.14 | 29.30 | Quasi Max | V | 98 | 148 | 43.50 | -14.20 | Pass |
| 170.00 | 37.44 | 12.11 | -24.76 | 24.78 | Quasi Max | V | 105 | 72 | 43.50 | -18.72 | Pass |
| 39.95 | 31.00 | 11.16 | -21.86 | 20.30 | Quasi Max | V | 108 | 146 | 40.00 | -19.70 | Pass |

Note: Both horizontal and vertical polarities were investigated. The results above show only the worst case.

10.2 Radiated Spurious Emissions between 1GHz – 25GHz

Requirement(s):

| Spec | Item | Requirement | Applicable |
|-----------------|--|---|-------------------------------------|
| 47CFR§15.247(d) | a) | For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required <input type="checkbox"/> 20 dB down <input checked="" type="checkbox"/> 30 dB down | <input checked="" type="checkbox"/> |
| | b) | or restricted band, emission must also comply with the radiated emission limits specified in 15.209 | <input checked="" type="checkbox"/> |
| Test Setup |  | | |
| Procedure | <ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. An average measurement was then made for that frequency point. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured. | | |
| Remark | Both horizontal and vertical polarities were investigated. The results show only the worst case. | | |
| Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail | | |

Test Data Yes (See below) N/A

Test Plot Yes (See below) N/A

Test was done by Rachana Khanduri at 10m chamber.

Radiated Emission Test Results (Above 1GHz)

Above 1GHz-25GHz – 802.11b – 2412MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 17428.21 | 36.29 | 0.98 | 7.70 | 44.98 | Peak Max | V | 127 | 50 | 74 | -29.03 | Pass |
| 7238.87 | 34.64 | 4.11 | 0.02 | 38.78 | Peak Max | H | 150 | 205 | 74 | -35.22 | Pass |
| 4021.12 | 33.63 | 5.33 | -5.8 | 33.16 | Peak Max | V | 109 | 233 | 74 | -40.84 | Pass |
| 17428.21 | 23.78 | 0.98 | 7.70 | 32.47 | Average Max | V | 127 | 50 | 54 | -21.53 | Pass |
| 7238.87 | 23.33 | 4.11 | 0.02 | 27.47 | Average Max | H | 150 | 205 | 54 | -26.53 | Pass |
| 4021.12 | 21.80 | 5.33 | -5.80 | 21.33 | Average Max | V | 109 | 233 | 54 | -32.67 | Pass |

Above 1GHz-25GHz- 802.11b - 2437MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 17938.24 | 36.72 | 0.86 | 8.42 | 46.00 | Peak Max | V | 121 | 65 | 74 | -28.00 | Pass |
| 7351.67 | 33.48 | 4.06 | -0.14 | 37.40 | Peak Max | H | 113 | 210 | 74 | -36.60 | Pass |
| 4826.57 | 34.76 | 5.32 | -5.00 | 35.08 | Peak Max | V | 110 | 165 | 74 | -38.92 | Pass |
| 17938.24 | 24.56 | 0.86 | 8.42 | 33.84 | Average Max | V | 121 | 65 | 54 | -20.16 | Pass |
| 7351.67 | 22.54 | 4.06 | -0.14 | 26.46 | Average Max | H | 113 | 210 | 54 | -27.54 | Pass |
| 4826.57 | 22.45 | 5.32 | -5.00 | 22.77 | Average Max | V | 110 | 165 | 54 | -31.23 | Pass |

Above 1GHz-25GHz – 802.11b – 2462MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 16688.25 | 36.80 | 1.17 | 6.09 | 44.07 | Peak Max | V | 173 | 222 | 74 | -29.94 | Pass |
| 7387.39 | 34.76 | 4.05 | -0.25 | 38.56 | Peak Max | H | 105 | 231 | 74 | -35.44 | Pass |
| 4802.53 | 34.02 | 5.29 | -4.97 | 34.35 | Peak Max | V | 190 | 194 | 74 | -39.65 | Pass |
| 16688.25 | 24.59 | 1.17 | 6.09 | 31.85 | Average Max | V | 173 | 222 | 54 | -22.15 | Pass |
| 7387.39 | 23.88 | 4.05 | -0.25 | 27.68 | Average Max | H | 105 | 231 | 54 | -26.32 | Pass |
| 4802.53 | 21.60 | 5.29 | -4.97 | 21.93 | Average Max | V | 190 | 194 | 54 | -32.07 | Pass |

Above 1GHz-25GHz- 802.11g - 2412MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 16878.96 | 36.74 | 1.09 | 5.82 | 43.65 | Peak Max | V | 156 | 264 | 74 | -30.35 | Pass |
| 7239.80 | 33.28 | 4.11 | 0.02 | 37.42 | Peak Max | H | 388 | 215 | 74 | -36.59 | Pass |
| 4826.21 | 33.90 | 5.32 | -5.01 | 34.21 | Peak Max | V | 171 | 332 | 74 | -39.79 | Pass |
| 16878.96 | 24.58 | 1.09 | 5.82 | 31.49 | Average Max | V | 156 | 264 | 54 | -22.51 | Pass |
| 7239.80 | 21.41 | 4.11 | 0.02 | 25.55 | Average Max | H | 388 | 215 | 54 | -28.45 | Pass |
| 4826.21 | 21.71 | 5.32 | -5.01 | 22.02 | Average Max | V | 171 | 332 | 54 | -31.98 | Pass |

Above 1GHz-25GHz - 802.11g - 2437MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|--------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 17951.92 | 35.13 | 0.86 | 8.34 | 44.32 | Peak Max | H | 265 | 272 | 74 | -29.68 | Pass |
| 7306.52 | 34.99 | 4.09 | 0.08 | 39.16 | Peak Max | H | 139 | 304 | 74 | -34.84 | Pass |
| 1345.26 | 36.07 | 7.45 | -14.89 | 28.64 | Peak Max | V | 389 | 115 | 74 | -45.37 | Pass |
| 17951.92 | 23.45 | 0.86 | 8.34 | 32.64 | Average Max | H | 265 | 272 | 54 | -21.36 | Pass |
| 7306.52 | 22.14 | 4.09 | 0.08 | 26.31 | Average Max | H | 139 | 304 | 54 | -27.69 | Pass |
| 1345.26 | 23.69 | 7.45 | -14.89 | 16.25 | Average Max | V | 389 | 115 | 54 | -37.75 | Pass |

Above 1GHz-25GHz- 802.11g - 2462MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 16572.54 | 36.94 | 1.22 | 6.42 | 44.58 | Peak Max | V | 120 | 356 | 74 | -29.42 | Pass |
| 7392.83 | 34.87 | 4.05 | -0.27 | 38.64 | Peak Max | H | 150 | 218 | 74 | -35.36 | Pass |
| 4199.41 | 34.23 | 5.17 | -5.83 | 33.58 | Peak Max | V | 180 | 149 | 74 | -40.42 | Pass |
| 16572.54 | 24.52 | 1.22 | 6.42 | 32.17 | Average Max | V | 120 | 356 | 54 | -21.83 | Pass |
| 7392.83 | 22.01 | 4.05 | -0.27 | 25.79 | Average Max | H | 150 | 218 | 54 | -28.21 | Pass |
| 4199.41 | 21.75 | 5.17 | -5.83 | 21.10 | Average Max | V | 180 | 149 | 54 | -32.90 | Pass |

Above 1GHz-25GHz- 802.11n20 - 2412MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 17405.77 | 35.70 | 0.99 | 7.88 | 44.56 | Peak Max | V | 197 | 238 | 74 | -29.44 | Pass |
| 7231.53 | 33.27 | 4.12 | 0.01 | 37.40 | Peak Max | H | 344 | 191 | 74 | -36.60 | Pass |
| 4851.50 | 33.80 | 5.35 | -5.05 | 34.10 | Peak Max | V | 226 | 185 | 74 | -39.90 | Pass |
| 17405.77 | 23.63 | 0.99 | 7.88 | 32.49 | Average Max | V | 197 | 238 | 54 | -21.51 | Pass |
| 7231.53 | 21.56 | 4.12 | 0.01 | 25.69 | Average Max | H | 344 | 191 | 54 | -28.32 | Pass |
| 4851.50 | 21.72 | 5.35 | -5.05 | 22.02 | Average Max | V | 226 | 185 | 54 | -31.99 | Pass |


Above 1GHz-25GHz – 802.11n20 – 2437MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 17988.16 | 35.39 | 0.85 | 8.14 | 44.38 | Peak Max | H | 335 | 136 | 74 | -29.62 | Pass |
| 16530.03 | 36.71 | 1.24 | 6.10 | 44.05 | Peak Max | H | 200 | 317 | 74 | -29.95 | Pass |
| 7315.20 | 35.82 | 4.08 | 0.05 | 39.95 | Peak Max | H | 139 | 328 | 74 | -34.05 | Pass |
| 17988.16 | 23.74 | 0.85 | 8.14 | 32.73 | Average Max | H | 335 | 136 | 54 | -21.27 | Pass |
| 16530.03 | 24.31 | 1.24 | 6.10 | 31.65 | Average Max | H | 200 | 317 | 54 | -22.35 | Pass |
| 7315.20 | 22.00 | 4.08 | 0.05 | 26.13 | Average Max | H | 139 | 328 | 54 | -27.87 | Pass |


Above 1GHz-25GHz- 802.11n20 - 2462MHz

| Frequency MHz | Raw dBuV | Cable Loss | AF dB | Level dBuV/m | Measurement Type | Pol | Hgt cm | Azt Deg | Limit dBuV/m | Margin dB | Pass /Fail |
|---------------|----------|------------|-------|--------------|------------------|-----|--------|---------|--------------|-----------|------------|
| 16661.13 | 36.89 | 1.18 | 6.26 | 44.33 | Peak Max | V | 339 | 4 | 74 | -29.67 | Pass |
| 7381.45 | 36.11 | 4.05 | -0.23 | 39.93 | Peak Max | H | 136 | 220 | 74 | -34.07 | Pass |
| 4853.45 | 33.62 | 5.35 | -5.06 | 33.91 | Peak Max | V | 338 | 258 | 74 | -40.09 | Pass |
| 16661.13 | 24.72 | 1.18 | 6.26 | 32.16 | Average Max | V | 339 | 4 | 54 | -21.84 | Pass |
| 7381.45 | 22.27 | 4.05 | -0.23 | 26.10 | Average Max | H | 136 | 220 | 54 | -27.90 | Pass |
| 4853.45 | 21.75 | 5.35 | -5.06 | 22.05 | Average Max | V | 338 | 258 | 54 | -31.95 | Pass |


Restricted Band Measurement Plots:




802.11b-2412MHz




802.11b-2462MHz




802.11g-2412MHz



802.11g-2462MHz



802.11n-HT20-2412MHz


























802.11n-HT20-2462MHz

Annex A. TEST INSTRUMENT

| Instrument | Model | Serial # | Cal Date | Cal Cycle | Cal Due | In use |
|--|----------|------------|------------|-----------|------------|-------------------------------------|
| Radiated Emissions | | | | | | |
| Keysight EXA 44GHz Spectrum Analyzer | N9010A | MY51440112 | 08/02/2016 | 1 Year | 08/02/2017 | <input checked="" type="checkbox"/> |
| R & S Wideband Communication Tester | CMW500 | 108852 | 07/28/2016 | 1 Year | 07/28/2017 | <input type="checkbox"/> |
| R & S Universal Radio Communication Tester | CMU200 | 111078 | N/A | N/A | N/A | <input type="checkbox"/> |
| Bi-Log antenna (30MHz-2GHz) | JB1 | A030702 | 01/13/2017 | 1 Year | 01/13/2018 | <input checked="" type="checkbox"/> |
| Horn Antenna (1GHz-26GHz) | 3115 | 100059 | 08/11/2016 | 1 Year | 08/11/2017 | <input checked="" type="checkbox"/> |
| Pre-Amplifier (1-40GHz) | SAS-474 | 579 | 04/04/2017 | 1 Year | 05/04/2018 | <input checked="" type="checkbox"/> |
| Preamplifier (100KHz-7GHz) | LPA-6-30 | 11140711 | 02/09/2017 | 1 Year | 02/09/2018 | <input checked="" type="checkbox"/> |
| 3 Meters SAC | 3M | N/A | 06/09/2016 | 1 Year | 09/09/2017 | <input type="checkbox"/> |
| 10 Meters SAC | 10M | N/A | 07/06/2016 | 1 Year | 07/06/2017 | <input checked="" type="checkbox"/> |
| RF Conducted Measurement | | | | | | |
| Spectrum Analyzer | N9010A | 10SL0219 | 11/16/2016 | 1 Year | 11/16/2017 | <input checked="" type="checkbox"/> |

Annex B. SIEMIC Accreditation

| Accreditations | Document | Scope / Remark |
|---|---|---|
| ISO 17025 (A2LA) |  | Please see the documents for the detailed scope |
| ISO Guide 65 (A2LA) |  | Please see the documents for the detailed scope |
| TCB Designation | | A1, A2, A3, A4, B1, B2, B3, B4, C |
| FCC DoC Accreditation |  | FCC Declaration of Conformity Accreditation |
| FCC Site Registration |  | 3 meter site |
| FCC Site Registration |  | 10 meter site |
| IC Site Registration |  | 3 meter site |
| IC Site Registration |  | 10 meter site |
| EU NB |  | Radio & Telecommunications Terminal Equipment: EN45001 – EN ISO/IEC 17025 |
| |  | Electromagnetic Compatibility: EN45001 – EN ISO/IEC 17025 |
| Singapore iDA CB(Certification Body) |   | Phase I, Phase II |
| Vietnam MIC CAB Accreditation |  | Please see the document for the detailed scope |
| Hong Kong OFCA |  | (Phase II) OFCA Foreign Certification Body for Radio and Telecom |
| |  | (Phase I) Conformity Assessment Body for Radio and Telecom |
| Industry Canada CAB |  | Radio: Scope A – All Radio Standard Specification in Category I |
| |  | Telecom: CS-03 Part I, II, V, VI, VII, VIII |

| | | |
|---|---|--|
| Japan Recognized Certification Body Designation |  | <p>Radio: A1. Terminal equipment for purpose of calling</p> <p>Telecom: B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law</p> |
| Korea CAB Accreditation |  | <p>EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI</p> <p>EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS</p> |
| | | <p>Radio: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10, RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80, RRL Notice 2004-68</p> <p>Telecom: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4</p> |
| Taiwan NCC CAB Recognition |  | LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS14336, PLMN07, PLMN01, PLMN08 |
| Taiwan BSMI CAB Recognition |  | CNS 13438 |
| Japan VCCI |  | <p>R-3083: Radiation 3 meter site</p> <p>C-3421: Main Ports Conducted Interference Measurement</p> <p>T-1597: Telecommunication Ports Conducted Interference Measurement</p> |
| Australia CAB Recognition |  | <p>EMC: AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3, AS/NZS 61000.6.4</p> |
| | | <p>Radio communications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771</p> |
| | | <p>Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1</p> |
| Australia NATA Recognition |  | AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2 |