



TEST REPORT

APPLICANT : Petasense Inc

PRODUCT NAME : Industrial asset reliability IOT sensor

MODEL NAME : Vibration Mote Model 3

BRAND NAME : Petasense

FCC ID : 2AJW7-00002

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2020-03-16

TEST DATE : 2020-04-04 to 2020-04-13

ISSUE DATE : 2020-04-15

Edited by: Peng Mi
Peng Mi (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

1. Technical Information	4
1.1. Applicant and Manufacturer Information	4
1.2. Equipment Under Test (EUT) Description	4
1.3. The Channel Number and Frequency	5
1.4. Test Standards and Results	6
1.5. Environmental Conditions	7
2. 47 CFR Part 15C Requirements	8
2.1. Antenna requirement	8
2.2. Duty Cycle Of Test Signal	9
2.3. Maximum Peak Conducted Output Power	10
2.4. Maximum Average Conducted Output Power	19
2.5. 6dB Bandwidth	21
2.6. Conducted Spurious Emissions and Band Edge	26
2.7. Power spectral density (PSD)	33
2.8. Conducted Emission	38
2.9. Restricted Frequency Bands	40
2.10. Radiated Emission	53
Annex A Test Uncertainty	69
Annex B Testing Laboratory Information	70



REPORT No.: SZ19110224W01

Change History		
Version	Date	Reason for change
1.0	2020-04-15	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Petasense Inc
Applicant Address:	2 North 1st St, 5th Floor, San Jose, California, United States
Manufacturer:	RocketEMS
Manufacturer Address:	2950 Patrick Henry Dr, Santa Clara CA 95054

1.2. Equipment Under Test (EUT) Description

Product Name:	Industrial asset reliability IOT sensor	
Serial No:	(N/A, marked #1 by test site)	
Hardware Version:	1.0	
Software Version:	1.0	
Equipment Type:	Bluetooth LE	
Modulation Type:	GFSK	
Bluetooth Version:	5.0	
Data Rate:	1Mbps, 2Mbps, 125Kbps, 500Kbps	
Operating Frequency Range:	2402MHz - 2480MHz	
Antenna Type:	PCB Antenna	
Antenna Gain:	2.0dBi	
Accessory Information:	Battery	
	Brand Name:	Duracell
	Model No.:	CR17345
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	1470mAh
	Rated Voltage:	3.00V

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.3.The Channel Number and Frequency

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note: The Lowest Channel 0, Middle 19 and Highest 39 were selected for test in the report.



1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle Of Test Signal	Apr 07, 2020	Ouyang Feng	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Apr 07, 2020	Ouyang Feng	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Apr 07, 2020	Ouyang Feng	PASS	No deviation
5	15.247(a)	Bandwidth	Apr 07, 2020	Ouyang Feng	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Apr 07, 2020	Ouyang Feng	PASS	No deviation
7	15.247(e)	Power spectral density (PSD)	Apr 07, 2020	Ouyang Feng	PASS	No deviation
8	15.207	Conducted Emission	N/A	N/A	N/A _{Note1}	N/A
9	15.247(d)	Restricted Frequency Bands	Apr 09, 2020	Peng Xuwei	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Apr 13, 2020	Peng Xuwei	PASS	No deviation

Note 1: Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.



Note 2: The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013 and KDB558074 D01 v05r02.

Note 3: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The Ref offset 2.0dB means the cable loss is 2.0dB.

Note 4: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2.47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Duty Cycle Of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

A. Test Set:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

2.2.3. Test Result

Test Mode	Data Rate	Duty Cycle (%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
GFSK	1Mbps	62.50	2.04
	2Mbps	32.91	4.83
	125Kbps	82.45	0.84
	500Kbps	57.22	2.42

2.3. Maximum Peak Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.3.3. Test procedure

The measured output power was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for Peak Output Power test on the spectrum analyzer:

- a) Set analyzer center frequency to channel center frequency.
- b) Set the RBW to 1MHz
- c) Set VBW to 3MHz
- d) Set span to 3MHz
- e) Sweep time to auto couple.
- f) Detector = peak.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use peak marker function to determine the peak amplitude level.




2.3.4. Test Result


The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

1Mbps

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-4.43	0.0004	30	1	PASS
19	2440	-4.02	0.0004			PASS
39	2480	-3.66	0.0004			PASS



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)



2Mbps

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-4.40	0.0004	30	1	PASS
19	2440	-3.98	0.0004			PASS
39	2480	-3.61	0.0004			PASS



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)



125Kbps


Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-4.46	0.0004	30	1	PASS
19	2440	-4.03	0.0004			PASS
39	2480	-3.54	0.0004			PASS



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)




(Channel 39, 2480MHz)




500Kbps


Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-4.34	0.0004	30	1	PASS
19	2440	-3.92	0.0004			PASS
39	2480	-3.57	0.0004			PASS



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)

2.4. Maximum Average Conducted Output Power


2.4.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

2.4.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.4.3. Test procedure

KDB 558074 Section 8.3.2 was used in order to prove compliance.



2.4.4. Test Result

1Mbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
0	2402	-7.03	2.04	-4.99	0.0003	30	1	PASS
19	2440	-6.60		-4.56	0.0003			PASS
39	2480	-6.18		-4.14	0.0004			PASS

2Mbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
0	2402	-9.45	4.83	-4.62	0.0003	30	1	PASS
19	2440	-9.01		-4.18	0.0004			PASS
39	2480	-8.63		-3.80	0.0004			PASS

125Kbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
0	2402	-5.89	0.84	-5.05	0.0003	30	1	PASS
19	2440	-5.33		-4.49	0.0004			PASS
39	2480	-4.88		-4.04	0.0004			PASS

500Kbps

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty factor Calculated				
		dBm		dBm	W	dBm	W	
0	2402	-7.05	2.42	-4.63	0.0003	30	1	PASS
19	2440	-6.95		-4.53	0.0004			PASS
39	2480	-6.64		-4.22	0.0004			PASS


2.5.6dB Bandwidth

2.5.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test procedure

The steps for the first option are as follows:

1. Set analyzer center frequency to channel center frequency.
 - a) Set RBW = 100 kHz.
 - b) Set the VBW=300 kHz.
 - c) Detector = peak.
 - d) Trace mode = max hold.
 - e) Sweep = auto couple
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



2. The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., $RBW = 100$ kHz, $VBW \geq 3 \times RBW$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

2.5.4. Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the module.

Below is the worst case situation(2Mbps,125Kbps) test data:

2Mbps

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	1.144	≥ 500	PASS
19	2440	1.142	≥ 500	PASS
39	2480	1.146	≥ 500	PASS

Test Plots



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)

**125Kbps**

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
0	2402	0.612	≥500	PASS
19	2440	0.611	≥500	PASS
39	2480	0.608	≥500	PASS

Test Plots

(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)


2.6. Conducted Spurious Emissions and Band Edge

2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.6.3. Test procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.



2.6.4. Test Result


The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.

Below is the worst case situation(2Mbps,125Kbps) test data:


2Mbps

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-55.03	-8.02	-28.02	PASS
19	2440	-54.15	-4.35	-24.35	PASS
39	2480	-54.10	-6.94	-26.94	PASS


Test Plots




(Channel = 0, 30MHz to 25GHz)




(Band Edge, Channel = 0)



(Channel = 19, 30MHz to 25GHz)



(Channel = 39, 30MHz to 25GHz)




(Band Edge, Channel = 39)




125Kbps

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-53.30	6.39	-13.61	PASS
19	2440	-53.94	-6.21	-26.21	PASS
39	2480	-54.26	-5.10	-25.10	PASS


Test Plots



(Channel = 0, 30MHz to 25GHz)



(Band Edge, Channel = 0)



(Channel = 19, 30MHz to 25GHz)



(Channel = 39, 30MHz to 25GHz)



(Band Edge, Channel = 39)


2.7. Power spectral density (PSD)

2.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.7.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.7.3. Test procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency.
- b) Set the span to 1.5 times DTS
- c) Set the RBW to 3 kHz
- d) Set the VBW to 10 kHz
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.



2.7.4. Test Result

The lowest, middle and highest channels are tested.

Below is the worst case situation(2Mbps,125Kbps) test data:

2Mbps

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-22.15	8	PASS
19	2440	-21.67	8	PASS
39	2480	-21.48	8	PASS


Test Plots



(Channel = 0, 2402MHz)



(Channel = 19, 2440MHz)



(Channel = 39, 2480MHz)



125Kbps

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	19.60	8	PASS
19	2440	-19.33	8	PASS
39	2480	-18.85	8	PASS


Test Plots



(Channel = 0, 2402MHz)



(Channel = 19, 2440MHz)



(Channel = 39, 2480MHz)

2.8. Conducted Emission

2.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency (MHz)	range	Conducted Limit (dB μ V)	
		Quai-peak	Average
0.15 - 0.50		66 to 56	56 to 46
0.50 - 5		56	46
5 - 30		60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.8.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



REPORT No.: SZ19110224W01

2.8.3. Test Result

Note: This test case does not apply this kind of EUT.


2.9. Restricted Frequency Bands

2.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.9.2. Test Description

Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.9.3. Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

1Mbps


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
0	2371.68	PK	46.57	-29.67	32.56	49.46	74	PASS
0	2355.04	AV	43.60	-29.67	32.56	46.49	54	PASS
39	2486.25	PK	47.37	-29.67	32.56	50.26	74	PASS
39	2485.32	AV	44.37	-29.67	32.56	47.26	54	PASS




Test Plots




(PEAK, Channel = 0)



(AVG, Channel = 0)



(PEAK, Channel = 39)




(AVG, Channel = 39)




2Mbps

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
0	2386.94	PK	46.23	-29.67	32.56	49.12	74	PASS
0	2385.59	AV	43.93	-29.67	32.56	46.82	54	PASS
39	2484.20	PK	46.71	-29.67	32.56	49.60	74	PASS
39	2484.07	AV	45.26	-29.67	32.56	48.15	54	PASS


Test Plots




(PEAK, Channel = 0)



(AVG, Channel = 0)



(PEAK, Channel = 39)




(AVG, Channel = 39)




125Kbps

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
0	2381.86	PK	47.12	-29.67	32.56	50.01	74	PASS
0	2385.39	AV	44.79	-29.67	32.56	47.68	54	PASS
39	2484.27	PK	46.39	-29.67	32.56	49.28	74	PASS
39	2484.09	AV	45.35	-29.67	32.56	48.24	54	PASS


Test Plots




(PEAK, Channel = 0)



(AVG, Channel = 0)



(PEAK, Channel = 39)




(AVG, Channel = 39)




500Kbps

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
0	2385.15	PK	47.15	-29.67	32.56	50.04	74	PASS
0	2387.39	AV	45.17	-29.67	32.56	48.06	54	PASS
39	2483.50	PK	47.70	-29.67	32.56	50.59	74	PASS
39	2486.14	AV	45.59	-29.67	32.56	48.48	54	PASS


Test Plots




(PEAK, Channel = 0)



(AVG, Channel = 0)



(PEAK, Channel = 39)



(AVG, Channel = 39)

2.10. Radiated Emission

2.10.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:


1. For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
2. For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.10.2. Test Description

Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10:2013. For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10:2013.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

- In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant



emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

2.10.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note2: For the frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.




1Mbps

Plots for Channel = 0



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
44.568	27.61	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
192.678	28.83	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1329.732	42.55	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5744.972	47.73	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
9212.002	47.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12729.442	47.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	32.35	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
503.467	27.83	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2317.007	43.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4733.988	45.06	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8517.476	46.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
13127.114	46.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 19



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	28.27	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
220.601	27.72	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1992.397	44.89	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4442.735	45.37	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5856.992	46.11	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10082.961	46.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	32.51	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
318.936	25.89	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2483.473	44.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5288.489	45.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8492.271	46.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12194.544	47.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 39



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	27.88	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
191.464	28.84	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2494.358	44.44	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5403.310	46.70	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7884.561	46.99	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10357.410	47.63	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	32.96	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
456.120	28.37	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2484.114	43.86	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4560.356	46.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8612.693	46.39	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12172.140	46.77	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




2Mbps

Plots for Channel = 0



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	26.76	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
192.678	28.93	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2147.979	43.39	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4711.584	45.66	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
7918.167	45.42	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12695.836	46.76	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	29.80	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	24.95	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2902.455	44.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5702.964	46.40	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8604.292	46.90	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12606.219	47.10	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 19



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
100.413	35.48	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
249.737	27.95	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1933.493	44.02	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4624.768	45.41	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8632.297	46.72	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12054.519	46.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	34.16	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
253.379	27.18	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2896.854	43.94	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5630.151	46.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8825.532	47.12	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12146.936	46.09	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 39



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	28.16	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
191.464	29.04	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2034.654	43.74	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4490.344	46.03	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8021.786	47.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12525.005	48.32	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	28.53	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
552.028	29.67	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2501.401	43.54	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5632.951	45.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8609.893	46.79	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12634.224	46.91	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




125Kbps

Plots for Channel = 0



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
191.464	28.96	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
503.467	32.65	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1330.372	46.62	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
1998.800	48.13	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5338.898	46.90	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12149.736	48.57	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
43.354	28.16	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
119.837	24.79	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1349.580	45.37	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
2933.261	45.20	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5694.563	47.13	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8951.555	46.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 19



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
192.678	27.46	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
527.747	32.10	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1998.800	45.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
3392.544	45.86	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5280.087	46.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
11007.129	46.52	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
97.985	24.76	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
191.464	25.46	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1796.479	43.36	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4546.354	45.76	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
7906.965	46.80	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12160.938	47.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 39



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
191.464	28.96	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
527.747	29.45	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2103.802	44.22	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4781.597	45.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
10337.807	47.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
16818.185	47.76	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
40.926	29.37	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	25.56	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2484.114	44.16	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5655.356	46.50	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8441.862	47.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
14992.253	47.58	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




500Kbps

Plots for Channel = 0



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
42.140	28.25	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
192.678	26.76	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2790.435	44.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4686.379	44.84	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8576.287	46.40	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12149.736	47.28	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	31.50	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
191.464	25.80	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2456.583	45.84	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4456.738	45.75	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8982.360	46.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12897.472	47.30	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel = 19



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
46.996	26.69	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
191.464	28.61	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
2518.687	44.52	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5764.575	46.58	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8481.069	47.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12522.204	47.47	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
53.066	29.03	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
518.035	29.41	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2413.045	45.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5324.895	46.45	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8996.363	46.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12536.207	47.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel = 39



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
57.922	27.92	N/A	N/A	N/A	40.00	N/A	Horizontal	PASS
527.747	32.46	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2818.440	45.07	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
5870.995	45.94	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8475.468	46.62	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12496.999	47.46	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
48.210	28.72	N/A	N/A	N/A	40.00	N/A	Vertical	PASS
192.678	25.45	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
2493.717	45.88	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
5747.772	46.68	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
8604.292	46.49	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12155.337	47.92	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2020.04.01	2021.03.31
RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial cable	CB02	RF02	Morlab	N/A	N/A
SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 List of Software Used

Description	Manufacturer	Software Version
Test system	Tonscend	V2.6
Power Panel	Agilent	V3.8
MORLAB EMCR V1.2	MORLAB	V1.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
Receiver	MY54130016	N9038A	Agilent	2019.07.29	2020.07.28
Test Antenna - Bi-Log	9163-520	VULB 9163	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna - Loop	1520-022	FMZB1520	Schwarzbeck	2019.02.14	2022.02.13
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna – Horn	BBHA9170 #774	BBHA9170	Schwarzbeck	2019.05.24	2022.05.23
Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2019.05.08	2020.05.09
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2019.12.01	2020.12.01
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

————— END OF REPORT —————