



America

Certification Exhibit

FCC ID: 2AJX7KP9000

FCC Rule Part: 47 CFR Part 2.1091

Project Number: 16-0273

Manufacturer: QSR Automations, Inc.
Model: KP-9000

RF Exposure

General Information:

Applicant: QSR Automations, Inc.
 Device Category: Mobile
 Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type: Printed Meandering Trace Antenna
 Antenna Gain: -7 dBi
 Maximum Transmitter Conducted Power: 3.27 dBm, 2.12 mW
 Maximum System EIRP: -3.73 dBm, 0.42 mW
 Exposure Conditions: 20 centimeters or greater

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

- S = power density (in appropriate units, e.g. mW/cm²)
- P = power input to the antenna (in appropriate units, e.g., mW)
- G = power gain of the antenna in the direction of interest relative to an isotropic radiator
- R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Table 1: MPE Calculation

Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm ²)
2440	3.27	1.00	2.12	-7	0.200	20	0.0001