

# Nomad Goods, Inc.

## MPE ASSESSMENT REPORT

**Report Type:**

FCC MPE assessment report

**Model:**

NM01215585

**REPORT NUMBER:**

230201522SHA-003

**ISSUE DATE:**

April 3, 2023

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-01\_V1 © 2018 Intertek



**Applicant:** Nomad Goods, Inc.  
**Address of Applicant:** 1187 Coast Village Rd. #638 Santa Barbara, CA 93108, United States

**Manufacturer:** Nomad Goods, Inc.  
**Address of Manufacturer:** 1187 Coast Village Rd. #638 Santa Barbara, CA 93108, United States

**Factory:** Zhongshan Zen Factory Ltd.  
**Address of Factory:** 6th.Industrial Area, Nanlang Town, Zhongshan City, Guangdong, China  
**FCC ID:** 2AJYRNM01215585

## SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

FCC PART 1 SECTION 1.1310

PREPARED BY:

REVIEWED BY:



---

Project Engineer  
Damon Ding

---

Reviewer  
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

### Revision History

| Report No.       | Version | Description             | Issued Date   |
|------------------|---------|-------------------------|---------------|
| 230201522SHA-003 | Rev. 01 | Initial issue of report | April 3, 2023 |
|                  |         |                         |               |
|                  |         |                         |               |

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

|                            |   |
|----------------------------|---|
| Product name:              | Base Station - Apple Watch Edition   Global   |
| Type/Model:                | NM01215585  |
| Description of EUT:        | The EUT is Base Station - Apple Watch Edition   Global                                |
| Rating:                    | Input:12V/3.3A  |
| Category of EUT:           | Class B   |
| EUT type:                  | <input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing |
| Operating Frequency range: | 127kHz  |
| Type of Modulation:        | ASK   |
| Antenna Type:              | Coil antenna  |
| Sample received date:      | January 30, 2023  |
| Date of test:              | February 10, 2023 to February 10, 2023  |

## 1.2 Description of Test Facility

|            |   |
|------------|---|
| Name:      | Intertek Testing Services Shanghai                                      |
| Address:   | Building 86, No. 1198 Qinzhou Road (North), Shanghai 200233, P.R. China |
| Telephone: | 86 21 61278200  |
| Telefax:   | 86 21 54262353  |

|   |   |
|---|---|
| The test facility is recognized, certified, or accredited by these organizations: | CNAS Accreditation Lab<br>Registration No. CNAS L0139                         |
|   | FCC Accredited Lab<br>Designation Number: CN0175                              |
|   | IC Registration Lab<br>CAB identifier.: CN0014                                |
|   | VCCI Registration Lab<br>Registration No.: R-14243, G-10845, C-14723, T-12252 |
|   | A2LA Accreditation Lab<br>Certificate Number: 3309.02                         |

All tests were sub-contracted.

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng Science and Technology Park, Longhua District, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

All tests were sub-contracted at Shenzhen UnionTrust Quality and Technology Co., Ltd, and conducted by Kieron Luo

Reviewed and approved by Wakeyou Wang from Intertek Testing Services Shanghai.

**The test facility is recognized, certified, or accredited by the following organizations:**

**CNAS-Lab Code: L9069**

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

**IC-Registration No.: 21600-1**

**TEST REPORT**

The 3m Semi-anechoic chamber of Shenzhen UnionTrust Quality and Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 21600-1.

**A2LA-Lab Certificate No.: 4312.01**

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

**FCC Accredited Lab.**

Designation Number: CN1194

Test Firm Registration Number: 259480

---

## 2 TEST SPECIFICATIONS

### 2.1 Standards or specification

FCC PART 1 SECTION 1.1310

KDB 680106 D01 RF Exposure Wireless Charging Apps v03r01

### 2.2 Mode of operation during the test

Within this test report, EUT was tested under all modes and tested under its rating voltage and frequency. Other voltage and frequency are specified if used. The test mode is as follows:

Test Mode 1: Wireless charging mode with phone (7.5W)

Test Mode 2: Wireless charging mode with phone (7.5W) + Wireless charging mode with phone (7.5W) + Wireless charging mode with watch (3W)

Test Mode 3: Wireless charging mode with phone (7.5W) + Wireless charging mode with watch (3W) + Wireless charging mode with Air Pods(5W)

Test Mode 4: Wireless charging mode with Air Pods (5W)

Test Mode 5: Wireless charging mode with Air Pods (5W) + Wireless charging mode with Air Pods (5W)

Test Mode 6: Wireless charging mode with Air Pods (5W) + Wireless charging mode with phone (7.5W)

Test Mode 7: Standby

### 2.3 Test peripherals list

| Item No. | Name          | Band and Model          | Description     |
|----------|---------------|-------------------------|-----------------|
| 1        | Mobile phone  | Apple, iphone12         | G0NZQLVGN746    |
| 2        | Adapter       | NOMAD, JZB302-1203300IX | G37895210J75R09 |
| 3        | Apple watches | Apple, WR-50M           | G99CCKJ7MLTK    |
| 4        | Air Pods      | Apple, air pods 3       | A9KJ65P7W569    |
| 5        | Mobile phone  | SAMSUNG, Galaxy S7      | R28HA1JC2WA     |

**TEST REPORT**

**2.4 Support Cable list**

| Item No | Description  | Length (m) | Cable Type               |
|---------|--------------|------------|--------------------------|
| 1       | Type-C Cable | 2.0        | Shielded without ferrite |

**2.5 Record of climatic conditions**

| Test Item   | Temperature (°C) | Relative Humidity (%) | Pressure (kPa) |
|-------------|------------------|-----------------------|----------------|
| RF Exposure | 26.5             | 56                    | 101.8          |

**2.6 Instrument list**

| Test Equipment List                 |                    |              |           |               |                         |                             |
|-------------------------------------|--------------------|--------------|-----------|---------------|-------------------------|-----------------------------|
| Used                                | Equipment          | Manufacturer | Model No. | Serial Number | Cal. date (mm dd, yyyy) | Cal. Due date (mm dd, yyyy) |
| <input checked="" type="checkbox"/> | Probe              | STT          | EHP-50F   | SZ186-04      | July 21, 2022           | July 20, 2023               |
| <input checked="" type="checkbox"/> | Probe holder       | STT          | TR-01     | N/A           | N/A                     | N/A                         |
| <input checked="" type="checkbox"/> | Optical fiber line | STT          | L=5M      | N/A           | N/A                     | N/A                         |

**2.7 Measurement uncertainty**

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| Measurement           | Expanded Uncertainty (k=2) |
|-----------------------|----------------------------|
| electromagnetic field | 5%                         |



### 3 MPE Assessment

Test result: Pass

#### 3.1 MPE Assessment Limit

According to 47 CFR §1.1310, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

##### Limits for Occupational / Controlled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6  |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f)*                                | 6  |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6  |
| 300-1500              | /                                 | /                                 | F/300                                   | 6  |
| 1500-100000           | /                                 | /                                 | 5                                       | 6  |

##### Limits for General Population/Uncontrolled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34              | 614                               | 1.63                              | *100                                    | 30   |
| 1.34-30               | 824/f                             | 2.19/f                            | *180/f <sup>2</sup>                     | 30   |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30   |
| 300-1,500             | /                                 | /                                 | f/1500                                  | 30   |
| 1,500-100,000         | /                                 | /                                 | 1.0                                     | 30   |

**Note:** f = frequency in MHz: \* = Plane-wave equivalent power density.

#### 3.2 Testing Procedure


Enabled the EUT to transmit and receive data continue

- a. The field strength of both E-field and H-field was measured at 15 cm surrounding the device and 20 cm above the top surface using the equipment list above for determining compliance with the MPE requirements of FCC Part 1.1310.
- b. The RF power density was measured with the battery at 3 different charge conditions: battery at less than 1 % , battery at 50% charger, battery at 99% charger,.
- c. Maximum E-field and H-field measurements were made 15cm from each side of the EUT. Along the side of the EUT and still 15cm away from the edge of the EU T, the field probes were positioned at the location where there is maximum field strength. The maximum E-field and H-field is reported below.
- d. This device uses a wireless charging circuit for power transfer operating at the frequency of X

**TEST REPORT**

kHz. Thus, the 300 kHz limits were used: E-field Limit = 614 (V/m); H-field limit = 1.63 (A/m).

**3.3 Test setup**



**Note**

The RF exposure test is performed in the shield room

The test distance is between the edge of the charger and the geometric center of probe

The aggregate at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated.

**TEST REPORT**

**3.4 TEST DATA**

**Worst case Test Mode 2**

Test result of E-Field Strength

| Test Position | Test distance (cm) | Test result (V/m)  |                     |                     | Limit (V/m) | Result (Pass/Fail) |
|---------------|--------------------|--------------------|---------------------|---------------------|-------------|--------------------|
|               |                    | <1% Battery status | <50% Battery status | <99% Battery status |             |                    |
| A: Right      | 15                 | 0.6699             | 0.6517              | 0.6441              | 614         | Pass               |
| B: Left       | 15                 | 0.7037             | 0.6819              | 0.6728              | 614         | Pass               |
| C: Front      | 15                 | 0.7966             | 0.7648              | 0.7516              | 614         | Pass               |
| D: Back       | 15                 | 0.6289             | 0.6151              | 0.6093              | 614         | Pass               |
| E: Top        | 20                 | 0.7780             | 0.7482              | 0.7358              | 614         | Pass               |
| F: Bottom     | 15                 | 0.5737             | 0.5658              | 0.5625              | 614         | Pass               |

Test result of Magnetic Field Strength

| Test Position | Test distance (cm) | Test result (A/m)  |                     |                     | Limit (A/m) | Result (Pass/Fail) |
|---------------|--------------------|--------------------|---------------------|---------------------|-------------|--------------------|
|               |                    | <1% Battery status | <50% Battery status | <99% Battery status |             |                    |
| A: Right      | 15                 | 0.0897             | 0.0801              | 0.0761              | 1.63        | Pass               |
| B: Left       | 15                 | 0.0186             | 0.0166              | 0.0158              | 1.63        | Pass               |
| C: Front      | 15                 | 0.0510             | 0.0455              | 0.0432              | 1.63        | Pass               |
| D: Back       | 15                 | 0.0348             | 0.0311              | 0.0295              | 1.63        | Pass               |
| E: Top        | 20                 | 0.0908             | 0.0811              | 0.0770              | 1.63        | Pass               |
| F: Bottom     | 15                 | 0.0100             | 0.0089              | 0.0085              | 1.63        | Pass               |

**Note:**

1. Test with 15cm distance from the center of the probe(s) to the edge of the device, 20 cm for top (Position E) test
2. All simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
3. All possible modes of operation were investigated, only the worst-case emissions reported.

**TEST REPORT**

Equipment Approval Considerations

| Requirements of section 5 of KDB680106 D01 RF Exposure Wireless Charging App v03r01  | Yes/No | Description  |
|--|--------|--|
| Power transfer frequency is less than 1 MHz.   | Yes    | The device operates in the frequency 127kHz                                |
| Output power from each primary coil is less than or equal to 15 watts.   | Yes    | The maximum output power of the primary coil is 7.5W                       |
| The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.   | Yes    | The transmission system consists of two coils, it can work simultaneously. |
| Client device is placed directly in contact with the transmitter.  | Yes    | Client device is placed directly in contact with the transmitter           |
| Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).  | Yes    | Product is not a portable device.  |
| The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit. | Yes    | See the test data in section 2.4 of this report                            |

**Appendix I: Photograph of test setup**

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

**Appendix II: Photograph of equipment under test**

Refer to Appendix 2 for EUT external and internal photos.

\*\*\*\*\* END \*\*\*\*\*