



# TEST REPORT

REPORT NUMBER: I22W00013-Rev2

ON

**Type of Equipment:** Wireless Module  
**Type of Designation:** SIM7500A-H  
**Manufacturer:** SIMCom Wireless Solutions Limited  
**Brand Name:** SIMCom  
**FCC ID:** 2AJYU-8PYA00B

## ACCORDING TO

FCC CFR 47 Part 2.1091 《Radiofrequency radiation exposure evaluation: mobile devices》

FCC CFR 47 Part1.1310 《Radiofrequency radiation exposure limits》

**Chongqing Academy of Information and Communication Technology**

*Month date, year*

Mar,30,2022

*Signature*

**Xiang Luoyong**

*Director*

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of Chongqing Academy of Information and Communications Technology.



**Revision Version**

<b>Report Number</b>	<b>Revision</b>	<b>Date</b>	<b>Memo</b>
I22W00013	01	2022-3-4	Initial creation of test report
I22W00013-Rev1	02	2022-3-21	First change of test report
I22W00013-Rev2	03	2022-3-30	Second change of test report



## CONTENTS

1. TEST LABORATORY.....	2
1.1. TESTING LOCATION.....	2
1.2. TESTING ENVIRONMENT.....	2
1.3. PROJECT DATA.....	2
1.4. SIGNATURE.....	2
2. CLIENT INFORMATION.....	3
2.1. APPLICANT INFORMATION.....	3
2.2. MANUFACTURER INFORMATION.....	3
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE).....	4
3.1. ABOUT EUT.....	4
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST.....	4
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	4
4. REFERENCE DOCUMENTS.....	5
4.1. APPLICABLE STANDARDS.....	5
4.2. TEST LIMITS.....	5
5. TEST RESULTS.....	6
5.1. RF POWER OUTPUT.....	6
5.2. CALCULATION INFORMATION.....	6
5.3. RESULTS.....	7
5.4. RESULT OF LTE BAND 2.....	8
5.5. RESULT OF LTE BAND 4.....	8
5.6. RESULT OF LTE BAND 12.....	8
ANNEX A: EUT PHOTOGRAPH.....	9

## 1. Test Laboratory

### 1.1. Testing Location

Company Name:	Chongqing Academy of Information and Communications Technology
Address:	Building C, Technology Innovation Center, No.8, Yuma Road, Chayuan New Area, Nan'an District, Chongqing, People's Republic of China
Postal Code:	401336
Telephone:	0086-23-88069965
Fax:	0086-23-88608777

### 1.2. Testing Environment

Normal Temperature:	21.3°C
Relative Humidity:	65%

### 1.3. Project Data


Testing Start Date:	2022-3-4
Testing End Date:	2022-3-30

### 1.4. Signature




2022-3-30

**Fu Bohao**  
**(Prepared this test report)**

**Date**

2022-3-30

**Wang Lili**  
**(Reviewed this test report)**

**Date**

2022-3-30

**Xiang Luoyong**  
**Director of the laboratory**  
**(Approved this test report)**

**Date**

**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777



## 2. Client Information

### 2.1. Applicant Information

Company Name:	SIMCom Wireless Solutions Limited
Address /Post:	Building 3,No. 289, Linhong Road, Changning District, Shanghai, P.R.China
Country:	CHINA
Telephone:	15902149520
Fax:	--
Email:	yue.hai@simcom.com
Contact Person:	Haiyue

### 2.2. Manufacturer Information

Company Name:	SIMCom Wireless Solutions Limited
Address /Post:	Building 3,No. 289, Linhong Road, Changning District, Shanghai, P.R.China
Country:	CHINA
Telephone:	15902149520
Fax:	--
Email:	yue.hai@simcom.com
Contact Person:	Haiyue

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

EUT Description:	Wireless Module
Model name:	SIM7500A-H
LTE Frequency Band:	Band2/4/12
Note: Photographs of EUT are shown in ANNEX A of this test report.	

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
S1	861475035587189	V2.01	B05V01	2022-02-11

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

EUT ID*	SN	Description
NA	NA	NA

\*AE ID: is used to identify the test sample in the lab internally.

## 4. Reference Documents

### 4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

**FCC CFR 47 Part 2.1091:** Radiofrequency radiation exposure evaluation: mobile devices

### 4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

MPE for the upper tier (people in controlled environments)

Frequency Range [MHz]	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

For the DUT, the limits for the general public when an RF safety program is unavailable.

## 5. Test Results

### 5.1. RF Power Output

Frequency Band	Highest Averaged Power Output(dBm)	Highest Frame-Averaged Output Power (dBm)	Antenna Gain(dBi)
LTE Band 2	26.00	26.00	1.87
LTE Band 4	27.00	27.00	-1.00
LTE Band 12	28.50	28.50	0.95

Notes:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

2) According to the conducted power as above, the measurements are performed with 1Txslots for 850MHz and 1900MHz.

3) Disclaimers: The Highest Power Output and antenna gain in the above table are provided by the customer

### 5.2. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D04 v01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$S = \frac{PG}{4\pi d^2}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter





### 5.3. Results

Frequency range	Limit(mW/cm <sup>2</sup> )	Results(mW/cm <sup>2</sup> )	Verdict
LTE Band 2	1.0	0.122	Pass
LTE Band 4	1.0	0.079	Pass
LTE Band 12	0.466	0.175	Pass

#### 5.4. Result of LTE Band 2

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1850.0 ~ 1909.9 MHz; The maximum conducted is 26.00 dBm. The maximum gain is 1.87 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (398.107 mW)

G = antenna gain (1.538numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(398.107*1.538)/(4\pi*20^2)=0.122\text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm<sup>2</sup> limit for uncontrolled exposure.

#### 5.5. Result of LTE Band 4

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0 ~ 1754.9MHz; The maximum conducted is 27.00 dBm. The maximum gain is -1.00 dBi. Therefore, maximum limit for general public RF exposure: 1.0 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (501.187 mW)

G = antenna gain (0.794numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(501.187*0.794)/(4\pi*20^2)=0.079\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm<sup>2</sup> limit for uncontrolled exposure.

#### 5.6. Result of LTE Band 12

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 699.0 ~ 715.9 MHz; The maximum conducted is 28..50 dBm. The maximum gain is 0.95 dBi. Therefore, maximum limit for general public RF exposure: 699.0/1500=0.466 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (707.946 mW)

G = antenna gain (1.245numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(707.946*1.245)/(4\pi*20^2)=0.175\text{mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.466 mW/cm<sup>2</sup> limit for uncontrolled exposure.



Report NO.: I22W00013-Rev2

**ANNEX A: EUT photograph**

See the document "SIM7500A-H -External Photos".

**\*\*\*END OF REPORT\*\*\***

**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777