Report No.: SHE23060104-02CE Date: 2023-08-07 Page 31 of 71



Figure 23: Conducted Spurious Emission & Authorized-band band-edge, 2441MHz, π /4-DQPSK Carrier Level



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 32 of 71





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 33 of 71

Figure 24: Conducted Spurious Emission & Authorized-band band-edge, 2480MHz, π /4-DQPSK Carrier Level



Band Edge



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 34 of 71





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 35 of 71

Figure 25: Conducted Spurious Emission & Authorized-band band-edge, 2402MHz, 8-DPSK Carrier Level



Band Edge



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 36 of 71





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 37 of 71

Figure 26: Conducted Spurious Emission & Authorized-band band-edge, 2441MHz, 8-DPSK Carrier Level





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 38 of 71



Figure 27: Conducted Spurious Emission & Authorized-band band-edge, 2480MHz, 8-DPSK Carrier Level



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 39 of 71

Band Edge





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 40 of 71



Figure 28: Conducted Spurious Emission & Authorized-band band-edge, Hopping Mode, GFSK Carrier Level



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 41 of 71

Band Edge(Low)



Band Edge(High)



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 42 of 71





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 43 of 71

Figure 29: Conducted Spurious Emission & Authorized-band band-edge, Hopping Mode, π /4-DQPSK Carrier Level



Band Edge(Low)



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 44 of 71

Band Edge(High)





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 45 of 71



Figure 30: Conducted Spurious Emission & Authorized-band band-edge, Hopping Mode, 8-DPSK Carrier Level



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 46 of 71

Band Edge(Low)



Band Edge(High)



Report No.: SHE23060104-02CE Date: 2023-08-07 Page 47 of 71





Report No.: SHE23060104-02CE Date: 2023-08-07 Page 48 of 71

4.1.5 Radiated Spurious Emission

RESULT: PASS

Test standard : FCC Part 15.247(d), 15.205, 15.209

Requirement : ANSI C63.10-2013, Clause 7.8.8 Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Test Channel : Low/Middle/High

Operation Mode : A

Ambient temperature : 22.1°C Relative humidity : 52%

Notes

Test plots please refer to the annex document "SHE23060104-02CE DATA BDEDR-TX EXHIBIT A".

- 1. For 9 kHz \sim 30 MHz, the amplitude of spurious emissions that are attenuated by more than 20dB below the permissible. The value has no need to be reported.
- 2. The spurious above 18GHz is noise only and 20dB below the limit. The value has no need to be reported.
- 3. All test mode had been pre-test. Only the worst mode data of GFSK&8DPSK-hopping-DH5 and GFSK&8DPSK_Middle channel (below 1GHz) were recorded in the test report.
- 4. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Report No.: SHE23060104-02CE Date: 2023-08-07 Page 49 of 71

4.1.6 Band Edge (Restricted-band band-edge)

RESULT: PASS

Test standard : FCC Part 15.247(d), 15.205, 15.209

Requirement : ANSI C63.10-2013, Clause 7.8.6 Kind of test site : 3m Semi-Anechoic Chamber

Test setup

Test Channel : Low/Middle/High

Operation Mode : A.1
Ambient temperature : 23.1°C
Relative humidity : 52%

Notes

- 1. Test plots please refer to the annex document "SHE23060104-02CE DATA BDEDR-TX EXHIBIT A".
- 2. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Report No.: SHE23060104-02CE Date: 2023-08-07 Page 50 of 71

4.1.7 Hopping Frequency Separation

RESULT: PASS

Test standard : FCC Part 15.247(a)(1)

Requirement : ANSI C63.10-2013, Clause 7.8.2

KDB 558074 D01 v05r02, Clause 2.2

Kind of test site : Shielded room

Test setup

Test Channel : Hopping
Operation Mode : A.1.a.iv
Ambient temperature : 24.9°C
Relative humidity : 51%

Table 3: Hopping Frequency Separation

Мос	le	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
GFS	SK	2441	1.040	0.9426
π /4-D0	QPSK	2441	1.002	0.8573
8-DP	SK	2441	0.957	0.8640

^{*}Note: The systems operate with an output power no greater than 125mW (π /4-DQPSK and 8-DPSK).