

# TEST REPORT

**Applicant:** SIMCom Wireless Solutions Limited  
**Address:** SIMCom Headquarters Building, Building 3, No.289  
Linhong Road, Changning District, Shanghai, China  
**Equipment Type:** MODULE  
**Model Name:** SIM7906G-M2  
**Brand Name:** SIMCom  
**FCC ID:** 2AJYU-8XM0002  
**Test Standard:** 47 CFR Part 2.1091  
KDB 447498 D04 v01  
**Test Date:** Jul. 20, 2022 - Sep. 07, 2022  
**Date of Issue:** Oct. 10, 2022


**ISSUED BY:**

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Huang Jiaquan

**Checked by:** Xu Rui

**Approved by:** Wei Yanquan  
(Chief Engineer)



### Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Sep. 27, 2022</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Oct. 09, 2022</u>	<u>Added the unit in Section 5.3.</u>
<u>Rev. 03</u>	<u>Oct. 10, 2022</u>	<u>Update the antenna gain of WCDMA Band 4 and LTE Band 4</u>

## TABLE OF CONTENTS

1	GENERAL INFORMATION .....	3
1.1	Test Laboratory .....	3
1.2	Test Location.....	3
2	PRODUCT INFORMATION.....	4
2.1	Applicant Information.....	4
2.2	Manufacturer Information .....	4
2.3	Factory Information .....	4
2.4	General Description for Equipment under Test (EUT) .....	4
2.5	Ancillary Equipment.....	4
2.6	Technical Information .....	5
3	SUMMARY OF TEST RESULT .....	6
3.1	Test Standards .....	6
4	DEVICE CATEGORY AND LEVELS LIMITS .....	7
5	ASSESSMENT RESULT .....	9
5.1	Output Power .....	9
5.2	Turn-up power .....	10
5.3	RF Exposure Evaluation Result .....	11
5.4	Conclusion.....	11

# 1 GENERAL INFORMATION

## 1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

## 1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

Applicant	SIMCom Wireless Solutions Limited
Address	SIMCom Headquarters Building, Building 3, No.289 Linhong Road, Changning District, Shanghai, China

### 2.2 Manufacturer Information

Manufacturer	SIMCom Wireless Solutions Limited
Address	SIMCom Headquarters Building, Building 3, No.289 Linhong Road, Changning District, Shanghai, China

### 2.3 Factory Information

Factory	N/A
Address	N/A

### 2.4 General Description for Equipment under Test (EUT)

EUT Name	MODULE
Model Name Under Test	SIM7906G-M2
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	V3.03
Software Version	2110B01V01X12M42A-M2
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

### 2.5 Ancillary Equipment

Note: Not applicable.

## 2.6 Technical Information

Network and Wireless connectivity	3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network FDD LTE Band 2/4/5/7/12/13/14/17/18/19/25/26/30/66 TDD LTE Band 38/40/41 GPS, GLONASS, BeiDou, Galileo
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	WCDMA, LTE		
Frequency Range	WCDMA Band 2	TX: 1850 MHz ~ 1910 MHz	RX: 1930 MHz ~ 1990 MHz
	WCDMA Band 4	TX: 1710 MHz ~ 1755 MHz	RX: 2110 MHz ~ 2155 MHz
	WCDMA Band 5	TX: 824 MHz ~ 849 MHz	RX: 869 MHz ~ 894 MHz
	LTE Band 2	TX: 1850 MHz ~ 1910 MHz	RX: 1930 MHz ~ 1990 MHz
	LTE Band 4	TX: 1710 MHz ~ 1755 MHz	RX: 2110 MHz ~ 2155 MHz
	LTE Band 5	TX: 824 MHz ~ 849 MHz	RX: 869 MHz ~ 894 MHz
	LTE Band 7	TX: 2500 MHz ~ 2570 MHz	RX: 2620 MHz ~ 2690 MHz
	LTE Band 12	TX: 699 MHz ~ 716 MHz	RX: 729 MHz ~ 746 MHz
	LTE Band 13	TX: 777 MHz ~ 787 MHz	RX: 746 MHz ~ 756 MHz
	LTE Band 14	TX: 788 MHz ~ 798 MHz	RX: 758 MHz ~ 768 MHz
	LTE Band 17	TX: 704 MHz ~ 716 MHz	RX: 734 MHz ~ 746 MHz
	LTE Band 18	TX: 815 MHz ~ 830 MHz	RX: 860 MHz ~ 875 MHz
	LTE Band 19	TX: 830 MHz ~ 845 MHz	RX: 875 MHz ~ 890 MHz
	LTE Band 25	TX: 1850 MHz ~ 1915 MHz	RX: 1930 MHz ~ 1995 MHz
	LTE Band 26	TX: 814 MHz ~ 849 MHz	RX: 859 MHz ~ 894 MHz
	LTE Band 30	TX: 2305 MHz ~ 2315 MHz	RX: 2350 MHz ~ 2360 MHz
	LTE Band 66	TX: 1710 MHz ~ 1780 MHz	RX: 2110 MHz ~ 2180 MHz
	LTE Band 38	TX: 2570 MHz ~ 2620 MHz	RX: 2570 MHz ~ 2620 MHz
LTE Band 40	TX: 2300 MHz ~ 2400 MHz	RX: 2300 MHz ~ 2400 MHz	
LTE Band 41	TX: 2496 MHz ~ 2690 MHz	RX: 2496 MHz ~ 2690 MHz	
Antenna Type	Rubber Duck Antenna		
Exposure Category	General Population/Uncontrolled Exposure		
EUT Stage	Mobile Device		

### 3 SUMMARY OF TEST RESULT

#### 3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices
2	KDB 447498 D04 v01	447498 D04 Interim General RF Exposure Guidance v01

## 4 DEVICE CATEGORY AND LEVELS LIMITS

### Mobile Device:

CFR Title 47 §2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

### FCC KDB 447498 D04 General RF Exposure Guidance v01 Limit

Evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i. e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad \text{(B. 2)}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distance (cm), and  $ERP_{20 \text{ cm}}$  is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169



## 5 ASSESSMENT RESULT

### 5.1 Output Power

WCDMA			
Mode	Band 2	Band 4	Band 5
Conducted Power (dBm)	23.11	<b>23.58</b>	23.11
Antenna Gain (dBi)	1.5	1.5	0.5
ERP/EIRP(dBm)	24.61	<b>25.08</b>	21.46

Note: This report listed the worst case power value, please refer to 22TJ0350-501 report for more details.

LTE					
Mode	Band 2	Band 4	Band 5	Band 7	Band 12
Conducted Power (dBm)	22.96	23.02	<b>24.00</b>	23.03	23.79
Antenna Gain (dBi)	1.5	1.5	0.5	1.0	0
ERP/EIRP(dBm)	24.46	24.52	22.35	24.03	21.64
Mode	Band 13	Band 14	Band 17	Band 18	Band 19
Conducted Power (dBm)	23.76	23.79	23.79	23.76	23.82
Antenna Gain (dBi)	0	0	0	0.5	0.5
ERP/EIRP(dBm)	21.61	21.64	21.64	22.11	22.17
Mode	Band 25	Band 26	Band 30	Band 38	Band 40
Conducted Power (dBm)	23.18	23.76	22.47	23.49	19.45
Antenna Gain (dBi)	1.5	0.5	1.0	1.0	1.0
ERP/EIRP(dBm)	<b>24.68</b>	22.11	23.47	24.49	20.45
Mode	Band 41		Band 66		
Conducted Power (dBm)	22.70		23.14		
Antenna Gain (dBi)	1.0		1.5		
ERP/EIRP(dBm)	23.70		24.64		

Note: This report listed the worst case power value, please refer to 22TJ0350-501 report for more details.

## 5.2 Turn-up power

Mode		Conducted Power Range (dBm)	EIRP Range (dBm)	ERP Range (dBm)
WCDMA	Band 2	22.00-24.00	23.50-25.50	21.35-23.35
	Band 4	22.00-24.00	23.50-25.50	21.35-23.35
	Band 5	22.00-24.00	/	20.35-22.35
LTE	Band 2	22.00-24.00	23.50-25.50	21.35-23.35
	Band 4	22.00-24.00	23.50-25.50	21.35-23.35
	Band 5	22.00-24.00	/	20.35-22.35
	Band 7	22.00-24.00	23.00-25.00	20.85-22.85
	Band 12	22.00-24.00	/	19.85-21.85
	Band 13	22.00-24.00	/	19.85-21.85
	Band 14	22.00-24.00	/	19.85-21.85
	Band 17	22.00-24.00	/	19.85-21.85
	Band 18	22.00-24.00	/	20.35-22.35
	Band 19	22.00-24.00	/	20.35-22.35
	Band 25	22.00-24.00	23.50-25.50	21.35-23.35
	Band 26	22.00-24.00	22.50-23.50	20.35-22.35
	Band 30	21.00-23.00	22.00-24.00	19.85-21.85
	Band 38	22.00-24.00	23.00-25.00	20.85-22.85
	Band 40	18.00-20.00	19.00-21.00	16.85-18.85
Band 41	21.00-23.00	22.00-24.00	19.85-21.85	
Band 66	22.00-24.00	23.50-25.50	21.35-23.35	

Note1: ERP= EIRP -2.15dB.

Note2: According KDB 447498 D04, used the greater of maximum conducted power and ERP to compare with the threshold value Pth.

### 5.3 RF Exposure Evaluation Result

Evolution mode		Maximum power (dBm)	Maximum power (mw)	Distance (mm)	Threshold Power (mW)	Power / Limit (mW)	Verdict
WCDMA	Band 2	24	251.19	200	3060.00	0.08	Pass
	Band 4	24	251.19	200	3060.00	0.08	Pass
	Band 5	24	251.19	200	1731.96	0.15	Pass
LTE	Band 2	24	251.19	200	3060.00	0.08	Pass
	Band 4	24	251.19	200	3060.00	0.08	Pass
	Band 5	24	251.19	200	1731.96	0.15	Pass
	Band 7	24	251.19	200	3060.00	0.08	Pass
	Band 12	24	251.19	200	1460.64	0.17	Pass
	Band 13	24	251.19	200	1605.48	0.16	Pass
	Band 14	24	251.19	200	1627.92	0.15	Pass
	Band 17	24	251.19	200	1460.64	0.17	Pass
	Band 18	24	251.19	200	1693.20	0.15	Pass
	Band 19	24	251.19	200	1723.80	0.15	Pass
	Band 25	24	251.19	200	3060.00	0.08	Pass
	Band 26	24	251.19	200	1731.96	0.15	Pass
	Band 30	23	199.53	200	3060.00	0.07	Pass
	Band 38	24	251.19	200	3060.00	0.08	Pass
	Band 40	20	100.00	200	3060.00	0.03	Pass
Band 41	23	199.53	200	3060.00	0.07	Pass	
Band 66	24	251.19	200	3060.00	0.08	Pass	

### 5.4 Conclusion

This EUT is deemed to comply with the reference level limits, therefore the basic restrictions are compliant with human exposure limits.

## Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--