



# TEST REPORT

REPORT NUMBER: I22W00026-MPE

ON

Type of Equipment: SIMCom Module  
Type of Designation: SIM8260A  
Manufacturer: SIMCom Wireless Solutions Limited  
Brand Name: SIMCom  
FCC ID: 2AJYU-8XN0001

## ACCORDING TO

FCC CFR 47 Part 2.1091 《Radiofrequency radiation exposure evaluation: mobile devices》

FCC CFR 47 Part1.1310 《Radiofrequency radiation exposure limits》

Chongqing Academy of Information and Communication Technology

*Month date, year*

Oct, 14, 2022

*Signature*

**Xiang Luoyong**

*Director*

### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of Chongqing Academy of Information and Communications Technology.



**Revision Version**

Report Number	Revision	Date	Memo
I22W00026-MPE	00	2022-10-14	Initial creation of test report



Report NO.: I22W00026-MPE

## CONTENTS

1. TEST LABORATORY .....	3
1.1. TESTING LOCATION .....	3
1.2. TESTING ENVIRONMENT .....	3
1.3. PROJECT DATA .....	3
1.4. SIGNATURE .....	3
2. CLIENT INFORMATION .....	4
2.1. APPLICANT INFORMATION .....	4
2.2. MANUFACTURER INFORMATION .....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) .....	5
3.1. ABOUT EUT .....	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST .....	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST .....	5
4. REFERENCE DOCUMENTS .....	6
4.1. APPLICABLE STANDARDS .....	6
4.2. TEST LIMITS .....	6
5. TEST RESULTS .....	7
5.1. TUNE UP POWER AND ANTENNA GAIN .....	7
5.2. CALCULATION INFORMATION .....	9
5.3. RESULTS .....	10
5.4. RESULT OF WCDMA BAND 2 .....	11
5.5. RESULT OF WCDMA BAND 4 .....	11
5.6. RESULT OF WCDMA BAND 5 .....	11
5.7. RESULT OF LTE BAND 2 .....	12
5.8. RESULT OF LTE BAND 4 .....	12
5.9. RESULT OF LTE BAND 5 .....	12

### Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336

Tel: 0086-23-88069965

FAX: 0086-23-88608777



Report NO.: I22W00026-MPE

5.10. RESULT OF LTE BAND 7 .....	13
5.11. RESULT OF LTE BAND 12 .....	13
5.12. RESULT OF LTE BAND 13 .....	13
5.13. RESULT OF LTE BAND 14 .....	14
5.14. RESULT OF LTE BAND 17 .....	14
5.15. RESULT OF LTE BAND 25 .....	14
5.16. RESULT OF LTE BAND 26 .....	15
5.17. RESULT OF LTE BAND 41 .....	15
5.18. RESULT OF LTE BAND 66 .....	15
5.19. RESULT OF LTE BAND 71 .....	16
5.20. RESULT OF NR BAND 2 .....	16
5.21. RESULT OF NR BAND 5 .....	16
5.22. RESULT OF NR BAND 7 .....	17
5.23. RESULT OF NR BAND 12 .....	17
5.24. RESULT OF NR BAND 14 .....	17
5.25. RESULT OF NR BAND 25 .....	18
5.26. RESULT OF NR BAND 26 .....	18
5.27. RESULT OF NR BAND 41 .....	18
5.28. RESULT OF NR BAND 66 .....	19
5.29. RESULT OF NR BAND 71 .....	19
5.30. RESULT OF NR BAND 77 .....	19
5.31. RESULT OF NR BAND 78 .....	20

**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336

Tel: 0086-23-88069965

FAX: 0086-23-88608777

## 1. Test Laboratory

### 1.1. Testing Location

Company Name:	Chongqing Academy of Information and Communications Technology
Address:	Building C, Technology Innovation Center, No.8, Yuma Road, Chayuan New Area, Nan'an District, Chongqing, People's Republic of China
Postal Code:	401336
Telephone:	0086-23-88069965
Fax:	0086-23-88608777

### 1.2. Testing Environment

Normal Temperature:	21.3°C
Relative Humidity:	65.0%

### 1.3. Project Data

Testing Start Date:	2022-10-10
Testing End Date:	2022-10-10

### 1.4. Signature



2022-10-14

Hu Bo  
(Prepared this test report)

Date



2022-10-14

Yu Chun  
(Reviewed this test report)

Date



2022-10-14

Xiang Luoyong  
Director of the laboratory  
(Approved this test report)

Date

## Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336  
Tel: 0086-23-88069965 FAX: 0086-23-88608777

## 2. Client Information

### 2.1. Applicant Information

Company Name:	SIMCom Wireless Solutions Limited
Address /Post:	SIMCom Headquarters Building, Building 3, No.289 Linhong Road, Changning District, Shanghai, China
Country:	China
Telephone:	+86 21 3157 5100
Fax:	--
Email:	Yongsheng Li@simcom.com
Contact Person:	Yongsheng Li

### 2.2. Manufacturer Information

Company Name:	SIMCom Wireless Solutions Limited
Address /Post:	SIMCom Headquarters Building, Building 3, No.289 Linhong Road, Changning District, Shanghai, China
Country:	China
Telephone:	+86 21 3157 5100
Fax:	--
Email:	Yongsheng Li@simcom.com
Contact Person:	Yongsheng Li

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

EUT Description:	SIMCom Module
Model name:	SIM8260A
WCDMA Frequency Band:	B2/B4/B5
LTE Frequency Band:	B1/B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/B29/B30/B66/B71
NR Frequency Band	B2,B5,B7,B12,B14,B25,B26,B41,B66,B71,B77,B78
Note: Photographs of EUT are shown in ANNEX A of this test report.	

#### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
S4	864284040456399	V1.02	V1.0.01	2022-03-28

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE used during the test

EUT ID*	SN	Description
NA	NA	NA

\*AE ID: is used to identify the test sample in the lab internally.

## 4. Reference Documents

### 4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

**FCC CFR 47 Part 2.1091:** Radiofrequency radiation exposure evaluation: mobile devices

### 4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

MPE for the upper tier (people in controlled environments)

Frequency Range [MHz]	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

For the DUT, the limits for the general public when an RF safety program is unavailable.

## Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336

Tel: 0086-23-88069965

FAX: 0086-23-88608777



## 5. Test Results

### 5.1. Tune up power and Antenna Gain

Frequency Band	Highest Averaged Tune up power(dBm)	Highest Frame-Averaged Tune up power (dBm)	Antenna Gain(dBi)
WCDMA Band 2	24.10	24.10	2.53
WCDMA Band 4	24.20	24.20	2.53
WCDMA Band 5	25.30	25.30	2.86
LTE Band 2	28.40	28.40	1.25
LTE Band 4	28.80	28.80	1.25
LTE Band 5	29.40	29.40	2.86
LTE Band 7	27.70	27.70	1.15
LTE Band 12	28.90	28.90	2.86
LTE Band 13	29.30	29.30	2.86
LTE Band 14	29.00	29.00	2.86
LTE Band 17	29.00	29.00	2.86
LTE Band 25	28.50	28.50	1.25
LTE Band 26	29.00	29.00	2.86
LTE Band 41	25.20	25.20	1.19
LTE Band 66	25.20	25.20	1.25
LTE Band 71	27.20	27.20	2.86

Notes:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

2) Disclaimers: The Highest Tune up power and antenna gain in the above table are provided by the customer

Frequency Band	Highest Averaged Tune up power(dBm)	Highest Frame-Averaged Tune up power (dBm)	Antenna Gain(dBi)
NR Band 2	23.71	23.71	1.25
NR Band 5	24.40	24.40	2.86
NR Band 7	24.50	24.50	1.15
NR Band 12	23.00	23.00	2.86
NR Band 14	24.00	24.00	1.89
NR Band 25	24.30	24.30	1.25
NR Band 26	24.00	24.00	2.86
NR Band 41	26.70	26.70	1.19
NR Band 66	24.50	24.50	1.25
NR Band 71	24.50	24.50	2.86
NR Band 77	26.80	26.80	2.38
NR Band 78	26.50	26.50	2.38

Notes:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

2) Disclaimers: The Highest Tune up power and antenna gain in the above table are provided by the customer

## Chongqing Academy of Information and Communication Technology

Address: No. 8,Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China,401336

Tel: 0086-23-88069965

FAX:0086-23-88608777

## 5.2. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$S = \frac{PG}{4\pi d^2}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

### 5.3. Results

Frequency range	Limit(mW/cm <sup>2</sup> )	Results(mW/cm <sup>2</sup> )	Verdict
WCDMA Band 2	1.00	0.09	PASS
WCDMA Band 4	1.00	0.09	PASS
WCDMA Band 5	0.55	0.13	PASS
LTE Band 2	1.00	0.18	PASS
LTE Band 4	1.00	0.20	PASS
LTE Band 5	0.55	0.33	PASS
LTE Band 7	1.00	0.15	PASS
LTE Band 12	0.47	0.30	PASS
LTE Band 13	0.33	0.33	PASS
LTE Band 14	0.51	0.31	PASS
LTE Band 17	0.47	0.31	PASS
LTE Band 25	1.00	0.19	PASS
LTE Band 26	0.54	0.31	PASS
LTE Band 41	1.00	0.09	PASS
LTE Band 66	1.00	0.09	PASS
LTE Band 71	0.44	0.20	PASS
NR Band 2	1.00	0.06	PASS
NR Band 5	0.55	0.11	PASS
NR Band 7	1.00	0.07	PASS
NR Band 12	0.47	0.08	PASS
NR Band 14	0.53	0.08	PASS
NR Band 25	1.00	0.07	PASS
NR Band 26	0.54	0.10	PASS
NR Band 41	1.00	0.12	PASS
NR Band 66	1.00	0.07	PASS
NR Band 71	0.44	0.11	PASS
NR Band 77	1.00	0.16	PASS
NR Band 78	1.00	0.15	PASS

#### 5.4. Result of WCDMA Band 2

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1852.4 MHz ~ 1907.6 MHz; The maximum conducted is 24.10 dBm. The maximum gain is 2.53 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.09mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

#### 5.5. Result of WCDMA Band 4

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1712.4 MHz ~ 1752.5MHz; The maximum conducted is 24.20 dBm. The maximum gain is 2.53 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.09 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

#### 5.6. Result of WCDMA Band 5

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 826.4 MHz ~ 846.6 MHz; The maximum conducted is 25.30 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure: 826.4/1500=0.55 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.13mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.55 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.7. Result of LTE Band 2

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1850.00 MHz~1909.90MHz; The maximum conducted is 28.40 dBm. The maximum gain is 1.25 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.18 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.8. Result of LTE Band 4

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0 MHz ~ 1754.9MHz; The maximum conducted is 28.80dBm. The maximum gain is 1.25 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.20 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.9. Result of LTE Band 5

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 824.0 MHz ~ 848.9MHz; The maximum conducted is 29.40 dBm. The maximum gain is 2.86dBi. Therefore, maximum limit for general public RF exposure: 824.0/1500=0.55 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.33 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.55 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.10. Result of LTE Band 7

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 2500.0MHz ~ 2569.9MHz; The maximum conducted is 27.70 dBm. The maximum gain is 1.15 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.15 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.11. Result of LTE Band 12

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 699.00 MHz ~ 715.90 MHz; The maximum conducted is 28.90 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure: 699.0/1500=0.47 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.30 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.47 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.12. Result of LTE Band 13

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 746.00 MHz ~ 755.90 MHz; The maximum conducted is 29.30 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure: 746.0/1500=0.50 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.33 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.50 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.13. Result of LTE Band 14

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 758.0 MHz ~ 767.9 MHz; The maximum conducted is 29.00 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure:  $758.0/1500=0.51 \text{ mW/cm}^2$ .

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.31 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.51 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.14. Result of LTE Band 17

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 704.0 MHz ~ 715.9MHz; The maximum conducted is 29.00 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure:  $704.0/1500=0.47 \text{ mW/cm}^2$ .

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.31 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.47 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.15. Result of LTE Band 25

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1850.0 MHz ~ 1914.9MHz; The maximum conducted is 28.50 dBm. The maximum gain is 1.25 dBi. Therefore, maximum limit for general public RF exposure:  $1.00 \text{ mW/cm}^2$ .

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.19mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.



### 5.16. Result of LTE Band 26

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 807.0 MHz ~ 823.9 MHz; The maximum conducted is 29.00 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure:  $807.00/1500=0.54$  mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.31 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.54 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.17. Result of LTE Band 41

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 2496.00 MHz ~ 2689.90 MHz; The maximum conducted is 25.20 dBm. The maximum gain is 1.19 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.09 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.18. Result of LTE Band 66

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0 MHz ~ 1780.0 MHz; The maximum conducted is 25.20 dBm. The maximum gain is 1.25 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.09 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.19. Result of LTE Band 71

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 663.0MHz ~ 698.0MHz; The maximum conducted is 27.20 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure:  $663.0/1500=0.44$  mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.20mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.44 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.20. Result of NR Band 2

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1850.0 MHz ~ 1910.0 MHz; The maximum conducted is 23.71 dBm. The maximum gain is 1.25 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.06 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.21. Result of NR Band 5

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 824.0 MHz ~ 849.0 MHz; The maximum conducted is 24.40 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure:  $824.0/1500=0.55$  mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.11 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.55 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.22. Result of NR Band 7

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @2500.0 MHz ~ 2570.0 MHz; The maximum conducted is 24.50 dBm. The maximum gain is 1.15 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.07 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.23. Result of NR Band 12

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 699.0 MHz ~ 716.0 MHz; The maximum conducted is 23.00 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure: 699.0/1500=0.47 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.08mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.47 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.24. Result of NR Band 14

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 788.0 MHz ~ 798.0 MHz; The maximum conducted is 24.00 dBm. The maximum gain is 1.89 dBi. Therefore, maximum limit for general public RF exposure: 788.0/1500=0.53 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.08mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.53 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.25. Result of NR Band 25

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1850.0 MHz ~ 1915.0 MHz; The maximum conducted is 24.30 dBm. The maximum gain is 1.25 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.07mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.26. Result of NR Band 26

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 814.0 MHz ~ 849.0 MHz; The maximum conducted is 24.00 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure: 814.0/1500=0.54 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.15mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.54 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.27. Result of NR Band 41

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 2496.0 MHz ~ 2690.0 MHz; The maximum conducted is 26.70 dBm. The maximum gain is 1.19 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.10 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.28. Result of NR Band 66

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0 MHz ~ 1780.0 MHz; The maximum conducted is 24.50 dBm. The maximum gain is 1.25 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.07 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.29. Result of NR Band 71

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 663.0 MHz ~ 698.0 MHz; The maximum conducted is 24.50 dBm. The maximum gain is 2.86 dBi. Therefore, maximum limit for general public RF exposure: 663.0/1500=0.44mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.11 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 0.44 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.30. Result of NR Band 77

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 3300.0 MHz ~ 4200.0 MHz; The maximum conducted is 26.80 dBm. The maximum gain is 2.38 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.16 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.

### 5.31. Result of NR Band 78

**Test Results:** MPE Limit Calculation: the EUT'S operating frequencies @ 3300.0 MHz~3800.0 MHz; The maximum conducted is 26.50 dBm. The maximum gain is 2.38 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm<sup>2</sup>.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

S=0.15 mW/cm<sup>2</sup>

Therefore, at 20 cm the spectral power density is less than the 1.00 mW/cm<sup>2</sup> limit for uncontrolled exposure.



Report NO.: I22W00026-MPE

ANNEX A: EUT photograph

See the document "SIMCom Module Photos".

**\*\*\*END OF REPORT\*\*\***

**Chongqing Academy of Information and Communication Technology**

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336

Tel: 0086-23-88069965

FAX: 0086-23-88608777