

MODULAR APPROVAL LETTER

SIMCom Wireless Solutions Limited
Building 3, No.289 Linhong Road, ChangNing District, Shanghai,
China

FCC ID: 2AJYU-8XN0003

| Modular Approval Requirement | Yes | No |
|---|------------|-----------|
| (i) The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements. | Yes | |
| (ii) The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation. | Yes | |
| (iii) The modular transmitter must have its own power supply regulation. | Yes | |
| (iv) The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section. | Yes | |
| (v) The modular transmitter must be tested in a stand-alone configuration | Yes | |
| (vi) The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number. | Yes | |
| (vii) The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. | Yes | |
| (viii) The modular transmitter must comply with any | Yes | |

C:\Users\jibin.zhang\Desktop\8262A-M2 3IN\Modular Approval Letter_SIM8262A_v2.docx

| | | |
|---|-----|--|
| applicable RF exposure requirements in its final configuration. | | |
| (iX) The modular must met the requirements in Section 15.212. KDB 996369 D01 and Part 15.212. | Yes | |

Sincerely,

Yongsheng Li

(signature)

Yongsheng.Li