



# RF EXPOSURE EXEMPT REPORT

**APPLICANT** : Hangzhou Konke Information Technology Co.,Ltd.  
**PRODUCT NAME** : Motion sensor  
**MODEL NAME** : Kit Pro-BS  
**BRAND NAME** : konke  
**FCC ID** : 2AJZ4-KPBS  
**STANDARD(S)** : 47CFR 2.1093  
KDB 447498  
**RECEIPT DATE** : 2019-01-11  
**TEST DATE** : 2019-03-29  
**ISSUE DATE** : 2019-03-29

Edited by: Su Jinhai  
Su Jinhai (Rapporteur)

Approved by: Peng Huarui  
Peng Huarui (Supervisor)

**NOTE:** This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





## DIRECTORY

<b>1. Technical Information.....</b>	<b>4</b>
<b>1.1 Applicant and Manufacturer Information.....</b>	<b>4</b>
<b>1.2 Equipment Under Test (EUT) Description.....</b>	<b>4</b>
<b>1.3 Identification of all used EUT.....</b>	<b>5</b>
<b>1.4 Applied Reference Documents.....</b>	<b>5</b>
<b>2. Device Category and RF Exposure Limit.....</b>	<b>6</b>
<b>3. Measurement of RF Output Power.....</b>	<b>7</b>
<b>4. RF Exposure Evaluation.....</b>	<b>8</b>
<b>Annex A General Information.....</b>	<b>9</b>



REPORT No. : SZ19010103S01

Change History		
Version	Date	Reason for change
1.0	2019-03-29	First edition



# 1. Technical Information

**Note:** Provide by manufacturer.

## 1.1 Applicant and Manufacturer Information

<b>Applicant:</b>	Hangzhou Konke Information Technology Co.,Ltd.
<b>Applicant Address:</b>	28F Huafeng international mansion, No.200 Xinye Road Jianggan District, Hangzhou China
<b>Manufacturer:</b>	Hangzhou Konke Information Technology Co.,Ltd.
<b>Manufacturer Address:</b>	28F Huafeng international mansion, No.200 Xinye Road Jianggan District, Hangzhou China

## 1.2 Equipment Under Test (EUT) Description

<b>EUT Type:</b>	Motion sensor
<b>Hardware Version:</b>	kpbs_hv_1.0.0
<b>Software Version:</b>	kpbs_rv_1.0.0
<b>Frequency Bands:</b>	Zigbee: 2405MHz-2480MHz
<b>Modulation Mode:</b>	GFSK
<b>Antenna Type:</b>	Ceramic Antenna
<b>Antenna Gain:</b>	2.1dBi



### 1.3 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	kpbs_hv_1.0.0	kpbs_rv_1.0.0

### 1.4 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1093	Radio Frequency Radiation Exposure Evaluation: portable devices
2	KDB 447498 D01v06	General RF Exposure Guidance



## 2. Device Category and RF Exposure Limit

Per user manual, this device is a Motion sensor. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

### **Portable Devices:**

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

### **GENERAL POPULATION / UNCONTROLLED EXPOSURE**

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.

### 3. Measurement of RF Output Power

#### 1. Zigbee output power

Mode	Channel	Frequency (MHz)	Average power (dBm)
			GFSK
Zigbee	CH 11	2405	<b>5.49</b>
	CH 18	2440	5.32
	CH 26	2480	5.15
Tune-up Limit			6.00

**Note:** According to KDB 447498 Section 4.3, SAR test exclusion conditions are based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.



## 4. RF Exposure Evaluation

The device only incorporates an Entry Sensor, so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

Standalone transmission SAR evaluation

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

The maximum tune-up limit power is **3.98mW @ 2.405GHz**

When the Motion sensor is used on the hand/head/body, so use **5mm** as the most conservative minimum test separation distance,

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = 1.23 \leq 3.0$$

Therefore SAR measurement is not required for this device.





## Annex A General Information

### 1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, Guangdong Province, P. R. China

\_\_\_\_\_ END OF REPORT \_\_\_\_\_