

## FCC Report (GSM&WCDMA)

**Applicant:** Mason America, Inc.  
**Address of Applicant:** 300 Park Street , Suite 380, Birmingham, Michigan 48009, United States  
**Manufacturer:** Mason America, Inc.  
**Address of Manufacturer:** 300 Park Street , Suite 380, Birmingham, Michigan 48009, United States  
**Equipment Under Test (EUT)**  
Product Name: Smart phone  
Model No.: D450A  
Trade mark: MASON  
**FCC ID:** 2AJZP-D450A  
**Applicable standards:** FCC CFR Title 47 Part 2: 2017  
FCC CFR Title 47 Part22 Subpart H: 2017  
FCC CFR Title 47 Part24 Subpart E: 2017  
**Date of sample receipt:** May 10, 2018  
**Date of Test:** May 11, 2018-June 04, 2018  
**Date of report issued:** June 05, 2018  
**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



**Robinson Lo**

**Laboratory Manager**

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 1 Version

Version No.	Date	Description
00	June 05, 2018	Original

Prepared By:

*Tiger Chen*

Date:

June 05, 2018

Project Engineer

Check By:

*Andy Wu*

Date:

June 05, 2018

Reviewer

## 2 Contents

	Page
<b>1 VERSION</b> .....	<b>2</b>
<b>2 CONTENTS</b> .....	<b>3</b>
<b>3 TEST SUMMARY</b> .....	<b>4</b>
<b>4 GENERAL INFORMATION</b> .....	<b>5</b>
4.1 GENERAL DESCRIPTION OF EUT .....	5
4.2 RELATED SUBMITTAL(S) / GRANT (S) .....	7
4.3 TEST METHODOLOGY .....	7
4.4 TEST FACILITY .....	7
4.5 TEST LOCATION .....	7
<b>5 TEST INSTRUMENTS LIST</b> .....	<b>8</b>
<b>6 SYSTEM TEST CONFIGURATION</b> .....	<b>9</b>
6.1 TEST MODE .....	9
6.2 CONFIGURATION OF TESTED SYSTEM .....	10
6.3 CONDUCTED PEAK OUTPUT POWER .....	11
6.4 PEAK-TO-AVERAGE RATIO .....	13
6.5 OCCUPY BANDWIDTH .....	15
6.6 MODULATION CHARACTERISTIC .....	25
6.7 OUT OF BAND EMISSION AT ANTENNA TERMINALS .....	25
6.8 ERP, EIRP MEASUREMENT .....	37
6.9 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT .....	43
6.10 FREQUENCY STABILITY V.S. TEMPERATURE MEASUREMENT .....	49
6.11 FREQUENCY STABILITY V.S. VOLTAGE MEASUREMENT .....	53
<b>7 TEST SETUP PHOTO</b> .....	<b>57</b>
<b>8 EUT CONSTRUCTIONAL DETAILS</b> .....	<b>57</b>

### 3 Test Summary

Test Item	Section in CFR 47	Result
RF Exposure (SAR)	Part 1.1307 Part 2.1093	Pass* (Please refer to SAR Report)
RF Output Power	Part 2.1046 Part 22.913 (a)(2) Part 24.232 (c)	Pass
Peak-to-Average Ratio	Part 2.1046 Part 24.232 (d)	Pass
Modulation Characteristics	Part 2.1047	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 22.917 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 22.917 (a) Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 22.917 (a) Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability vs. temperature	Part 2.1055(a)(1)(b)	Pass
Frequency stability vs. voltage	Part 2.1055(d)(1)(2)	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

## 4 General Information

### 4.1 General Description of EUT

Product Name:	Smart phone
Model No.:	D450A
Serial No.:	MX-QD0201-R5FHN-7PAC8-VEFIPI
Test sample(s) ID:	GTS201805000172-1
Sample(s) Status	Engineer sample
Hardware version:	H01
Software version:	D450A-H01-S005
Support Networks:	GSM, GPRS, EGPRS, WCDMA
Support Bands:	GSM850, PCS1900, WCDMA Band V, WCDMA Band II
TX Frequency:	GSM850: 824.20MHz-848.80MHz PCS1900: 1850.20MHz-1909.80MHz WCDMA Band V: 826.40MHz -846.60MHz WCDMA Band II: 1852.40MHz -1907.60MHz
GPRS Class:	10
EGPRS Class	12
Release	R99
Modulation type:	GSM/GPRS: GMSK EGPRS: GMSK/8PSK WCDMA Band II/V: QPSK
Antenna type:	Integral antenna
Antenna gain:	GSM850/ WCDMA Band V: -2.30dBi PCS1900/ WCDMA Band II: -0.93dBi
Power supply:	ADAPTER POWER Model: A138A-120150U-US2 Input: AC 100-240V, 50/60Hz, 0.5A Output: DC 5V, 2.5A/9V, 2A/12V, 1.5A DC 3.85V, 4000mAh Li-Pol 15.4Wh

**Operation Frequency List:**

GSM 850		PCS1900		WCDMA Band V		WCDMA Band II	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20	4132	826.40	9262	1852.40
129	824.40	513	1850.40	4133	826.60	9263	1852.60
· ∴	· ∴	· ∴	· ∴	· ∴	· ∴	· ∴	· ∴
189	836.40	660	1879.80	4181	836.20	9399	1879.80
190	836.60	661	1880.00	4182	836.40	9400	1880.00
191	836.80	662	1880.20	4183	836.60	9401	1880.20
· ∴	· ∴	· ∴	· ∴	· ∴	· ∴	· ∴	· ∴
250	848.60	809	1909.60	4232	846.40	9537	1907.40
251	848.80	810	1909.80	4233	846.60	9538	1907.60

Regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

**Final test channel:**

GSM 850		PCS1900		WCDMA Band V		WCDMA Band II	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
128	824.20	512	1850.20	4132	826.40	9262	1852.40
190	836.60	661	1880.00	4183	836.60	9400	1880.00
251	848.80	810	1909.80	4233	846.60	9538	1907.60

## 4.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is filing to comply with Section Part 22 subpart H and Part 24 subpart E of the FCC CFR 47 Rules.

## 4.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures document on TIA/EIA 603 and FCC CFR 47.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055 and 2.1057

## 4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

## 4.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480

Fax: 0755-27798960

## 5 Test Instruments list

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 28 2017	June 27 2018
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 28 2017	June 27 2018
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2017	June 27 2018
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 28 2017	June 27 2018
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June 28 2017	June 27 2018
9	Coaxial Cable	GTS	N/A	GTS211	June 28 2017	June 27 2018
10	Coaxial cable	GTS	N/A	GTS210	June 28 2017	June 27 2018
11	Coaxial Cable	GTS	N/A	GTS212	June 28 2017	June 27 2018
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 28 2017	June 27 2018
13	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 28 2017	June 27 2018
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2017	June 27 2018
15	Band filter	Amindeon	82346	GTS219	June 28 2017	June 27 2018
16	Universal radio communication tester	Rohde & Schwarz	CMU200	GTS235	June 28 2017	June 27 2018
17	Signal Generator	Rohde & Schwarz	SML03	GTS236	June 28 2017	June 27 2018
18	Temp. Humidity/ Barometer	Oregon Scientific	BA-888	GTS248	June 28 2017	June 27 2018
19	D.C. Power Supply	Instek	PS-3030	GTS232	NA	NA
20	Splitter	Agilent	11636B	GTS237	June 28 2017	June 27 2018
21	Power meter	Rohde & Schwarz	NRVS	GTS238	June 28 2017	June 27 2018
22	Spectrum Analyzer	Agilent	E4440A	GTS533	June 28 2017	June 27 2018
23	Temp.&Humidity chamber	Chuang wei	GDS-225	GTS005-1	June 28 2017	June 27 2018
24	Highpass filter	Micro-Tronics	HPM50108	GTS549	June 28 2017	June 27 2018
25	Highpass filter	Micro-Tronics	HPM50111	GTS550	June 28 2017	June 27 2018
26	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS588	May 07 2017	May 06 2018



## 6 System test configuration

### 6.1 Test mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Test modes		
Band	Radiated	Conducted
<b>GSM 850</b>	<ul style="list-style-type: none"> <li>■ GSM link</li> <li>■ GPRS 1 link</li> <li>■ EPRS 1 link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM link</li> <li>■ GPRS 1 link</li> <li>■ EGPRS 1 link</li> </ul>
<b>PCS 1900</b>	<ul style="list-style-type: none"> <li>■ GSM link</li> <li>■ GPRS 1 link</li> <li>■ EGPRS 1 link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM link</li> <li>■ GPRS 1 link</li> <li>■ EGPRS 1 link</li> </ul>
<b>WCDMA II</b>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps link</li> </ul>
<b>WCDMA Band V</b>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps link</li> </ul>


Note: The maximum power levels are GSM mode for GMSK link, GPRS multi-slot class 10 mode for GMSK link, EGPRS multi-slot class 12 mode for 8PSK link, RMC12.2Kbps mode for WCDMA Band V/II. only these modes were used for all tests.

The conducted power tables are as follows:


Conducted Power (dBm)						
Band	GSM850			PCS1900		
Channel	128	190	251	512	661	810
Frequency	824.20	836.60	848.80	1850.20	1880.00	1909.80
GSM (GMSK, 1 TX slot)	32.95	33.05	33.14	29.24	29.56	29.84
GPRS (GMSK, 1 TX slot)	32.97	33.1	33.12	29.44	29.12	29.09
GPRS (GMSK, 2 TX slot)	31.87	31.10	31.08	29.44	29.04	29.11
GPRS (GMSK, 3 TX slot)	31.27	31.97	31.50	27.03	27.08	27.97
GPRS (GMSK, 4 TX slot)	28.24	28.53	28.50	27.92	27.93	27.47
EGPRS (8PSK, 1 TX slot)	27.32	27.14	27.07	24.26	24.54	24.82
EGPRS (8PSK, 2 TX slot)	27.05	27.15	27.74	23.44	23.32	23.08
EGPRS (8PSK, 3 TX slot)	25.82	25.29	25.34	22.44	22.62	22.57
EGPRS (8PSK, 4 TX slot)	25.25	25.22	25.70	21.37	21.67	21.26

Conducted Power (dBm)						
Band	WCDMA Band II			WCDMA Band V		
Channel	9262	9400	9538	4132	4183	4233
Frequency	1852.4	1880.0	1907.6	826.4	836.6	846.6
RMC 12.2Kbps	21.26	21.38	21.86	22.12	22.24	21.98
HSDPA Subtest-1	19.96	19.19	19.58	21.86	21.75	21.49
HSDPA Subtest-2	19.56	19.49	19.79	21.75	21.98	21.17
HSDPA Subtest-3	19.11	19.39	19.63	21.50	21.52	21.34
HSDPA Subtest-4	19.40	19.08	20.00	21.54	21.38	21.49
HSUPA Subtest-1	20.00	19.05	19.79	22.24	22.31	22.34
HSUPA Subtest-2	19.76	19.22	19.53	22.81	22.46	22.03
HSUPA Subtest-3	19.67	19.51	19.86	22.73	22.40	22.83
HSUPA Subtest-4	19.25	19.77	19.97	22.74	22.37	22.27
HSUPA Subtest-5	19.27	19.35	19.05	22.03	22.03	22.69
AMR	19.71	19.11	19.43	22.41	22.95	22.17

## 6.2 Configuration of Tested System




## 6.3 Conducted Peak Output Power

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850, WCDMA Band V: 7W PCS1900, WCDMA Band II: 2W
Test setup:	 <pre> graph LR     EUT[EUT] --- Splitter[Splitter]     Splitter --- CT[Communication Tester]     Splitter --- PM[Power meter]     </pre> <p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> <li>1. The transmitter output port was connected to base station.</li> <li>2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.</li> <li>3. Set EUT at maximum power through base station.</li> <li>4. Select lowest, middle, and highest channels for each band and different modulation.</li> <li>5. Measure the maximum burst peak power.</li> </ol>
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data

EUT Mode	Channel	Frequency (MHz)	PK power (dBm)	Limit (dBm)	Result
GSM 850 (GSM link)	128	824.20	35.34	38.45	Pass
	190	836.60	35.16		
	251	848.80	34.98		
GSM 850 (GPRS 1 link)	128	824.20	35.37	38.45	Pass
	190	836.60	35.54		
	251	848.80	35.09		
GSM 850 (EGPRS 1 link)	128	824.20	31.31	38.45	Pass
	190	836.60	31.34		
	251	848.80	31.09		
PCS 1900 (GSM link)	512	1850.20	32.48	33.01	Pass
	661	1880.00	32.36		
	810	1909.80	32.47		
PCS 1900 (GPRS 1 link)	512	1850.20	32.58	33.01	Pass
	661	1880.00	32.33		
	810	1909.80	32.82		
PCS 1900 (EGPRS 1 link)	512	1850.20	28.63	33.01	Pass
	661	1880.00	28.49		
	810	1909.80	28.28		
WCDMA Band V (RMC 12.2Kbps link)	4132	826.40	26.25	38.45	Pass
	4183	836.60	26.72		
	4233	846.60	26.22		
WCDMA Band II (RMC 12.2Kbps link)	9262	1852.4	24.61	33.01	Pass
	9400	1880.0	24.37		
	9538	1907.6	24.81		


## 6.4 Peak-to-Average Ratio

Test Requirement:	FCC part24.232(d)
Test Method:	FCC part2.1046
Limit:	13db
Test setup:	 <p style="text-align: center;"><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> <li>1. The transmitter output port was connected to base station.</li> <li>2. The RF output of EUT was connected to the power meter by RF cable and attenuator, the path loss was compensated to the results for each measurement.</li> <li>3. Set EUT at maximum power through base station.</li> <li>4. Select lowest, middle, and highest channels for each band and different modulation.</li> <li>5. Measure the maximum burst average power.</li> <li>6. Record the maximum peak-to-average ratio value.</li> </ol>
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement data

Test mode	Channel	Peak power (dBm)	Average power(dBm)	PAR(dB)	Limit (dB)	Verdict
GPRS 850	824.2	35.37	32.97	2.4	13	Compliant
	836.6	35.54	33.10	2.44		
	848.8	35.09	33.12	1.97		
PCS 1900	1850.2	32.48	29.44	3.04		
	1880.0	32.36	29.12	3.24		
	1909.8	32.47	29.09	3.38		
WCDMA Band V	826.4	26.25	22.12	4.13		
	836.6	26.72	22.24	4.48		
	846.6	26.22	21.98	4.24		
WCDMA Band II	1852.4	24.61	21.26	3.35		
	1880.0	24.37	21.38	2.99		
	1907.6	24.81	21.86	2.95		

## 6.5 Occupancy Bandwidth

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1049
Test setup:	 <p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> <li>1. The EUT's output RF connector was connected with a short cable to the spectrum analyzer</li> <li>2. RBW was set to about 1% of emission BW, VBW= 3 times RBW.</li> <li>3. -26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.</li> </ol>
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass


Measurement Data

EUT Mode	Channel	Frequency (MHz)	99% Occupy bandwidth (KHz)	-26dB bandwidth (KHz)
GSM 850 (GSM link)	128	824.20	248.478	327.630
	190	836.60	249.621	315.144
	251	848.80	243.955	315.245
GSM 850 (GPRS 1 link)	128	824.20	241.650	317.853
	190	836.60	246.911	319.439
	251	848.80	245.224	320.410
GSM 850 (EGPRS 1 link)	128	824.20	237.817	310.128
	190	836.60	236.829	317.257
	251	848.80	237.671	312.033
PCS 1900 (GSM link)	512	1850.20	245.584	312.215
	661	1880.00	240.889	310.998
	810	1909.80	248.773	314.824
PCS 1900 (GPRS 1 link)	512	1850.20	244.448	320.249
	661	1880.00	240.947	316.770
	810	1909.80	245.173	319.159
PCS 1900 (EGPRS 1 link)	512	1850.20	237.099	318.855
	661	1880.00	239.537	310.308
	810	1909.80	238.989	308.803
WCDMA Band V (RMC 12.2Kbps link)	4132	826.40	4119.7	4748.0
	4183	836.60	4121.2	4732.0
	4233	846.60	4131.0	4753.0
WCDMA Band II (RMC 12.2Kbps link)	9262	1852.4	4144.0	4743.0
	9400	1880.0	4139.9	4719.0
	9538	1907.6	4112.9	4727.0




Test plot as follows:

Test band:	GSM 850 (GSM link)
------------	--------------------



Lowest channel




Middle channel




Highest channel


Test band: GSM 850 (GPRS 1 link)



Lowest channel




Middle channel




Highest channel

Test band: GSM 850 (EGPRS 1 link)



Lowest channel




Middle channel




Highest channel


Test band: PCS 1900 (GSM link)



Lowest channel




Middle channel




Highest channel


Test band: PCS 1900 (GPRS 1 link)



Lowest channel




Middle channel




Highest channel


Test band: PCS 1900 (EGPRS 1 link)



Lowest channel




Middle channel




Highest channel


Test band: WCDMA Band V (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel


Test band: WCDMA Band II (RMC 12.2Kbps link)



Lowest channel



Middle channel




Highest channel



## 6.6 MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.



## 6.7 Out of band emission at antenna terminals

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1051
Limit:	-13dBm
Test setup:	 <p><i>Note: Measurement setup for testing on Antenna connector</i></p>
Test Procedure:	<ol style="list-style-type: none"> <li>1 The RF output of the transceiver was connected to a spectrum analyzer through appropriate attenuation.</li> <li>2 The resolution bandwidth of the spectrum analyzer was set at 1MHz, sufficient scans were taken to show the out of band Emissions if any up to 10th harmonic.</li> <li>3 For the out of band: Set the RBW, VBW = 1MHz, Start=30MHz, Stop= 10th harmonic.</li> <li>4 Band Edge Requirements: In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 1 percent of the emission bandwidth of the fundamental emission of the transmitter may be employed to measure the out of band Emissions.</li> </ol>
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass



Test plot as follows:

Note: During the conducted spurious emission test, a band filter was used. The information of the filter is reported at section 6.0 (refer to item 24, 25).



Test Mode: Traffic mode GSM 850 (GSM link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode GSM 850 (GPRS 1 link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode GSM 850 (EGPRS 1 link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode      PCS1900 (GSM link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode      PCS1900 (GPRS 1 link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode      PCS1900 (EGPRS 1 link)



Lowest channel





Middle channel





Highest channel



Test Mode: Traffic mode WCDMA Band V (RMC 12.2Kbps link)



Lowest channel





Middle channel





Highest channel





Test Mode: Traffic mode WCDMA Band II (RMC 12.2Kbps link)



Lowest channel




Middle channel




Highest channel

Band Edge:

Test Mode: Traffic mode GSM850 (GSM link)




Lowest channel




Highest channel

Test Mode: Traffic mode GSM850 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode GSM850 (EGPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode PCS1900 (GSM link)




Lowest channel




Highest channel

Test Mode: Traffic mode PCS1900 (GPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode PCS1900 (EGPRS 1 link)




Lowest channel




Highest channel

Test Mode: Traffic mode WCDMA Band V (RMC 12.2Kbps link)




Lowest channel




Highest channel

Test Mode: Traffic mode WCDMA Band II (RMC 12.2Kbps link)






Lowest channel



Highest channel

## 6.8 ERP, EIRP Measurement

Test Requirement:	FCC part22.913(a) and FCC part24.232(b)
Test Method:	FCC part2.1046
Limit:	GSM850, WCDMA Band V: 7W PCS1900, WCDMA Band II: 2W WCDMA Band IV: 1W
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p>  <p>Substituted method:</p> 

<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.</li> <li>2. During the measurement, the EUT was in communication with the station. The highest emission was recorded with the rotation of the turntable and the lowering of the test antenna from 4m to 1m. The reading was recorded and the field strength (E in dBuV/m) was calculated.</li> <li>3. ERP in frequency band 824.2 –848.80.8MHz were measured using a substitution method. The EUT was replaced by a dipole antenna connected, the S.G. output was recorded and ERP was calculated as follows:  <math display="block">\text{ERP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBd)} - \text{Cable Loss (dB)}</math> </li> <li>4. EIRP in frequency band 1850.2 –1909.8MHz were measured using a substitution method. The EUT was replaced by a horn antenna connected, the S.G. output was recorded and EIRP was calculated as follows:  <math display="block">\text{EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain (dBi)} - \text{Cable Loss (dB)}</math> </li> </ol>
<p>Test Instruments:</p>	<p>Refer to section 5.0 for details</p>
<p>Test mode:</p>	<p>Refer to section 6.1 for details</p>
<p>Test results:</p>	<p>Pass</p>

## Measurement Data

Remark: All conditions have been considered and test, only the worst case report.

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GSM link)	Lowest	H	V	30.46	38.45	Pass
			H	29.40		
	Middle	H	V	30.56	38.45	Pass
			H	29.55		
	Highest	H	V	30.96	38.45	Pass
			H	29.27		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
	V	H		
Lowest	V	32.51	2.5	4.55
	H	31.45		
Middle	V	32.66	2.5	4.6
	H	31.65		
Highest	V	33.11	2.5	4.65
	H	31.42		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (GPRS 1 link)	Lowest	H	V	30.15	38.45	Pass
			H	29.08		
	Middle	H	V	30.20	38.45	Pass
			H	29.15		
	Highest	H	V	30.61	38.45	Pass
			H	28.89		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
	V	H		
Lowest	V	32.2	2.5	4.55
	H	31.13		
Middle	V	32.3	2.5	4.6
	H	31.25		
Highest	V	32.76	2.5	4.65
	H	31.04		

EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
GSM850 (EGPRS 1 link)	Lowest	H	V	27.41	38.45	Pass
			H	24.35		
	Middle	H	V	27.63	38.45	Pass
			H	24.72		
	Highest	H	V	27.84	38.45	Pass
			H	24.12		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
	Pol.	Value		
Lowest	V	29.46	2.5	4.55
	H	26.4		
Middle	V	29.73	2.5	4.6
	H	26.82		
Highest	V	29.99	2.5	4.65
	H	26.27		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GSM link)	Lowest	H	V	28.61	33.01	Pass
			H	25.87		
	Middle	H	V	28.74	33.01	Pass
			H	26.02		
	Highest	H	V	29.20	33.01	Pass
			H	25.88		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
	Pol.	Value		
Lowest	V	30.79	2.7	4.88
	H	28.05		
Middle	V	30.94	2.7	4.9
	H	28.22		
Highest	V	31.42	2.7	4.92
	H	28.1		



EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (GPRS 1 link)	Lowest	H	V	28.23	33.01	Pass
			H	25.46		
	Middle	H	V	28.26	33.01	Pass
			H	25.49		
	Highest	H	V	28.74	33.01	Pass
			H	25.39		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
	V	H		
Lowest	V	30.41	2.7	4.88
	H	27.64		
Middle	V	30.46	2.7	4.9
	H	27.69		
Highest	V	30.96	2.7	4.92
	H	27.61		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP (dBm)	Limit (dBm)	Result
PCS1900 (EGPRS 1 link)	Lowest	H	V	25.04	33.01	Pass
			H	20.74		
	Middle	H	V	24.03	33.01	Pass
			H	20.74		
	Highest	H	V	24.42	33.01	Pass
			H	20.42		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
	V	H		
Lowest	V	27.22	2.7	4.88
	H	22.92		
Middle	V	26.23	2.7	4.9
	H	22.94		
Highest	V	26.64	2.7	4.92
	H	22.64		




EUT mode	Channel	EUT Pol.	Antenna Pol.	ERP(dBm)	Limit (dBm)	Result
WCDMA Band V	Lowest	H	V	22.86	38.45	Pass
			H	21.78		
	Middle	H	V	22.61	38.45	Pass
			H	21.39		
	Highest	H	V	22.51	38.45	Pass
			H	20.02		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
Lowest	V	24.91	2.5	4.55
	H	23.83		
Middle	V	24.71	2.5	4.6
	H	23.49		
Highest	V	24.66	2.5	4.65
	H	22.17		

EUT mode	Channel	EUT Pol.	Antenna Pol.	EIRP(dBm)	Limit (dBm)	Result
WCDMA Band II	Lowest	H	V	21.24	33.01	Pass
			H	21.21		
	Middle	H	V	22.13	33.01	Pass
			H	21.04		
	Highest	H	V	20.05	33.01	Pass
			H	20.60		

	S.G. output (dBm)		Antenna gain(dBi)	Cable loss(dB)
Lowest	V	23.42	2.7	4.88
	H	23.39		
Middle	V	24.33	2.7	4.9
	H	23.24		
Highest	V	22.27	2.7	4.92
	H	22.82		

## 6.9 Field strength of spurious radiation measurement

Test Requirement:	FCC part22.917(a) and FCC part24.238(a)
Test Method:	FCC part2.1053
Limit:	-13dBm
Test setup:	<p><b>Below 1GHz</b></p>  <p><b>Above 1GHz</b></p>  <p><b>Substituted method:</b></p> 

<p>Test Procedure:</p>	<ol style="list-style-type: none"> <li>1. The EUT was placed on a non-conductive turntable using a non-conductive support. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and EMI spectrum analyzer.</li> <li>2. During the tests, the antenna height and the EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.</li> <li>3. The frequency range up to tenth harmonic was investigated for each of three fundamental frequency (low, middle and high channels). Once spurious emission was identified, the power of the emission was determined using the substitution method.</li> <li>4. The spurious emissions attenuation was calculated as the difference between radiated power at the fundamental frequency and the spurious emissions frequency.   <math display="block">\text{ERP / EIRP} = \text{S.G. output (dBm)} + \text{Antenna Gain(dB/dBi)} - \text{Cable Loss (dB)}</math> </li> </ol>
<p>Test Instruments:</p>	<p>Refer to section 5.0 for details</p>
<p>Test mode:</p>	<p>Refer to section 6.1 for details</p>
<p>Test results:</p>	<p>Pass</p>

Measurement Data

Test mode:	GSM850		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1648.40	Vertical	-56.42	-13.00	Pass
2472.60	V	-55.14		
3296.80	V	-53.38		
4121.00	V	-51.53		
4945.20	V	-49.74		
1648.40	Horizontal	-55.63	-13.00	Pass
2472.60	H	-54.47		
3296.80	H	-50.02		
4121.00	H	-51.72		
4945.20	H	-48.92		
Test mode:	GSM850		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1673.20	Vertical	-55.70	-13.00	Pass
2509.80	V	-53.96		
3346.40	V	-51.83		
4183.00	V	-53.63		
5019.60	V	-50.08		
1673.20	Horizontal	-55.04	-13.00	Pass
2509.80	H	-53.24		
3346.40	H	-50.53		
4183.00	H	-51.79		
5019.60	H	-49.63		
Test mode:	GSM850		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
1697.60	Vertical	-57.87	-13.00	Pass
2546.40	V	-55.88		
3395.20	V	-52.54		
4244.00	V	-51.15		
5092.80	V	-48.96		
1697.60	Horizontal	-56.73	-13.00	Pass
2546.40	H	-55.58		
3395.20	H	-50.73		
4244.00	H	-51.73		
5092.80	H	-47.25		

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:	PCS1900		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3700.40	Vertical	-57.05	-13.00	Pass
5550.60	V	-53.43		
7400.80	V	-51.40		
9251.00	V	-53.29		
11101.20	V	-49.60		
3700.40	Horizontal	-54.62	-13.00	Pass
5550.60	H	-51.00		
7400.80	H	-52.35		
9251.00	H	-49.71		
11101.20	H	-48.63		
Test mode:	PCS1900		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3760.00	Vertical	-54.77	-13.00	Pass
5640.00	V	-57.23		
7520.00	V	-53.26		
9400.00	V	-51.23		
11280.00	V	-50.08		
3760.00	Horizontal	-55.50	-13.00	Pass
5640.00	H	-52.98		
7520.00	H	-52.39		
9400.00	H	-51.84		
11280.00	H	-49.12		
Test mode:	PCS1900		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result
	Polarization	Level (dBm)		
3819.60	Vertical	-56.94	-13.00	Pass
5729.40	V	-54.33		
7639.20	V	-55.30		
9549.00	V	-52.20		
11458.80	V	-48.09		
3819.60	Horizontal	-56.52	-13.00	Pass
5729.40	H	-55.91		
7639.20	H	-54.26		
9549.00	H	-50.64		
11458.80	H	-47.66		

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.

Test mode:		WCDMA Band V		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1652.80	Vertical	-58.28	-13.00	Pass	
2479.20	V	-56.02			
3305.60	V	-53.77			
4132.00	V	-51.30			
4958.40	V	-49.96			
1652.80	Horizontal	-55.09	-13.00	Pass	
2479.20	H	-53.78			
3305.60	H	-51.20			
4132.00	H	-49.84			
4958.40	H	-47.96			
Test mode:		WCDMA Band V		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1672.80	Vertical	-56.33	-13.00	Pass	
2509.20	V	-54.64			
3345.60	V	-54.27			
4182.00	V	-51.73			
5018.40	V	-50.08			
1672.80	Horizontal	-55.79	-13.00	Pass	
2509.20	H	-52.70			
3345.60	H	-51.39			
4182.00	H	-50.79			
5018.40	H	-48.11			
Test mode:		WCDMA Band V		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
1693.20	Vertical	-56.84	-13.00	Pass	
2539.80	V	-55.28			
3386.40	V	-52.91			
4233.00	V	-54.18			
5079.60	V	-47.08			
1693.20	Horizontal	-54.20	-13.00	Pass	
2539.80	H	-53.62			
3386.40	H	-50.00			
4233.00	H	-51.19			
5079.60	H	-48.41			

Remark :

1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.


Test mode:		WCDMA Band II		Test channel:	Lowest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3704.80	Vertical	-53.01	-13.00	Pass	
5557.20	V	-55.08			
7409.60	V	-53.62			
9262.00	V	-51.07			
11114.40	V	-48.18			
3704.80	Horizontal	-54.91	-13.00	Pass	
5557.20	H	-55.25			
7409.60	H	-51.00			
9262.00	H	-54.06			
11114.40	H	-49.14			
Test mode:		WCDMA Band II		Test channel:	Middle
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3760.00	Vertical	-56.72	-13.00	Pass	
5640.00	V	-55.64			
7520.00	V	-53.04			
9400.00	V	-52.37			
11280.00	V	-48.18			
3760.00	Horizontal	-55.32	-13.00	Pass	
5640.00	H	-56.44			
7520.00	H	-54.10			
9400.00	H	-53.00			
11280.00	H	-50.07			
Test mode:		WCDMA Band II		Test channel:	Highest
Frequency (MHz)	Spurious Emission		Limit (dBm)	Result	
	Polarization	Level (dBm)			
3815.20	Vertical	-56.94	-13.00	Pass	
5722.80	V	-55.66			
7630.40	V	-50.90			
9538.00	V	-49.07			
11445.60	V	-50.69			
3815.20	Horizontal	-56.16	-13.00	Pass	
5722.80	H	-53.01			
7630.40	H	-51.55			
9538.00	H	-50.25			
11445.60	H	-48.14			

Remark:

1. The emission behaviour belongs to narrowband spurious emission.
2. The emission levels of below 1 GHz are very lower than the limit and not show in test report.



## 6.10 Frequency stability V.S. Temperature measurement

Test Requirement:	FCC Part2.1055(a)(1)(b)
Test Method:	FCC Part2.1055(a)(1)(b)
Limit:	2.5ppm
Test setup:	 <p style="text-align: center;"><b>Note :</b> Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> <li>1. The equipment under test was connected to an external DC power supply and input rated voltage.</li> <li>2. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators.</li> <li>3. The EUT was placed inside the temperature chamber.</li> <li>4. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 25°C operating frequency as reference frequency.</li> <li>5. Turn EUT off and set the chamber temperature to -20°C. After the temperature stabilized for approximately 30 minutes recorded the frequency.</li> <li>6. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.</li> </ol>
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass


### Measurement Data

Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	35	0.0420	2.5	Pass
	-20	40	0.0475		
	-10	34	0.0402		
	0	28	0.0329		
	10	32	0.0384		
	20	28	0.0329		
	30	46	0.0548		
	40	41	0.0493		
	50	40	0.0475		
Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	22	0.0258	2.5	Pass
	-20	24	0.0290		
	-10	20	0.0242		
	0	18	0.0211		
	10	19	0.0227		
	20	16	0.0195		
	30	31	0.0370		
	40	26	0.0306		
	50	24	0.0290		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	49	0.0583	2.5	Pass
	-20	56	0.0670		
	-10	47	0.0565		
	0	41	0.0494		
	10	46	0.0550		
	20	40	0.0482		
	30	67	0.0799		
	40	58	0.0699		
	50	55	0.0663		

Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz				
Power supplied (Vdc)	Temperature (°C)	Frequency error		Result
		Hz	ppm	
3.85	-30	34	0.0181	2.5 Pass
	-20	41	0.0218	
	-10	34	0.0181	
	0	28	0.0151	
	10	34	0.0181	
	20	30	0.0157	
	30	49	0.0260	
	40	42	0.0224	
	50	40	0.0212	
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz				
Power supplied (Vdc)	Temperature (°C)	Frequency error		Result
		Hz	ppm	
3.85	-30	38	0.0199	2.5 Pass
	-20	44	0.0233	
	-10	35	0.0186	
	0	29	0.0153	
	10	36	0.0193	
	20	29	0.0153	
	30	50	0.0266	
	40	41	0.0219	
	50	44	0.0233	
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz				
Power supplied (Vdc)	Temperature (°C)	Frequency error		Result
		Hz	ppm	
3.85	-30	102	0.0542	2.5 Pass
	-20	120	0.0637	
	-10	98	0.0521	
	0	81	0.0431	
	10	99	0.0527	
	20	83	0.0443	
	30	134	0.0714	
	40	113	0.0599	
	50	118	0.0629	

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	93	0.0493	2.5	Pass
	-20	83	0.0439		
	-10	71	0.0379		
	0	67	0.0355		
	10	61	0.0325		
	20	53	0.0283		
	30	67	0.0355		
	40	75	0.0397		
	50	71	0.0379		
Reference Frequency: WCDMA Band II Middle channel=9400 channel=1880.0MHz					
Power supplied (Vdc)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
3.85	-30	97	0.1159	2.5	Pass
	-20	139	0.1658		
	-10	158	0.1885		
	0	70	0.0841		
	10	108	0.1295		
	20	120	0.1431		
	30	181	0.2158		
	40	169	0.2022		
	50	203	0.2431		

## 6.11 Frequency stability V.S. Voltage measurement

Test Requirement:	FCC Part2.1055(d)(1)(2)
Test Method:	FCC Part2.1055(d)(1)(2)
Limit:	2.5ppm
Test setup:	 <p style="text-align: center;">Temperature Chamber</p> <p style="text-align: center;">Spectrum analyzer</p> <p style="text-align: center;">Att.</p> <p style="text-align: center;">EUT</p> <p style="text-align: center;">Variable Power Supply</p> <p><b>Note :</b> Measurement setup for testing on Antenna connector</p>
Test procedure:	<ol style="list-style-type: none"> <li>1. Set chamber temperature to 25°C. Use a variable DC power source to power the EUT and set the voltage to rated voltage.</li> <li>2. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.</li> <li>3. Reduce the input voltage to specified extreme voltage variation (+/- 15%) and endpoint, record the maximum frequency change.</li> </ol>
Test Instruments:	Refer to section 5.0 for details
Test mode:	Refer to section 6.1 for details
Test results:	Pass

Measurement Data

Reference Frequency: GSM850 (GSM link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	44	0.0531	2.5	Pass
	3.85	51	0.0610		
	3.5	58	0.0690		
Reference Frequency: GSM850 (GPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	32	0.0377	2.5	Pass
	3.85	23	0.0274		
	3.5	26	0.0308		
Reference Frequency: GSM850 (EGPRS 1 link) Middle channel=190 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	26	0.0313	2.5	Pass
	3.85	30	0.0357		
	3.5	33	0.0399		



Reference Frequency: PCS1900 (GSM link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	46	0.0244	2.5	Pass
	3.85	56	0.0298		
	3.5	56	0.0298		
Reference Frequency: PCS1900 (GPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	43	0.0230	2.5	Pass
	3.85	32	0.0171		
	3.5	34	0.0183		
Reference Frequency: PCS1900 (EGPRS 1 link) Middle channel=661 channel=1880MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	62	0.0329	2.5	Pass
	3.85	71	0.0378		
	3.5	71	0.0380		

Reference Frequency: WCDMA Band V Middle channel=4183 channel=836.6MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	54	0.0288	2.5	Pass
	3.85	46	0.0243		
	3.5	51	0.0269		
Reference Frequency: WCDMA Band II Middle channel=940 channel=1880.0MHz					
Temperature (°C)	Power supplied (Vdc)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
25	4.25	14	0.0161	2.5	Pass
	3.85	17	0.0203		
	3.5	10	0.0120		



## 7 Test Setup Photo

Radiated Emission



## 8 EUT Constructional Details

Reference to the test report No. GTS201805000172F01

-----End-----