

# FCC REPORT

**Applicant:** Shenzhen Jin Yu Electronic Technology Co., Ltd

**Address of Applicant:** 21A, Haowei Technology Building, Keji South 8th Road, Nanshan District, Shenzhen, China

## Equipment Under Test (EUT)

**Product Name:** Mobile Phone

**Model No.:** K1, G5506

**FCC ID:** 2AJZT-K1

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart B

**Date of sample receipt:** 08 Feb., 2017

**Date of Test:** 08 Feb., to 20 Feb., 2017

**Date of report issued:** 20 Feb., 2017

**Test Result:** Pass \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang  
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

## 2 Version

Version No.	Date	Description
00	20 Feb., 2017	Original

**Tested by:**



**Date:**

20 Feb., 2017

**Test Engineer**

**Reviewed by:**



**Date:**

20 Feb., 2017

**Project Engineer**

### **3 Contents**

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 CONTENTS.....</b>	<b>3</b>
<b>4 TEST SUMMARY.....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION .....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS .....	6
5.6 LABORATORY FACILITY.....	6
5.7 LABORATORY LOCATION .....	6
5.8 TEST INSTRUMENTS LIST.....	7
<b>6 TEST RESULTS AND MEASUREMENT DATA.....</b>	<b>8</b>
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION.....	11
<b>7 TEST SETUP PHOTO .....</b>	<b>17</b>
<b>8 EUT CONSTRUCTIONAL DETAILS .....</b>	<b>18</b>

## 4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass

*Pass: The EUT complies with the essential requirements in the standard.*

## 5 General Information

### 5.1 Client Information

Applicant:	Shenzhen Jin Yu Electronic Technology Co., Ltd
Address of Applicant:	21A, Haowei Technology Building, Keji South 8th Road, Nanshan District, Shenzhen, China
Manufacturer	Shenzhen Jin Yu Electronic Technology Co., Ltd
Address of Manufacturer:	21A, Haowei Technology Building, Keji South 8th Road, Nanshan District, Shenzhen, China

### 5.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	K1, G5506
Power supply:	Rechargeable Li-ion Battery DC3.8V-3000mAh
AC adapter :	Model: CLV-14 Input: AC100-300V 50/60Hz 0.15A Output: DC 5.0V, 1A
Remark:	The No.: K1, G5506 were identical inside, the electrical circuit design, layout, components used and internal wiring, with only difference being model name.

### 5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode
GPS mode	Keep the EUT in GPS receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

### 5.4 Measurement Uncertainty

Items	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

## 5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
HP	Printer	CB495A	05257893	DoC
MERCURY	Wireless router	MW150R	12922104015	FCC ID
NAKAMICHI	Bluetooth earphone	T8	N/A	FCC ID

## 5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **FCC - Registration No.: 817957**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 817957, February 27, 2012.

• **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

• **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

## 5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,  
Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282

Fax: +86-755-23116366

## 5.8 Test Instruments list

<b>Radiated Emission:</b>						
<b>Item</b>	<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal. Date (mm-dd-yy)</b>	<b>Cal. Due date (mm-dd-yy)</b>
1	3m SAC	SAEMC	9(L)*6(W)* 6(H)	CCIS0001	08-23-2014	08-22-2017
2	BiConiLog Antenna	SCHWARZBECK	VULB9163	CCIS0005	03-25-2016	03-25-2017
3	Horn Antenna	SCHWARZBECK	BBHA9120D	CCIS0006	03-25-2016	03-25-2017
4	Pre-amplifier (10kHz-1.3GHz)	HP	8447D	CCIS0003	04-01-2016	03-31-2017
5	Pre-amplifier (1GHz-18GHz)	Compliance Direction Systems Inc.	PAP-1G18	CCIS0011	04-01-2016	03-31-2017
6	Spectrum analyzer 9k-30GHz	Rohde & Schwarz	FSP30	CCIS0023	03-28-2016	03-28-2017
7	EMI Test Receiver	Rohde & Schwarz	ESRP7	CCIS0167	03-28-2016	03-28-2017
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	N/A	N/A	CCIS0018	04-01-2016	03-31-2017
10	Coaxial Cable	N/A	N/A	CCIS0020	04-01-2016	03-31-2017

<b>Conducted Emission:</b>						
<b>Item</b>	<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal.Date (mm-dd-yy)</b>	<b>Cal.Due date (mm-dd-yy)</b>
1	Shielding Room	ZhongShuo Electron	11.0(L)x4.0(W)x3.0(H)	CCIS0061	08-23-2014	08-22-2017
2	EMI Test Receiver	Rohde & Schwarz	ESCI	CCIS0002	03-24-2016	03-24-2017
3	LISN	CHASE	MN2050D	CCIS0074	03-26-2016	03-26-2017
4	Coaxial Cable	CCIS	N/A	CCIS0086	04-01-2016	03-31-2017
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A


## 6 Test results and Measurement Data

### 6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107					
Test Method:	ANSI C63.4:2014					
Test Frequency Range:	150kHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9kHz, VBW=30kHz					
Limit:	Frequency range (MHz)	Limit (dB $\mu$ V)				
		Quasi-peak	Average			
	0.15-0.5	66 to 56*	56 to 46*			
	0.5-5	56	46			
	0.5-30	60	50			
* Decreases with the logarithm of the frequency.						
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>40cm</p> <p>80cm</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>EMI Receiver</p> <p>Filter</p> <p>AC power</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>					
Test procedure	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). They provide a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.</li> </ol>					
Test environment:	Temp.:	23 °C	Humid.:	56%	Press.:	101kPa
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					

**Measurement data:**

Line:




Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN LINE  
 EUT : Mobile Phone  
 Model : K1  
 Test Mode : PC mode  
 Power Rating : AC 120V/50Hz  
 Environment : Temp: 23 °C Huni:56% Atmos:101KPa  
 Test Engineer: Mike  
 Remark :

Freq	Read	LISN	Cable	Limit	Over	Remark
	Level	Factor	Loss			
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.154	21.35	0.14	10.78	32.27	55.78 -23.51 Average
2	0.158	27.35	0.14	10.78	38.27	65.56 -27.29 QP
3	0.253	13.81	0.16	10.75	24.72	51.64 -26.92 Average
4	2.946	24.60	0.33	10.92	35.85	56.00 -20.15 QP
5	2.946	18.30	0.33	10.92	29.55	48.00 -16.45 Average
6	8.776	15.49	0.32	10.89	26.70	50.00 -23.30 Average
7	9.107	24.81	0.32	10.90	36.03	60.00 -23.97 QP
8	11.870	25.88	0.28	10.92	37.08	60.00 -22.92 QP
9	17.383	29.31	0.30	10.91	40.52	60.00 -19.48 QP
10	17.383	22.46	0.30	10.91	33.67	50.00 -16.33 Average
11	20.162	29.88	0.34	10.93	41.15	60.00 -18.85 QP
12	22.775	24.65	0.35	10.89	35.89	50.00 -14.11 Average

**Notes:**

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.

Neutral:





Site : CCIS Shielding Room  
 Condition : FCC PART15 B QP LISN NEUTRAL  
 EUT : Mobile Phone  
 Model : K1  
 Test Mode : PC mode  
 Power Rating : AC 120V/50Hz  
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa  
 Test Engineer: Mike  
 Remark :

	Read Freq	LISN Level	Cable Factor	Limit Loss	Line Level	Over Line Limit	Remark
	MHz	dBuV		dB	dBuV	dBuV	
1	0.154	21.24	0.12	10.78	32.14	55.78	-23.64 Average
2	0.158	26.44	0.13	10.78	37.35	65.56	-28.21 QP
3	0.258	13.70	0.17	10.75	24.62	51.51	-26.89 Average
4	0.502	8.39	0.24	10.76	19.39	46.00	-26.61 Average
5	2.900	19.54	0.30	10.92	30.76	46.00	-15.24 Average
6	3.025	25.59	0.31	10.92	36.82	56.00	-19.18 QP
7	7.025	23.99	0.32	10.80	35.11	60.00	-24.89 QP
8	8.869	24.03	0.27	10.89	35.19	60.00	-24.81 QP
9	9.011	15.77	0.26	10.90	26.93	50.00	-23.07 Average
10	13.841	24.23	0.26	10.91	35.40	60.00	-24.60 QP
11	16.398	28.07	0.27	10.91	39.25	60.00	-20.75 QP
12	23.018	23.32	0.25	10.89	34.46	50.00	-15.54 Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.


## 6.2 Radiated Emission

Test Requirement:	FCC Part 15 B Section 15.109								
Test Method:	ANSI C63.4:2014								
Test Frequency Range:	30MHz to 26000MHz								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)								
Receiver setup:	Frequency	Detector	RBW	VBW	Remark				
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value				
	Above 1GHz	Peak	1MHz	3MHz	Peak Value				
Limit:	Frequency	Limit (dBuV/m @3m)		Remark					
	30MHz-88MHz	40.0		Quasi-peak Value					
	88MHz-216MHz	43.5		Quasi-peak Value					
	216MHz-960MHz	46.0		Quasi-peak Value					
	960MHz-1GHz	54.0		Quasi-peak Value					
	Above 1GHz	54.0		Average Value					
Test setup:	74.0								
	Peak Value								
Below 1GHz									
Above 1GHz									

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Test environment:	Temp.:	25 °C	Humid.:	55%	Press.:	1 01kPa
Test Instruments:	Refer to section 5.7 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Passed					
Remark:	All of the observed value above 6GHz were the noise floor , which were not recorded					

**Measurement Data:****Below 1GHz**


Horizontal:



Site : 3m chamber  
Condition : FCC PART15 CLASS B 3m VULB9163(30M3G) HORIZONTAL  
EUT : MobilePhone  
Model : K1  
Test mode : PC mode  
Power Rating : AC120V/60Hz  
Environment : Temp:25.5°C Huni:55% 101KPa  
Test Engineer: Mike  
REMARK :

Freq	ReadAntenna		Cable Preamp		Limit Line	Over Limit	Remark
	Level	Factor	Loss	Factor			
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	46.503	41.83	16.96	1.28	29.85	30.22	40.00 -9.78 QP
2	165.487	55.48	9.84	2.62	29.09	38.85	43.50 -4.65 QP
3	191.745	53.41	9.79	2.81	28.89	37.12	43.50 -6.38 QP
4	314.377	49.13	13.12	2.98	28.48	36.75	46.00 -9.25 QP
5	365.539	45.90	14.72	3.09	28.63	35.08	46.00 -10.92 QP
6	576.644	44.21	18.31	3.92	29.01	37.43	46.00 -8.57 QP

Vertical:




Site : 3m chamber  
Condition : FCC PART15 CLASS B 3m VULB9163 (30M3G) VERTICAL  
EUT : MobilePhone  
Model : K1  
Test mode : PC mode  
Power Rating : AC120V/60Hz  
Environment : Temp:25.5°C Huni:55% 101KPa  
Test Engineer: Mike  
REMARK :

Freq	ReadAntenna	Cable	Preamp	Limit	Over	Remark
	Level	Factor	Loss			
MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	46.503	47.15	16.96	1.28	29.85	35.54
2	53.318	46.90	13.27	1.32	29.81	31.68
3	151.597	51.89	10.53	2.53	29.21	35.74
4	365.539	53.42	14.72	3.09	28.63	42.60
5	576.644	46.35	18.31	3.92	29.01	39.57
6	758.041	44.29	20.43	4.36	28.43	40.65

**Above 1GHz**


Horizontal:



Site : 3m chamber  
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) HORIZONTAL  
 EUT : MobilePhone  
 Model : K1  
 Test mode : PC mode  
 Power Rating : AC120V/60Hz  
 Environment : Temp:25.5°C Huni:55% 101KPa  
 Test Engineer: Mike  
 REMARK :

Freq	Read		Antenna	Cable	Preamp	Limit Level	Line	Over Limit	Remark
	Level	Factor		Loss	Factor				
MHz	dBuV	dB/m		dB	dB	dBuV/m	dBuV/m	dB	
1	3239.211	49.32	26.72	5.47	41.40	40.11	74.00	-33.89	Peak
2	3239.211	39.72	26.72	5.47	41.40	30.51	54.00	-23.49	Average
3	4139.249	50.09	32.90	6.30	41.81	47.48	74.00	-26.52	Peak
4	4139.249	41.22	32.90	6.30	41.81	38.61	54.00	-15.39	Average
5	4989.431	50.55	36.84	6.93	41.88	52.44	74.00	-21.56	Peak
6	4989.431	40.98	36.84	6.93	41.88	42.87	54.00	-11.13	Average

Vertical:



Site : 3m chamber  
Condition : FCC PART 15 (PK) 3m BBHA9120(1G18) VERTICAL  
EUT : MobilePhone  
Model : K1  
Test mode : PC mode  
Power Rating : AC120V/60Hz  
Environment : Temp:25.5°C Huni:55% 101KPa  
Test Engineer: Mike  
REMARK :

Freq	Read	Antenna	Cable	Preamp	Limit	Over	Remark
	MHz	Level	Factor	Loss			
1	3214.096	50.42	26.60	5.44	41.40	41.06	74.00 -32.94 Peak
2	3214.096	38.45	26.60	5.44	41.40	29.09	54.00 -24.91 Average
3	3874.255	50.72	31.25	6.09	41.80	46.26	74.00 -27.74 Peak
4	3874.255	39.87	31.25	6.09	41.80	35.41	54.00 -18.59 Average
5	4950.745	51.13	36.64	6.90	41.86	52.81	74.00 -21.19 Peak
6	4950.745	40.12	36.64	6.90	41.86	41.80	54.00 -12.20 Average