



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.249 TEST REPORT

For

Keeson Technology Corporation Limited

No. 195, Yuanfeng East Road, Wangjiangjing, Xiuzhou District, Jiaxing City, China 314000

FCC ID: 2AK23RF502A



Report Type: Original Report	Product Type: REMOTE CONTROL
Test Engineer:	<u>Tyrone Wang</u> 
Report Number:	<u>RSHA210827002-00A</u>
Report Date:	<u>2021-09-01</u>
Reviewed By:	<u>Chris Wang</u> 
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY.....	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE.....	5
BLOCK DIAGRAM OF TEST SETUP.....	6
SUMMARY OF TEST RESULTS.....	8
TEST EQUIPMENT LIST	9
FCC§15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION.....	11
APPLICABLE STANDARD	11
EUT SETUP.....	11
TEST EQUIPMENT SETUP	12
TEST PROCEDURE	12
LEVEL & OVER LIMIT CALCULATION	13
TEST RESULTS SUMMARY.....	13
TEST DATA	13
FCC §15.215(C) – 20 DB BANDWIDTH TESTING.....	21
APPLICABLE STANDARD	21
TEST PROCEDURE	21
TEST DATA	21

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Keeson Technology Corporation Limited
Tested Model:	RF502A
Product Type:	REMOTE CONTROL
Power Supply:	DC 4.5V
RF Function:	2.4G SRD
Operating Band/Frequency:	2403-2480MHz
Channel Number:	78
Channel Separation:	1MHz
Antenna Type:	PCB antenna
*Maximum Antenna Gain:	1.0 dBi

Note: The maximum antenna gain was provided by the applicant.*

All measurement and test data in this report was gathered from production sample serial number: RSHA210827002-1. (Assigned by BACL(Kunshan). The EUT was received on 2021-08-27.)

Objective

This type approval report is prepared on behalf of *Keeson Technology Corporation Limited* in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209, 15.215 and 15.249 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11 dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Justification

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2403	40	2442
2	2404
...
38	2440	77	2479
39	2441	78	2480

EUT was tested with Channel 1, 40 and 78.

All buttons triggered the same RF parameters (Contain bandwidth, power level, duty cycle).

EUT Exercise Software

No software was used during the test.

*Power level setting: Default

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
15.205, §15.209, §15.249	Radiated Emissions& Out of Band Emission	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 2#)					
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
MICRO-TRONICS	Notch Filter	BRM50702	G024	2021-08-05	2022-08-04
A.H.Systems, inc	Amplifier	PAM-0118P	512	2021-08-14	2022-08-13
SELECTOR	Amplifier	EM18G40G	060726	2021-08-14	2022-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2021-08-15	2022-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2021-08-15	2022-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2021-08-15	2022-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2021-08-15	2022-08-14
Radiated Emission Test (Chamber 3#)					
Sonoma Instrument	Amplifier	310N	185700	2021-08-14	2022-08-13
Rohde & Schwarz	EMI Test Receiver	ESR	102454	2020-11-27	2021-11-26
Sunol Sciences	Hybrid Antenna	JB3	A090314-1	2020-08-05	2023-08-04
Sunol Sciences	Hybrid Antenna	JB3	A090314-2	2020-01-07	2023-01-06
Sunol Sciences	Hybrid Antenna	JB3	A060217	2020-11-28	2023-11-27
Audix	Test Software	e3	V9	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-11	011	2021-08-15	2022-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2021-07-30	2022-07-29
Narda	Attenuator	10dB	010	2020-10-10	2021-10-09
Keeson Technology	RF Cable	Keeson Technology C01	C01	Each Time	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT has a PCB antenna for SRD, which was permanently attached to the EUT, antenna gain is 1.0 dBi, fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS& OUT OF BAND EMISSION

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:


Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24GHz-24.25GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

Test Equipment Setup

The system was investigated from 30 MHz to 25GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	QP
Above 1GHz	1MHz	3 MHz	PK
	1MHz	3 MHz	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Level & Over Limit Calculation for Below 1GHz

The Level is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Factor = Antenna Factor + Cable Loss - Amplifier Gain

Level = Read level + Factor

The “Over Limit” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit of 7 dB means the emission is 7 dB above the limit. The equation for Over Limit calculation is as follows:

Over Limit = Level – Limit

Corrected Amplitude & Margin Calculation for Above 1GHz

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249.

Test Data

Environmental Conditions

Temperature:	21.2°C
Relative Humidity:	51%
ATM Pressure:	101.6kPa

The testing was performed by Tyrone Wang on 2021-08-30.


Test Mode: Transmitting

Spurious Emission Test:

30MHz-1GHz:


*Pre-scan with low, middle and high channels of operation in the X, Y and Z axes of orientation, the worst case **low channel of operation in Y-axis of orientation** was recorded.*

Horizontal:



	Read Freq	Read Level	Factor	Level	Limit Line	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg	
1	30.85	23.97	-4.83	19.14	40.00	-20.86	100	88	QP
2	34.88	24.36	-7.66	16.70	40.00	-23.30	200	235	QP
3	125.89	24.45	-10.83	13.62	43.50	-29.88	200	78	QP
4	164.91	25.37	-11.83	13.54	43.50	-29.96	200	257	QP
5	213.02	25.03	-12.32	12.71	43.50	-30.79	100	154	QP
6	348.03	23.90	-9.65	14.25	46.00	-31.75	100	216	QP

Vertical:



	Read Freq	Read Level	Read Factor	Limit Level	Over Limit	APos	TPos	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	deg
1	30.53	23.28	-4.61	18.67	40.00	-21.33	200	217 QP
2	33.92	24.31	-6.98	17.33	40.00	-22.67	100	332 QP
3	124.57	24.46	-10.85	13.61	43.50	-29.89	200	230 QP
4	144.84	25.17	-11.70	13.47	43.50	-30.03	100	215 QP
5	182.56	25.41	-12.02	13.39	43.50	-30.11	100	164 QP
6	304.61	24.25	-8.67	15.58	46.00	-30.42	100	247 QP

1GHz-18GHz


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded.)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBµV/m) = Corrected Factor (dB/m) + Reading (dBµV)
 Margin (dB) = Limit (dBµV/m) – Corrected Amplitude (dBµV/m)

Low Channel: 2403MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1244.800000	---	26.22	200.0	H	345.0	-7.8	54.00	27.78
1244.800000	35.99	---	200.0	H	345.0	-7.8	74.00	38.01
2050.600000	---	30.26	150.0	V	220.0	-4.8	54.00	23.74
2050.600000	38.83	---	150.0	V	220.0	-4.8	74.00	35.17
4804.600000	---	43.95	150.0	V	259.0	0.6	54.00	10.05
4804.600000	51.17	---	150.0	V	259.0	0.6	74.00	22.83
7208.400000	---	50.62	200.0	V	73.0	5.3	54.00	3.38
7208.400000	55.60	---	200.0	V	73.0	5.3	74.00	18.40
11203.400000	---	44.00	150.0	V	130.0	10.0	54.00	10.00
11203.400000	51.02	---	150.0	V	130.0	10.0	74.00	22.98
17653.200000	---	47.25	200.0	V	22.0	14.1	54.00	6.75
17653.200000	55.23	---	200.0	V	22.0	14.1	74.00	18.77

Middle Channel: 2442MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Max Peak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1763.300000	40.23	---	150.0	H	225.0	-5.6	74.00	33.77
1763.300000	---	32.61	150.0	H	225.0	-5.6	54.00	21.39
3476.900000	42.01	---	150.0	V	338.0	-1.7	74.00	31.99
3476.900000	---	32.42	150.0	V	338.0	-1.7	54.00	21.58
4882.800000	53.13	---	150.0	H	161.0	0.4	74.00	20.87
4882.800000	---	47.34	150.0	H	161.0	0.4	54.00	6.66
7325.700000	---	49.05	150.0	H	72.0	5.1	54.00	4.95
7325.700000	54.22	---	150.0	H	72.0	5.1	74.00	19.78
11240.800000	51.80	---	150.0	H	270.0	10.1	74.00	22.20
11240.800000	---	42.29	150.0	H	270.0	10.1	54.00	11.71
17580.100000	---	46.48	200.0	V	22.0	14.3	54.00	7.52
17580.100000	55.69	---	200.0	V	22.0	14.3	74.00	18.31

High Channel: 2480MHz

Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1205.700000	---	26.04	200.0	V	46.0	-8.0	54.00	27.96
1205.700000	35.43	---	200.0	V	46.0	-8.0	74.00	38.57
1935.000000	---	30.42	200.0	H	0.0	-5.1	54.00	23.58
1935.000000	38.74	---	200.0	H	0.0	-5.1	74.00	35.26
3033.200000	---	32.53	150.0	V	142.0	-2.0	54.00	21.47
3033.200000	41.23	---	150.0	V	142.0	-2.0	74.00	32.77
4959.300000	---	44.76	150.0	H	310.0	0.3	54.00	9.24
4959.300000	50.44	---	150.0	H	310.0	0.3	74.00	23.56
7439.600000	56.11	---	200.0	V	191.0	4.9	74.00	17.89
7439.600000	---	51.93	200.0	V	191.0	4.9	54.00	2.07
11655.600000	---	42.07	200.0	H	0.0	10.4	54.00	11.93
11655.600000	51.41	---	200.0	H	0.0	10.4	74.00	22.59

18GHz-25GHz:


(Pre-scan with low, middle and high channels of operation in the X,Y and Z axes of orientation, the worst case low channel of operation in Y-axis of orientation was recorded)

Horizontal



Date: 30.AUG.2021 17:58:02

Vertical



Date: 30.AUG.2021 18:06:59

Fundamental Test & Out-of-band Emissions Test:*(Pre-scan in the X, Y and Z axes of orientation, the worst case Y-axis of orientation was recorded.)*

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	Max Peak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)	Degree			
Low Channel: 2403MHz								
2403.00	87.79	---	250	H	241	-2.9	114	26.21
2403.00	---	87.68	250	H	241	-2.9	94	6.32
2403.00	87.81	---	200	V	181	-2.9	114	26.19
2403.00	---	87.71	200	V	181	-2.9	94	6.29
2400.00	---	51.95	150	H	110	-2.9	54	2.05
2400.00	54.68	---	150	H	110	-2.9	74	19.32
Middle Channel: 2442MHz								
2442.00	85.63	---	150	H	5	-2.8	114	28.37
2442.00	---	85.58	150	H	5	-2.8	94	8.42
2442.00	85.66	---	100	V	261	-2.8	114	28.34
2442.00	---	85.61	100	V	261	-2.8	94	8.39
High Channel: 2480MHz								
2480.00	83.59	---	200	H	354	-2.5	114	30.41
2480.00	---	83.51	200	H	354	-2.5	94	10.49
2480.00	83.62	---	200	V	42	-2.5	114	30.38
2480.00	---	83.54	200	V	42	-2.5	94	10.46
2483.50	---	48.86	200	H	259	-2.5	54	5.14
2483.50	52.76	---	200	H	259	-2.5	74	21.24

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data

Environmental Conditions

Temperature:	22.4°C
Relative Humidity:	50%
ATM Pressure:	101.3kPa


The testing was performed by Tyrone Wang on 2021-08-30.

Test Result: Compliant.

Test Mode: Transmitting


Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2403	1.081
Middle	2442	1.077
High	2480	1.016

Low Channel




Date: 30.AUG.2021 18:01:12

Middle Channel



Date: 30.AUG.2021 18:02:22

High Channel



Date: 30.AUG.2021 18:03:23

Declarations

- 1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.
- 2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
- 3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
- 4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
- 5: This report cannot be reproduced except in full, without prior written approval of the Company.
- 6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

***** END OF REPORT *****