



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Zedly, Inc.

Model: Trakkit

Description: Wireless Tracking Device

Serial Number: NA

FCC ID: 2AK2G-TK-GS1

To

FCC Part 1.1310

Date of Issue: August 17, 2017

On the behalf of the applicant:

Zedly, Inc.
180 Matterhorn Dr
Park City, UT 84098

Attention of:

Tom Roberts
Ph: (954)609-9961
Email: tom@uviewit.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1760015

Poona Saber
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	July 11, 2017	Poona Saber	Original Document

ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: Trakkit

Description: Wireless Tracking Device

Firmware: NA

Software: NA

Serial Number: NA

Additional Information: EUT is wireless access point with an 802.11 b, g and n radio incorporated.

EUT Operation during Tests

For testing purposes EUT was put on continuous modulated b, g and n mode.



Source Based Time Averaged Power Calculation

Average Power calculations

Average Power = Peak Power * duty-cycle%

Tuned Frequency (MHz)	Peak Output power EIRP (dBm)	Antenna Gain (dBi)	Peak Output Power Conducted (mW)	Duty Cycle (%)	Average Power (mW)
2462	14.04	3.2	12.13	72	8.73



EUT comes to close proximity of human's body and is investigated below for SAR exclusion per KDB 447498

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* $\leq$ 50 mm are determined by:

$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})]}{[\sqrt{f(\text{GHz})}]} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁶
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

$$(8.73/5) \times \sqrt{2.462} = 2.619 \leq 3.0$$

Note: The test exclusions are applicable only when the minimum *test separation distance* is $\leq$ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is $<$ 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

END OF TEST REPORT