

RF Exposure Evaluation Report

Product : Rat Riddance Connect
Trade mark : Rentokil
Model/Type reference : 304885
Serial Number : N/A
Report Number : EED32K00334202
FCC ID : 2AK3PGSD-500349
Date of Issue : Jan. 02, 2019
47 CFR Part 1.1307
Test Standards : 47 CFR Part 1.1310
KDB447498D01v06
Test result : PASS

Prepared for:

Rentokil Initial 1927 plc
Riverbank, Meadows Business Park, Camberley, GU17 9AB

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Tested by:

Peter
Peter

Compiled by:

Tom-Chen
Tom-Chen

Reviewed by:

Max Liang
Max Liang

Approved by:

Kevin Yang
Kevin yang

Date:

Jan. 02, 2019



Check No.:2447611580

2 Version

Version No.	Date	Description
00	Jan. 02, 2019	Original

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	4
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.1.1 Limits.....	6
5.1.2 Test Procedure.....	6
5.1.3 EUT RF Exposure Evaluation.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	8

4 General Information

4.1 Client Information

Applicant:	Rentokil Initial 1927 plc
Address of Applicant:	Riverbank, Meadows Business Park, Camberley, GU17 9AB
Manufacturer:	Rentokil Initial 1927 plc
Address of Manufacturer:	Riverbank, Meadows Business Park, Camberley, GU17 9AB
Factory:	Rentokil Initial 1927 plc
Address of Factory:	Riverbank, Meadows Business Park, Camberley, GU17 9AB

4.2 General Description of EUT

Product Name:	Rat Riddance Connect
Model No.(EUT):	304885
Trade Mark:	Rentokil
EUT Supports Radios application:	915.25MHz to 927.5MHz

4.3 Product Specification subjective to this standard

Frequency Range:	915.25MHz to 927.5MHz
Modulation Type:	FSK Chrip
Test Power Grade:	N/A
Test Software of EUT:	N/A
Antenna Type:	Integral antenna
Antenna gain:	-1.85dBi
Power Supply:	Battery, DC 4.5V
Conducted Peak Output Power:	22.56dBm The Conducted Peak Output Power data refer to the report EED32K00334201
Firmware version of the sample:	V1.8(Manufacturer declare)
Hardware version of the sample:	EB3(Manufacturer declare)
Sample Received Date:	Dec. 14, 2018
Sample tested Date:	Dec. 17, 2018 to Dec. 20, 2018
The tested sample(s) and the sample information are provided by the client.	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation:

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R= distance to the centre of radiation of the antenna

EIRP = P*G

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user.

Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. Therefore, the S of the device is calculated with R=20cm, and if it is below the limit S, then we can conclude the device complies with the rules.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.

5.1.3 EUT RF Exposure Evaluation

Antenna Gain: -1.85dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power(dBm)	Gain (dBi)	EIRP* (dBm)	EIRP (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)	Result
Lowest	915.25	22.56	-1.85	20.71	117.76	20	0.023	1.0	Pass

Note: Refer to report No. EED32K00334201 for EUT test Max Conducted Peak Output Power value.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32K00334201 for EUT external and internal photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.