

0007DA456789

**PLATINUM**

**996**

JOHN SMITH

PNRADR

**TO:** FRANKFURT

**PRI0**

**FRA**

DA 2240 23SEP 1340

**VIA:**

**ORD**

DA 1243 23SEP 0850

**VIA:**



## FLEXIBLE MOUNTING

By mounting your BAGTAG device on a strap, you can use one device for multiple bags. It is recommended to use this method for all soft bags (such as weekend-bags or duffel bags) and leather bags. When you cannot find a flat surface, large enough on your bag to permanently mount your BAGTAG device, it is also recommended to mount your device on a strap.

Required items:

1 x BAGTAG device

1 x Adapter plate

1 x Baggage strap (not included)

1 x Cleaning wipe / degreaser (not included)



Installation steps:

Clean the side of the adapter plate that contains a gap. Then, put the adapter plate on a flat surface while making sure the plate's side with the gap is facing upward.





Align the BAGTAG directly above the installed adapter plate and press the device firmly onto the plate. Let the BAGTAG device cure for 24 hours and you are good to go!



When applying your baggage belt with mounted BAGTAG device, make sure the device's screen is readable and the handle of your bag is still good to use.

## COMPLIANCE STATEMENT (part 15.19)

This device complies with part 15 of the FCC Rules  
Operation is subject to the following two conditions:

- (1) this device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

## WARNING (part 15.21)

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

## RF EXPOSURE (OET bulletin 65)

To comply with FCC RF exposure requirements for mobile transmitting devices, this transmitter should only be used or installed at locations where there is at least 20cm separation distance between the antenna and all persons.

## MANUFACTURER PERFORMANCE SPECIFICATION

The BAGTAG device has been certified according to IEC 61000-4-3, the UHF RFID scanning function of the Airport interface of the BAGTAG device could be sensitive to radiated emissions between 600Mhz and 700Mhz resulting in performance criterion B. After the influence of the emissions in the afore mentioned spectrum have stopped, the BAGTAG device will self-recover its functionality with respect to the UHF RFID scanning function without operator intervention. During normal operating conditions the afore mentioned emissions should not be present in the environment where the BAGTAG is used with the UHF RFID scanning function.

## DISCLAIMER

1. Nothing in this disclaimer excludes or limits our liability for:

- (a) death or personal injury caused by our negligence;
- (b) fraud or fraudulent misrepresentation;
- (c) any other matter for which it would be illegal for us to exclude or attempt to exclude our liability.

2. Subject to 1(a) to 1(f) of this section above, we will not be liable for losses that result from our failure to comply with these terms and conditions that fall into the following categories:

- (a) loss of income or revenue;
- (b) loss of business;
- (c) loss of profits;
- (d) loss of anticipated savings;
- (e) loss of data;
- (g) loss of baggage
- (f) waste of management or office time or
- (h) indirect, consequential or special loss or damage.

However, this will not prevent claims for loss of or damage to your physical property that are foreseeable or any other claims for direct loss that are not excluded by categories 2(a) to 2(h) of this section above.

BAGTAG will not be liable for:

- 3(a) any losses that result from damage to or malfunctioning of a BAGTAG electronic baggage tag,
- 3(b) any losses that result from the information that a user stores on his BAGTAG electronic baggage tag
- 3(c) any losses that result from the loss of information that a user stores on his BAGTAG electronic baggage tag
- 3(d) any losses that result from the baggage information provided by an airline to the user to be stored on his BAGTAG electronic baggage tag.
- 3(e) for any losses or damage when a BAGTAG electronic baggage tag gets disconnected or removed from the baggage item on which the BAGTAG electronic baggage tag was installed.



USER MANUAL

## TABLE OF CONTENTS

Quick Start	1
What's in the box	1
Functionality	2
Button	2
Installation Guide	3
Compliance Statement	9
Manufacturer Performance Specification	9
Disclaimer	10

### QUICK START

To set up your BAGTAG for the first time, please make sure you have downloaded the BAGTAG mobile application from the Apple App Store or Google Play Store. iPhones running iOS 8.4.1 or higher and Android devices running on Android 4.4 are supported. By following the steps in the BAGTAG app, you can setup your account and register your BAGTAG device to your account.

### WHAT'S IN THE BOX

In the box of your BAGTAG device you should find:

- Your BAGTAG device
- 4x screws
- 4x screw studs
- User manual
- Warranty

## FUNCTIONALITY

Welcome to your BAGTAG device. The BAGTAG device works in combination with the BAGTAG app and only works with connected airlines. For a list of connected airlines, please keep updated through our website.

## BUTTON

Your BAGTAG device has a button as indicated



Pressing the button once activates the Bluetooth low energy module inside your device for a duration of 15 seconds. Within that 15 seconds you can use your mobile phone to update the information on your BAGTAG device. Make sure you have Bluetooth enabled on your mobile device before attempting to connect to your BAGTAG device.

Pressing the button three times in rapid succession blanks the BAGTAG screen. This means your baggage information is no longer displayed on the screen.



# INSTALLATION GUIDE

BAGTAG advises to use permanent mounting method 1 whenever possible. Permanent mounting method 2 is advised only when your suitcase contains a flat surface large enough to fit the BAGTAG. Please note, that the adhesive tape on you BAGTAG device is not to be re-used.

## PERMANENT MOUNTING – METHOD 1

Relevant for soft and hard shell cases. This mounting method can be used on fabric and hard shell cases that contain a clear and flat surface at least the size of your BAGTAG device.

Required items:

1 x BAGTAG device

1 x Adapter plate

4 x Self-tapping screws

4 x Screw nuts

1 x Screwdriver (not included)

1 x Cleaning wipe / degreaser (not included)



Installation steps:

The preferred location to attach the adapter plate is right next to or close to the handle that is found on the long side of your suitcase. If there is no room next to the handle, move the tag along the long side of your suitcase until you find a clear and flat surface to fit the adapter plate. Make sure the handle of your suitcase can still function properly. Note that your adapter plate's gap must face downward. Carefully select the desired location of the adapter plate.





Keep it firmly in place while using the self-tapping screws to fasten it.



Once you have fastened the adapter plate on your bag using the screws, place the screw nuts on the inside of your bag over the sharp ends of the screws.



Then clean the upward facing surface of the adapter plate, preferably using degreaser. After cleaning the adapter plate, wait until the surface is completely dry. Then, remove all three segments of the cover paper on the back-side of your BAGTAG device without touching the adhesive tape.



Align the BAGTAG directly above the installed adapter plate and press the device firmly onto the plate. Let the BAGTAG device cure for 24 hours and you are good to go!

## PERMANENT MOUNTING – METHOD 2

Relevant for hard shell cases. This mounting method can be used on hard shell cases that contain a clear and flat surface at least the size of your BAGTAG device.

Required items:

1 x BAGTAG device

1 x Cleaning wipe / degreaser (not included)

Installation steps:

The preferred location to attach your BAGTAG device is right next to or close to the handle that is found on the long side of your suitcase. If there is no room next to the handle, move the tag along the long side of your suitcase until you find a clear and flat surface large enough to fit your BAGTAG device. Make sure the handle of your suitcase can still function properly.



2



Clean the surface of the desired area for your BAGTAG device, preferably using degreaser.

3



Wait until the cleaned surface is completely dry and remove all three segments of the cover paper on the back-side of your BAGTAG device without touching the adhesive tape.

4



Align the BAGTAG directly above the desired area on your bag and press the device firmly onto the bag. Let the BAGTAG device cure for 24 hours.