

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a R/C Plane operating at 2.4G Band. The EUT can be powered by DC3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 0dBi.

The normal radiated output power (e.i.r.p) is: -7.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -7.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 88.5 dBμV/m at 3m in the frequency 2416MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -6.73dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 86.3 dBμV/m at 3m in the frequency 2475MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -8.93dBm

which is within the production variation.

The maximum conducted output power specified is -4dBm= 0.398mW

The source- based time-averaging conducted output power
= $0.398 \cdot \text{Duty cycle}$ mW < 0.398 mW (Duty cycle < 100%)

The SAR Exclusion Threshold Level:

= $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

= $3.0 \cdot 5 / \sqrt{2.475}$ mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 2.4638ms

Effective period of the cycle = 1.5217ms

DC = $1.5217\text{ms} / 2.4638\text{ms}$ = 0.6176 or 61.76%