

## RF Exposure Report

**Report No.:** SA170208C45

**FCC ID:** 2AK45-NSD-SW01

**Test Model:** SW-01

**Received Date:** Feb. 08, 2017

**Test Date:** Mar. 16 ~ Mar. 20, 2017

**Issued Date:** Mar. 30, 2017

**Applicant:** Nano-Second Technology Company LTD

**Address:** 2F., No.69-8, Sec. 2, Zhongzheng E. Rd., Tamsui Dist., New Taipei City 251, Taiwan (R.O.C.)

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|  |   |
|--|---|
| <b>Release Control Record</b> .....          | 3 |
| <b>1 Certificate of Conformity</b> .....     | 4 |
| <b>2 Accessories of EUT</b> .....            | 5 |
| <b>3 Evaluation Result</b> .....             | 6 |
| <b>4 SAR Test Exclusion Thresholds</b> ..... | 7 |
| <b>5 Conclusion</b> .....                    | 7 |

### Release Control Record

| Issue No.   | Description      | Date Issued   |
|-------------|------------------|---------------|
| SA170208C45 | Original release | Mar. 30, 2017 |

## 1 Certificate of Conformity

**Product:** Swim Training Aid

**Brand:** NSD

**Test Model:** SW-01

**Sample Status:** Engineering Sample

**Applicant:** Nano-Second Technology Company LTD


**Test Date:** Mar. 16 ~ Mar. 20, 2017

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06 (October 23, 2015)

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**   
Polly Chien / Specialist

, **Date:** Mar. 30, 2017

**Approved by :**   
Ken Liu / Senior Manager

, **Date:** Mar. 30, 2017

## 2 Accessories of EUT

The EUT contains the following accessories.

| No. | Product            | Brand    | Model          | Description                      |
|-----|--------------------|----------|----------------|----------------------------------|
| 1   | Battery            | GEB      | GEB602535      | Rating: 3.7Vdc, 1.67Wh, 450mAh   |
| 2   | USB Charging Cable | NSD Swim | KL-YQ1606-0701 | 0.6m non-shielded cable w/o core |
| 3   | Float belt         | NSD Swim | ZH-G13         | 1.43m                            |
| 4   | Rope               | NSD Swim | 253A200        | 2.0m                             |
| 5   | Rope               | NSD Swim | 253A80         | 0.8m                             |

\* The USB cable is for charging only, it does not have data transmission function.

### 3 Evaluation Result

Following FCC KDB 447498 D01 "General SAR test exclusion guidance"

The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, 16 where}$$

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison. The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:

a) [Threshold at 50 mm in step 1) + (test separation distance - 50mm) · (f(MHz)/150)] mW, at 100MHz to 1500 MHz

b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at  $> 1500$  MHz and  $\leq 6$  GHz

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.

a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$  for test separation distances  $> 50$  mm and  $< 200$  mm.

b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq 50$  mm.

c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

#### 4 SAR Test Exclusion Thresholds

Maximum measured transmitter power:

| Mode          | Max. Power (mW) | Min. test separation distance (mm) | SAR test exclusion calculation value <sup>(NOTE 2)</sup> | 1-g body SAR test exclusion thresholds | Result |
|---------------|-----------------|------------------------------------|--|--|--------|
| 2.402 ~ 2.480 | 0.8017          | 5                                  | 0.248  | 3                                      | Pass   |

**NOTE:** 1. The antenna type is Onboard F Antenna with 3.3dBi gain.  
2. Calculate SAR test exclusion thresholds from condition “1” formulas.

#### 5 Conclusion

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.

--- END ---