

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| A | | | | | | | | |
| B | | | | | | | | |
| C | | | | | | | | |
| D | | | | | | | | |
| E | | | | | | | | |

尺寸:165mm*165mm
 材质:80g书纸正反单色印刷
 折法:三折风琴折然后对折
 折后尺寸:55*55mm

更新说明:增加OTA说明
 更新时间:2020.12.2

| <p>Water Leakage Alarm User Manual M420-21ver1.0</p> <p><small>*Please read the user manual carefully before operation. The guide picture is for reference only, please in real print.</small></p> | <p>01/Product Introduction</p> <p>This Water Leakage Alarm is for domestic premises, adopts WiFi wireless technology, it will issue alarms if leaked water is detected and send alarm notification to user remotely. With high precision and sensitivity, the water leakage alarm can work high stably for a long time.</p> <p style="text-align: center;">Blue LED flashes slowly</p> | <p>02/Illustration</p> | | | | | | | | | | | | | | | |
|--|---|---|-----------------------------------|---|--|---|---|---------------|-------------------------|---|-------------------------------|--------------|---|-------|--------------------------|--------------------------------|---|
| <p>03/Technical Data</p> <ol style="list-style-type: none"> Working voltage: DC3V (1*CR17335/CR123A battery) Alarm indicator: blue LED indicator Alarm sound: > 75dB/m Networking: WiFi-2.4 GHz WiFi Protocol: IEEE 802.11 b/g/n Working temperature: -10°C ~ +50°C Working humidity: <math>\leq 95\%RH</math> (no condensation) Dimensions: 46x33mm x 42.7mm Protection Against Moisture: IP67 | <p>04/ Visual and audible indications</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Product Status</th> <th>Visual Indication</th> <th>Audible Indication</th> </tr> </thead> <tbody> <tr> <td>EZ-networking</td> <td>Blue LED Flashes quickly</td> <td>/</td> </tr> <tr> <td>AP-networking</td> <td>Blue LED Flashes slowly</td> <td>/</td> </tr> <tr> <td>Networking success or failure</td> <td>Blue LED off</td> <td>/</td> </tr> <tr> <td>Alarm</td> <td>Blue LED Flashes quickly</td> <td>Buzzer "Di Di Di" continuously</td> </tr> </tbody> </table> | Product Status | Visual Indication | Audible Indication | EZ-networking | Blue LED Flashes quickly | / | AP-networking | Blue LED Flashes slowly | / | Networking success or failure | Blue LED off | / | Alarm | Blue LED Flashes quickly | Buzzer "Di Di Di" continuously | <p>05/Networking</p> <p>Scan the QR code above to download the Smart Life APP and register a user's account.</p> <ul style="list-style-type: none"> The guide may be little differ from description in App, use the software system. Pls follow the guide in App when operation. Networking failed Make sure WiFi configuration succeed before installation. This sensor is an IoT device, using the latest software can get a better user experience. |
| Product Status | Visual Indication | Audible Indication | | | | | | | | | | | | | | | |
| EZ-networking | Blue LED Flashes quickly | / | | | | | | | | | | | | | | | |
| AP-networking | Blue LED Flashes slowly | / | | | | | | | | | | | | | | | |
| Networking success or failure | Blue LED off | / | | | | | | | | | | | | | | | |
| Alarm | Blue LED Flashes quickly | Buzzer "Di Di Di" continuously | | | | | | | | | | | | | | | |
| <p>06/Application</p> <p>Place the product in a location where may occur water leaking.</p> | <p>07/Battery Replacement</p> <p>Rotate the upper cover counterclockwise, remove the battery, then insert the same type of battery and align the short line mark on the top cover to the short line mark above "QR" position on the bottom cover, and rotate the top cover clockwise until you hear a "click" sound.</p> | <p>08/Notes</p> <ul style="list-style-type: none"> It's forbidden to be used in highly corrosive environments (such as H2S, SOx, Cl2, HCl, etc.). Do not subject the product to strong shocks and vibrations, otherwise the product and its accessories may be damaged, resulting in product failure. Organic solvents cannot be used to clean the product. The user can clean the product surface with a soft cloth. If there happens a product failure, please contact the local dealer. The user is forbidden to disassemble the product privately. | | | | | | | | | | | | | | | |
| <p>09/Troubleshooting</p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>Problem</th> <th>Solution</th> </tr> </thead> <tbody> <tr> <td>The alarm device does not respond</td> <td>Install a new battery. Contact with local dealer</td> </tr> </tbody> </table> | Problem | Solution | The alarm device does not respond | Install a new battery. Contact with local dealer | <p>10/Statement</p> <ul style="list-style-type: none"> The information in the user manual is for reference only and does not constitute any form of commitment. Without the written permission of the manufacturer, any individual or organization shall not extract or copy part or all of the contents of this user manual, and shall not spread it in any form. As the technology is constantly updated, the manufacturer reserves the right to modify the user manual without prior notice. If the user manual and the actual operations is inconsistent, the final interpretation is reserved to the manufacturer herein. | <p>11/FCC STATEMENT :</p> <p>This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.</p> <p>Warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.</p> <p>NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment causes harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures: Reorient or relocate the receiving antenna. Increase the separation between the equipment and receiver. Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Consult the dealer or an experienced radio/TV technician for help.</p> <p>FCC Radiation Exposure Statement: This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.</p> | | | | | | | | | | | |
| Problem | Solution | | | | | | | | | | | | | | | | |
| The alarm device does not respond | Install a new battery. Contact with local dealer | | | | | | | | | | | | | | | | |

| | | | | | | | | | | | | |
|---|-------|-------|--------|-------|---------|-------|----------|-------|-------|-------|--|---|
| <h2 style="margin: 0;">Heiman海曼</h2> <p style="margin: 0;">深圳市海曼科技股份有限公司 Shenzhen Heiman Technology Co.,Ltd.</p> | | | | | | | | | | | | |
| <p>视角: </p> <p>未注尺寸公差参照下表 线性公差:</p> <table style="font-size: small;"> <tr><td><=2</td><td>±0.03</td></tr> <tr><td>> 2-25</td><td>±0.05</td></tr> <tr><td>> 25-75</td><td>±0.08</td></tr> <tr><td>> 75-100</td><td>±0.10</td></tr> <tr><td>> 100</td><td>±0.15</td></tr> </table> <p>角度公差 ±0.5°</p> | <=2 | ±0.03 | > 2-25 | ±0.05 | > 25-75 | ±0.08 | > 75-100 | ±0.10 | > 100 | ±0.15 | <p>名称: WS2WL-TY智能水浸报警器中性英文说明书</p> <p>型号: WS2WL-TY</p> <p>物料编号: 601011868</p> <p>版本: Ver1.1</p> <p>材质:</p> <p>单位: mm 图幅: 1/1</p> | <p>文件编号:</p> <p>日期: 2020.12.2</p> <p>制图: 苏家锦</p> <p>审核:</p> <p>核准:</p> <p>比例: 1:1</p> |
| <=2 | ±0.03 | | | | | | | | | | | |
| > 2-25 | ±0.05 | | | | | | | | | | | |
| > 25-75 | ±0.08 | | | | | | | | | | | |
| > 75-100 | ±0.10 | | | | | | | | | | | |
| > 100 | ±0.15 | | | | | | | | | | | |