

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	Smart Temperature & Humidity Sensor
<b>Model Number</b>	H1-E
<b>FCC ID</b>	2AK7XH1-E
<b>Antenna gain (Max)</b>	-1.52 dBi
<b>Operation Frequency</b>	2405 MHz to 2480 MHz
<b>Input Rating</b>	DC 3 V
<b>Max. output power</b>	6.5dBm

### Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

#### Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

$$11.1 \text{ Friis transmission formula: } Pd = (Pout * G) / (4 * \pi * R^2)$$

Where

Pd= Power density in mW/cm<sup>2</sup>

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm=20cm

Pd the limit of MPE,  $1\text{mW/cm}^2$ . If we know the maximum gain of the nd total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## 11.2 Measurement Result

Antenna gain: -1.52dBi

Zigbee:

Mode	Channe l Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
O-QPSK	2405	6.5	7±1	8	0.704693	0.000885	1
	2440	5.83	6±1	7	0.704693	0.000703	1
	2480	4.87	5±1	6	0.704693	0.000558	1

Signature:



Shawn Wen

Date: 2024-03-22