



FCC - TEST REPORT

Report Number	: 68.950.18.0074.01	Date of Issue: <u>November 28, 2017</u>
Model	: TWSD01A, TBSD01A	
Product Type	: Tracking Module \ Fitness module	
Applicant	: Titan Company Limited	
Address	: Integrity, #193, Veerasandra, Electronics City P.O., Off Hosur Main Road Bangalore, 560100, India	
Production Facility	: Shenzhen Yinrun Technology Co., Ltd	
Address	: 16F, Building B1, NanShan zhiyuan, No.1001 XueYuan Road, NanShan District, ShenZhen, PEOPLE'S REPUBLIC OF CHINA	
Test Result	: <input checked="" type="checkbox"/> Positive <input type="checkbox"/> Negative	
Total pages including Appendices	: <u>27</u>	

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.



1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks.....	7
7	Test Setups	8
8	Systems test configuration.....	9
9	Technical Requirement.....	10
9.1	Conducted peak output power.....	10
9.2	6dB bandwidth	12
9.3	Power spectral density	14
9.4	Spurious RF conducted emissions.....	16
9.5	Band edge	20
9.6	Spurious radiated emissions for transmitter	22
10	Test Equipment List.....	26
11	System Measurement Uncertainty	27



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13, Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2, Nanshan District,
Shenzhen City, 518052,
P. R. China

FCC Registration Number: 502708

Telephone: 86 755 8828 6998
Fax: 86 755 828 5299



3 Description of the Equipment under Test

Description of the Equipment Under Test

Product: Tracking Module \Fitness module

Model no.: TWSD01A

FCC ID: 2AK9F-000001

Options and accessories: NIL

Rating: 3.0VDC supplied by 1*3.0VDC CR1632 Battery

RF Transmission Frequency: 2402-2480MHz

No. of Operated Channel: 40

Modulation: GFSK

Antenna Type: Integrated Antenna

Antenna Gain: 0dBi

Description of the EUT: The Equipment Under Test (EUT) is a Tracking Module \Fitness module with Bluetooth function operating at 2.4GHz



4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2016 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB558074 D01 DTS Meas Guidance v04 and ANSI C63.10 (2013).



5 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition		Pages	Test Result	Test Site
§15.207	Conducted emission AC power port	--	N/A	--
§15.247(b)(1)	Conducted peak output power	10	Pass	Site 1
§15.247(e)	Power spectral density*	14	Pass	Site 1
§15.247(a)(2)	6dB bandwidth	12	Pass	Site 1
§15.247(a)(1)	20dB bandwidth and 99% Occupied Bandwidth	12	Pass	Site 1
§15.247(a)(1)	Carrier frequency separation	--	N/A	--
§15.247(a)(1)(iii)	Number of hopping frequencies	--	N/A	--
§15.247(a)(1)(iii)	Dwell Time	--	N/A	--
§15.247(d)	Spurious RF conducted emissions	16	Pass	Site 1
§15.247(d)	Band edge	20	Pass	Site 1
§15.247(d) & §15.209 &	Spurious radiated emissions for transmitter and receiver	22	Pass	Site 1
§15.203	Antenna requirement	See note 1	Pass	--

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an Integrated Antenna, which gain is 0dBi. According to §15.203, it is considered sufficiently to comply with the provisions of this section.



6 General Remarks

Remarks

Model TWSD01A is identical with model TBSD01A include the interior structure, electrical circuits, components, appearance, software and power level except model name, and intend using, unless otherwise specified the model: TWSD01A was selected as representative models to perform all tests.

This submittal(s) (test report) is intended for FCC ID: 2AK9F-000001, complies with Section 15.205, 15.209, 15.247 of the FCC Part 15, Subpart C.

This report is for the BT 4.0 part.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.

Sample Received Date: October 16, 2017

Testing Start Date: October 16, 2017

Testing End Date: November 24, 2017

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:


Reviewed by:

Trevor You
EMC Senior Project Engineer


Ricky Yin
EMC Project Engineer

7 Test Setups


Below 1GHz



Above 1GHz



7.2 Conducted RF test setups





8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
---	---	---	---

Test software: RF test tool, which used to control the EUT in continues transmitting mode.

The system was configured to channel 0, 19, and 39 for the test.

9 Technical Requirement

9.1

9.1 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
 RBW > the 6 dB bandwidth of the emission being measured, $VBW \geq 3RBW$, $Span \geq 3RBW$
 Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.


Limits

According to §15.247 (b) (1), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Test result as below table


Frequency MHz	Conducted Peak Output Power dBm	Result
Top channel 2402MHz	-4.79	Pass
Middle channel 2440MHz	-5.26	Pass
Bottom channel 2480MHz	-5.94	Pass



Date: 21.NOV.2017 09:56:48




2440MHz



Date: 21.NOV.2017 09:58:46

2480MHz



Date: 21.NOV.2017 09:59:23



9.2 6dB bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit


Limit [kHz]

≥500

Test result

Frequency MHz	6dB bandwidth kHz	99 bandwidth kHz	Result
Top channel 2402MHz	668.60	1124.45	Pass
Middle channel 2440MHz	668.60	1133.14	Pass
Bottom channel 2480MHz	681.60	1137.48	Pass

2402MHz




Date: 21.NOV.2017 10:06:10




6 dB Bandwidth

2440MHz



Date: 21.NOV.2017 10:03:40

2480MHz



Date: 21.NOV.2017 10:01:30

9.3 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.
RBW=3kHz,VBW≥3RBW,Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

Limit


Limit [dBm]

≤8

Test result

Frequency MHz	Power spectral density dBm	Result
Top channel 2402MHz	-11.88	Pass
Middle channel 2440MHz	-12.44	Pass
Bottom channel 2480MHz	-13.04	Pass


2402MHz



Date: 21.NOV.2017 10:08:18




2440MHz



Date: 21.NOV.2017 10:08:51

2480MHz



Date: 21.NOV.2017 10:09:29

9.4 Spurious RF conducted emissions

Test Method

1. Establish a reference level by using the following procedure:
 - a. Set RBW=100 kHz. VBW \geq 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
 - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
 - a. Set the center frequency and span to encompass frequency range to be measured.
 - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.


Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20




Spurious RF conducted emissions

2402MHz



Date: 21.NOV.2017 10:15:39




Date: 21.NOV.2017 10:15:25




Spurious RF conducted emissions

2440MHz



Date: 21.NOV.2017 10:13:57




Date: 21.NOV.2017 10:13:42




Spurious RF conducted emissions

2480MHz



Date: 21.NOV.2017 10:11:22



Date: 21.NOV.2017 10:10:42



9.5 Band edge


Test Method

- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20

Test result




Date: 21.NOV.2017 10:19:08



Band edge

2480MHz



Date: 21.NOV.2017 10:20:07

9.6 Spurious radiated emissions for transmitter

Test Method

- 1: The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:

For Above 1GHz

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW \geq RBW for peak measurement and VBW = 10Hz for average measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 KHz, VBW \geq RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Note:

- 1: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
- 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (20log(1/duty cycle)).
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.



Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK



Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Transmitting spurious emission test result as below:

2402MHz (30MHz – 1GHz)

Frequency MHz	Emission Level dBuV/m	Corr. dB	Polarization	Limit dBuV/m	Detector	Result
944.76	30.00	-15.30	Horizontal	46.00	QP	Pass
944.76	36.40	-14.40	Vertical	46.00	QP	Pass

2402MHz (Above 1GHz)

Frequency MHz	Emission Level dBuV/m	Corr. dB	Polarization	Limit dBuV/m	Detector	Result
4803.28 *	42.32	2.50	Horizontal	74.00	PK	Pass
4804.21 *	38.52	2.60	Vertical	74.00	PK	Pass

2440MHz (30MHz – 1GHz)

Frequency MHz	Emission Level dBuV/m	Corr. dB	Polarization	Limit dBuV/m	Detector	Result
/	/	/	Horizontal	46.00	QP	Pass
/	/	/	Vertical	46.00	QP	Pass

2440MHz (Above 1GHz)

Frequency MHz	Emission Level dBuV/m	Corr. dB	Polarization	Limit dBuV/m	Detector	Result
4880.15 *	41.72	2.50	Horizontal	74.00	PK	Pass
4880.15 *	39.39	2.60	Vertical	74.00	PK	Pass

Remark:

- (1) Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.
- (2) “**” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.



2480MHz (30MHz – 1GHz)

Frequency	Emission Level	Corr.	Polarization	Limit	Detector	Result
MHz	dBuV/m	dB		dBµV/m		
/	/	/	Horizontal	46.00	QP	Pass
/	/	/	Vertical	46.00	QP	Pass

2480MHz (Above 1GHz)

Frequency	Emission Level	Corr.	Polarization	Limit	Detector	Result
MHz	dBuV/m	dB		dBµV/m		
4959.84 *	42.73	2.70	Horizontal	74.00	PK	Pass
4959.37 *	41.78	2.80	Vertical	74.00	PK	Pass

Remark:

- (1) Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20db below the permissible limits or the field strength is too small to be measured.
- (2) “*” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.



10 Test Equipment List

List of Test Instruments

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	2018-7-14
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	2018-7-14
Horn Antenna	Rohde & Schwarz	HF907	102294	2018-7-14
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2018-7-14
Signal Generator	Rohde & Schwarz	SMY01	839369/005	2018-7-7
Attenuator	Agilent	8491A	MY39264334	2018-7-7
3m Semi-anechoic chamber	TDK	9X6X6	----	2020-7-7
Test software	Rohde & Schwarz	EMC32	Version 9.15.00	N/A

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge



11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Radiated Spurious Emission 25MHz-3000MHz	Horizontal: 4.95dB; Vertical: 5.02dB;
Uncertainty for Radiated Spurious Emission 3000MHz-18000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Radiated Spurious Emission 18000MHz-40000MHz	Horizontal: 4.93dB; Vertical: 4.92dB;
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV216)	3.50dB
Uncertainty for Conducted RF test	2.04dB