

TEST REPORT

Applicant: Shenzhen Hysiry Technology Co., Ltd.

Address of Applicant: 2403D, 24th floor, coast huanqing building, no.24 futian road, xu town community, futian street, futian district, shenzhen

Manufacturer/Factory: Shenzhen Hysiry Technology Co., Ltd.

Address of Manufacturer/Factory: 2403D, 24th floor, coast huanqing building, no.24 futian road, xu town community, futian street, futian district, shenzhen

Equipment Under Test (EUT)

Product Name: Smart Light Bulb

Model No.: BQ3CWM

Trade Mark: 

FCC ID: 2AKBP-BQ3CWM

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: December 18, 2019

Date of Test: December 18-30, 2019

Date of report issued: January 07, 2020

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

| Version No. | Date | Description |
|-------------|------------------|-------------|
| 00 | January 07, 2020 | Original |
| | | |
| | | |
| | | |
| | | |

Prepared By:




Date:

January 07, 2020

Project Engineer

Check By:



Date:

January 07, 2020

Reviewer

3 Contents

| | Page |
|--|------|
| 1 COVER PAGE..... | 1 |
| 2 VERSION..... | 2 |
| 3 CONTENTS | 3 |
| 4 TEST SUMMARY | 4 |
| 5 GENERAL INFORMATION..... | 5 |
| 5.1 GENERAL DESCRIPTION OF EUT | 5 |
| 5.2 TEST MODE | 7 |
| 5.3 DESCRIPTION OF SUPPORT UNITS | 7 |
| 5.4 DEVIATION FROM STANDARDS..... | 7 |
| 5.5 ABNORMALITIES FROM STANDARD CONDITIONS | 7 |
| 5.6 TEST FACILITY..... | 7 |
| 5.7 TEST LOCATION | 7 |
| 6 TEST INSTRUMENTS LIST | 8 |
| 7 TEST RESULTS AND MEASUREMENT DATA..... | 10 |
| 7.1 ANTENNA REQUIREMENT | 10 |
| 7.2 CONDUCTED EMISSIONS | 11 |
| 7.3 CONDUCTED OUTPUT POWER | 14 |
| 7.4 CHANNEL BANDWIDTH | 17 |
| 7.5 POWER SPECTRAL DENSITY | 20 |
| 7.6 BAND EDGES | 23 |
| 7.6.1 Conducted Emission Method..... | 23 |
| 7.6.2 Radiated Emission Method..... | 25 |
| 7.7 SPURIOUS EMISSION..... | 34 |
| 7.7.1 Conducted Emission Method..... | 34 |
| 7.7.2 Radiated Emission Method..... | 37 |
| 8 TEST SETUP PHOTO | 44 |
| 9 EUT CONSTRUCTIONAL DETAILS | 44 |

4 Test Summary

| Test Item | Section in CFR 47 | Result |
|----------------------------------|-------------------|--------|
| Antenna requirement | 15.203/15.247 (c) | Pass |
| AC Power Line Conducted Emission | 15.207 | Pass |
| Conducted Output Power | 15.247 (b)(3) | Pass |
| Channel Bandwidth | 15.247 (a)(2) | Pass |
| Power Spectral Density | 15.247 (e) | Pass |
| Band Edge | 15.247(d) | Pass |
| Spurious Emission | 15.205/15.209 | Pass |

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013

Measurement Uncertainty

| Test Item | Frequency Range | Measurement Uncertainty | Notes |
|----------------------------------|-----------------|-------------------------|-------|
| Radiated Emission | 30MHz-200MHz | 3.8039dB | (1) |
| Radiated Emission | 200MHz-1GHz | 3.9679dB | (1) |
| Radiated Emission | 1GHz-18GHz | 4.29dB | (1) |
| Radiated Emission | 18GHz-40GHz | 3.30dB | (1) |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | 3.44dB | (1) |

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

| | |
|----------------------|------------------------|
| Product Name: | Smart Light Bulb |
| Model No.: | BQ3CWM |
| Test sample(s) ID: | GTS202001000029-1 |
| Sample(s) Status: | Engineer sample |
| Serial No.: | N/A |
| Hardware Version: | V1.0 |
| Software Version: | V1.0 |
| Operation Frequency: | 2402MHz~2480MHz |
| Channel Numbers: | 40 |
| Bluetooth version: | Bluetooth 5.0 |
| Modulation Type: | GFSK |
| Antenna Type: | Line-polarized Antenna |
| Antenna Gain: | 1.5dBi |
| Power Supply: | Input: AC 120V/60Hz |

| Operation Frequency each of channel | | | | | | | |
|-------------------------------------|-----------|---------|-----------|---------|-----------|---------|-----------|
| Channel | Frequency | Channel | Frequency | Channel | Frequency | Channel | Frequency |
| 1 | 2402 MHz | 11 | 2422 MHz | 21 | 2442 MHz | 31 | 2462 MHz |
| 2 | 2404 MHz | 12 | 2424 MHz | 22 | 2444 MHz | 32 | 2464 MHz |
| 3 | 2406 MHz | 13 | 2426 MHz | 23 | 2446 MHz | 33 | 2466 MHz |
| 4 | 2408 MHz | 14 | 2428 MHz | 24 | 2448 MHz | 34 | 2468 MHz |
| 5 | 2410 MHz | 15 | 2430 MHz | 25 | 2450 MHz | 35 | 2470 MHz |
| 6 | 2412 MHz | 16 | 2432 MHz | 26 | 2452 MHz | 36 | 2472 MHz |
| 7 | 2414 MHz | 17 | 2434 MHz | 27 | 2454 MHz | 37 | 2474 MHz |
| 8 | 2416 MHz | 18 | 2436 MHz | 28 | 2456 MHz | 38 | 2476 MHz |
| 9 | 2418 MHz | 19 | 2438 MHz | 29 | 2458 MHz | 39 | 2478 MHz |
| 10 | 2420 MHz | 20 | 2440 MHz | 30 | 2460 MHz | 40 | 2480 MHz |

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel | Frequency |
|---------------------|-----------|
| The lowest channel | 2402MHz |
| The middle channel | 2442MHz |
| The Highest channel | 2480MHz |

5.2 Test mode

| | |
|---|--|
| Transmitting mode | Keep the EUT in continuously transmitting mode |
| <p><i>Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.</i></p> | |

5.3 Description of Support Units

| |
|-------|
| None. |
|-------|

5.4 Deviation from Standards

| |
|-------|
| None. |
|-------|

5.5 Abnormalities from Standard Conditions

| |
|-------|
| None. |
|-------|

5.6 Test Facility

| |
|---|
| <p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC —Registration No.: 381383 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383. ● IC —Registration No.: 9079A The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A ● NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP). LAB CODE:600179-0 |
|---|

5.7 Test Location

| |
|---|
| All tests were performed at: |
| <p>Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960</p> |

6 Test Instruments list

| Radiated Emission: | | | | | | |
|--------------------|-------------------------------------|--------------------------------|-----------------------------|---------------|---------------------|-------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1 | 3m Semi- Anechoic Chamber | ZhongYu Electron | 9.2(L)*6.2(W)* 6.4(H) | GTS250 | July. 03 2015 | July. 02 2020 |
| 2 | Control Room | ZhongYu Electron | 6.2(L)*2.5(W)* 2.4(H) | GTS251 | N/A | N/A |
| 3 | EMI Test Receiver | Rohde & Schwarz | ESU26 | GTS203 | June. 26 2019 | June. 25 2020 |
| 4 | BiConiLog Antenna | SCHWARZBECK MESS-ELEKTRONIK | VULB9163 | GTS214 | June. 26 2019 | June. 25 2020 |
| 5 | Double -ridged waveguide horn | SCHWARZBECK MESS-ELEKTRONIK | BBHA 9120 D | GTS208 | June. 26 2019 | June. 25 2020 |
| 6 | Horn Antenna | ETS-LINDGREN | 3160 | GTS217 | June. 26 2019 | June. 25 2020 |
| 7 | EMI Test Software | AUDIX | E3 | N/A | N/A | N/A |
| 8 | Coaxial Cable | GTS | N/A | GTS213 | June. 26 2019 | June. 25 2020 |
| 9 | Coaxial Cable | GTS | N/A | GTS211 | June. 26 2019 | June. 25 2020 |
| 10 | Coaxial cable | GTS | N/A | GTS210 | June. 26 2019 | June. 25 2020 |
| 11 | Coaxial Cable | GTS | N/A | GTS212 | June. 26 2019 | June. 25 2020 |
| 12 | Amplifier(100kHz-3GHz) | HP | 8347A | GTS204 | June. 26 2019 | June. 25 2020 |
| 13 | Amplifier(2GHz-20GHz) | HP | 84722A | GTS206 | June. 26 2019 | June. 25 2020 |
| 14 | Amplifier (18-26GHz) | Rohde & Schwarz | AFS33-18002 650-30-8P-44 | GTS218 | June. 26 2019 | June. 25 2020 |
| 15 | Band filter | Amindeon | 82346 | GTS219 | June. 26 2019 | June. 25 2020 |
| 16 | Power Meter | Anritsu | ML2495A | GTS540 | June. 26 2019 | June. 25 2020 |
| 17 | Power Sensor | Anritsu | MA2411B | GTS541 | June. 26 2019 | June. 25 2020 |
| 18 | Wideband Radio Communication Tester | Rohde & Schwarz | CMW500 | GTS575 | June. 26 2019 | June. 25 2020 |
| 19 | Splitter | Agilent | 11636B | GTS237 | June. 26 2019 | June. 25 2020 |
| 20 | Loop Antenna | ZHINAN | ZN30900A | GTS534 | June. 26 2019 | June. 25 2020 |
| 21 | Breitband hornantenne | SCHWARZBECK | BBHA 9170 | GTS579 | Oct. 19 2019 | Oct. 18 2020 |
| 22 | Amplifier | TDK | PA-02-02 | GTS574 | Oct. 19 2019 | Oct. 18 2020 |
| 23 | Amplifier | TDK | PA-02-03 | GTS576 | Oct. 19 2019 | Oct. 18 2020 |
| 24 | PSA Series Spectrum Analyzer | Rohde & Schwarz | FSP | GTS578 | June. 26 2019 | June. 25 2020 |

| Conducted Emission | | | | | | |
|---------------------------|--------------------------|-----------------------------|----------------------|---------------|---------------------|-------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1 | Shielding Room | ZhongYu Electron | 7.3(L)x3.1(W)x2.9(H) | GTS252 | May.15 2019 | May.14 2022 |
| 2 | EMI Test Receiver | R&S | ESCI 7 | GTS552 | June. 26 2019 | June. 25 2020 |
| 3 | Coaxial Switch | ANRITSU CORP | MP59B | GTS225 | June. 26 2019 | June. 25 2020 |
| 4 | Artificial Mains Network | SCHWARZBECK MESS | NSLK8127 | GTS226 | June. 26 2019 | June. 25 2020 |
| 5 | Coaxial Cable | GTS | N/A | GTS227 | N/A | N/A |
| 6 | EMI Test Software | AUDIX | E3 | N/A | N/A | N/A |
| 7 | Thermo meter | KTJ | TA328 | GTS233 | June. 26 2019 | June. 25 2020 |
| 8 | Absorbing clamp | Elektronik- Feinmechanik | MDS21 | GTS229 | June. 26 2019 | June. 25 2020 |
| 9 | ISN | SCHWARZBECK | NTFM 8158 | GTD565 | June. 26 2019 | June. 25 2020 |

| RF Conducted Test: | | | | | | |
|---------------------------|--|--------------|------------------|------------|---------------------|-------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Serial No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1 | MXA Signal Analyzer | Agilent | N9020A | GTS566 | June. 26 2019 | June. 25 2020 |
| 2 | EMI Test Receiver | R&S | ESCI 7 | GTS552 | June. 26 2019 | June. 25 2020 |
| 3 | Spectrum Analyzer | Agilent | E4440A | GTS533 | June. 26 2019 | June. 25 2020 |
| 4 | MXG vector Signal Generator | Agilent | N5182A | GTS567 | June. 26 2019 | June. 25 2020 |
| 5 | ESG Analog Signal Generator | Agilent | E4428C | GTS568 | June. 26 2019 | June. 25 2020 |
| 6 | USB RF Power Sensor | DARE | RPR3006W | GTS569 | June. 26 2019 | June. 25 2020 |
| 7 | RF Switch Box | Shongyi | RFSW3003328 | GTS571 | June. 26 2019 | June. 25 2020 |
| 8 | Programmable Constant Temp & Humi Test Chamber | WEWON | WHTH-150L-40-880 | GTS572 | June. 26 2019 | June. 25 2020 |

| General used equipment: | | | | | | |
|--------------------------------|---------------------------------|--------------|-----------|---------------|---------------------|-------------------------|
| Item | Test Equipment | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1 | Humidity/ Temperature Indicator | KTJ | TA328 | GTS243 | June. 26 2019 | June. 25 2020 |
| 2 | Barometer | ChangChun | DYM3 | GTS255 | June. 26 2019 | June. 25 2020 |

7 Test results and Measurement Data


7.1 Antenna requirement


| | |
|--|-------------------------------------|
| Standard requirement: | FCC Part15 C Section 15.203 /247(c) |
| 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. | |
| 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi. | |
| E.U.T Antenna: The antennas are Line-polarized Antenna, the best case gain of the antennas are 1.5dBi, reference to the appendix II for details. | |

7.2 Conducted Emissions


| | | | | | | |
|--|--|--------------|-----------|-----|---------|----------|
| Test Requirement: | FCC Part15 C Section 15.207 | | | | | |
| Test Method: | ANSI C63.10:2013 | | | | | |
| Test Frequency Range: | 150KHz to 30MHz | | | | | |
| Class / Severity: | Class B | | | | | |
| Receiver setup: | RBW=9KHz, VBW=30KHz, Sweep time=auto | | | | | |
| Limit: | Frequency range (MHz) | Limit (dBuV) | | | | |
| | | Quasi-peak | Average | | | |
| | 0.15-0.5 | 66 to 56* | 56 to 46* | | | |
| | 0.5-5 | 56 | 46 | | | |
| | 5-30 | 60 | 50 | | | |
| * Decreases with the logarithm of the frequency. | | | | | | |
| Test setup: | | | | | | |
| | <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p> | | | | | |
| Test procedure: | <ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2009 on conducted measurement. | | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | | |
| Test mode: | Refer to section 5.2 for details | | | | | |
| Test environment: | Temp.: | 24.8 °C | Humid.: | 42% | Press.: | 1010mbar |
| Test voltage: | AC 120V/60Hz | | | | | |
| Test results: | Pass | | | | | |

Measurement data





7.3 Conducted Output Power

| | |
|-------------------|--|
| Test Requirement: | FCC Part15 C Section 15.247 (b)(3) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02 |
| Limit: | 30dBm |
| Test setup: |  <p>The diagram shows a Spectrum Analyzer on the left and an E.U.T. on the right, connected by a red cable. They are both on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p> |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |


Measurement Data

| Test Mode | Test channel | Peak Output Power (dBm) | Limit(dBm) | Result |
|-----------|--------------|-------------------------|------------|--------|
| BLE 1M | Lowest | -0.976 | 30.00 | Pass |
| | Middle | -0.948 | | |
| | Highest | -1.212 | | |


| Test Mode | Test channel | Peak Output Power (dBm) | Limit(dBm) | Result |
|-----------|--------------|-------------------------|------------|--------|
| BLE 2M | Lowest | -0.968 | 30.00 | Pass |
| | Middle | -0.928 | | |
| | Highest | -1.214 | | |

Test plot as follows:
BLE 1M:


Lowest channel



Middle channel




Highest channel




Test plot as follows:
BLE 2M


Lowest channel




Middle channel



Highest channel



7.4 Channel Bandwidth

| | |
|-------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(2) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02 |
| Limit: | >500KHz |
| Test setup: |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |


Measurement Data

| Test Mode | Test channel | 6dB Bandwidth (MHz) | 99% Bandwidth (MHz) | Limit(KHz) | Result |
|-----------|--------------|---------------------|---------------------|------------|--------|
| BLE 1M | Lowest | 0.6608 | 1.0468 | >500 | Pass |
| | Middle | 0.6567 | 1.0481 | | |
| | Highest | 0.6643 | 1.0486 | | |


| Test Mode | Test channel | 6dB Bandwidth (MHz) | 99% Bandwidth (MHz) | Limit(KHz) | Result |
|-----------|--------------|---------------------|---------------------|------------|--------|
| BLE 2M | Lowest | 0.5466 | 2.0637 | >500 | Pass |
| | Middle | 0.5438 | 2.0640 | | |
| | Highest | 0.5382 | 2.0603 | | |

Test plot as follows:
BLE 1M:


Lowest channel



Middle channel




Highest channel




Test plot as follows:
BLE 2M


Lowest channel




Middle channel



Highest channel



7.5 Power Spectral Density

| | |
|-------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (e) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02 |
| Limit: | 8dBm/3kHz |
| Test setup: |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |


Measurement Data

| Test Mode | Test channel | Power Spectral Density (dBm/3kHz) | Limit(dBm/3kHz) | Result |
|-----------|--------------|-----------------------------------|-----------------|--------|
| BLE 1M | Lowest | -13.488 | 8.00 | Pass |
| | Middle | -13.452 | | |
| | Highest | -13.749 | | |


| Test Mode | Test channel | Power Spectral Density (dBm/3kHz) | Limit(dBm/3kHz) | Result |
|-----------|--------------|-----------------------------------|-----------------|--------|
| BLE 2M | Lowest | -17.768 | 8.00 | Pass |
| | Middle | -17.653 | | |
| | Highest | -17.957 | | |

Test plot as follows:
BLE 1M


Lowest channel



Middle channel




Highest channel




Test plot as follows:
BLE 2M


Lowest channel



Middle channel




Highest channel




7.6 Band edges

7.6.1 Conducted Emission Method


| | |
|-------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (d) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02 |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test setup: |  |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |

Test plot as follows:

BLE 1M




Lowest channel




Highest channel

Test plot as follows:
BLE 2M



Lowest channel




Highest channel

7.6.2 Radiated Emission Method

| | | | | | |
|-----------------------|---|----------|--------------------|------|---------|
| Test Requirement: | FCC Part15 C Section 15.209 and 15.205 | | | | |
| Test Method: | ANSI C63.10:2013 | | | | |
| Test Frequency Range: | All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed. | | | | |
| Test site: | Measurement Distance: 3m | | | | |
| Receiver setup: | Frequency | Detector | RBW | VBW | Value |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| | | RMS | 1MHz | 3MHz | Average |
| Limit: | Frequency | | Limit (dBuV/m @3m) | | Value |
| | Above 1GHz | | 54.00 | | Average |
| | | | 74.00 | | Peak |
| Test setup: | | | | | |
| Test Procedure: | <ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. | | | | |
| Test Instruments: | Refer to section 6.0 for details | | | | |
| Test mode: | Refer to section 5.2 for details | | | | |
| Test results: | Pass | | | | |


(1) Radiation Test


| | |
|------------|---------------------|
| Ant. Pol. | Horizontal |
| Test Mode: | BLE 1M Mode 2402MHz |
| Remark: | N/A |




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB/m | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|
| 1 | | 2390.000 | 50.30 | 2.91 | 53.21 | 74.00 | -20.79 | peak |
| 2 | | 2390.000 | 30.93 | 2.91 | 33.84 | 54.00 | -20.16 | AVG |
| 3 | X | 2402.000 | 88.98 | 2.95 | 91.93 | 74.00 | 17.93 | peak |
| 4 | * | 2402.000 | 81.57 | 2.95 | 84.52 | 54.00 | 30.52 | AVG |

Emission Level= Read Level+ Correct Factor







| | |
|-------------------|---------------------|
| Ant. Pol. | Vertical |
| Test Mode: | BLE 1M Mode 2480MHz |
| Remark: | N/A |




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB/m | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|
| 1 | X | 2479.800 | 86.42 | 3.38 | 89.80 | 74.00 | 15.80 | peak |
| 2 | * | 2480.000 | 78.96 | 3.38 | 82.34 | 54.00 | 28.34 | AVG |
| 3 | | 2483.500 | 58.29 | 3.40 | 61.69 | 74.00 | -12.31 | peak |
| 4 | | 2483.500 | 38.72 | 3.40 | 42.12 | 54.00 | -11.88 | AVG |

Emission Level= Read Level+ Correct Factor






| | |
|-------------------|---------------------|
| Ant. Pol. | Horizontal |
| Test Mode: | BLE 2M Mode 2480MHz |
| Remark: | N/A |



| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB/m | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|
| 1 | X | 2479.400 | 81.40 | 3.38 | 84.78 | 74.00 | 10.78 | peak |
| 2 | * | 2479.800 | 67.09 | 3.38 | 70.47 | 54.00 | 16.47 | AVG |
| 3 | | 2483.500 | 46.63 | 3.40 | 50.03 | 74.00 | -23.97 | peak |
| 4 | | 2483.500 | 33.85 | 3.40 | 37.25 | 54.00 | -16.75 | AVG |

Emission Level= Read Level+ Correct Factor

| | |
|-------------------|---------------------|
| Ant. Pol. | Vertical |
| Test Mode: | BLE 2M Mode 2480MHz |
| Remark: | N/A |




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB/m | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Detector |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|
| 1 | X | 2479.600 | 86.46 | 3.38 | 89.84 | 74.00 | 15.84 | peak |
| 2 | * | 2480.000 | 72.13 | 3.38 | 75.51 | 54.00 | 21.51 | AVG |
| 3 | | 2483.500 | 51.08 | 3.40 | 54.48 | 74.00 | -19.52 | peak |
| 4 | | 2483.500 | 36.36 | 3.40 | 39.76 | 54.00 | -14.24 | AVG |


Emission Level= Read Level+ Correct Factor

7.7 Spurious Emission

7.7.1 Conducted Emission Method


| | |
|-------------------|---|
| Test Requirement: | FCC Part15 C Section 15.247 (d) |
| Test Method: | ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V05r02 |
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test setup: |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details |
| Test mode: | Refer to section 5.2 for details |
| Test results: | Pass |

Test plot as follows:
BLE 1M
 Lowest channel




30MHz~25GHz

Middle channel




30MHz~25GHz

Highest channel




30MHz~25GHz

Test plot as follows:
BLE 2M
 Lowest channel




30MHz~25GHz

Middle channel





30MHz~25GHz


Highest channel



30MHz~25GHz

7.7.2 Radiated Emission Method

| | | | | | |
|--|--|--------------|---------|----------------------|------------|
| Test Requirement: | FCC Part15 C Section 15.209 | | | | |
| Test Method: | ANSI C63.10: 2013 | | | | |
| Test Frequency Range: | 9kHz to 25GHz | | | | |
| Test site: | Measurement Distance: 3m | | | | |
| Receiver setup: | Frequency | Detector | RBW | VBW | Value |
| | 9KHz-150KHz | Quasi-peak | 200Hz | 600Hz | Quasi-peak |
| | 150KHz-30MHz | Quasi-peak | 9KHz | 30KHz | Quasi-peak |
| | 30MHz-1GHz | Quasi-peak | 100KHz | 300KHz | Quasi-peak |
| | Above 1GHz | Peak | 1MHz | 3MHz | Peak |
| Peak | | 1MHz | 10Hz | Average | |
| Limit: | Frequency | Limit (uV/m) | Value | Measurement Distance | |
| | 0.009MHz-0.490MHz | 2400/F(KHz) | QP | 300m | |
| | 0.490MHz-1.705MHz | 24000/F(KHz) | QP | 300m | |
| | 1.705MHz-30MHz | 30 | QP | 30m | |
| | 30MHz-88MHz | 100 | QP | 3m | |
| | 88MHz-216MHz | 150 | QP | | |
| | 216MHz-960MHz | 200 | QP | | |
| | 960MHz-1GHz | 500 | QP | | |
| | Above 1GHz | 500 | Average | | |
| | | 5000 | Peak | | |
| Test setup: | For radiated emissions from 9kHz to 30MHz | | | | |
| |  | | | | |
| | For radiated emissions from 30MHz to 1GHz | | | | |
|  | | | | | |
| For radiated emissions above 1GHz | | | | | |

| | | | | | | | |
|--------------------------|--|---------|---------|---------|----------|---------|----------|
| |  | | | | | | |
| <p>Test Procedure:</p> | <ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. | | | | | | |
| <p>Test Instruments:</p> | <p>Refer to section 6.0 for details</p> | | | | | | |
| <p>Test mode:</p> | <p>Refer to section 5.2 for details</p> | | | | | | |
| <p>Test environment:</p> | <table border="1"> <tr> <td>Temp.:</td> <td>24.5 °C</td> <td>Humid.:</td> <td>44%</td> <td>Press.:</td> <td>1012mbar</td> </tr> </table> | Temp.: | 24.5 °C | Humid.: | 44% | Press.: | 1012mbar |
| Temp.: | 24.5 °C | Humid.: | 44% | Press.: | 1012mbar | | |
| <p>Test voltage:</p> | <p>AC 120V, 60Hz</p> | | | | | | |
| <p>Test results:</p> | <p>Pass</p> | | | | | | |


Measurement Data


9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz





Above 1G

| Ant. Pol. | | Horizontal | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 1M Mode 2402MHz | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | 4803.712 | 46.64 | 15.56 | 62.20 | 74.00 | -11.80 | peak |
| 2 | * 4803.922 | 32.94 | 15.56 | 48.50 | 54.00 | -5.50 | AVG |

| Ant. Pol. | | Vertical | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 1M Mode 2402MHz | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | 4803.874 | 45.79 | 15.56 | 61.35 | 74.00 | -12.65 | peak |
| 2 | * 4803.922 | 31.46 | 15.56 | 47.02 | 54.00 | -6.98 | AVG |

| Ant. Pol. | | Horizontal | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 1M Mode 2442MHz | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | * 4883.922 | 30.52 | 15.93 | 46.45 | 54.00 | -7.55 | AVG |
| 2 | 4884.444 | 45.29 | 15.93 | 61.22 | 74.00 | -12.78 | peak |

| Ant. Pol. | | Vertical | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 1M Mode 2442MHz | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | * 4883.922 | 31.44 | 15.93 | 47.37 | 54.00 | -6.63 | AVG |
| 2 | 4884.336 | 45.61 | 15.94 | 61.55 | 74.00 | -12.45 | peak |

| Ant. Pol. | | Horizontal | | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|--|
| Test Mode: | | TX BLE 1M Mode 2480MHz | | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | |
| 1 | 4959.406 | 45.73 | 16.26 | 61.99 | 74.00 | -12.01 | peak | |
| 2 | * 4959.922 | 31.48 | 16.26 | 47.74 | 54.00 | -6.26 | AVG | |

| Ant. Pol. | | Vertical | | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|--|
| Test Mode: | | TX BLE 1M Mode 2480MHz | | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | |
| 1 | 4959.256 | 45.49 | 16.27 | 61.76 | 74.00 | -12.24 | peak | |
| 2 | * 4959.922 | 31.03 | 16.26 | 47.29 | 54.00 | -6.71 | AVG | |

| Ant. Pol. | | Horizontal | | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|--|
| Test Mode: | | TX BLE 2M Mode 2402MHz | | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | |
| 1 | * 4803.610 | 29.01 | 15.56 | 44.57 | 54.00 | -9.43 | AVG | |
| 2 | 4803.898 | 42.95 | 15.56 | 58.51 | 74.00 | -15.49 | peak | |

| Ant. Pol. | | Vertical | | | | | | |
|-------------------|------------|------------------------|----------------|-------------|--------|--------|----------|--|
| Test Mode: | | TX BLE 2M Mode 2402MHz | | | | | | |
| No. Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | | |
| | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector | |
| 1 | * 4803.604 | 29.27 | 15.56 | 44.83 | 54.00 | -9.17 | AVG | |
| 2 | 4804.660 | 44.60 | 15.57 | 60.17 | 74.00 | -13.83 | peak | |

| Ant. Pol. | | Horizontal | | | | | | |
|-------------------|-----|------------------------|---------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 2M Mode 2442MHz | | | | | | |
| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | * | 4882.500 | 29.05 | 15.92 | 44.97 | 54.00 | -9.03 | AVG |
| 2 | | 4882.836 | 43.08 | 15.92 | 59.00 | 74.00 | -15.00 | peak |

| Ant. Pol. | | Vertical | | | | | | |
|-------------------|-----|------------------------|---------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 2M Mode 2442MHz | | | | | | |
| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | * | 4883.130 | 29.72 | 15.92 | 45.64 | 54.00 | -8.36 | AVG |
| 2 | | 4883.208 | 44.90 | 15.92 | 60.82 | 74.00 | -13.18 | peak |

| Ant. Pol. | | Horizontal | | | | | | |
|-------------------|-----|------------------------|---------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 2M Mode 2480MHz | | | | | | |
| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | | 4960.450 | 44.20 | 16.27 | 60.47 | 74.00 | -13.53 | peak |
| 2 | * | 4960.450 | 28.92 | 16.27 | 45.19 | 54.00 | -8.81 | AVG |

| Ant. Pol. | | Vertical | | | | | | |
|-------------------|-----|------------------------|---------------|----------------|-------------|--------|--------|----------|
| Test Mode: | | TX BLE 2M Mode 2480MHz | | | | | | |
| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | |
| | | MHz | dBuV | dB/m | dBuV/m | dBuV/m | dB | Detector |
| 1 | * | 4959.760 | 29.61 | 16.26 | 45.87 | 54.00 | -8.13 | AVG |
| 2 | | 4960.732 | 44.73 | 16.27 | 61.00 | 74.00 | -13.00 | peak |

Remark:

- 1.No report for the emission which more than 10 dB below the prescribed limit.
- 2.Emission Level= Read Level+ Correct Factor

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----