

FCC Test Report

Report No.: AGC00688240501FR02

FCC ID : 2AKC6-BT540

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: WIRELESS USB ADAPTER

BRAND NAME : N/A

MODEL NAME : BT540, BT541, BT542, BT512

APPLICANT: SHEN ZHEN XIN HUA TIAN TECHNOLOGY CO., LTD

DATE OF ISSUE : May 21, 2024

STANDARD(S) : FCC Part 15 Subpart C §15.247

REPORT VERSION: V1.0

Attestation Of Global Conclude (Shenzhen) Co., Ltd



Page 2 of 51


Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	May 21, 2024	Valid	Initial Release	




Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Special Accessories	7
2.6 Equipment Modifications	7
2.7 Antenna Requirement	7
3. Test Environment	8
3.1 Address of the Test Laboratory	8
3.2 Test Facility	8
3.3 Environmental Conditions	9
3.4 Measurement Uncertainty	9
3.5 List of Equipment Use	10
4.System Test Configuration	12
4.1 EUT Configuration	12
4.2 EUT Exercise	12
4.3 Configuration of Tested System	12
4.4 Equipment Used In Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	
6. Duty Cycle Measurement	
7. RF Output Power Measurement	
7.1 Provisions Applicable	16
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	16
7.4 Measurement Result	
8. 6dB Bandwidth Measurement	19
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	19
8.4 Measurement Results	20
9. Power Spectral Density Measurement	24
9.1 Provisions Applicable	24
9.2 Measurement Procedure	24
9.3 Measurement Setup (Block Diagram of Configuration)	24
9.4 Measurement Results	
10. Conducted Band Edge and Out-of-Band Emissions	27
10.1 Provisions Applicable	27





10.2 Measurement Procedure	27
10.3 Measurement Setup (Block Diagram of Configuration)	27
10.4 Measurement Results	28
11. Radiated Spurious Emission	34
11.1 Measurement Limit	
11.2 Measurement Procedure	34
11.3 Measurement Setup (Block Diagram of Configuration)	37
11.4 Measurement Result	
12. AC Power Line Conducted Emission Test	47
12.1 Measurement Limit	47
12.2 Measurement Setup (Block Diagram of Configuration)	47
12.3 Preliminary Procedure of Line Conducted Emission Test	48
12.4 Final Procedure of Line Conducted Emission Test	
12.5 Measurement Results	48
Appendix I: Photographs of Test Setup	51
Appendix II: Photographs of Test EUT	51





1. General Information

Applicant	SHEN ZHEN XIN HUA TIAN TECHNOLOGY CO., LTD
Address	3Floor, B Buliding, DaHong Industrial Park, GuangMin District, Shenzhen City, China
Manufacturer	SHEN ZHEN XIN HUA TIAN TECHNOLOGY CO., LTD
Address	3Floor, B Buliding, DaHong Industrial Park, GuangMin District, Shenzhen City, China
Factory	SHEN ZHEN XIN HUA TIAN TECHNOLOGY CO., LTD
Address	3Floor, B Buliding, DaHong Industrial Park, GuangMin District, Shenzhen City, China
Product Designation	WIRELESS USB ADAPTER
Brand Name	N/A
Test Model	BT540
Series Model(s)	BT541, BT542, BT512
Difference Description	All the same except for the model name and plastic appearance.
Date of receipt of test item	May 07, 2024
Date of Test	May 07, 2024 to May 21, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BLE-V1


Note: The test results of this report relate only to the tested sample identified in this report.

Cici Li
(Project Engineer)

Reviewed By

Calvin Liu
(Reviewer)

May 21, 2024





2. Product Information

2.1 Product Technical Description

Fraguescy Dond	2400MH= 2402 FMH=
Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.4
Modulation Type	BLE ⊠GFSK 1Mbps □GFSK 2Mbps
Number of channels	40
Carrier Frequency of Each Channel	40 Channels (37 Data channels + 3 advertising channels)
Channel Separation	2 MHz
Maximum Transmitter Power	0.561dBm
Hardware Version	V2.0
Software Version	V1.2
Antenna Designation	PCB Antenna
Antenna Gain	2.97dBi
Power Supply	DC 5V
Adapter Information	N/A

2.2 Test Frequency List

Channel Number	Frequency		
0	2402 MHz		
1	2404 MHz		
:	: 2440MHz		
19			
:	:		
38	2478 MHz		
39	2480 MHz		
	0 1 : : 19 : :		



Page 7 of 51

2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2AKC6-BT540**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

2.5 Special Accessories

Not available for this EUT intended for grant.

2.6 Equipment Modifications

Not available for this EUT intended for grant.

2.7 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2.97dBi.



Page 8 of 51

3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02


Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.






3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 5V

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$






3.5 List of Equipment Use

RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2023-06-01	2024-05-31	
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31	
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31	
\boxtimes	AGC-EM-A152	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08	
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2023-06-01	2024-05-31	
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A	
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A	

• F	Radiated Spurious Emission							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)	
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31	
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2023-06-03	2024-06-02	
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2023-06-01	2024-05-31	
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04	
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10	
\boxtimes	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30	
\boxtimes	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23	
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03	
\boxtimes	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2023-06-01	2024-05-31	
\boxtimes	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08	
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2024-06-08	

• .	AC Power Line Conducted Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2023-06-03	2024-06-02		
\boxtimes	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2024-06-08		
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2023-06-03	2024-06-02		





• Te:	Test Software					
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information	
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71	
	AGC-EM-S003	RE-Test System	FARA	EZ-EMC	VRA-03A	
\boxtimes	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0	
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6	
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0	



Page 12 of 51

4. System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	USB Cable				
2	Xiaomi Notebook PC	Xiaomi	4VF5A4T		
3	Xiaomi Notebook Adapter	Xiaomi	ADC6501TM	Input: 100-240V 50/60Hz 1.7A Output: 5V/2A;12V/2A;15V/3A;9V/2A;20V/3.25A;65W	1.4m,unshielded

☐ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	WIRELESS USB ADAPTER	SHEN ZHEN XIN HUA TIAN TECHNOLOGY CO., LTD	BT540		



Page 13 of 51

4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(3)	RF Output Power	Pass
3	§15.247 (a)(2)	6 dB Bandwidth	Pass
4	§15.247 (e)	Power Spectral Density	Pass
4	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
5	§15.209	Radiated Emission& Band Edge	Pass
6	§15.207	AC Power Line Conducted Emission	Pass




5. Description of Test Modes

Summary Table of Test Cases			
Data Rate / Modulation			
Test Item	Bluetooth – LE(1Mbps) / GFSK		
Radiated & Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps(Connect PC) Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps(Connect PC)		
Test Cases	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps(Connect PC)		
AC Conducted Emission	Mode 1: Bluetooth Link + Cable (connected PC+AC Adapter)		

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.





Page 15 of 51

6. Duty Cycle Measurement


The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
BLE_1Mbps	394.6	63.10	2.00	2.53

Remark:

- Duty Cycle factor = 10 * log (1/ Duty cycle)
- The duty cycle of each frequency band mode reflects the determination requirements of the low channel measurement value

The test plots as follows:





7. RF Output Power Measurement

7.1 Provisions Applicable


For DTSs employing digital modulation techniques operating in the bands 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W.


7.2 Measurement Procedure

For Peak Power, the testing follows ANSI C63.10 Section 11.9.1.1 Method Max peak power:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the RBW ≥ DTS bandwidth
- 3. Set the VBW ≥ [3 x RBW].
- 4. Span ≥ [3 x RBW].
- 5. Sweep= auto couple.
- 6. Detector Function= Peak.
- 7. Trace mode= Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

7.3 Measurement Setup (Block Diagram of Configuration)








7.4 Measurement Result

Test Data of Conducted Output Power				
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2402	0.561	≤30	Pass
GFSK_1Mbps	2440	-0.423	≤30	Pass
	2480	-0.259	≤30	Pass

Test Graphs of Conducted Output Power







Test_Graph_LE1M_ANT1_2480_1Mbps_Peak Power



Page 19 of 51

8. 6dB Bandwidth Measurement

8.1 Provisions Applicable


The minimum 6 dB bandwidth shall be 500 kHz.


8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the OBW and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Measure and record the results in the test report.

8.3 Measurement Setup (Block Diagram of Configuration)









8.4 Measurement Results

Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	DTS BW (MHz)	DTS BW Limits	Pass or Fail
	2402	1.037	0.667	≥0.5	Pass
GFSK_1Mbps	2440	1.038	0.660	≥0.5	Pass
	2480	1.039	0.658	≥0.5	Pass


Test Graphs of Occupied Bandwidth Center Freq: 2.402000000 GHz Trig: Free Run Avg|Hole #Atten: 30 dB Avg|Hold: 10/10


















Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/











9. Power Spectral Density Measurement

9.1 Provisions Applicable


The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

9.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.

- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss
 was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz in order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 5. Measure and record the results in the test report.
- 6. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

9.3 Measurement Setup (Block Diagram of Configuration)







9.4 Measurement Results

Test Data of Conducted Output Power Spectral Density					
Test Mode	Test Frequency (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail	
	2402	-15.018	≤8	Pass	
GFSK_1Mbps	2440	-15.171	≤8	Pass	
	2480	-14.093	≤8	Pass	

Test Graphs of Conducted Output Power Spectral Density Frequency Center Freq 2.402000000 GHz Avg Type: Log-Pwr Avg|Hold: 73/100 Trig: Free Run #Atten: 30 dB PNO: Wide --IFGain:Low **Auto Tune** Mkr1 2.401 888 3 GHz -15.018 dBm 10 dB/div Ref 20.00 dBm Center Freq 2.402000000 GHz Start Freq 2.401499750 GHz Stop Freq 2.402500250 GHz **CF Step** 100.050 kHz <u>Auto</u> Freq Offset 0 Hz Center 2.4020000 GHz #Res BW 3.0 kHz Span 1.001 MHz Sweep 105.5 ms (1000 pts) **#VBW 10 kHz** Test_Graph_LE1M_ANT1_2402_1Mbps_PSD









10. Conducted Band Edge and Out-of-Band Emissions


10.1 Provisions Applicable


The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure.

10.2 Measurement Procedure

- Reference level measurement
- 1. Set instrument center frequency to DTS channel center frequency
- 2. Set the span to ≥ 1.5 times the DTS bandwidth
- 3. Set the RBW = 100 kHz
- Set the VBW ≥ 3 x RBW
- 5. Detector = peak
- 6. Sweep time = auto couple
- Trace mode = max hold
- 8. Allow trace to fully stabilize
- Emission level measurement
- 1. Set the center frequency and span to encompass frequency range to be measured
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Trace mode = max hold
- 6. Sweep time = auto couple
- 7. The trace was allowed to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)








10.4 Measurement Results


Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands




Test_Graph_LE1M_ANT1_2402_1Mbps_Reference Level
















Test_Graph_LE1M_ANT1_2440_1Mbps_Higher Band Emissions

#VBW 300 kHz





















Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands







Page 34 of 51

11. Radiated Spurious Emission

11.1 Measurement Limit

FCC Part 15,209 Limit in the below table to be followed

1 CO 1 art 13.209 Einnit in the below table to be followed				
Frequencies	Field Strength	Measurement Distance		
(MHz)	(microvolts/meter)	(meters)		
0.009~0.490	2400/F(kHz)	300		
0.490~1.705	24000/F(kHz)	30		
1.705~30.0	30	30		
30~88	100	3		
88~216	150	3		
216~960	200	3		
Above 960	500	3		

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds.

Any rep Ashang alternative (provided pther, transmitteral operates a forrill ongern than one in seconds) e or bin cases in where othe Stamp" is deemed to be invalid. Copying or excepting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15 days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.



Report No.: AGC00688240501FR02 Page 35 of 51

pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start - Stop i requertoy	1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP



Report No.: AGC00688240501FR02 Page 36 of 51

Quasi-Peak Measurements below 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

Average Measurements above 1GHz (Method VB)


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle ≥ 98%, set VBW = 10 Hz.
- 5. If the EUT duty cycle is < 98%, set VBW $\ge 1/T$. T is the minimum transmission duration.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold
- 8. Trace was allowed to stabilize






11.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9KHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/




11.4 Measurement Result


Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

	Radiated Emission Test Results at 30MHz-1GHz							
EUT NameWIRELESS USB ADAPTERModel NameBT540								
Temperature	21.8℃	Relative Humidity	59.8%					
Pressure	960hPa	Test Voltage	Normal Voltage					
Test Mode	Mode 1	Antenna Polarity	Horizontal					




Final [Data List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	36.79	22.57	11.23	40.00	17.43	100	167	Horizontal
2	100.81	27.14	17.03	43.50	16.36	100	288	Horizontal
3	239.52	21.30	16.00	46.00	24.70	100	1	Horizontal
4	460.68	29.80	24.60	46.00	16.20	100	42	Horizontal
5	622.67	31.44	25.54	46.00	14.56	100	78	Horizontal
6	857.41	36.16	29.93	46.00	9.84	100	30	Horizontal





	Radiated Emission Test Results at 30MHz-1GHz							
EUT Name WIRELESS USB ADAPTER Model Name BT540								
Temperature	21.8℃	Relative Humidity	59.8%					
Pressure	960hPa	Test Voltage	Normal Voltage					
Test Mode	Mode 1	Antenna Polarity	Vertical					



Final [Data List							
NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	33.88	22.44	12.12	40.00	17.56	100	1	Vertical
2	100.81	35.31	17.03	43.50	8.19	100	184	Vertical
3	242.43	20.11	15.24	46.00	25.89	100	281	Vertical
4	458.74	29.35	24.42	46.00	16.65	100	1	Vertical
5	622.67	31.66	25.54	46.00	14.34	100	305	Vertical
6	852.56	36.04	29.77	46.00	9.96	100	1	Vertical

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Limit-Level.

2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.



Page 40 of 51

Radiated Emissions Test Results for Above 1GHz

EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	46.26	0.08	46.34	74	-27.66	peak
4804.000	37.84	0.08	37.92	54	-16.08	AVG
7206.000	42.46	2.21	44.67	74	-29.33	peak
7206.000	33.28	2.21	35.49	54	-18.51	AVG
Remark:					•	•


Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	46.91	0.08	46.99	74	-27.01	peak
4804.000	37.65	0.08	37.73	54	-16.27	AVG
7206.000	42.48	2.21	44.69	74	-29.31	peak
7206.000	32.82	2.21	35.03	54	-18.97	AVG
				_		

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: Pass





Radiated Emissions Test Results for Above 1GHz

EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	- Value Type	
4880.000	46.35	0.14	46.49	74	-27.51	peak	
4880.000	37.45	0.14	37.59	54	-16.41	AVG	
7320.000	42.56	2.36	44.92	74	-29.08	peak	
7320.000	33.28	2.36	35.64	54	-18.36	AVG	
		_					

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	46.69	0.14	46.83	74	-27.17	peak
4880.000	37.85	0.14	37.99	54	-16.01	AVG
7320.000	42.41	2.36	44.77	74	-29.23	peak
7320.000	33.52	2.36	35.88	54	-18.12	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass



Page 42 of 51

Radiated Emissions Test Results for Above 1GHz

EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Horizontal

Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
46.17	0.22	46.39	74	-27.61	peak
38.25	0.22	38.47	54	-15.53	AVG
42.36	2.64	45	74	-29	peak
32.41	2.64	35.05	54	-18.95	AVG
	46.17 38.25 42.36	46.17 0.22 38.25 0.22 42.36 2.64	46.17 0.22 46.39 38.25 0.22 38.47 42.36 2.64 45	46.17 0.22 46.39 74 38.25 0.22 38.47 54 42.36 2.64 45 74	46.17 0.22 46.39 74 -27.61 38.25 0.22 38.47 54 -15.53 42.36 2.64 45 74 -29

|Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	46.32	0.22	46.54	74	-27.46	peak
4960.000	38.58	0.22	38.8	54	-15.2	AVG
7440.000	41.49	2.64	44.13	74	-29.87	peak
7440.000	32.67	2.64	35.31	54	-18.69	AVG


Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

RESULT: Pass

Note:


- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.







EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Horizontal


Test Graph for Peak Measurement








RESULT: Pass







EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Vertical


Test Graph for Peak Measurement








RESULT: Pass







EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Horizontal


Test Graph for Peak Measurement








RESULT: Pass







EUT Name	WIRELESS USB ADAPTER	Model Name	BT540
Temperature	21.8℃	Relative Humidity	59.8%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical

Test Graph for Peak Measurement







RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



12. AC Power Line Conducted Emission Test


12.1 Measurement Limit

F	Maximum RF	Line Voltage
Frequency	Q.P. (dBµV)	Average (dBμV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

12.2 Measurement Setup (Block Diagram of Configuration)





Page 48 of 51

12.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from PC which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5 Measurement Results







ode	Mode	1				LISN Line	Э	Neutral :	Side
	I [dBμV]								
80									
70	-				· ·				ii
60									
50	M - 11	i ==:		- <u>;</u> ;- <u></u>	· i ·	<u></u>	1 1 1 1		i
40 ⁴ ₹	*^#W#.~	h	+	- -					
30	Mundin	γ- (- ₁ λΛΜΜ <u>Υ</u>	switchild	ANTALAHTANANAHAHA	MANAGEMENT OF THE PARTY OF THE	And the last of th		A STATE OF THE PARTY OF THE PAR	1
20		Jane Wales	70 WU Lange	المسيح والمعالم المعالم	And of the Assessment of the State of the St	Actual Control of the			THE PERSON
10		·			i I				
-10	+		+ - -	 		- 			1
150)k 30	00k 400	k 600k 8	00k 1M	2M	3M 4M 5N	6M 8M 10M	20	OM 30M
					Frequency [H	Z]			
x x x ME	S agc_fir	n							
MEZ	cimem	י מודאי	DECIII M	: "agc	fin				
PIPIP	SUKEPH	TINT 1	RESULT	. auc					
					•				
2024		10:30							
	/5/9 requen	10:30 cy	Level	Transd	Limit		Detector	Line	PE
	/5/9 requen	10:30)	_		Margin dB	Detector	Line	PE
F	/5/9 'requen M	10:30 cy Hz	Level dBµV	Transd dB	Limit dBµV	dB			
F	/5/9 Tequen M	10:30 cy Hz	Level dBµV	Transd dB	Limit dBµV	dB 16.4	QP	N	GND
F	75/9 Trequent 0.1580	10:30 cy Hz 00	Level dBµV 49.20 42.70	Transd dB	Limit dBµV 66 65	dB 16.4 21.9	QP QP		GND GND
F	/5/9 Tequen M	10:30 cy Hz 00 00	Level dBµV	Transd dB	Limit dBµV	dB 16.4	QP	N N	GND
F	75/9 Trequen M 0.1580 0.1780 0.2300	10:30 cy Hz 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50	Transd dB 6.1 6.1 6.1 6.1 6.1	Limit dBµV 66 65 62 62 62	dB 16.4 21.9 26.5 27.9 28.1	QP QP QP	N N N	GND GND GND
F	75/9 requen M 0.1580 0.1780 0.2300 0.2420	10:30 cy Hz 00 00 00	Level dBµV 49.20 42.70 35.90 34.10	Transd dB 6.1 6.1 6.1 6.1	Limit dBµV 66 65 62 62	dB 16.4 21.9 26.5 27.9	QP QP QP QP	N N N	GND GND GND GND
F	0.1580 0.1780 0.2300 0.2420 0.2540	10:30 cy Hz 00 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50	Transd dB 6.1 6.1 6.1 6.1 6.1	Limit dBµV 66 65 62 62 62	dB 16.4 21.9 26.5 27.9 28.1	QP QP QP QP QP	N N N N	GND GND GND GND GND
F	0.1580 0.1780 0.2300 0.2420 0.2540	10:30 cy Hz 00 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50	Transd dB 6.1 6.1 6.1 6.1 6.1	Limit dBµV 66 65 62 62 62	dB 16.4 21.9 26.5 27.9 28.1	QP QP QP QP QP	N N N N	GND GND GND GND GND
F	0.1580 0.1580 0.1780 0.2300 0.2420 0.2540 1.2300	10:30 cy Hz 00 00 00 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30	Transd dB 6.1 6.1 6.1 6.1 6.1 6.2	Limit dBµV 66 65 62 62 62 56	dB 16.4 21.9 26.5 27.9 28.1	QP QP QP QP QP	N N N N	GND GND GND GND GND
F	0.1580 0.1580 0.1780 0.2300 0.2420 0.2540 1.2300	10:30 cy Hz 00 00 00 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50	Transd dB 6.1 6.1 6.1 6.1 6.1 6.2	Limit dBµV 66 65 62 62 62	dB 16.4 21.9 26.5 27.9 28.1	QP QP QP QP QP	N N N N	GND GND GND GND GND
MEA.	0.1580 0.1580 0.1780 0.2300 0.2420 0.2540 1.2300	10:30 cy Hz 00 00 00 00 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30	Transd dB 6.1 6.1 6.1 6.1 6.2	Limit dBµV 66 65 62 62 56	dB 16.4 21.9 26.5 27.9 28.1 31.7	QP QP QP QP QP	N N N N N	GND GND GND GND GND GND
MEA . 2024	/5/9 requent M 0.1580 0.1780 0.2300 0.2420 0.2540 1.2300 SUREM /5/9 requent	10:30 cy Hz 00 00 00 00 00 00 00 00 00 cy 10:30	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30 RESULT	Transd dB 6.1 6.1 6.1 6.1 6.2 : "agc_	Limit dBµV 66 65 62 62 56 fin2" Limit	dB 16.4 21.9 26.5 27.9 28.1 31.7	QP QP QP QP QP	N N N N N	GND GND GND GND GND GND
MEA . 2024	/5/9 requent M 0.1580 0.1780 0.2300 0.2420 0.2540 1.2300 SUREM /5/9 requent	10:30 cy Hz 00 00 00 00 00 00 00 00 00 10:30	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30	Transd dB 6.1 6.1 6.1 6.1 6.2	Limit dBµV 66 65 62 62 56	dB 16.4 21.9 26.5 27.9 28.1 31.7	QP QP QP QP QP	N N N N N	GND GND GND GND GND GND
MEA . 2024 F	0.1580 0.1780 0.2300 0.2420 0.2540 1.2300 SUREMI	10:30 cy Hz 00 00 00 00 00 00 00 00 to:30 cy Hz	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30 RESULT	Transd dB 6.1 6.1 6.1 6.1 6.2 Transd dB	Limit dBµV 66 65 62 62 62 56 fin2" Limit dBµV	dB 16.4 21.9 26.5 27.9 28.1 31.7 Margin dB	QP QP QP QP QP QP	N N N N N	GND GND GND GND GND
MEA . 2024 F	0.1580 0.1580 0.1780 0.2300 0.2420 0.2540 1.2300 SUREMI	10:30 cy Hz 00 00 00 00 00 00 00 10:30 cy Hz	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30 RESULT Level dBµV 24.60	Transd dB 6.1 6.1 6.1 6.2 Transd dB 6.1	Limit dBµV 66 65 62 62 56 fin2" Limit dBµV 54	dB 16.4 21.9 26.5 27.9 28.1 31.7 Margin dB	QP QP QP QP QP QP	N N N N N N	GND GND GND GND GND FE
MEA . 2024	0.1580 0.1780 0.2300 0.2420 0.2540 1.2300 SUREMI	10:30 cy Hz 00 00 00 00 00 00 00 00 00 00 Hz 10:30 cy Hz	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30 RESULT Level dBµV 24.60 22.30	Transd dB 6.1 6.1 6.1 6.1 6.2 Transd dB 6.1 6.1 6.1	Limit dBµV 66 65 62 62 56 56 fin2" Limit dBµV 54 52	dB 16.4 21.9 26.5 27.9 28.1 31.7 Margin dB 29.4 29.3	QP QP QP QP QP QP AV	N N N N N N	GND GND GND GND GND FE
MEA . 2024	/5/9 Trequence M 0.1580 0.1780 0.2300 0.2420 0.2540 1.2300 SUREM /5/9 Trequence M 0.1900 0.2540 0.5020	10:30 cy Hz 00 00 00 00 00 00 00 00 00 00 00 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30 RESULT Level dBµV 24.60 22.30 23.50	Transd dB 6.1 6.1 6.1 6.1 6.2 Transd dB 6.1 6.1 6.2	Limit dBµV 66 65 62 62 56 56 fin2" Limit dBµV 54 52 46	dB 16.4 21.9 26.5 27.9 28.1 31.7 Margin dB 29.4 29.3 22.5	QP QP QP QP QP QP AV AV	N N N N N N N	GND GND GND GND GND GND GND GND
MEA . 2024	0.1580 0.1780 0.2300 0.2420 0.2540 1.2300 SUREMI	10:30 cy Hz 00 00 00 00 00 00 00 00 00 00 00 00 00	Level dBµV 49.20 42.70 35.90 34.10 33.50 24.30 RESULT Level dBµV 24.60 22.30	Transd dB 6.1 6.1 6.1 6.1 6.2 Transd dB 6.1 6.1 6.1	Limit dBµV 66 65 62 62 56 56 fin2" Limit dBµV 54 52	dB 16.4 21.9 26.5 27.9 28.1 31.7 Margin dB 29.4 29.3	QP QP QP QP QP QP AV AV AV	N N N N N N	GND GND GND GND GND FE



Page 51 of 51

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC00688240501AP02

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC00688240501AP03

----End of Report----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.