

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

| | |
|---------------------|----------------------|
| Product Description | Wireless USB Adapter |
| Model Name | 5B07, 5B03 |
| FCC ID | 2AKC6XHT-5B07 |

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

2.4G WIFI:

$P_t = 7.63 \text{ dBm} = 5.79 \text{ mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (5.79 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.62(\text{GHz})}] = 1.82 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

5G WIFI:

$P_t = 5.72 \text{ dBm} = 3.73 \text{ mW}$

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation $\text{SAR} = (3.73 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.62(\text{GHz})}] = 1.70 < 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Note: The 2.4G WIFI and 5GHz WIFI band can not transmit simultaneously.

4. CONCLUSION

The SAR evaluation is not required.

