


FCC Part 15C**Measurement and Test Report****For****Shenzhen Sunvell electronics Co ., Ltd****FCC ID:2AKCR-22630**

FCC Rule(s):	<u>FCC Part 15C</u>
Product Description:	<u>TV BOX</u>
Model:	<u>T95S2,X95A,T95R1,T95R2,T95S1PRO,T95S1PLUS, T95S2PRO,T95S2PLUS</u>
Report No.:	<u>BSL190212157201</u>
Tested Date:	<u>2019-03-12 to 2019-03-22</u>
Issued Date:	<u>2019-03-22</u>
Tested By:	<u>Messi Wang / Engineer</u> 
Reviewed By:	<u>Lisa. Ji / EMC Manager</u> 
Approved & Authorized By:	<u>Mike mo / PSQ Manager</u> 
Prepared By:	

BSL Testing Co.,LTD.

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

Tel: 86- 755-26508703

Fax: 86- 755-26508703

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF EXPOSURE.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
5. POWER SPECTRAL DENSITY.....	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 ENVIRONMENTAL CONDITIONS.....	10
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	11
6. 6DB BANDWIDTH.....	17
6.1 STANDARD APPLICABLE.....	17
6.2 TEST PROCEDURE.....	17
6.3 ENVIRONMENTAL CONDITIONS.....	17
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	17
7. RF OUTPUT POWER.....	23
7.1 STANDARD APPLICABLE.....	23
7.2 TEST PROCEDURE.....	23
7.3 ENVIRONMENTAL CONDITIONS.....	23
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	24
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	25
8.1 MEASUREMENT UNCERTAINTY.....	25
8.2 STANDARD APPLICABLE.....	25
8.3 TEST PROCEDURE.....	25
8.4 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	27
8.5 ENVIRONMENTAL CONDITIONS.....	27
8.6 SUMMARY OF TEST RESULTS/PLOTS.....	27
9. OUT OF BAND EMISSIONS.....	36
9.1 STANDARD APPLICABLE.....	36
9.2 TEST PROCEDURE.....	36
9.3 ENVIRONMENTAL CONDITIONS.....	37
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	37
10. CONDUCTED EMISSIONS.....	41
10.1 MEASUREMENT UNCERTAINTY.....	41
10.2 TEST PROCEDURE.....	41
10.3 BASIC TEST SETUP BLOCK DIAGRAM.....	41
10.4 ENVIRONMENTAL CONDITIONS.....	41
10.5 TEST RECEIVER SETUP.....	42
10.6 SUMMARY OF TEST RESULTS/PLOTS.....	42
10.7 CONDUCTED EMISSIONS TEST DATA.....	42

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen Sunvell electronics Co ., Ltd
Address of applicant: Floor 5th, Building F,Hongzhuyongqi Technology Park,Lezhujiao Village, Xixiang Town,Bao' an District, Shenzhen City,Guangdong Province,China

Manufacturer: Shenzhen Sunvell electronics Co ., Ltd
Address of manufacturer: Floor 5th, Building F,Hongzhuyongqi Technology Park,Lezhujiao Village, Xixiang Town,Bao' an District, Shenzhen City,Guangdong Province,China

General Description of EUT

Product Name:	TV BOX
Trade Name:	Sunvell
Model No.:	T95S2
Adding Model(s):	X95A,T95R1,T95R2,T95S1PRO,T95S1PLUS, T95S2PRO,T95S2PLUS
Rated Voltage:	DC 5V from adapter

Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model T95S2,but the circuit and the electronic construction do not change, declared by the manufacturer.

Technical Characteristics of EUT

Support Standards:	802.11b, 802.11g, 802.11n
Frequency Range:	2412-2462MHz for 802.11b/g/n(HT20),
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Data Rate:	1-11Mbps, 6-54Mbps, up to 72.2Mbps
Channel Separation:	5MHz
Type of Antenna:	FPC antenna
Antenna Gain:	2dBi
Software version	V1.1
Hardware version	V1.1

1.2 Test Standards

The following report is prepared on behalf of the Shenzhen Sunvell electronics Co ., Ltd in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 Meas Guidance v05 for digital transmission systems and KDB 662911 D01 Multiple Transmitter Output v02r01 shall be performed also.

1.4 Test Facility

BSL Testing Co.,LTD.

NO. 24, ZH Park, Nantou, Shenzhen, 518000 China

FCC:

Designation Number : CN1217

Test Firm Registration Number: 866035

IC:

CAB identifier: CN0019

ISED#: 11093A

Tel: 86- 755-26508703

Fax: 86- 755-26508703

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List			
Test Mode	Description	Remark	
TM1	802.11b	2412MHz, 2437MHz, 2462MHz	
TM2	802.11g	2412MHz, 2437MHz, 2462MHz	
TM3	802.11n-HT20	2412MHz, 2437MHz, 2462MHz	

Note: All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty			
Parameter	Conditions	Uncertainty	
RF Output Power	Conducted	±0.42dB	
Occupied Bandwidth	Conducted	±1.5%	
Power Spectral Density	Conducted	±1.8dB	
Conducted Spurious Emission	Conducted	±2.17dB	
Conducted Emissions	Conducted	±2.88dB	
Transmitter Spurious Emissions	Radiated	±5.1dB	

1.7 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
Communication Tester	Rohde & Schwarz	CMW500	100358	2018-11-08	2019-11-07
Spectrum Analyzer	R&S	FSP40	100550	2018-10-08	2019-10-07
Test Receiver	R&S	ESCI7	US47140102	2018-10-08	2019-10-07
Signal Generator	HP	83630B	3844A01028	2018-10-08	2019-10-07
Test Receiver	R&S	ESPI-3	100180	2018-10-08	2019-10-07
Amplifier	Agilent	8449B	4035A00116	2018-10-08	2019-10-07
Amplifier	HP	8447E	2945A02770	2018-10-08	2019-10-07
Signal Generator	IFR	2023A	202307/242	2018-10-08	2019-10-07
Broadband Antenna	SCHAFFNER	2774	2774	2018-10-21	2019-10-20
Biconical and log periodic antennas	ELECTRO-METRI CS	EM-6917B-1	171	2018-10-21	2019-10-20
Horn Antenna	R&S	HF906	100253	2018-10-21	2019-10-20
Horn Antenna	EM	EM-6961	6462	2018-10-21	2019-10-20
LISN	R&S	ESH3-Z5	100196	2018-10-08	2019-10-07
LISN	COM-POWER	LI-115	02027	2018-10-08	2019-10-07
3m Semi-Anechoic Chamber	Chengyu Electron	9 (L)*6 (W)* 6 (H)	BSL086	2018-10-08	2019-10-07
Horn Antenna	Schwarzbeck	BBHA9170	00814	2018-10-21	2019-10-20
Loop Antenna	Schwarz beck	FMZB 1516	9773	2018-06-16	2019-06-15
Power Meter	DARE	RPR3006W	15I00041SNO03	2018-10-21	2019-10-20

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§2.1091	RF Exposure	Compliant
§15.203;§15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	6 dB Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to §1.1307 and §2.1091, the mobile transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203&RSS-Gen Issue 5, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a FPC antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii)&RSS-247 Issue 2, For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 Meas Guidance v05, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set VBW $\geq 3 \times \text{RBW}$.
- e) Detector = PK
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

5.3 Environmental Conditions

Temperature:	26°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
802.11b	2412	-15.20	8
	2437	-15.43	8
	2462	-15.14	8
802.11g	2412	-19.40	8
	2437	-20.81	8
	2462	-20.74	8
802.11n HT20	2412	-22.16	8
	2437	-22.13	8
	2462	-21.62	8

Note:

1. Limit=8dBm/MHz


Please refer to the following test plots:

802.11b-Low Channel




Date: 19.MAR.2019 13:14:33

802.11b-Middle Channel




Date: 19.MAR.2019 13:17:56

802.11b-High Channel




Date: 19.MAR.2019 13:18:57

802.11g-Low Channel




Date: 19.MAR.2019 13:34:38

802.11g-Middle Channel




Date: 19.MAR.2019 13:40:30

802.11g-High Channel




Date: 20.MAR.2019 13:52:16

802.11n-HT20-Low Channel




Date: 20.MAR.2019 14:14:49

802.11n-HT20-Middle Channel



Date: 20.MAR.2019 14:21:17

802.11n-HT20-High Channel



Date: 20.MAR.2019 14:22:23

6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2)&RSS-247 Issue 2. Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions


Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

6.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth MHz	99% Bandwidth MHz	Limit kHz
802.11b	2412	9.48	12.56	≥500
	2437	9.52	12.64	≥500
	2462	9.52	12.64	≥500
802.11g	2412	16.56	16.44	≥500
	2437	16.56	16.44	≥500
	2462	16.56	16.44	≥500
802.11n-HT20	2412	17.76	17.64	≥500
	2437	17.70	17.64	≥500
	2462	17.70	17.64	≥500


Please refer to the following test plots:

802.11b-Low Channel




Date: 14.MAR.2019 15:43:06

802.11b-Middle Channel




Date: 14.MAR.2019 15:46:03

802.11b-High Channel




Date: 15.MAR.2019 13:03:54

802.11g-Low Channel




Date: 15.MAR.2019 13:47:09

802.11g-Middle Channel




Date: 15.MAR.2019 13:49:43

802.11g-High Channel




Date: 15.MAR.2019 13:51:09

802.11n-HT20-Low Channel




Date: 15.MAR.2019 13:54:41

802.11n-HT20-Middle Channel



Date: 15.MAR.2019 14:05:13

802.11n-HT20-High Channel



Date: 15.MAR.2019 14:07:19


7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3)&RSS-247 Issue 2. For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.



7.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results

Test Mode	Frequency MHz	Power dBm	Output Power mW	Limit mW
802.11b_11Mbps	2412	15.75	37.5837	1000
	2437	15.29	33.8065	1000
	2462	16.04	40.1791	1000
802.11g_54Mbps	2412	13.90	24.5471	1000
	2437	14.33	27.1019	1000
	2462	14.72	29.6483	1000
802.11n HT20_MCS7	2412	13.98	25.0035	1000
	2437	14.33	27.1019	1000
	2462	14.66	29.2415	1000

Note:

1. Limit=30dBm

8. Field Strength of Spurious Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ± 5.10 dB.

8.2 Standard Applicable

According to §15.247(d)&RSS-247 Issue 2, in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.



8.3 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

Below 30MHz Test Setup



30M-1GHz:**Above 1GHz:**

Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.4 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.5 Environmental Conditions


Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.6 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:


Note:

1. *Worst-case radiated emission below 1GHz is 802.11b (CH High) .*
2. *Worst-case radiated emission above 1GHz is 802.11b (CH Low Middle High).*

Plot of Radiated Emissions Test Data (30MHz to 1GHz): 802.11b (CH High)*Test Specification:* Horizontal

No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit dBuV/m	Over dB	Over Detector
			Level dBuV	Factor	ment dBuV/m			
1		36.2541	19.48	4.80	24.28	40.00	-15.72	QP
2		74.9191	22.43	1.13	23.56	40.00	-16.44	QP
3		136.9389	19.35	3.37	22.72	43.50	-20.78	QP
4	*	332.5187	27.48	8.06	35.54	46.00	-10.46	QP
5		651.9415	17.51	12.77	30.28	46.00	-15.72	QP
6		836.2441	16.26	18.01	34.27	46.00	-11.73	QP

Test Specification: Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
		MHz	dBuV	dBuV/m	dBuV/m	dB	Detector
1		44.2751	17.55	3.28	20.83	40.00	-19.17 QP
2		72.0841	19.59	1.05	20.64	40.00	-19.36 QP
3		135.0319	25.06	3.42	28.48	43.50	-15.02 QP
4		199.2855	19.60	3.41	23.01	43.50	-20.49 QP
5		276.1235	21.80	6.33	28.13	46.00	-17.87 QP
6	*	429.5228	22.06	9.57	31.63	46.00	-14.37 QP

Spurious Emissions Above 1GHz

Test Mode: 802.11b

Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar	Detector
Low channel-2412MHz					
4824.000	52.49	74	-21.51	H	PK
4824.000	39.22	54	-14.78	H	AV
7236.000	50.37	74	-23.63	H	PK
7236.000	36.35	54	-17.65	H	AV
4824.000	52.98	74	-21.02	V	PK
4824.000	39.64	54	-14.36	V	AV
7236.000	51.17	74	-22.83	V	PK
7236.000	37.49	54	-16.51	V	AV
Middle channel-2437MHz					
4874.000	52.21	74	-21.79	H	PK
4874.000	40.39	54	-13.61	H	AV
7311.000	49.7	74	-24.3	H	PK
7311.000	37.59	54	-16.41	H	AV
4874.000	54.18	74	-19.82	V	PK
4874.000	40.97	54	-13.03	V	AV
7311.000	50.72	74	-23.28	V	PK
7311.000	37.65	54	-16.35	V	AV
High channel-2462MHz					
4924.000	51.26	74	-22.74	H	PK
4924.000	38.01	54	-15.99	H	AV
7386.000	49.82	74	-24.18	H	PK
7386.000	37.37	54	-16.63	H	AV
4924.000	53.37	74	-20.63	V	PK
4924.000	39.95	54	-14.05	V	AV
7386.000	51.22	74	-22.78	V	PK
7386.000	38.59	54	-15.41	V	AV


Note:

1. Calculation of result is: Result (dBm) = Reading (dBm) + Correction Factor (dB).
2. Correction Factor (dB)=Ant. Factor + Cable Loss – Ampl. Gain.
3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The worst data of spurious (Conducted)


802.11b-Lowest

Lowest




Date: 15.MAR.2019 14:21:30

Middle



Date: 15.MAR.2019 14:25:02


Highest



Date: 15.MAR.2019 14:26:34


802.11g-Lowest

Lowest




Date: 15.MAR.2019 14:28:18

Middle



Date: 15.MAR.2019 14:29:32


Highest



Date: 15.MAR.2019 14:30:25


802.11n-HT20-Lowest

Lowest




Date: 15.MAR.2019 14:32:04

Middle



Date: 15.MAR.2019 14:37:46

Highest



Date: 15.MAR.2019 14:39:15

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d)&RSS-247 Issue 2 In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 Meas Guidance v05, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 Meas Guidance v05, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW \geq 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Environmental Conditions

Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

802.11b- Bandedge (Radiated)


Note: we pre-scan all modes, the worst data is 802.11b mode.

Channel	Freq.(MHz)	Level(dBuV)	Limit(dBuV)	Margin(dB)	Detector
	2400	55.75	74	-18.25	Peak
LOW	2400	39.59	54	-14.41	Average
	2483.5	52.64	74	-21.36	Peak
HIGH	2483.5	38.72	54	-15.28	Average

Bandedge (Conducted)


802.11b-Lowest

Lowest




Date: 15.MAR.2019 15:49:20

Highest




Date: 18.MAR.2019 14:57:20

802.11g-Lowest



Date: 15.MAR.2019 15:47:57


Highest



Date: 18.MAR.2019 15:01:03


802.11n-HT20-Lowest

Lowest



Date: 15.MAR.2019 15:46:30

Highest



Date: 18.MAR.2019 15:03:07

10. Conducted Emissions

10.1 Measurement Uncertainty


Base on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement is ± 2.88 dB.

10.2 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207&RSS-Gen Issue 5 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.3 Basic Test Setup Block Diagram



10.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.5 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth.....	9 kHz
Quasi-Peak Adapter Mode.....	Normal

10.6 Summary of Test Results/Plots

According to the data in section 10.7, the EUT complied with the FCC Part 15.207 Conducted margin for this device

Note: we are pre-scan all modes, the worst data is 802.11n HT20(Low) mode.

10.7 Conducted Emissions Test Data

Test Results:PASS


NOTE:

Corret Factor=LISN Factor+Cable loss.

Measurementt=Reading level+Corret Factor.


Plot of Conducted Emissions Test Data

Test Specification: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Over Detector
1		0.1980	41.97	0.50	42.47	63.69	-21.22	QP
2		0.1980	25.74	0.50	26.24	53.69	-27.45	AVG
3		0.3420	40.87	0.48	41.35	59.15	-17.80	QP
4		0.3420	22.46	0.48	22.94	49.15	-26.21	AVG
5	*	0.5580	39.06	0.51	39.57	56.00	-16.43	QP
6		0.5580	24.98	0.51	25.49	46.00	-20.51	AVG
7		0.7780	35.24	0.58	35.82	56.00	-20.18	QP
8		0.7780	20.13	0.58	20.71	46.00	-25.29	AVG
9		1.1220	31.77	0.64	32.41	56.00	-23.59	QP
10		1.1220	17.23	0.64	17.87	46.00	-28.13	AVG
11		2.9420	29.55	0.79	30.34	56.00	-25.66	QP
12		2.9420	11.60	0.79	12.39	46.00	-33.61	AVG

Test Specification: Line



No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit dBuV	Over dB	Over Detector
			Level dBuV	Factor dB	ment dBuV			
1		0.1620	38.48	0.50	38.98	65.36	-26.38	QP
2		0.1620	21.64	0.50	22.14	55.36	-33.22	AVG
3		0.3180	37.68	0.49	38.17	59.76	-21.59	QP
4		0.3180	22.20	0.49	22.69	49.76	-27.07	AVG
5 *		0.4420	35.66	0.48	36.14	57.02	-20.88	QP
6		0.4420	19.58	0.48	20.06	47.02	-26.96	AVG
7		0.7900	31.54	0.58	32.12	56.00	-23.88	QP
8		0.7900	15.96	0.58	16.54	46.00	-29.46	AVG
9		1.1620	28.15	0.65	28.80	56.00	-27.20	QP
10		1.1620	17.18	0.65	17.83	46.00	-28.17	AVG
11		2.8140	25.19	0.78	25.97	56.00	-30.03	QP
12		2.8140	10.56	0.78	11.34	46.00	-34.66	AVG

***** END OF REPORT *****