

工业4寸

预留不干胶
空白位置
(≥1.8*2.8cm)



HALO
AC INPUT:
120 VAC ~.09A
60 HZ Pfc.9



Patent: www.eaton.com/patents
Le brevet: www.eaton.com/patents
La marca: www.eaton.com/patents
2700k-5000K LL5182024EN
10.9Watts FCC ID: 2AKCY-RL4HLBLE
IC: 4706A-RL4HLBLE



AIR-TITE™ certified per ASTM-E283-04
AIR-TITE™ certificada por ASTM-E283-04
AIR-TITE™ homologué par ASTM-E283-04

Do Not Use With Standard Dimmers.
See instructions. Disconnect power before servicing. /
Ne pas utiliser avec les gradateurs standards. Débranchez
l'alimentation avant de procéder à l'entretien. / No utilizar con un regulador de intensidad estándar.
Vea las instrucciones. Desconecte la alimentación antes de realizar el mantenimiento.

HALO-HUBICAL, HUBICAL, HUBITAL, HUBITAL,
HUBICAL, HUBICAL, HUBICAL, HUBICAL,
EVALCISA, EVALCISA, EVALCISA,
ALL-PRO-EMODATOR, EEMODATOR

EATON
1121 HIGHWAY 74 SOUTH
PEACHTREE CITY, GA 30269
LL5182024EN

Smart LED Lamp Assembly
Intelligente Assemblée de lampe LED
RLA099BLE40AMH

See the instruction sheet or visit us at www.haloled.com for more information.
Consultez la notice ou visitez le site www.haloled.com pour plus d'informations.
Consultar el manual de instrucciones o ir a www.haloled.com para más información.

SUITABLE FOR WET LOCATIONS COVERED
CEILING MOUNT ONLY / CONVIENT AUX ENDROITS
HUMIDES AVEC UN PLAFOND COUVERT /
ADECUADO PARA LUGARES HÚMEDOS
CON UN TECHO CUBIERTO

UL Certified for use with the following non-halo dimmers:
UL Certified for use with the following non-halo dimmers:
UL Certified for use with the following non-halo dimmers:
UL Certified for use with the following non-halo dimmers:
UL Certified for use with the following non-halo dimmers: