



Label

		<b>IC5003 063 22 10043130</b>			
CATALOG NO. N° CATALOGUE CATÁLOGO NO.		<b>4NWS3C3MS-UNV</b>		SUITABLE FOR OPERATION IN AMBIENT NOT EXCEEDING 40°C PEUT ÊTRE UTILISÉ À UNE TEMPÉRATURE AMBIANTE N'EXCÉDANT PAS 40°C. APTO PARA FUNCIONAR EN AMBIENTES HASTA 40°C. SUITABLE FOR DAMP LOCATION CONVIENT AUX EMPLACEMENTS HUMIDES. APTO PARA LUGARES HUMEDOS. MIN 90 °C SUPPLY CONDUCTORS LES FILS D'ALIMENTATION 90 °C MIN CONDUCTORES DE ALIMENTACIÓN 90°C MÍN	
MATERIAL NO. N° MATÉRIEL MATERIAL NO.		<b>13598919</b>			
<b>120-277V</b>	<b>40 W</b>	<b>50/60Hz</b>			
ASSEMBLED IN CHINA ASSEMBLÉ DANS CHINE ENSAMBLADO EN CHINA		<b>0.330A</b>			
FCC ID:2AKCY4NWS3C3MS-UNV THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE. (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRED OPERATION					

label location

