

RF Exposure Report

Report No.: SA180524C28A

FCC ID: 2AKCZ-0D1

Test Model: APL46-0D1

Received Date: May 04, 2018

Test Date: May 04 ~ Jun. 20, 2018

Issued Date: Jul. 26, 2018

Applicant: SonicWall Inc.

Address: 1033 McCarthy Blvd., Milpitas, CA 95035, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)

**FCC Registration /
Designation Number:** 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA180524C28A	Original release	Jul. 26, 2018

1 Certificate of Conformity

Product: Wireless Access Point

Brand: SONICWALL

Test Model: APL46-0D1

Sample Status: Engineering sample

Applicant: SonicWall Inc.

Test Date: May 04 ~ Jun. 20, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Jul. 26, 2018
Celine Chou / Specialist

Approved by : Bruce Chen , **Date:** Jul. 26, 2018
Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 40cm away from the body of the user. So, this device is classified as Mobile Device.

3 Calculation Result of Maximum Conducted Power

Function	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN	Radio 1, Dipole Ant., CDD Mode					
	2412-2462	22.56	7.51	40	0.05054	1
	Radio 1, Dipole Ant., Beamforming Mode					
	2412-2462	19.22	7.51	40	0.02342	1
	Radio 1, Sector Ant., CDD Mode					
	2412-2462	21.72	15.61	40	0.26895	1
	Radio 1, Sector Ant., Beamforming Mode					
	2412-2462	18.47	15.61	40	0.12725	1
	Radio 2, Dipole Ant., CDD Mode					
	5180-5240	23.19	9.31	40	0.08844	1
	5260-5320	23.37	9.31	40	0.09219	1
	5500-5700	22.53	9.31	40	0.07597	1
	5745-5825	23.00	9.31	40	0.08466	1
	Radio 2, Dipole Ant., Beamforming Mode					
	5180-5240	20.16	9.31	40	0.04402	1
	5260-5320	20.36	9.31	40	0.04610	1
	5500-5700	19.52	9.31	40	0.03799	1
	5745-5825	19.96	9.31	40	0.04204	1
	Radio 2, Sector Ant., CDD Mode					
	5180-5240	14.13	17.61	40	0.07425	1
	5260-5320	15.31	17.61	40	0.09742	1
	5500-5700	15.37	17.61	40	0.09878	1
	5745-5825	21.35	17.61	40	0.39144	1
	Radio 2, Sector Ant., Beamforming Mode					
	5180-5240	11.12	17.61	40	0.03713	1
	5260-5320	12.30	17.61	40	0.04872	1
	5500-5700	12.36	17.61	40	0.04939	1
	5745-5825	18.34	17.61	40	0.19574	1
	Radio 3, PIFA Ant.					
	2412-2462	16.92	3.67	40	0.00570	1

Function	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
BT LE	2402-2480	-4.25	3.69	40	0.00004	1

Note:

1. For Radio 1, Dipole Ant. 2.4G Directional gain = $4.50\text{dBi} + 10\log(2) = 7.51\text{dBi}$
2. For Radio 1, Sector Ant. 2.4G Directional gain = $12.60\text{dBi} + 10\log(2) = 15.61\text{dBi}$
3. For Radio 2, Dipole Ant. 5G Directional gain = $6.30\text{dBi} + 10\log(2) = 9.31\text{dBi}$
4. For Radio 2, Sector Ant. 5G Directional gain = $14.60\text{dBi} + 10\log(2) = 17.61\text{dBi}$

Frequency Band	Max Power (dBm)			Total Power (dBm)	Power Limit (dBm)
	Radio 1 WLAN	Radio 3 WLAN	BT LE		
2.4GHz	22.56	16.92	-4.25	23.62	30

Conclusion:

The formula of calculated the MPE is:

$\text{CPD1} / \text{LPD1} + \text{CPD2} / \text{LPD2} + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

Radio 1 WLAN 2.4GHz + Radio 2 WLAN 5GHz + Radio 3 WLAN 2.4GHz + BT LE = $0.26895 + 0.39144 + 0.00570 + 0.00004 = 0.66613 < 1$

---END---