

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)
Report No.: RFBIDS-WTW-P22031091C-1
FCC ID: 2AKCZ-108
Product: Wireless Access Point
Brand: SONICWALL
Model No.: APL68-108
Received Date: 2024/3/28
Test Date: 2024/4/25 ~ 2024/8/6
Issued Date: 2024/9/3
Applicant: SonicWall Inc.
Address: 1033 McCarthy Blvd., Milpitas, CA 95035, USA
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories
Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan
FCC Registration /
Designation Number: 788550 / TW0003

Approved by: _____

Jeremy Lin

Jeremy Lin / Project Engineer

, Date: _____

2024/9/3

This test report consists of 90 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Pettie Chen / Senior Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Antenna Description of EUT	9
3.3 Channel List.....	10
3.4 Test Mode Applicability and Tested Channel Detail.....	12
3.5 Duty Cycle of Test Signal.....	13
3.6 Test Program Used and Operation Descriptions	15
3.7 Connection Diagram of EUT and Peripheral Devices	15
3.8 Configuration of Peripheral Devices and Cable Connections	16
4 Test Instruments	17
4.1 RF Output Power.....	17
4.2 Power Spectral Density	17
4.3 6 dB Bandwidth	17
4.4 Occupied Bandwidth.....	17
4.5 Frequency Stability	17
4.6 AC Power Conducted Emissions	18
4.7 Unwanted Emissions below 1 GHz	19
4.8 Unwanted Emissions above 1 GHz.....	20
5 Limits of Test Items.....	21
5.1 RF Output Power.....	21
5.2 Power Spectral Density	21
5.3 6 dB Bandwidth	21
5.4 Occupied Bandwidth.....	21
5.5 Frequency Stability	21
5.6 AC Power Conducted Emissions	21
5.7 Unwanted Emissions below 1 GHz	22
5.8 Unwanted Emissions above 1 GHz.....	22
6 Test Arrangements.....	24
6.1 RF Output Power.....	24
6.1.1 Test Setup	24
6.1.2 Test Procedure.....	24
6.2 Power Spectral Density	24
6.2.1 Test Setup	24
6.2.2 Test Procedure.....	24
6.3 6 dB Bandwidth	25
6.3.1 Test Setup	25
6.3.2 Test Procedure.....	25
6.4 Occupied Bandwidth.....	25
6.4.1 Test Setup	25
6.4.2 Test Procedure.....	25
6.5 Frequency Stability	26
6.5.1 Test Setup	26
6.5.2 Test Procedure.....	26
6.6 AC Power Conducted Emissions	27
6.6.1 Test Setup	27
6.6.2 Test Procedure.....	27
6.7 Unwanted Emissions below 1 GHz	28
6.7.1 Test Setup	28
6.7.2 Test Procedure.....	29

6.8	Unwanted Emissions above 1 GHz.....	30
6.8.1	Test Setup	30
6.8.2	Test Procedure	30
7	Test Results of Test Item	31
7.1	RF Output Power.....	31
7.2	Power Spectral Density	33
7.3	6 dB Bandwidth	37
7.4	Occupied Bandwidth.....	39
7.5	Frequency Stability	43
7.6	AC Power Conducted Emissions	44
7.7	Unwanted Emissions below 1 GHz	52
7.8	Unwanted Emissions above 1 GHz.....	60
8	Pictures of Test Arrangements	89
9	Information of the Testing Laboratories	90

Release Control Record

Issue No.	Description	Date Issued
RFBDYS-WTW-P22031091C-1	Original release.	2024/9/3

1 Certificate

Product: Wireless Access Point

Brand: SONICWALL

Test Model: APL68-108

Sample Status: Engineering sample

Applicant: SonicWall Inc.

Test Date: 2024/4/25 ~ 2024/8/6

Standard: 47 CFR FCC Part 15, Subpart E (Section 15.407)

Measurement procedure: ANSI C63.10-2013

KDB 789033 D02 General UNII Test Procedure New Rules v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
Clause	Test Item	Result	Remark
15.407(a)(2)	26 dB Bandwidth	-	For U-NII-2A U-NII-2C Band output power limitation is determined based on 26dBc bandwidth.
15.407(a)(1) 15.407(a)(3)	RF Output Power	Pass	Meet the requirement of limit.
15.407(a)(1) 15.407(a)(3)	Power Spectral Density	Pass	Meet the requirement of limit.
15.407(e)	6 dB Bandwidth	Pass	Meet the requirement of limit. (U-NII-3 Band only)
---	Occupied Bandwidth	-	Reference only.
15.407(g)	Frequency Stability	Pass	Meet the requirement of limit.
15.407(b)(9)	AC Power Conducted Emissions	Pass	Minimum passing margin is -5.58 dB at 0.50600 MHz
15.407(b)(9)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -2.9 dB at 31.94 MHz
15.407(b) (1/10) 15.407(b) (4(i)/10)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -4.3 dB at 5150.00 MHz
15.203	Antenna Requirement	Pass	Antenna connector is I-PEX not a standard connector.

Notes:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. The "Dynamic Frequency Selection measurement" was recorded in DFS test report.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.371 dB
Power Spectral Density	-	1.017 dB
6 dB Bandwidth	-	206.5 Hz
Occupied Bandwidth	-	72 Hz
Frequency Stability	-	0.176 ppm
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.6 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Wireless Access Point
Brand	SONICWALL
Test Model	APL68-108
Status of EUT	Engineering sample
Power Supply Rating	12Vdc from adapter 48-56Vdc from POE
Modulation Type	256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM 1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDMA
Modulation Technology	OFDM, OFDMA
Transfer Rate	802.11a: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 300Mbps 802.11ac: up to 866.7Mbps 802.11ax: up to 1200Mbps
Operating Frequency	5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5720MHz, 5745MHz ~ 5825MHz
Number of Channel	5G traffic radio (Radio 1): 5180 ~ 5240MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 5260 ~ 5320MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 5500 ~ 5720MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 12 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 6 802.11ac (VHT80), 802.11ax (HE80): 3 5745 ~ 5825MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 5 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 Scanning radio (Radio 3): 5180 ~ 5240MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 4 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (VHT80): 1 5745 ~ 5825MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20): 5 802.11n (HT40), 802.11ac (VHT40): 2 802.11ac (VHT80): 1
Output Power	Scanning radio (Radio 3): 5.18 GHz ~ 5.24 GHz : 17.539 mW (12.44 dBm) 5.745 GHz ~ 5.825 GHz : 17.498 mW (12.43 dBm)
EUT Category	Indoor Access Point

Note:

1. This report is prepared for FCC class II permissive change. This report is issued as a supplementary report to BV CPS report no. RFBDYS-WTW-P22031091-1, RFBDYS-WTW-P22031091A. The differences compared with original report are changing 2.4G traffic radio 2nd source (pin-to-pin) chip and changing 5G scan radio 2nd source (pin-to-pin) FEM. Therefore, the Scanning radio (Radio 3) is re-tested for all tests, and 5G traffic radio (Radio 1) is re-tested AC Power Conducted Emissions and Unwanted Emissions below 1 GHz tests in this report.

2. The EUT uses following accessories.

Item	Brand	Model	Specification
BRACKET T-BAR LFP	Senao	6301A4133020	Accessory
AC Adapter (Optional)	Sunny	SYS1546-3612-T3	AC Input : 100-240Vac, 1.5A MAX, 50-60Hz DC Output : 12.0Vdc, 3.0A power cord : Non-shielded AC (1.77m) Non-shielded DC (1.86m with one ferrite core)
POE (Support unit only)	EnGenius	EPA5006GAT	AC Input : 100-240Vac, 0.8A, 50-60Hz DC Output : 48-56Vdc, 0.6A Non-shielded AC (0.5m)

3. The simultaneous operation mode was determined by client.

No	Mode
1	2GHz traffic radio (Radio 2) + 5GHz traffic radio (Radio 1) + 5GHz Scanning radio (Radio 3) + BLE
2	5GHz traffic radio (Radio 1) + 2GHz Scanning radio (Radio 3) + BLE

* 5GHz traffic radio (Radio 1) and 5GHz Scanning radio (Radio 3) cannot transmit in the same band at same time.

* 2GHz traffic radio (Radio 2) and 2GHz Scanning radio (Radio 3) cannot transmit at same time.

* Spurious emission of the simultaneous operation has been evaluated and no non-compliance was found.

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

No.	Type	Connector	Gain (dBi)					
			2400MHz	2450MHz	2500MHz	5150MHz	5500MHz	5850MHz
2G1	PIFA	I-PEX	3.05	3.14	3.21	-	-	-
2G2	PIFA	I-PEX	3.52	3.43	3.64	-	-	-
5G1	PIFA	I-PEX	-	-	-	4.52	4.63	5.07
5G2	PIFA	I-PEX	-	-	-	4.13	4.98	4.62
Scan	PIFA	I-PEX	3.83	3.93	3.81	3.81	4.23	4.89
BLE	PIFA	I-PEX	3.09	3.70	3.58	-	-	-

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

Radio	Modulation Mode	Beamforming Mode	TX Function
5G traffic radio (Radio 1)	802.11a	Not Support	2TX
	802.11n (HT20)	Support	2TX
	802.11n (HT40)	Support	2TX
	802.11ac (VHT20)	Support	2TX
	802.11ac (VHT40)	Support	2TX
	802.11ac (VHT80)	Support	2TX
	802.11ax (HE20)	Support	2TX
	802.11ax (HE40)	Support	2TX
	802.11ax (HE80)	Support	2TX
Scanning radio (Radio 3)	802.11a	Not Support	1TX
	802.11n (HT20)	Not Support	1TX
	802.11n (HT40)	Not Support	1TX
	802.11ac (VHT20)	Not Support	1TX
	802.11ac (VHT40)	Not Support	1TX
	802.11ac (VHT80)	Not Support	1TX

Note:

1. For 802.11ax mode, this EUT doesn't support partial RU mode.
2. The bandwidth and modulation are similar for HT20/HT40 on 802.11n mode and VHT20/VHT40/VHT80 on 802.11ac mode and HE20/HE40/HE80 on 802.11ax mode. Therefore, the investigated worst case is the representative mode in test report.
3. CDD mode is the worst case for final tests after pretesting CDD mode and Beamforming mode except output power test.

3.3 Channel List

For 5180 ~ 5240 MHz

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
42	5210 MHz

For 5260 ~ 5320MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
52	5260 MHz	60	5300 MHz
56	5280 MHz	64	5320 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
54	5270 MHz	62	5310 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
58	5290MHz

For 5500 ~ 5720MHz:

12 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
100	5500 MHz	124	5620 MHz
104	5520 MHz	128	5640 MHz
108	5540 MHz	132	5660 MHz
112	5560 MHz	136	5680 MHz
116	5580 MHz	140	5700 MHz
120	5600 MHz	144	5720 MHz

6 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
102	5510 MHz	126	5630 MHz
110	5550 MHz	134	5670 MHz
118	5590 MHz	142	5710 MHz

3 channels are provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency	Channel	Frequency
106	5530 MHz	122	5610 MHz
138	5690 MHz		

For 5745 ~ 5825 MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
151	5755 MHz	159	5795 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
155	5775 MHz

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	EUT can be used in the following ways: X/Y/Z axis. Pre-scan in these ways and find the worst case as a representative test condition.
Worst Case:	Y-Axis

Following channel(s) was (were) selected for the final test as listed below:

Test Item	EUT Configure Mode	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	C	802.11a	-	36, 40, 48, 149, 157, 165	BPSK	6Mb/s
		802.11ac (VHT20)	-	36, 40, 48, 149, 157, 165	BPSK	MCS0
		802.11ac (VHT40)	-	38, 46, 151, 159	BPSK	MCS0
		802.11ac (VHT80)	-	42, 155	BPSK	MCS0
Power Spectral Density	C	802.11a	-	36, 40, 48, 149, 157, 165	BPSK	6Mb/s
		802.11ac (VHT20)	-	36, 40, 48, 149, 157, 165	BPSK	MCS0
		802.11ac (VHT40)	-	38, 46, 151, 159	BPSK	MCS0
		802.11ac (VHT80)	-	42, 155	BPSK	MCS0
6 dB Bandwidth	C	802.11a	-	149, 157, 165	BPSK	6Mb/s
		802.11ac (VHT20)	-	149, 157, 165	BPSK	MCS0
		802.11ac (VHT40)	-	151, 159	BPSK	MCS0
		802.11ac (VHT80)	-	155	BPSK	MCS0
Occupied Bandwidth	C	802.11a	-	36, 40, 48, 149, 157, 165	BPSK	6Mb/s
		802.11ac (VHT20)	-	36, 40, 48, 149, 157, 165	BPSK	MCS0
		802.11ac (VHT40)	-	38, 46, 151, 159	BPSK	MCS0
		802.11ac (VHT80)	-	42, 155	BPSK	MCS0
Frequency Stability	C	802.11a	-	36	unmodulated	-
AC Power Conducted Emissions	A, B	802.11ax (HE40)	CDD	159	BPSK	MCS0
	C, D	802.11ac (VHT40)	-	46	BPSK	MCS0
Unwanted Emissions below 1 GHz	A, B	802.11ax (HE40)	CDD	159	BPSK	MCS0
	C, D	802.11ac (VHT40)	-	46	BPSK	MCS0
Unwanted Emissions above 1 GHz	C	802.11a	-	36, 40, 48, 149, 157, 165	BPSK	6Mb/s
		802.11ac (VHT20)	-	36, 40, 48, 149, 157, 165	BPSK	MCS0
		802.11ac (VHT40)	-	38, 46, 151, 159	BPSK	MCS0
		802.11ac (VHT80)	-	42, 155	BPSK	MCS0
EUT Configure Mode:	A	Radio 1	Powered by adapter			
	B		Powered by PoE			
	C	Radio 3	Powered by adapter			
	D		Powered by PoE			

3.5 Duty Cycle of Test Signal


Radio 3

802.11a: Duty cycle = $2.035 \text{ ms} / 2.1 \text{ ms} \times 100\% = 96.9\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.14 \text{ dB}$


802.11ac (VHT20): Duty cycle = $1.905 \text{ ms} / 1.97 \text{ ms} \times 100\% = 96.7\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.15 \text{ dB}$

802.11ac (VHT40): Duty cycle = $0.94 \text{ ms} / 1 \text{ ms} \times 100\% = 94.0\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.27 \text{ dB}$


802.11ac (VHT80): Duty cycle = $0.458 \text{ ms} / 0.522 \text{ ms} \times 100\% = 87.7\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.57 \text{ dB}$




802.11a



802.11ac (VHT20)



802.11ac (VHT40)




802.11ac (VHT80)

3.6 Test Program Used and Operation Descriptions


Controlling software QSPR Version 5.0-00199 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices

Test Mode A, C



Test Mode B, D



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	Lenovo	X250ALT5	PC06HPSE	FCC DoC Approved	-
B.	Adapter	Sunny	SYS1546-3612-T3	NA	NA	Provided by client
C.	PoE	EnGenius	EPA5006GAT	NA	NA	Provided by client
D.	USB Flash	SanDisk	SDDDC3-032G	5	NA	-

No.	Cable Descriptions	Qty.	Length (m)	Shielded (Yes/ No)	Cores (Qty.)	Remark
1.	DC Power Cable	1	1.86	N	1	Provided by client
2.	LAN Cable	1	10.0	N	0	RJ45, Cat5e
3.	LAN Cable	1	1.5	N	0	RJ45, Cat5e
4.	Micro USB cable	1	1.5	Y	0	-
5.	AC Power Cable	1	1.77	N	0	Provided by client
6.	AC Power Cable	1	0.5	N	0	Provided by client

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Peak Power Analyzer Keysight	8990B	MY51000485	2024/1/21	2025/1/20
Wideband Power Sensor Keysight	N1923A	MY58020002	2024/1/18	2025/1/17
		MY58140009	2024/1/18	2025/1/17

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2024/7/19

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Signal & Spectrum Analyzer R&S	FSV3044	101105	2024/2/27	2025/2/26
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2024/7/19

4.3 6 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Occupied Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 Frequency Stability

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
AC Power Supply JIN YIH Technology	6905S	1720444	N/A	N/A
Digital Multimeter Fluke	8050A	4660081	2024/6/14	2025/6/13
Signal & Spectrum Analyzer R&S	FSV3044	101105	2024/2/27	2025/2/26
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A
Temperature & Humidity Chamber Terchy	HRM-120RF	931022	2023/12/19	2024/12/18

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2024/7/19

4.6 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance HUBER+SUHNER	E1-011315	13	2023/11/22	2024/11/21
50 ohm terminal resistance	E1-011279	04	2023/11/22	2024/11/21
	E1-011280	05	2023/11/22	2024/11/21
DC-LISN Schwarzbeck	NNBM 8126G	8126G-069	2023/11/7	2024/11/6
EMI Test Receiver R&S	ESCI	100613	2023/12/4	2024/12/3
Fixed Attenuator Mini-Circuits	HAT-10+	PAD-COND1-01	2024/1/6	2025/1/5
LISN R&S	ENV216	101826	2024/3/25	2025/3/24
	ESH3-Z5	100311	2023/9/6	2024/9/5
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2024/1/6	2025/1/5
Software BVADT	BVADT_Cond_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2023/8/31	2024/8/30

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2024/7/13 ~ 2024/8/6

4.7 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-160	2023/10/17	2024/10/16
Loop Antenna Electro-Metrics	EM-6879	269	2023/9/23	2024/9/22
Loop Antenna TESEQ	HLA 6121	45745	2023/8/8	2024/8/7
MXE EMI Receiver Keysight	N9038B	MY60180018	2024/3/13	2025/3/12
Preamplifier Agilent	8447D	2944A10638	2024/5/1	2025/4/30
Preamplifier EMCI	EMC001340	980201	2023/9/27	2024/9/26
RF Coaxial Cable Woken	8D-FB	Cable-CH9-01	2024/5/1	2025/4/30
Signal & Spectrum Analyzer R&S	FSW43	101867	2023/12/29	2024/12/28
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2024/7/12 ~ 2024/8/6

4.8 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1169	2023/11/12	2024/11/11
	BBHA 9170	9170-480	2023/11/12	2024/11/11
		BBHA9170243	2023/11/12	2024/11/11
MXE EMI Receiver Keysight	N9038B	MY60180018	2024/3/13	2025/3/12
Preamplifier Agilent	8449B	3008A02367	2024/1/6	2025/1/5
Preamplifier EMCI	EMC 184045	980116	2023/9/27	2024/9/26
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2023/7/8	2024/7/7
	EMC102-KM-KM-3000	150929	2023/7/8	2024/7/7
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	2024/1/6	2025/1/5
RF Coaxial Cable HUBER+SUHNER&EMCI	SUCOFLEX 104& EMC104-SM-SM8000	CABLE-CH9-02 (248780+171006)	2024/1/6	2025/1/5
Signal & Spectrum Analyzer R&S	FSW43	101867	2023/12/29	2024/12/28
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2024/4/25

5 Limits of Test Items

5.1 RF Output Power

Operation Band	EUT Category	Limit
U-NII-1	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
	Fixed point-to-point Access Point	1 Watt (30 dBm)
	Indoor Access Point	1 Watt (30 dBm)
	Mobile and Portable client device	250mW (24 dBm)

Operation Band	Limit
U-NII-3	1 Watt (30 dBm)

5.2 Power Spectral Density

Operation Band	EUT Category	Limit
U-NII-1	Outdoor Access Point	17 dBm/MHz
	Fixed point-to-point Access Point	
	Indoor Access Point	
	Mobile and Portable client device	11 dBm/MHz

Operation Band	Limit
U-NII-3	30 dBm/500 kHz

5.3 6 dB Bandwidth

Within the 5.725-5.850 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

5.4 Occupied Bandwidth

The results are for reference only.

5.5 Frequency Stability

The frequency of the carrier signal shall be maintained within band of operation.

5.6 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.7 Unwanted Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.8 Unwanted Emissions above 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Applicable To	Limit	
789033 D02 General UNII Test Procedure New Rules v02r01	Field Strength at 3 m	
	PK: 74 (dBμV/m)	AV: 54 (dBμV/m)

For transmitters operating in the 5.15-5.25 GHz band:

Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
15.407(b)(1)	PK: -27 (dBm/MHz)	PK: 68.2 (dBμV/m)

For transmitters operating in the 5.725-5.850 GHz band:

Applicable To	EIRP Limit	Equivalent Field Strength at 3 m
15.407(b)(4)(i)	PK: -27 (dBm/MHz) ^{*1} PK: 10 (dBm/MHz) ^{*2} PK: 15.6 (dBm/MHz) ^{*3} PK: 27 (dBm/MHz) ^{*4}	PK: 68.2 (dBμV/m) ^{*1} PK: 105.2 (dBμV/m) ^{*2} PK: 110.8 (dBμV/m) ^{*3} PK: 122.2 (dBμV/m) ^{*4}
^{*1} beyond 75 MHz or more above of the band edge. ^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. ^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. ^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.		


Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \quad \mu\text{V/m, where P is the eirp (Watts).}$$

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup




6.1.2 Test Procedure

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to average. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup



6.2.2 Test Procedure

For specified measurement bandwidth 1 MHz:

Method SA-2

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz, Set VBW $\geq$ 3 MHz, Detector = RMS
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- Record the max value and add $10 \log (1/\text{duty cycle})$.


For specified measurement bandwidth 500 kHz:

Method SA-2

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz, Set VBW $\geq$ 1 MHz, Detector = RMS
- Scale the observed power level to an equivalent value in 500 kHz by adjusting (increasing) the measured power by a bandwidth correction factor (BWCF) where $\text{BWCF} = 10 \log(500 \text{ kHz} / 300 \text{ kHz})$
- Sweep points $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.)
- Sweep time = auto, trigger set to "free run".
- Trace average at least 100 traces in power averaging mode.
- Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- Record the max value and add $10 \log (1/\text{duty cycle})$.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Occupied Bandwidth

6.4.1 Test Setup




6.4.2 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to Sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

6.5 Frequency Stability

6.5.1 Test Setup




6.5.2 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 Minutes.
- Repeat step (d) with the temperature chamber set to the next desired temperature until measurements down to the lowest specified temperature have been completed.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 Minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

6.6 AC Power Conducted Emissions

6.6.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.7 Unwanted Emissions below 1 GHz

6.7.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.8 Unwanted Emissions above 1 GHz

6.8.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.8.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

Radio 3

802.11a

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
36	5180	15.885	12.01	30	Pass
40	5200	16.144	12.08	30	Pass
48	5240	15.922	12.02	30	Pass
149	5745	17.1	12.33	30	Pass
157	5785	16.444	12.16	30	Pass
165	5825	17.338	12.39	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.81 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
36	5180	15.668	11.95	30	Pass
40	5200	16.904	12.28	30	Pass
48	5240	16.711	12.23	30	Pass
149	5745	16.788	12.25	30	Pass
157	5785	16.218	12.10	30	Pass
165	5825	16.558	12.19	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.81 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
38	5190	15.885	12.01	30	Pass
46	5230	17.539	12.44	30	Pass
151	5755	17.498	12.43	30	Pass
159	5795	15.417	11.88	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.81 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the output power limit shall not be reduced.

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)	Power Limit (dBm)	Test Result
42	5210	16.255	12.11	30	Pass
155	5775	14.894	11.73	30	Pass

Notes:

1. For U-NII-1, the antenna gain is 3.81 dBi < 6 dBi, so the output power limit shall not be reduced.
2. For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the output power limit shall not be reduced.

7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

Radio 3

802.11a

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)	Duty Factor (dB)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
36	5180	-0.97	0.14	-0.83	17	Pass
40	5200	-0.89	0.14	-0.75	17	Pass
48	5240	-0.95	0.14	-0.81	17	Pass

Note: For U-NII-1, the antenna gain is 3.81 dBi < 6dBi, so the power density limit shall not be reduced.

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)	Duty Factor (dB)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
36	5180	-1.39	0.15	-1.24	17	Pass
40	5200	-1.10	0.15	-0.95	17	Pass
48	5240	-1.15	0.15	-1.00	17	Pass

Note: For U-NII-1, the antenna gain is 3.81 dBi < 6dBi, so the power density limit shall not be reduced.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)	Duty Factor (dB)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
38	5190	-4.65	0.27	-4.38	17	Pass
46	5230	-4.23	0.27	-3.96	17	Pass

Note: For U-NII-1, the antenna gain is 3.81 dBi < 6dBi, so the power density limit shall not be reduced.

802.11ac (VHT80)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/MHz)	Duty Factor (dB)	PSD (dBm/MHz)	Max. PSD Limit (dBm/MHz)	Test Result
42	5210	-7.73	0.57	-7.16	17	Pass

Note: For U-NII-1, the antenna gain is 3.81 dBi < 6dBi, so the power density limit shall not be reduced.

802.11a

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)	Duty Factor (dB)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
149	5745	-9.17	0.14	-6.81	30	Pass
157	5785	-9.32	0.14	-6.96	30	Pass
165	5825	-9.07	0.14	-6.71	30	Pass

Note: For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11ac (VHT20)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)	Duty Factor (dB)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
149	5745	-9.58	0.15	-7.21	30	Pass
157	5785	-9.72	0.15	-7.35	30	Pass
165	5825	-9.59	0.15	-7.22	30	Pass

Note: For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11ac (VHT40)

Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)	Duty Factor (dB)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
151	5755	-12.76	0.27	-10.27	30	Pass
159	5795	-13.36	0.27	-10.87	30	Pass


Note: For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the power density limit shall not be reduced.

802.11ac (VHT80)


Chan.	Chan. Freq. (MHz)	PSD w/o Duty Factor (dBm/300kHz)	Duty Factor (dB)	PSD (dBm/500kHz)	PSD Limit (dBm/500kHz)	Test Result
155	5775	-16.55	0.57	-13.76	30	Pass

Note: For U-NII-3, the antenna gain is 4.89 dBi < 6 dBi, so the power density limit shall not be reduced.


Spectrum Plot of Maximum Value




802.11a : CH 40




802.11ac (VHT20) : CH 40




802.11ac (VHT40) : CH 46



802.11ac (VHT80) : CH 42




802.11a : CH 165




802.11ac (VHT20) : CH 149

Spectrum Plot of Maximum Value



802.11ac (VHT40) : CH 151



802.11ac (VHT80) : CH 155

7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

Radio 3

802.11a

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
149	5745	16.37	0.5	Pass
157	5785	16.39	0.5	Pass
165	5825	16.34	0.5	Pass

802.11ac (VHT20)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
149	5745	17.62	0.5	Pass
157	5785	17.58	0.5	Pass
165	5825	17.61	0.5	Pass





802.11ac (VHT40)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
151	5755	36.22	0.5	Pass
159	5795	36.89	0.5	Pass

802.11ac (VHT80)

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
155	5775	74.53	0.5	Pass

Spectrum Plot of Minimum Value



7.4 Occupied Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

Radio 3

802.11a

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
36	5180	17.16
40	5200	16.92
48	5240	17.1
149	5745	17.1
157	5785	17.04
165	5825	16.98

802.11ac (VHT20)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
36	5180	18.12
40	5200	18.12
48	5240	18.12
149	5745	18.24
157	5785	18.24
165	5825	18.12





802.11ac (VHT40)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
38	5190	37.2
46	5230	37.2
151	5755	37.2
159	5795	37.2


802.11ac (VHT80)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)
42	5210	76.32
155	5775	76.8


Spectrum Plot of Maximum Value




Spectrum Plot for nearby DFS band (DFS is required, if 99% OCP straddle into U-NII-2A)




802.11a : CH 48



802.11ac (VHT20) : CH 48







802.11ac (VHT40) : CH 46



802.11ac (VHT80) : CH 42

Spectrum Plot for nearby DFS band (DFS is required, if 99% OCP straddle into U-NII-2C)



7.5 Frequency Stability

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Lin
--------------	----------------	---------------------------	--------------	------------	----------

Radio 3

Frequency Stability Versus Temperature									
Operating Frequency: 5180 MHz									
Temp. (°C)	Power Supply (Vac)	0 Minute		2 Minutes		5 Minutes		10 Minutes	
		Measured Frequency (MHz)	Test Result	Measured Frequency (MHz)	Test Result	Measured Frequency (MHz)	Test Result	Measured Frequency (MHz)	Test Result
40	120	5180.017	Pass	5180.0158	Pass	5180.0179	Pass	5180.0169	Pass
30	120	5180.0034	Pass	5179.9992	Pass	5180.0027	Pass	5180.0026	Pass
20	120	5179.9939	Pass	5179.9966	Pass	5179.9937	Pass	5179.9949	Pass
10	120	5180.0052	Pass	5180.0069	Pass	5180.0055	Pass	5180.0059	Pass
0	120	5180.022	Pass	5180.0218	Pass	5180.0212	Pass	5180.023	Pass

Frequency Stability Versus Voltage									
Operating Frequency: 5180 MHz									
Temp. (°C)	Power Supply (Vac)	0 Minute		2 Minutes		5 Minutes		10 Minutes	
		Measured Frequency (MHz)	Test Result	Measured Frequency (MHz)	Test Result	Measured Frequency (MHz)	Test Result	Measured Frequency (MHz)	Test Result
20	138	5179.999	Pass	5180.0025	Pass	5179.9998	Pass	5180.0004	Pass
	120	5179.9939	Pass	5179.9966	Pass	5179.9937	Pass	5179.9949	Pass
	102	5179.9936	Pass	5179.9939	Pass	5179.9902	Pass	5179.9923	Pass

7.6 AC Power Conducted Emissions


Mode A

RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15400	9.67	36.60	14.21	46.27	23.88	65.78	55.78	-19.51	-31.90
2	0.17755	9.66	32.37	12.14	42.03	21.80	64.60	54.60	-22.57	-32.80
3	0.23400	9.67	29.51	5.94	39.18	15.61	62.31	52.31	-23.13	-36.70
4	1.61000	9.75	11.36	1.27	21.11	11.02	56.00	46.00	-34.89	-34.98
5	2.42600	9.77	7.30	2.52	17.07	12.29	56.00	46.00	-38.93	-33.71
6	16.89400	9.96	16.47	10.51	26.43	20.47	60.00	50.00	-33.57	-29.53

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16600	9.64	35.95	16.14	45.59	25.78	65.16	55.16	-19.57	-29.38
2	0.19000	9.65	33.88	12.33	43.53	21.98	64.04	54.04	-20.51	-32.06
3	0.25800	9.67	25.11	3.45	34.78	13.12	61.50	51.50	-26.72	-38.38
4	1.33800	9.75	9.74	2.42	19.49	12.17	56.00	46.00	-36.51	-33.83
5	1.71400	9.75	10.91	2.75	20.66	12.50	56.00	46.00	-35.34	-33.50
6	21.03800	10.21	18.90	13.21	29.11	23.42	60.00	50.00	-30.89	-26.58

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode B

RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16579	9.63	37.47	21.55	47.10	31.18	65.17	55.17	-18.07	-23.99
2	0.19000	9.64	35.61	25.39	45.25	35.03	64.04	54.04	-18.79	-19.01
3	0.30600	9.66	31.66	20.70	41.32	30.36	60.08	50.08	-18.76	-19.72
4	0.50531	9.68	35.94	30.61	45.62	40.29	56.00	46.00	-10.38	-5.71
5	10.17400	9.80	30.83	26.09	40.63	35.89	60.00	50.00	-19.37	-14.11
6	23.55800	9.81	29.61	28.86	39.42	38.67	60.00	50.00	-20.58	-11.33

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17800	9.64	38.54	29.19	48.18	38.83	64.58	54.58	-16.40	-15.75
2	0.18600	9.64	36.54	26.93	46.18	36.57	64.21	54.21	-18.03	-17.64
3	0.50600	9.69	34.81	29.57	44.50	39.26	56.00	46.00	-11.50	-6.74
4	10.03400	9.82	29.95	24.95	39.77	34.77	60.00	50.00	-20.23	-15.23
5	23.56200	9.93	28.09	24.94	38.02	34.87	60.00	50.00	-21.98	-15.13
6	29.38600	9.93	29.02	26.96	38.95	36.89	60.00	50.00	-21.05	-13.11

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode C

RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15800	9.67	35.39	15.63	45.06	25.30	65.57	55.57	-20.51	-30.27
2	0.17000	9.67	34.63	14.40	44.30	24.07	64.96	54.96	-20.66	-30.89
3	0.19400	9.66	31.74	11.19	41.40	20.85	63.86	53.86	-22.46	-33.01
4	0.21800	9.66	30.60	8.62	40.26	18.28	62.89	52.89	-22.63	-34.61
5	0.60200	9.70	10.59	0.45	20.29	10.15	56.00	46.00	-35.71	-35.85
6	1.27400	9.74	9.57	1.24	19.31	10.98	56.00	46.00	-36.69	-35.02

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16105	9.64	35.37	16.23	45.01	25.87	65.41	55.41	-20.40	-29.54
2	0.18200	9.65	32.69	12.75	42.34	22.40	64.39	54.39	-22.05	-31.99
3	0.20740	9.65	32.04	8.95	41.69	18.60	63.31	53.31	-21.62	-34.71
4	0.23000	9.66	25.96	5.19	35.62	14.85	62.45	52.45	-26.83	-37.60
5	1.45800	9.75	9.69	2.14	19.44	11.89	56.00	46.00	-36.56	-34.11
6	22.04200	10.25	19.49	13.62	29.74	23.87	60.00	50.00	-30.26	-26.13

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




Mode D

RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17400	9.63	38.19	27.60	47.82	37.23	64.77	54.77	-16.95	-17.54
2	0.24200	9.65	33.95	23.54	43.60	33.19	62.03	52.03	-18.43	-18.84
3	0.50600	9.68	35.12	30.74	44.80	40.42	56.00	46.00	-11.20	-5.58
4	10.01000	9.80	30.83	25.94	40.63	35.74	60.00	50.00	-19.37	-14.26
5	23.81400	9.81	29.53	28.82	39.34	38.63	60.00	50.00	-20.66	-11.37
6	29.63800	9.79	28.75	27.21	38.54	37.00	60.00	50.00	-21.46	-13.00

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75 % RH
Tested By	Rex Wang		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.63	39.21	24.02	48.84	33.65	66.00	56.00	-17.16	-22.35
2	0.23400	9.65	31.75	21.43	41.40	31.08	62.31	52.31	-20.91	-21.23
3	0.27000	9.65	30.07	17.67	39.72	27.32	61.12	51.12	-21.40	-23.80
4	0.50200	9.69	34.90	29.72	44.59	39.41	56.00	46.00	-11.41	-6.59
5	9.95400	9.82	29.78	24.84	39.60	34.66	60.00	50.00	-20.40	-15.34
6	23.81000	9.93	29.32	28.51	39.25	38.44	60.00	50.00	-20.75	-11.56

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



7.7 Unwanted Emissions below 1 GHz


Mode A

RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	21.6 °C, 73.3 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	57.16	28.3 QP	40.0	-11.7	1.99 H	58	37.5	-9.2
2	106.63	39.6 QP	43.5	-3.9	1.99 H	292	51.5	-11.9
3	155.13	36.5 QP	43.5	-7.0	1.99 H	272	44.7	-8.2
4	337.49	31.1 QP	46.0	-14.9	1.00 H	127	36.9	-5.8
5	428.67	32.2 QP	46.0	-13.8	1.99 H	184	36.3	-4.1
6	535.37	40.6 QP	46.0	-5.4	1.49 H	155	42.9	-2.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	21.6 °C, 73.3 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.40	33.3 QP	40.0	-6.7	1.00 V	6	43.8	-10.5
2	57.16	36.4 QP	40.0	-3.6	1.00 V	35	45.6	-9.2
3	101.78	40.2 QP	43.5	-3.3	1.00 V	97	52.9	-12.7
4	155.13	34.1 QP	43.5	-9.4	1.00 V	318	42.3	-8.2
5	335.55	29.6 QP	46.0	-16.4	1.00 V	210	35.5	-5.9
6	535.37	39.3 QP	46.0	-6.7	1.00 V	163	41.6	-2.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




Mode B

RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	142.52	28.2 QP	43.5	-15.3	1.51 H	269	36.7	-8.5
2	173.56	26.6 QP	43.5	-16.9	2.00 H	126	35.4	-8.8
3	299.66	24.6 QP	46.0	-21.4	1.00 H	127	31.2	-6.6
4	457.77	25.1 QP	46.0	-20.9	2.00 H	156	28.5	-3.4
5	547.01	32.9 QP	46.0	-13.1	1.51 H	157	35.0	-2.1
6	946.65	41.1 QP	46.0	-4.9	1.00 H	228	35.6	5.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11ax (HE40)	Channel	CH 159 : 5795 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	106.63	28.4 QP	43.5	-15.1	1.00 V	309	40.3	-11.9
2	241.46	23.0 QP	46.0	-23.0	1.00 V	74	31.9	-8.9
3	399.57	26.4 QP	46.0	-19.6	1.49 V	184	31.2	-4.8
4	500.45	26.3 QP	46.0	-19.7	1.00 V	251	29.2	-2.9
5	609.09	34.3 QP	46.0	-11.7	1.49 V	190	34.8	-0.5
6	953.44	41.0 QP	46.0	-5.0	1.49 V	299	35.5	5.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




Mode C

RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	21.6 °C, 73.3 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	33.88	35.3 QP	40.0	-4.7	1.00 H	58	45.6	-10.3
2	106.63	38.8 QP	43.5	-4.7	1.00 H	151	50.7	-11.9
3	155.13	33.4 QP	43.5	-10.1	1.00 H	258	41.6	-8.2
4	335.55	31.3 QP	46.0	-14.7	1.00 H	113	37.2	-5.9
5	535.37	39.1 QP	46.0	-6.9	1.00 H	330	41.4	-2.3
6	915.61	37.7 QP	46.0	-8.3	1.00 H	278	32.5	5.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	21.6 °C, 73.3 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	31.94	37.1 QP	40.0	-2.9	1.00 V	180	47.7	-10.6
2	70.74	36.0 QP	40.0	-4.0	1.00 V	129	46.8	-10.8
3	101.78	39.9 QP	43.5	-3.6	1.00 V	91	52.6	-12.7
4	129.91	38.1 QP	43.5	-5.4	1.49 V	2	47.8	-9.7
5	155.13	35.9 QP	43.5	-7.6	1.00 V	326	44.1	-8.2
6	535.37	35.9 QP	46.0	-10.1	1.00 V	156	38.2	-2.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




Mode D

RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	90.14	29.4 QP	43.5	-14.1	2.00 H	243	43.7	-14.3
2	230.79	23.7 QP	46.0	-22.3	1.51 H	133	34.0	-10.3
3	404.42	25.8 QP	46.0	-20.2	2.00 H	126	30.5	-4.7
4	550.89	31.9 QP	46.0	-14.1	1.51 H	143	33.9	-2.0
5	610.06	33.7 QP	46.0	-12.3	1.00 H	147	34.2	-0.5
6	946.07	41.0 QP	46.0	-5.0	1.00 H	228	35.4	5.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67 % RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	106.63	28.4 QP	43.5	-15.1	1.00 V	309	40.3	-11.9
2	140.58	29.6 QP	43.5	-13.9	1.00 V	82	38.3	-8.7
3	209.45	23.4 QP	43.5	-20.1	1.00 V	40	34.2	-10.8
4	345.25	24.3 QP	46.0	-21.7	1.49 V	264	30.2	-5.9
5	412.18	26.6 QP	46.0	-19.4	1.00 V	9	31.2	-4.6
6	952.44	41.0 QP	46.0	-5.0	1.49 V	299	35.5	5.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.8 Unwanted Emissions above 1 GHz

RF Mode	802.11a	Channel	CH 36 : 5180 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.2 PK	74.0	-13.8	1.83 H	345	47.5	12.7
2	5150.00	47.7 AV	54.0	-6.3	1.83 H	345	35.0	12.7
3	*5180.00	102.9 PK			1.83 H	345	59.8	43.1
4	*5180.00	92.9 AV			1.83 H	345	49.8	43.1
5	#10360.00	61.3 PK	68.2	-6.9	2.81 H	155	39.6	21.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	59.9 PK	74.0	-14.1	1.00 V	19	47.2	12.7
2	5150.00	47.3 AV	54.0	-6.7	1.00 V	19	34.6	12.7
3	*5180.00	100.0 PK			1.00 V	19	56.9	43.1
4	*5180.00	90.2 AV			1.00 V	19	47.1	43.1
5	#10360.00	60.9 PK	68.2	-7.3	1.92 V	221	39.2	21.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 40 : 5200 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	103.9 PK			1.82 H	339	60.9	43.0
2	*5200.00	93.7 AV			1.82 H	339	50.7	43.0
3	#10400.00	61.8 PK	68.2	-6.4	2.85 H	159	39.8	22.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	99.5 PK			1.08 V	23	56.5	43.0
2	*5200.00	89.7 AV			1.08 V	23	46.7	43.0
3	#10400.00	61.6 PK	68.2	-6.6	1.99 V	225	39.6	22.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 48 : 5240 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	103.7 PK			1.82 H	338	60.7	43.0
2	*5240.00	93.8 AV			1.82 H	338	50.8	43.0
3	5350.00	60.9 PK	74.0	-13.1	1.82 H	338	48.0	12.9
4	5350.00	47.7 AV	54.0	-6.3	1.82 H	338	34.8	12.9
5	#10480.00	61.4 PK	68.2	-6.8	2.77 H	159	39.5	21.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	99.8 PK			1.05 V	18	56.8	43.0
2	*5240.00	89.7 AV			1.05 V	18	46.7	43.0
3	5350.00	60.5 PK	74.0	-13.5	1.05 V	18	47.6	12.9
4	5350.00	47.4 AV	54.0	-6.6	1.05 V	18	34.5	12.9
5	#10480.00	61.1 PK	68.2	-7.1	1.89 V	221	39.2	21.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 36 : 5180 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.3 PK	74.0	-13.7	1.75 H	344	47.6	12.7
2	5150.00	47.7 AV	54.0	-6.3	1.75 H	344	35.0	12.7
3	*5180.00	102.5 PK			1.75 H	344	59.4	43.1
4	*5180.00	92.4 AV			1.75 H	344	49.3	43.1
5	#10360.00	61.2 PK	68.2	-7.0	2.72 H	154	39.5	21.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.2 PK	74.0	-13.8	1.09 V	15	47.5	12.7
2	5150.00	47.3 AV	54.0	-6.7	1.09 V	15	34.6	12.7
3	*5180.00	99.8 PK			1.09 V	15	56.7	43.1
4	*5180.00	89.6 AV			1.09 V	15	46.5	43.1
5	#10360.00	61.0 PK	68.2	-7.2	1.89 V	228	39.3	21.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 40 : 5200 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	103.0 PK			1.79 H	338	60.0	43.0
2	*5200.00	93.0 AV			1.79 H	338	50.0	43.0
3	#10400.00	61.5 PK	68.2	-6.7	2.86 H	152	39.5	22.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	99.8 PK			1.08 V	19	56.8	43.0
2	*5200.00	89.5 AV			1.08 V	19	46.5	43.0
3	#10400.00	61.2 PK	68.2	-7.0	1.95 V	227	39.2	22.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 48 : 5240 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	103.6 PK			1.91 H	335	60.6	43.0
2	*5240.00	93.8 AV			1.91 H	335	50.8	43.0
3	5350.00	60.9 PK	74.0	-13.1	1.91 H	335	48.0	12.9
4	5350.00	47.7 AV	54.0	-6.3	1.91 H	335	34.8	12.9
5	#10480.00	61.5 PK	68.2	-6.7	2.78 H	158	39.6	21.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	99.0 PK			1.05 V	19	56.0	43.0
2	*5240.00	89.2 AV			1.05 V	19	46.2	43.0
3	5350.00	60.5 PK	74.0	-13.5	1.05 V	19	47.6	12.9
4	5350.00	47.4 AV	54.0	-6.6	1.05 V	19	34.5	12.9
5	#10480.00	61.1 PK	68.2	-7.1	1.85 V	225	39.2	21.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT40)	Channel	CH 38 : 5190 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=2 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	61.0 PK	74.0	-13.0	1.88 H	343	48.3	12.7
2	5150.00	47.9 AV	54.0	-6.1	1.88 H	343	35.2	12.7
3	*5190.00	100.2 PK			1.88 H	343	57.1	43.1
4	*5190.00	90.2 AV			1.88 H	343	47.1	43.1
5	#10380.00	61.2 PK	68.2	-7.0	2.75 H	159	39.3	21.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.7 PK	74.0	-13.3	1.07 V	16	48.0	12.7
2	5150.00	47.3 AV	54.0	-6.7	1.07 V	16	34.6	12.7
3	*5190.00	97.1 PK			1.07 V	16	54.0	43.1
4	*5190.00	86.7 AV			1.07 V	16	43.6	43.1
5	#10380.00	60.8 PK	68.2	-7.4	1.92 V	225	38.9	21.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT40)	Channel	CH 46 : 5230 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=2 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	101.8 PK			1.88 H	336	58.8	43.0
2	*5230.00	91.3 AV			1.88 H	336	48.3	43.0
3	5350.00	60.4 PK	74.0	-13.6	1.88 H	336	47.5	12.9
4	5350.00	47.5 AV	54.0	-6.5	1.88 H	336	34.6	12.9
5	#10460.00	61.2 PK	68.2	-7.0	2.77 H	153	39.2	22.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	97.8 PK			1.09 V	19	54.8	43.0
2	*5230.00	87.5 AV			1.09 V	19	44.5	43.0
3	5350.00	60.1 PK	74.0	-13.9	1.09 V	19	47.2	12.9
4	5350.00	47.3 AV	54.0	-6.7	1.09 V	19	34.4	12.9
5	#10460.00	60.8 PK	68.2	-7.4	1.85 V	223	38.8	22.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT80)	Channel	CH 42 : 5210 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.6 PK	74.0	-11.4	2.04 H	336	49.9	12.7
2	5150.00	49.7 AV	54.0	-4.3	2.04 H	336	37.0	12.7
3	*5210.00	98.8 PK			2.04 H	336	55.8	43.0
4	*5210.00	89.0 AV			2.04 H	336	46.0	43.0
5	5350.00	59.9 PK	74.0	-14.1	2.04 H	336	47.0	12.9
6	5350.00	47.7 AV	54.0	-6.3	2.04 H	336	34.8	12.9
7	#10420.00	61.0 PK	68.2	-7.2	2.76 H	149	39.0	22.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	61.9 PK	74.0	-12.1	1.07 V	21	49.2	12.7
2	5150.00	49.3 AV	54.0	-4.7	1.07 V	21	36.6	12.7
3	*5210.00	95.4 PK			1.07 V	21	52.4	43.0
4	*5210.00	85.0 AV			1.07 V	21	42.0	43.0
5	5350.00	59.7 PK	74.0	-14.3	1.07 V	21	46.8	12.9
6	5350.00	47.4 AV	54.0	-6.6	1.07 V	21	34.5	12.9
7	#10420.00	60.7 PK	68.2	-7.5	1.95 V	228	38.7	22.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11a	Channel	CH 149 : 5745 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5745.00	105.2 PK			1.89 H	359	60.6	44.6
2	*5745.00	94.7 AV			1.89 H	359	50.1	44.6
3	11490.00	62.7 PK	74.0	-11.3	2.72 H	153	39.5	23.2
4	11490.00	49.6 AV	54.0	-4.4	2.72 H	153	26.4	23.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5745.00	100.2 PK			1.07 V	39	55.6	44.6
2	*5745.00	90.5 AV			1.07 V	39	45.9	44.6
3	11490.00	62.4 PK	74.0	-11.6	1.88 V	226	39.2	23.2
4	11490.00	49.2 AV	54.0	-4.8	1.88 V	226	26.0	23.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11a	Channel	CH 157 : 5785 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5785.00	105.7 PK			1.82 H	359	60.9	44.8
2	*5785.00	95.9 AV			1.82 H	359	51.1	44.8
3	11570.00	62.5 PK	74.0	-11.5	2.77 H	162	39.5	23.0
4	11570.00	49.5 AV	54.0	-4.5	2.77 H	162	26.5	23.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5785.00	101.3 PK			1.07 V	42	56.5	44.8
2	*5785.00	91.2 AV			1.07 V	42	46.4	44.8
3	11570.00	62.2 PK	74.0	-11.8	1.95 V	228	39.2	23.0
4	11570.00	49.2 AV	54.0	-4.8	1.95 V	228	26.2	23.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11a	Channel	CH 165 : 5825 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5825.00	105.7 PK			1.77 H	358	61.0	44.7
2	*5825.00	95.9 AV			1.77 H	358	51.2	44.7
3	11650.00	62.1 PK	74.0	-11.9	2.78 H	162	39.5	22.6
4	11650.00	49.1 AV	54.0	-4.9	2.78 H	162	26.5	22.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5825.00	102.2 PK			1.08 V	39	57.5	44.7
2	*5825.00	92.8 AV			1.08 V	39	48.1	44.7
3	11650.00	61.8 PK	74.0	-12.2	1.95 V	221	39.2	22.6
4	11650.00	48.8 AV	54.0	-5.2	1.95 V	221	26.2	22.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11ac (VHT20)	Channel	CH 149 : 5745 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5604.00	60.8 PK	68.2	-7.4	1.77 H	356	47.8	13.0
2	*5745.00	104.2 PK			1.77 H	356	59.6	44.6
3	*5745.00	94.5 AV			1.77 H	356	49.9	44.6
4	#5988.40	62.0 PK	68.2	-6.2	1.77 H	356	47.6	14.4
5	11490.00	62.6 PK	74.0	-11.4	2.75 H	159	39.4	23.2
6	11490.00	49.6 AV	54.0	-4.4	2.75 H	159	26.4	23.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5639.60	60.2 PK	68.2	-8.0	1.07 V	39	47.0	13.2
2	*5745.00	99.8 PK			1.07 V	39	55.2	44.6
3	*5745.00	90.1 AV			1.07 V	39	45.5	44.6
4	#5938.40	62.0 PK	68.2	-6.2	1.07 V	39	47.8	14.2
5	11490.00	62.2 PK	74.0	-11.8	1.95 V	228	39.0	23.2
6	11490.00	49.1 AV	54.0	-4.9	1.95 V	228	25.9	23.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11ac (VHT20)	Channel	CH 157 : 5785 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5616.40	60.4 PK	68.2	-7.8	1.67 H	357	47.3	13.1
2	*5785.00	105.0 PK			1.67 H	357	60.2	44.8
3	*5785.00	95.7 AV			1.67 H	357	50.9	44.8
4	#5931.60	61.9 PK	68.2	-6.3	1.67 H	357	47.7	14.2
5	11570.00	62.5 PK	74.0	-11.5	2.78 H	153	39.5	23.0
6	11570.00	49.4 AV	54.0	-4.6	2.78 H	153	26.4	23.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5621.60	60.1 PK	68.2	-8.1	1.08 V	44	47.0	13.1
2	*5785.00	100.4 PK			1.08 V	44	55.6	44.8
3	*5785.00	90.9 AV			1.08 V	44	46.1	44.8
4	#5977.20	61.6 PK	68.2	-6.6	1.08 V	44	47.3	14.3
5	11570.00	62.2 PK	74.0	-11.8	1.85 V	227	39.2	23.0
6	11570.00	49.1 AV	54.0	-4.9	1.85 V	227	26.1	23.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT20)	Channel	CH 165 : 5825 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5632.80	61.1 PK	68.2	-7.1	1.67 H	357	48.0	13.1
2	*5825.00	105.6 PK			1.67 H	357	60.9	44.7
3	*5825.00	96.0 AV			1.67 H	357	51.3	44.7
4	#5980.80	62.0 PK	68.2	-6.2	1.67 H	357	47.7	14.3
5	11650.00	62.1 PK	74.0	-11.9	2.75 H	159	39.5	22.6
6	11650.00	49.1 AV	54.0	-4.9	2.75 H	159	26.5	22.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5622.40	61.0 PK	68.2	-7.2	1.07 V	39	47.9	13.1
2	*5825.00	101.9 PK			1.07 V	39	57.2	44.7
3	*5825.00	92.3 AV			1.07 V	39	47.6	44.7
4	#5982.40	61.8 PK	68.2	-6.4	1.07 V	39	47.5	14.3
5	11650.00	61.8 PK	74.0	-12.2	1.95 V	224	39.2	22.6
6	11650.00	48.7 AV	54.0	-5.3	1.95 V	224	26.1	22.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT40)	Channel	CH 151 : 5755 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=2 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5642.00	61.0 PK	68.2	-7.2	1.63 H	356	47.8	13.2
2	*5755.00	102.4 PK			1.63 H	356	57.8	44.6
3	*5755.00	92.2 AV			1.63 H	356	47.6	44.6
4	#5929.20	62.3 PK	68.2	-5.9	1.63 H	356	48.1	14.2
5	11510.00	62.3 PK	74.0	-11.7	2.76 H	153	39.2	23.1
6	11510.00	49.2 AV	54.0	-4.8	2.76 H	153	26.1	23.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5626.00	60.5 PK	68.2	-7.7	1.09 V	40	47.4	13.1
2	*5755.00	98.3 PK			1.09 V	40	53.7	44.6
3	*5755.00	87.9 AV			1.09 V	40	43.3	44.6
4	#5956.80	61.4 PK	68.2	-6.8	1.09 V	40	47.2	14.2
5	11510.00	61.9 PK	74.0	-12.1	1.98 V	215	38.8	23.1
6	11510.00	48.9 AV	54.0	-5.1	1.98 V	215	25.8	23.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT40)	Channel	CH 159 : 5795 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=2 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5619.20	60.6 PK	68.2	-7.6	1.68 H	356	47.5	13.1
2	*5795.00	103.6 PK			1.68 H	356	58.8	44.8
3	*5795.00	93.3 AV			1.68 H	356	48.5	44.8
4	#5998.80	62.3 PK	68.2	-5.9	1.68 H	356	47.9	14.4
5	11590.00	62.1 PK	74.0	-11.9	2.76 H	152	39.3	22.8
6	11590.00	48.8 AV	54.0	-5.2	2.76 H	152	26.0	22.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5638.00	60.5 PK	68.2	-7.7	1.14 V	43	47.3	13.2
2	*5795.00	100.5 PK			1.14 V	43	55.7	44.8
3	*5795.00	90.3 AV			1.14 V	43	45.5	44.8
4	#5990.80	61.7 PK	68.2	-6.5	1.14 V	43	47.3	14.4
5	11590.00	61.8 PK	74.0	-12.2	1.88 V	228	39.0	22.8
6	11590.00	48.5 AV	54.0	-5.5	1.88 V	228	25.7	22.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

RF Mode	802.11ac (VHT80)	Channel	CH 155 : 5775 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 66 % RH
Tested By	Titan Hsu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5636.00	60.8 PK	68.2	-7.4	1.63 H	353	47.7	13.1
2	*5775.00	99.8 PK			1.63 H	353	55.1	44.7
3	*5775.00	89.0 AV			1.63 H	353	44.3	44.7
4	#5998.40	62.3 PK	68.2	-5.9	1.63 H	353	47.9	14.4
5	11550.00	62.2 PK	74.0	-11.8	2.75 H	152	39.2	23.0
6	11550.00	48.8 AV	54.0	-5.2	2.75 H	152	25.8	23.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5607.20	60.0 PK	68.2	-8.2	1.14 V	42	47.0	13.0
2	*5775.00	96.9 PK			1.14 V	42	52.2	44.7
3	*5775.00	86.5 AV			1.14 V	42	41.8	44.7
4	#5958.40	61.0 PK	68.2	-7.2	1.14 V	42	46.8	14.2
5	11550.00	61.9 PK	74.0	-12.1	1.95 V	229	38.9	23.0
6	11550.00	48.6 AV	54.0	-5.4	1.95 V	229	25.6	23.0


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.


Plot of Band Edge

Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11a Channel 36




802.11a Channel 48




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11ac (VHT20) Channel 36




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11ac (VHT20) Channel 48




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=2 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11ac (VHT40) Channel 38




Horizontal (Peak)




Horizontal (Average)




Vertical (Peak)




Vertical (Average)

802.11ac (VHT40) Channel 46


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)



Vertical (Average)


Frequency Range	4.5 GHz ~ 5.46 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=3 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--

802.11ac (VHT80) Channel 42




Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------


802.11a Channel 149



802.11a Channel 157





802.11a Channel 165





Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------



802.11ac (VHT20) Channel 149



802.11ac (VHT20) Channel 157




802.11ac (VHT20) Channel 165




Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------

802.11ac (VHT40) Channel 151




802.11ac (VHT40) Channel 159



Frequency Range	5.6 GHz ~ 6 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak
-----------------	-----------------	-------------------------------	----------------------------------

802.11ac (VHT80) Channel 155



8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---