

# RF EXPOSURE EVALUATION

## 1. PRODUCT INFORMATION

Product Description	True Wireless Earbuds
Model Name	A10
Series Model	MANKIW-A10, MOOR DS1
FCC ID	2AKHJ-A10

## 2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

# 3. CALCULATION

P<sub>t</sub>= -0.299dBm=0.933mW

The value of the Maximum output power P<sub>t</sub> is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR= $(0.933\text{mW} / 5\text{mm}) \cdot [\sqrt{2.402\text{GHz}}] = 0.289 < 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

### 4. CONCLUSION

The SAR evaluation is not required.